MIL-W-63389 (AR)
AMENDMENT 3
14 DECEMBER 1982
SUPERSEDING
AMENDMENT 2
28 May 1981

MILITARY SPECIFICATION

WARHEAD, GUIDED MISSILE, HE, M207E1
LINER FOR

This Amendment forms a part of Military Specification MIL-W-63389 (AR) dated 7 January 1980 and is approved for use by the U.S. Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

Pages 1, 2, 3, 4, 5, 6, & 7 change "Liner" to "Liner, Improved TOW."

PAGE 2

Add 3.5 as follows:

"3.5 Data Requirements: The contractor shall generate data in accordance with requirements of data item description cited in 6.4."

PAGE 6

4.4.2.1 Majors 101, 104, 105, 110 and 111 change "0.40% to "0.25% under "AQL or 100% column."

Majors 107, 108, 109, 110 and 111 delete and substitute:

"107. Length from datum B to inside spherical radius.
108. Length from datum B to basic dimension at apex end
109. Length from large to small basic dimensions at apex end
110. Wall thickness at large basic dimension at apex end
111. Wall thickness at small basic dimension at apex end."

FSC 1336

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

Add majors 114 and 115 as follows:

"114. Runout between two basic dimensions - 0.25, 3.2, Gage on outside surfaces at apex end (See Note 8 on dwg)
115. Wall thickness at apex 0.40, 3.2, Gage."

4.4.2.1 Add major defects, 116, 117, 118 and 119 as follows:

"116	Inside diameter	0.40%	3.2	Gage
117	Length of liner step	0.40%	3.2	Gage
118	Wall thickness at large datum, 42° section	0.40%	3.2	Gage
119	Wall thickness at small datum, 42° section	0.40%	3.2	Gage"

Add Minor defects, 203, 204 and 205 as follows:

"203	Presence of four slots on O.D.	0.65%	3.2	Visual
204	Inside spherical radius, apex (see Note 1)		3.2	Gage
205	Outside spherical radius, apex	0.65%	3.2	Gage"

NOTE: 1. All new and resharpened tooling shall be certified prior to use. A cast of the inside spherical radius of the liner shall be made from "dental plaster" or equivalent, which shall be inspected by an optical comparator of 10X magnification or greater. This inspection shall be performed at the beginning of the shift, half way through the shift and whenever tooling is changed.

* 4.4.2.1 Majors 118 and 119: Delete in their entirety and substitute the following:

"120	Wall thickness in area as show by notes 4 and 5 on dwg.	0.40%	3.2	Gage"

Add 6.4 and 6.5 as follows:

"6.4 Data Requirements. Deliverable data required by the specification is cited in the following paragraph:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

Paragraph	Data Requirement	Applicable DID
6.5	Ammunition Data	DI-L-1410"

NOTE: The margins of this amendment are marked with an asterisk or vertical line to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requiremnts of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1336-A425)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.