NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.



AN PART NO.	TYPE OF DRIVE REF DWG
AN4147-1	AND20001

FLANGE THICKNESS .38 (REF) AT MOUNTING HOLES.

MOUNTING FLANGE, DRIVE AND WRENCH CLEARANCE DETAILS SHALL BE IN ACCORDANCE WITH PROCUREMENT SPECIFICATION.

REMOVE ALL BURRS AND SHARP EDGES.

DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: TWO-PLACE DECIMALS ±.02, THREE-PLACE DECIMALS ±.005, ANGLES ±.5°.

THE AIRPLANE OR ENGINE MANUFACTURER SHALL ALLOW CLEARANCE FOR THE MAXIMUM DIMENSIONS SHOWN ON THIS DRAWING FOR INSTALLATIONS.

APPROVED 28 Sep 48 REVISED

AIR FORCE NOTE: This drawing was approved by joint action of the [redacted] and Navy Departments as the [redacted]-Navy standard for this product. This drawing supersedes all antecedent standard drawings for the same product and shall become effective for the procurement of aeronautical supplies, or for use in new designs, not later than six months after the latest date of approval shown. It may be put into effect, however, at an earlier date after promulgation.

PROCUREMENT SPECIFICATION	AIR FORCE-NAVY AERONAUTICAL STANDARD	AN4147
AN-P-11	PUMP — 1 GPM AT 3000 PSI POWER DRIVEN HYDRAULIC	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:20Z
Check the source to verify that this is the current version before use.