A-A-54
September 26, 1979

COMMERCIAL ITEM DESCRIPTION

LANTERN, ELECTRIC, SINGLE CONCENTRATED LIGHT BEAM

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification W-L-200.

This commercial item description covers electric hand lanterns, dry cell operated, single concentrated light beam.

Salient characteristics:

The lantern shall be a complete unit including battery case, light source, switch, handle, reflector assembly, and spare beam bulb. A positive means of holding the 4Fd 6-V lantern battery in the battery case shall be used. A metal stand is optional.

Switch. The switch shall have an "on" and "off" position. The switch shall remain electrically operative after 25,000 cycles from "off" to "on" and back to "off."

Impact resistance. The lantern shall not be damaged when subjected to an impact of 1 ft-lb at $0^{\circ} \pm 2^{\circ}$ F using a 1-lb steel ball. The impact shall be applied to the base (side opposite the handle), the end opposite the reflector and the lens ring side. The lantern shall be at the indicated temperature for 2 hours.

Durability drop. The lantern (battery included) shall not be damaged when tested as follows: Drop the lantern at $75^{\circ} \pm 2^{\circ}$ F from a minimum height of 3 ft into a box of loose dry sand with a minimum depth of 1 ft. Drop the lantern three times on the base and three times on the end opposite the reflector.

Concentrated beam. The concentrated light beam shall have a maximum diameter of 10 inches at a distance of 60 inches from the lantern lens.

Beam candlepower. The minimum beam candlepower (candelas) of the concentrated beam shall be 5,000 at 5.2 V. The test distance shall be 10 ft between the lantern and photoreceptor. The photoreceptor shall be calibrated using the standard lamp with a color temperature of 2856° K. The photoreceptor shall have a minimum diameter of 1 inch and be equipped with light filter to yield a response curve matching that of the International Commission on Illumination standard observer. The calculation shall be as follows:

$$I = ED^2$$

Where I = Illuminous intensity of the light beam in candelas.
E = Illuminance reading of photometer calculated in footcandles.
D = Distance between the lantern lens and photometer.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product as the product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. The lantern shall be packaged in accordance with normal commercial practice and packed in fiberboard boxes that will assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with National Motor Freight Classification and Uniform Freight Classification. Marking shall be as specified in the contract or order.

FSC 6230

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:04Z
Check the source to verify that this is the current version before use.