A-A-674
May 1, 1980

COMMERCIAL ITEM DESCRIPTION

HOLDER, CAN, GARBAGE

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification RR-H-1070

This commercial item description covers fixed post type garbage can holders for one or two cans up to and including 32 gallon size.

Salient characteristics

(1) Design - Type as specified below
(a) Type I - holds one garbage can
(b) Type II - holds two garbage cans

(2) Surface treatment -
(a) All exposed steel component parts except corrosion resistant hardware shall be hot dip galvanized after fabrication.

(3) Bottom can support -
(a) Steel or cast aluminum
(b) Adjustable height with means to securely position after adjustment
(c) Designed to accommodate either Type I or Type II, as specified, to support 32 gallon cans at a minimum of 9 inches above the ground
(d) Serve as the major weight support and provide a method to prevent the can from being easily dislodged from its normal position of rest
(e) Provide a means for easy replacement if damaged or destroyed

(4) Cap -
(a) Shall completely cover the top end of the pipe and shall fit snugly against the end of the pipe.
(b) Attached in a manner to keep the cap from being easily dislodged

(5) Evelet, ring, or loop -
(a) Secured in a permanent manner such as weld, threads, or locknut with minimum inside diameter of 0.375 inch to accept chain to secure the cover of the can.
(b) If a single evelet, ring or loop is used for Type II holder, the minimum inside diameter is 0.750 inches

(6) Handle retaining support -
(a) Designed such that the can(s), having handles with 70 degree limited movements from the normal vertical hanging position cannot be dislodged without lifting, when in the installed position.

(7) Galvanized post - inside and outside -
(a) Length - 48 (± 1) inches
(b) Hot-dip galvanized steel pipe.

(8) Assembly instructions -
(a) Furnished with the holder to insure proper installation and use of the unit.

(9) Stability - when installed in accordance with the manufacturer's instructions
(a) Type I and Type II - capable of withstanding the weight of one 32 gallon can loaded with 250 pounds of weight with a maximum deflection of 1/2 inch for any part in any direction excluding any deformation of the can.
(b) Type II - capable of withstanding the weight of two 32 gallon cans each loaded with 250 pounds with a maximum deflection of 1/2 inch for any part in any direction excluding any deformation of the can.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.

(10) Workmanship -

(a) Holder (all component parts) free from burrs, sharp edges, cracks, and uncoated surfaces.

(b) Weld - sound and free of flux, splatter, holes, or cracks.

(c) All component parts free from any defects which might affect serviceability, durability, or appearance.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices and is the same product offered for sale in the commercial marketplace The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable

Packaging, Packing and Marking. The packaging and packing shall be in accordance with normal commercial practice and shall assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage The shipping container shall be in compliance with the National Motor Freight Classification and Uniform Freight Classification Marking shall be as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.