A-A-916
January 24, 1980

COMMERCIAL ITEM DESCRIPTION

ASPHALT, ROOFING (HOT-CEMENT, MOPPING COAT)

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification SS-A-666.

This commercial item description covers four types of asphalt used primarily in the construction of built-up roof coverings laid either over boards or concrete on various inclines.

Salient characteristics: The asphalt types shall conform to ASTM D 312.

Type I - Suitable for roofs with inclines not exceeding 1 in/ft.
Type II - Suitable for roofs with inclines between 1/2 in and 3 in/ft.
Type III - Suitable for roofs with inclines between 1/2 in and 6 in/ft.
Type IV - Suitable for roofs with relatively steep slopes and relatively high temperatures.

The issue of ASTM D 312 in effect on the date of solicitation shall be used to determine compliance with stated requirements.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Packaging, packing, and marking. The roofing asphalt shall be packed in accordance with normal commercial practice. The complete pack shall be designed to protect the item against damage during shipment, handling, and storage; to assure delivery at destination; to provide for redistribution by the initial receiving activity; and to be acceptable by common carrier under National Motor Freight Classification and Uniform Freight Classification. Marking shall be as specified in the contract or order.

Unitization. The asphalt shall be unitized on a pallet or slip sheet to facilitate handling by forklift truck in accordance with commercial practice. The unitized load shall not exceed 2,500 lb in weight, 63 inches in height, 56 inches in length, and 45 inches in width.

ASTM Standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

FSC 5610

GSA DC-81004435

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.