MILITARY SPECIFICATION

SPLICER AND REWINDER, PHOTOGRAPHIC FILM FM-16( )

This specification is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for a splicer and rewinder incorporating a splicer capable of cutting and splicing 70mm, 5-inch, and 9.5-inch roll films and roll papers and a motor driven rewinder capable of rewinding the spliced material onto spools.

1.2 Classification. The splicer and rewinder shall be of one (1) type, designated FM-16( ). (See 6.3).

2. APPLICABLE DOCUMENTS

2.1 Issues of Documents. The following documents of the issue in effect on the date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

J-C-175	- Cable Assembly, Power, Electrical, for 125-Volt Equipment.
W-C-596/19	- Connector, Receptacle, Electrical, Specific Purpose, Locking, 2 Pole, 2 Wire, 20 Amperes, 250 Volts.
W-C-596/20	- Connector, Plug, Electrical, Specific Purpose, Locking, 2 Pole, 2 Wire, 20 Amperes, 250 Volts.
CC-M-1807	- Motor, Alternating Current, Fractional and Integral Horsepower (500 HP and Smaller).
TT-E-529	- Enamel, Alkyd, Semi-gloss.

MILITARY

MIL-F-32	- Film, Photographic, Aerial, Black and White.
MIL-P-116	- Preservation-Packaging, Methods of.

"Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Naval Air Engineering Center, ESSD (Code 93), Lakehurst, NJ 08733 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter."

FSC 6740

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:41Z
Check the source to verify that this is the current version before use.

MIL-P-4672 - Paper, Photographic, Black and White, Sensitized.
MIL-W-8604 - Welding of Aluminum Alloys, Process for.
MIL-T-26317 - Tape, Pressure, Sensitive Adhesive, Transparent, Film Splicing.
MIL-W-52574 - Welding Process and Welding Procedure Requirements for The Manufacture of Equipment Utilizing Steels.

STANDARDS

FEDERAL

FED-STD-H28 - Screw-Thread Standards For Federal Services.

FED-STD-595 - Colors.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of U. S. Military Property.
MIL-STD-155 - Joint Photographic Type Designation System.
MIL-STD-167/1 - Mechanical Vibrations of Shipboard Equipment (Type I - Environmental and Type II - Internally Excited).
MIL-STD-454 - Standard General Requirements for Electronic Equipment.
MIL-STD-461 - Electromagnetic Interference Characteristics, Requirements for Equipment.
MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement of.
MIL-STD-794 - Parts and Equipment, Procedures for Packaging and Packing of.
MIL-STD-810 - Environmental Test Methods.
MIL-STD-882 - System Safety Program for Systems and Associated Subsystems and Equipment: Requirements for

MS-26565 - Spool, Photographic Film, Aerial.

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:41Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN NATIONAL STANDARDS INSTITUTE

ANSI Y32.16 - 1975 - Reference Designations for Electrical and Electronic Parts and Equipment.

(Applications for copies should be addressed to the American National Standards Institute, 1430 Broadway, New York, New York 10018.)

2.3 Conflict with referenced documents. Where requirements stated in this specification conflict with any requirements in a referenced specification, the requirements of this specification shall apply.

3. REQUIREMENTS

3.1 First article. This specification makes provision for first article testing. (See 4.5 and 6.2).

3.2 Design. The splicer and rewinder shall be designed to accomplish the rapid and smooth cutting and splicing of aerial roll films in accordance with MIL-F-32 and water-resistant base roll papers in accordance with MIL-P-4672 under conditions of total darkness. The splicer shall utilize splicing tapes conforming to MIL-T-26317 and Scotch #471 or equal. The splicer and rewinder shall be designed to prevent the generation of static electricity capable of fog exposing aerial roll films. The rewinder shall be capable of rewinding the spliced material onto spools in accordance with MS26565-6, MS26565-12, and MS26565-22, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:41Z
Check the source to verify that this is the current version before use.

3.3 Materials. Materials shall be as specified herein. Materials not specified shall be of the best commercial quality and entirely suitable for the purpose. Materials shall be free from all defects and imperfections that might affect serviceability or appearance of the finished product.

3.3.1 Metals. Metals shall be of the corrosion-resistant type or treated to resist corrosion due to atmospheric conditions likely to be encountered in storage or service.

3.3.1.1 Dissimilar metals. Unless protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact with each other.

3.3.2 Standard parts. Standard commercial parts such as rollers, bearings, etc., shall be used to the maximum extent possible.

3.3.3 Fungus-proof materials. Materials which are not nutrients for fungi shall be used to the maximum extent possible. When materials that are nutrients for fungi must be used, such materials shall be treated with a fungicidal agent, as approved by the procuring activity.

3.3.4 Protective treatment. When materials are used in the construction of the splicer and rewinder that are subject to deterioration when exposed to environmental conditions likely to occur during service usage, the material shall be protected against such deterioration in a manner that shall in no way prevent compliance with the performance requirements of this specification. The use of any protective coating that will crack, chip, or scale with age or extremes of environmental conditions shall be avoided.

3.4 Construction. The splicer and rewinder shall be constructed to allow complete operation under conditions of total darkness. The splicer and rewinder shall be constructed of light-weight metal to the maximum extent possible. The splicer and rewinder shall be constructed to withstand, with a minimum of maintenance and readjustment, long periods of continuous operation. Each assembly and part of the splicer and rewinder shall be of sufficient strength and rigidity to accomplish its respective function and to maintain smooth operation with proper fit and alignment during the life of the splicer and rewinder.

3.4.1 Ease of maintenance. The splicer and rewinder shall utilize readily removable and replaceable parts to facilitate maintenance, repair, and adjustment with a minimum of down time.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:41Z
Check the source to verify that this is the current version before use.

3.4.2 Screw threads. Screw threads employed in the fabrication of the splicer and rewinder shall conform to the requirements of FED-STD-H28.

3.4.3 Welding. The welding of aluminum shall be in accordance with MIL-W-8604. The welding of steel shall be in accordance with MIL-W-52574.

3.4.4 Moving and rotating parts. All gears, pulleys, and other similar working parts shall be positively locked to shafts.

3.4.5 Interchangeability. All parts having the same manufacturer's part number shall be directly and completely interchangeable with each other with respect to installation and performance.

3.4.6 Safety. The splicer and rewinder shall be designed and constructed in accordance with the requirements of MIL-STD-882.

3.5 Environmental conditions.

3.5.1 Operational. The splicer and rewinder shall operate satisfactorily at any temperature from plus 40°F to plus 120°F at relative humidities up to 95 percent.

3.5.2 Storage. The splicer and rewinder shall withstand prolonged storage at temperatures ranging from minus 60°F to plus 160°F without damage or loss of operational efficiency.

3.5.3 Dielectric strength. All electrical circuits of the splicer and rewinder shall be capable of withstanding the conditions specified herein. There shall be no flashover or breakdown when twice the rated test voltage plus 1000 volts is applied between any electrical circuit and ground. All adjacent metal parts not in the circuit under test shall be considered as ground.

3.5.4 Leakage current. Following the exposure to the temperature and humidity conditions specified herein the leakage current between all electrical circuits and ground shall not exceed a total of 2 milliamperes. All adjacent metal parts not in the circuit under test shall be considered as ground.

3.5.5 Shock and vibration. The splicer and rewinder shall withstand the shock and vibration specified in Type I of MIL-STD-167/1 without suffering misalignment, malfunction or loosening of parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:41Z
Check the source to verify that this is the current version before use.

3.5.6 Electromagnetic interference. The splicer and rewinder shall conform to the requirements of MIL-STD-461 for Class IIB equipment.

3.6 Major components. The splicer and rewinder shall consist of the following major components:

Base unit
Film clamping and cutting assembly
Spool mounting brackets

3.6.1 Base unit. The base unit shall consist of a lightweight sturdy metal housing capable of being hard mounted to a table. The base unit shall have a smooth working surface free from sharp edges, sharp corners or other defects. The base unit shall house the tape dispenser and drive motor. The base unit shall be provided with the means for attaching the film clamping and cutting assembly and the film spool brackets.

3.6.1.1 Film alignment guides. Suitable film alignment guides shall be provided on the working surface of the base unit to assure the accurate alignment of material during the cutting and splicing operations.

3.6.1.2 Film transport rollers. Suitable rollers shall be provided on the working surface of the base unit to eliminate contact between the film and working surface during film transport. The rollers shall in no way damage the film.

3.6.1.3 Cutter groove. A groove of sufficient length, width, and depth shall be provided in the top surface of the base unit to guide the cutter blade. The groove shall provide proper relief for the cutter blade to prevent damage to the blade.

3.6.1.4 Spool bracket holders. Spool bracket holders shall be provided on the supply and take up sides of the base unit. The bracket holders shall utilize detents or other suitable means to provide for the accurate and rapid alignment of the spool brackets.

3.6.1.5 Control switch. A three-position flush-mounted toggle switch shall be provided on the front of the base unit to control the drive motor. The three positions of the control switch shall be durably marked "ON", "OFF", and "FOOT SWITCH" on the front of the base unit next to the switch.

3.6.1.6 Foot switch receptacle. The base unit shall be provided with a foot switch receptacle. The foot switch receptacle shall be in accordance with W-C-596/19. The receptacle shall be flush-mounted on the front of the base unit. The receptacle shall be wired to the "FOOT SWITCH" position of the control switch. The words "FOOT SWITCH" shall be durably marked next to the receptacle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:41Z
Check the source to verify that this is the current version before use.

3.6.1.7 Foot switch. A suitable foot switch shall be provided. The foot switch shall consist of a dual-action foot pedal connected to a 6-foot length of 2-conductor cable. The end of the cable shall terminate in a 2-prong twist-lock male plug in accordance with W-C-596/20.

3.6.1.8 Variable speed control. A solid state variable speed control shall be provided to control the speed of the drive motor. The speed control shall be capable of controlling the speed of the drive motor over a range of zero to 250 feet per minute. The control shall be flush mounted on the front of the base unit. The words "SPEED CONTROL" shall be durably marked on the front of the base unit next to the control.

3.6.1.9 Drive Motor. A suitable motor in accordance with CC-M-1807 and capable of operating on 115 volts, 50/60 cycles, and single phase alternating current shall be mounted within the base unit. The motor shall supply power to rewind the film or paper onto the bracket mounted spools. The power shall be transmitted to the spools through a "V" belt. The drive mechanism of the motor, on which the "V" belt pulley is mounted, shall protrude from the rear of the base unit. The drive mechanism of the motor and the "V" belt shall be covered by a belt guard.

3.6.1.9.1 Drive motor output. The output of the drive motor shall be sufficient to maintain the linear speed of the transported film within plus or minus ten percent of the 250 feet per minute when the total film footage on both the supply and takeup spools is 2,000 feet of 5-inch wide 0.0025-inch thick film.

3.6.1.9.2 Drive motor duty cycle. The drive motor shall be capable of continuous operation at maximum film transport speed while under maximum film load of 2,000 feet of 5-inch 0.0025-inch film for 2 periods of 60 minutes each. Off time between the 60-minute periods shall not exceed 10 minutes.

3.6.1.10 Tape dispenser. A suitable tape dispenser shall be provided. The tape dispenser shall be mounted in such a manner within the base unit that the tape may be unwound and guided under the materials to be spliced under conditions of total darkness. The tape dispenser shall be securely mounted within the base unit and shall be readily removable for reloading with tape without the tipping or inverting of the base unit.

3.6.1.10.1 Tape sizes. The tape dispenser shall accommodate rolls of tape with core diameters from 1-inch up to and including 3 inches, tape widths from 1-inch up to and including 2 inches, and rolls of tape with a maximum outside diameter of 5 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:41Z
Check the source to verify that this is the current version before use.

3.6.1.11 Tape alignment guides. Suitable tape alignment guides shall be provided on the working surface of the base unit to assure the proper alignment of the tape and the material to be spliced.

3.6.1.12 Tape cutter assembly. A tape cutter assembly shall be provided to cut the tape after the length of the tape required to make a wrap around splice has been drawn across the working surface of the base unit. The cutter shall make a smooth cut with no evidence of a ragged edge on the tape. The cutter shall provide easy access for grasping the end of the unused tape and shall not be a hazard to the operator.

3.6.2 Film clamping and cutting assembly. A detachable assembly consisting of two film clamps and a cutter assembly shall be provided as specified herein.

3.6.2.1 Film clamps. The film clamps shall be evenly spaced on each side of the cutter assembly. There shall be approximately 5 inches between the film clamps to allow sufficient space for applying the tape to the material being spliced. The film clamps shall be hinged and spring-loaded at the point of connection to the base unit. The film clamps shall be provided with a simple and positive means for holding the clamps in the "DOWN" position. The film clamps shall hold the material to be spliced in a fixed position during the cutting and splicing operations. The film clamps shall not damage the material being held during the cutting and splicing operations.

3.6.2.2 Cutter assembly. The cutter assembly shall be designed and constructed to assure the positive alignment of the cutter blade with the cutter groove in the top surface of the base unit. The cutter blade shall be capable of performing repeated smooth cuttings of two thickness of 0.007-inch thick material. The cutter assembly shall be hinged and spring-loaded at the point of connection of the base unit. When in the "UP" position the cutter assembly shall not interfere with the application of tape to the material being spliced. The cutter blade shall be a commercial off-the-shelf item. The cutter blade shall be easily adjustable and replaceable without the use of special tools.

3.6.3 Spool mounting brackets. The splicer and rewinder shall be provided with two sets of spool mounting brackets. The pair of brackets for the supply (left) side of the splicer and rewinder shall consist of one hand-crank driven bracket and one idler bracket. The idler bracket shall incorporate a fully adjustable drag brake. The pair of brackets for the takeup (right) side of the splicer and rewinder shall consist of one hand-crank driven bracket and one motor driven bracket. Each hand crank shall be spring-loaded so as not to engage the drive spindle unitl set by the operator. Each pair of brackets shall accept and support fully loaded spools in accordance with MS2656-5, MS26565-12, and MS-26565-22. Eack bracket spindle shall have full bearing support.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:41Z
Check the source to verify that this is the current version before use.

3.7 Electrical requirements. The splicer and rewinder shall be capable of operating from a nominal 115 volt, 50/60 cycle, single phase, alternating current power supply.

3.7.1 Power consumption. The power consumption of the splicer and rewinder shall not exceed 600 watts.

3.7.2 Power cable. The splicer and rewinder shall be provided with a power cable in accordance with J-C-175 designated S-1-A-2-B-9.

3.7.3 Controls and circuits. All electrical wiring, manner of connecting assembly and selection of components shall be in accordance with established high grade electrical manufacturing practices.

3.7.4 Fusing. Fuses shall be provided to break both sides of the power supply line. Fuses shall be conveniently located to provide easy access and shall be arranged to permit safe and easy replacement without removal of equipment housings. The current rating of the fuse shall be marked adjacent to the fuse.

3.7.5 Insulation. All electrical wiring shall be insulated. Insulated wiring shall be lashed together or enclosed in a conduit.

3.7.6 Wiring. The arrangement of the electrical wiring shall be in accordance with high grade commercial practice. The size of the wire, insulation, switch mounting, and all other electrical items and connections shall meet the requirements specified herein.

3.7.6.1 Wiring diagram. When specified by the procuring activity, (see 6.2), a permanent and legible wiring diagram shall be securely fastened to the splicer and rewinder. The diagram shall be accessible for maintenance purposes. The lines of the diagram shall be numbered or coded to correspond with the numbering or coding of the wires.

3.7.6.2 Symbols and electrical references. All electrical symbols and all electrical reference designations shall be in accordance with ASNI Y32.16.

3.8 Spare parts. The spare parts to be provided shall be as specified by the procuring activity (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:41Z
Check the source to verify that this is the current version before use.

3.9 Dimensions. The overall dimensions of the splicer and rewinder shall not exceed 36 inches long, by 18 inches wide and 12 inches high.

3.10 Weight. The weight of the splicer and rewinder shall not exceed 75 pounds.

3.11 Preparatory cleaning. Prior to the application of any process, all surfaces shall be cleaned free from dirt, grease, oil, solder-flux, visible rust, scale, oxides and all other debris that might interfere with the adherence of the finish.

3.12 Finish. Corrosion-resistant metals shall be buffed to a smooth state. All other metal surfaces of the splicer and rewinder shall be coated with a primer providing sufficient adherence for enamel. All primer-coated metal surfaces shall be finished with a baked alkyd semi-gloss enamel conforming to TT-E-529. The color of the enamel shall be shade 16440 in accordance with FED-STD-595.

3.13 Identification marking. Equipment, assemblies, and parts shall be marked in accordance with MIL-STD-130.

3.13.1 Serial number. The contractor shall assign a serial number to each splicer and rewinder. This serial number shall not be duplicated for any similar piece of equipment.

3.13.2 Stock number. The procuring activity shall furnish the contractor the stock number for the splicer and rewinder.

3.14 Workmanship. Workmanship shall be in accordance with Requirement 9 of MIL-STD-454.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:41Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.5).
2. Quality conformance inspection (see 4.6).

4.3 Inspection conditions. The inspection conditions shall be as specified herein.

4.3.1 Temperature and humidity. Unless otherwise specified, the splicer and rewinder shall be inspected under room ambient conditions of 73°F ± 9 degrees and relative humidity of 50 percent ± 10 percent.

4.3.2 Line voltage. Unless otherwise specified, the line voltage during the inspections shall be 115 volts, ± 2 volts, 60 cycles, single phase, alternating current.

4.3.3 Test materials. The test materials shall be as specified herein. The photographic film used for the cutting and splicing inspection shall be 9.5-inch wide, polyester base, and shall have a minimum total thickness of 0.007-inch. The photographic film used for the drive motor inspection shall be 5-inch wide, 0.0025-inch thick, 2000 feet in length, and wound on a spool in accordance with MS26565-12.

4.4 Failure during inspections. Any characteristics exhibited by the splicer and rewinder such as deterioration, power loss, overheating, binding, sticking, excessive power drain, corrosion, etc., during any inspection specified in this specification which would cause the splicer and rewinder to fail to meet any of the requirements of Section 3 of this specification, while in service, shall constitute failure of the splicer and rewinder to pass the inspection and may be the basis for rejection of the splicer and rewinder.

4.5 First article inspection. The inspection shall consist of all inspections specified herein.

4.5.1 First artcile sample. The quantity of first article samples shall be as specified by the procuring activity (see 6.2). The first article sample shall be representative of the production model splicer and rewinder.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:41Z
Check the source to verify that this is the current version before use.

4.6 Quality conformance inspection. This inspection shall consist of the following inspections:

a. Individual inspections (see 4.6.1).
b. Sampling inspections (see 4.6.2).

4.6.1 Individual inspections. Each splicer and rewinder shall be inspected as specified herein.

4.6.1.1 Physical examination. Examine each splicer and rewinder visually and with gauges to determine conformance to specified requirements for design, materials, construction, fit and interchangeability of components, safety, fusing, power consumption, wiring, dimensions, weight, finish, marking, and workmanship. Determine that the spool mounting brackets will accept and support the specified spools. Determine that the film alignment guides maintain the accurate alignment of the material during the cutting and splicing operations. Determine that the tape dispenser accepts the specified sizes of tape. Determine that the tape alignment guides maintain the proper alignment of the tape during the splicing operation. Determine that the tape cutter operates properly and is not a safety hazard to the operator. Operate all controls and moving parts to determine suitability for their intended purpose. Examine the splicer and rewinder for ease of attachment and detachment of unit parts.

4.6.2 Sampling inspections. The sampling inspections shall be in addition to the individual inspections specified herein. Sampling for these inspections shall be in accordance with MIL-STD-105 general inspection level II. The acceptable quality level (AQL) shall be as specified by the procuring activity (see 6.2).

4.6.2.1 Environmental inspections. Sample splicer and rewinders from each contract shall be subjected to the environmental inspections specified herein.

4.6.2.1.1 High temperature (operating). The sample splicer and rewinder shall be inspected in accordance with Method 501.1, Procedure II of MIL-STD-810 except that Steps 4 and 5 shall be eliminated. Determine conformance to the high temperature requirements of 3.5.1.

4.6.2.1.2 High temperature (non-operating). The sample splicer and rewinder shall be inspected in accordance with Method 501.1, Procedure I of MIL-STD-810 except that Steps 4 and 5 shall be eliminated. Determine conformance to the high temperature requirement of 3.5.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:41Z
Check the source to verify that this is the current version before use.

4.6.2.1.3 Low temperature. The sample splicer and rewinder shall be inspected in accordance with Method 502.1, Procedure I of MIL-STD-810 except that the temperature specified in Step 2 shall be minus 60°F. Determine conformance to the low temperature requirements of 3.5.1 and 3.5.2.

4.6.2.1.4 Humidity. The sample splicer and rewinder shall be inspected in accordance with Method 507.1, Procedure IV of MIL-STD-810 to determine conformance to the humidity requirement of 3.5.1.

4.6.2.1.5 Fungus. The sample splicer and rewinder shall be inspected in accordance with Method 508.1, Procedure I of MIL-STD-810 to determine conformance to the requirements of 3.3.3.

4.6.2.1.6 Dielectric strength. The insulation strength of all electrical circuits of the sample splicer and rewinder shall be inspected to withstand twice the rated voltage plus 1000 volts to determine conformance to the requirements of 3.5.3. The test potential may be direct current or peak alternating current of the same value, and shall be applied between all wiring and adjacent conductors not in the circuit and between all wiring and ground.

4.6.2.1.7 Leakage current. Following the humidity inspection, the leakage current shall be determined with the splicer and rewinder power cord connected to an alternating current power source having a potential of 115 volts. This inspection shall be between the power terminal and ground. The leakage current between any electrical circuit and any adjacent metal part not in the circuit and between any electrical circuit and ground shall not exceed 2 milliamperes.

4.6.2.1.8 Shock and vibration. The sample splicer and rewinder shall be inspected as specified in MIL-STD-167, Type I. Failure to pass the inspection shall be cause for rejection.

4.6.2.1.9 Electromagnetic interference. The sample splicer and rewinder shall be inspected in accordance with MIL-STD-462 to determine conformance to 3.5.6. Failure to pass the inspection shall be cause for rejection.

4.6.2.2 Performance inspections. The sample splicer and rewinder shall be inspected as specified herein.

4.6.2.2.1 Drive motor output. The drive motor shall be inspected for linear speed of the spool core and material transport rate to determine conformance to the requirements of 3.6.1.9.1. The method of inspection shall be any suitable method approved by the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:41Z
Check the source to verify that this is the current version before use.

4.6.2.2.2 Drive motor duty cycle. The drive motor shall be inspected to determine conformance to the requirements of 3.6.1.9.2. The splicer and rewinder shall be loaded with the specified maximum film load. The drive motor shall be operated at maximum speed and under maximum film load for a period of 60 minutes. The 60-minute period shall include actual motor operating time only. Upon completion of the 60-minute period the drive motor shall be turned off for a period of 10 minutes maximum. At the end of the 10-minute period the drive motor shall be restarted for another 60-minute period of operation at maximum speed and under maximum film load. Upon completion of this inspection the motor shall show no signs of deterioration or loss of operational efficiency. Failure to pass this inspection shall be cause for rejection.

4.6.2.2.3 Film clamps. A suitable length of 9.5-inch wide and 0.0025-inch thick film shall be placed emulsion side up on the top surface of the base unit. The film edge shall be butted to the film guides. The film clamps shall be placed in the "Down" position. The film clamps and film shall be examined to determine conformance to the requirements of 3.5.2.1.

4.6.2.2.4 Film cutter. Two suitable lengths of 9.5-inch wide and 0.007-inch thick film shall be placed emulsion side up on the top surface of the base unit. The films shall be butted to the film guides. The film clamps shall be placed in the "Down" position. The cutter shall be operated to cut through the films. This procedure shall be repeated 100 times to determine conformance to the requirements of 3.6.2.2.

4.7 Rejection and retest. Rejected splicer and rewinders shall be replaced or reworked to correct the defects, after which all necessary inspections shall be repeated. Rejected splicer and rewinders shall not be resubmitted for inspection without furnishing complete particulars concerning previous rejections and the measures taken to correct the defects. When investigation indicates that the defects may exist in splicer and rewinders previously accepted, complete particulars concerning the defects found, including recommendations for correction, shall be furnished to the procuring activity.

4.8 Destroyed specimen. All parts, specimens or assemblies destroyed in making inspections required to determine compliance with this specification shall be in addition to the quantity specified in the contract or purchase order and shall be furnished without increasing the cost of the contract or order.

4.9 Examination of packaging and packing. Examine the packaging and packing of the splicer and rewinders in accordance with the Quality Assurance Provisions of the specifications referenced in Section 5 of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:41Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation and packaging. Preservation and packaging shall be Level A or C as specified. (See 6.2).

5.1.1 Level A. Each splicer and rewinder shall be preserved and packaged in accordance with Method IIe of MIL-P-116. No contact preservative shall be applied.

5.1.2 Level C. Each splicer and rewinder shall be packaged to prevent deterioration and damage during shipment from the supplier to the first receiving activity.

5.2 Packing. Packing shall be Level A or C as specified. (See 6.2).

5.2.1 Level A. Each splicer and rewinder preserved and packaged Level A as specified herein shall be packed in accordance with the applicable provisions of MIL-STD-794.

5.2.2 Level C. Each splicer and rewinder preserved and packaged Level C as specified herein shall be packed for shipment to ensure carrier acceptance and safe delivery at the destination.

5.3 Marking. Each interior and exterior shipping container shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The splicer and rewinder is intended to be used for the cutting and tape splicing of film, paper and leader or any combination thereof in widths up to 9.5 inches and the motorized rewinding of the spliced material onto spools.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Number of splicer and rewinders required.
(c) First article samples required (see 3.1).
(d) Wiring diagram required (see 3.7.6.1).
(e) Spare parts required (see 3.8).
(f) Acceptable quality level (AQL) required (see 4.6.2).
(g) Level of preservation, packaging, and packing required (see Section 5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:41Z
Check the source to verify that this is the current version before use.

6.3 Type designator. The parenthesis in the type designator will be replaced by a suffix letter and a production issue number, in accordance with the provisions of MIL-STD-155. This complete type designator shall then be used on nameplates, shipping records, in instruction books, and wherever reference is made to the specific equipment defined by the designator. As soon as possible after award of the contract, the contractor should apply to the contracting officer for such information.

Custodians:

Navy - AS

Review Activities:

Navy - AS

Defense - GS

User Activities:

Navy - AS

Preparing Activity:

Navy - AS

(Project No. 6740-N119)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:41Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE: MIL-S-4639E(AS) Splicer and Rewinder, Photographic Film FM-16 ( )

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:41Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
Naval Air Engineering Center
Lakehurst, NJ 08733

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Engineering Specifications and Standards Department (Code 93)
Naval Air Engineering Center
Lakehurst,NJ 08733

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:41Z
Check the source to verify that this is the current version before use.