MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

MICROWAVE/WAVEGUIDE COMPONENTS

TO ALL HOLDERS OF MIL-STD-35-75(MI)

1. The following pages of MIL-STD-35-75(MI) have been revised and supersede the pages listed:

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
5-23	23 May 1975	5-23	31 December 1974
5-24	31 December 1974	Reprinted without change	
5-25	31 December 1974	Reprinted without change	
5-26	23 May 1975	5-26	31 December 1974
5-27	23 May 1975	5-27	31 December 1974
5-28	23 May 1975	5-28	31 December 1974
5-51	31 December 1974	Reprinted without change	
5-52	23 May 1975	5-52	31 December 1974
5-57	31 December 1974	Reprinted without change	
5-58	23 May 1975	5-58	31 December 1974
5-59	31 December 1974	Reprinted without change	
5-60	23 May 1975	5-60	31 December 1974
5-61	23 May 1975	5-61	31 December 1974
5-62	31 December 1974	Reprinted without change	
5-63	31 December 1974	Reprinted without change	
5-64	23 May 1975	5-64	31 December 1974
5-65	23 May 1975	5-65	31 December 1974
5-66	31 December 1974	Reprinted without change	
5-73	23 May 1975	5-73	31 December 1974
5-74	31 December 1974	Reprinted without change	
5-77	31 December 1974	Reprinted without change	
5-78	23 May 1975	5-78	31 December 1974
5-83	23 May 1975	5-83	31 December 1974
5-84	31 December 1974	Reprinted without change	
5-121	31 December 1974	Reprinted without change	
5-122	23 May 1975	5-122	31 December 1974
5-129	23 May 1975	5-129	31 December 1974
5-130	31 December 1974	Reprinted without change	
5-131	31 December 1974	Reprinted without change	
5-132	23 May 1975	5-132	31 December 1974
5-133	23 May 1975	5-133	31 December 1974
5-134	31 December 1974	Reprinted without change	
5-137	23 May 1975	5-137	31 December 1974
5-138	23 May 1975	5-138	31 December 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

2. Retain this notice page and insert before the Table of Contents.

3. Holders of MIL-STD-35-75(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or cancelled.

Custodians:
Army-MI

Review Activities:
Army-AT
Army-AV
Army-EL
Army-ME
Army-MR
Army-SG
Army-WC

User Activity:
Army-MU

Preparing Activity:
Army-MI
Project EDS-A106

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 1703 and an "X", entered on the SRS, will specify that the attenuation shall be measured at minimum, 50 percent, and maximum attenuation.

Code 1704 and a value, entered on the SRS, will specify the attenuation value in db for test pad number one.

Code 1705 and a value, entered on the SRS, will specify the attenuation value in db for test pad number two.

Code 1706 and a value, entered on the SRS, will specify the impedance value of the test cables in ohms.

Code 1707 is the 1006 requirements code (5.4).

Code 1708 is the 1006 except requirements code (5.4).

Code 1709 and a value, entered on the SRS, will specify the maximum measured attenuation in db.

Code 1710 and a value, entered on the SRS, will specify the minimum measured attenuation in db.

Code 1716 and an "X", entered on the SRS, will specify the minimum test band frequency as direct current.

Code 1711 and a value, entered on the SRS, will specify the minimum test band frequency in gigahertz.

Code 1712 and a value, entered on the SRS, will specify the maximum test band frequency in giaghertz. If Code 1711 is used, it is mandatory that Code 1712 be used.

Code 1713 and a value, entered on the SRS, will specify the accuracy of attenuation as plus or minus db/db over the reference db level plus insertion loss.

Code 1714 and a value, entered on the SRS, will specify the db level used as reference during measurement of the attenuation accuracy. If Code 1713 is used, it is mandatory that Code 1714 be used.

Code 1715 and a value, entered on the SRS, will specify the accuracy of attenuation as plus or minus db. Code 1715 shall be not used with Codes 1713 and 1714.

5.16 Attenuation Range (Variable Attenuators)

Code 1717 is the 1006 test code (5.4).

Code 1718 is the 1006 except test code (5.4).

Supersedes page 5-23 of 31 December 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 1719 and an "X", entered on the SRS, will specify to test in accordance with MIL-A-38728.

Code 1720 is the 1006 requirements code (5.4).

Code 1721 is the 1006 except requirements code (5.4).

Codes 1722 and 1723 and values, entered on the SRS, will specify the attenuation range in db above insertion loss.

5.17 Attenuation Stability (Fixed Attenuators)

Code 1726 is the 1006 test code (5.4).

Code 1727 is the 1006 except test code (5.4).

Code 1728 and an "X", entered on the SRS, will specify to test in accordance with MIL-A-3933.

There are six codes applicable to the type of tests that may be performed in order to determine the stability of attenuation. These codes and information concerning them are as follows:

Code 3140 and an "X", entered on the SRS, will specify that the Moisture Resistance test shall be performed.

Any one of the remaining five codes entered on the SRS with an "X" will specify the following tests:

Code 3141	Peak Power
Code 3142	Shock, Specified Impulse
Code 3143	Temperature Change
Code 3144	Thermal Shock
Code 3145	Vibration, Low Frequency

Code 1730 is the 1006 requirements code (5.4).

Code 1731 is the 1006 except requirements code (5.4).

Code 1732 and an "X", entered on the SRS, will specify that there shall be no evidence of mechanical damage.

Code 1733 and a value, entered on the SRS, will specify the maximum db change in attenuation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

5.18 Connector Wear Resistance (Fixed Attenuators)

Code 1736 is the 1006 test code (5.4).

Code 1737 is the 1006 except test code (5.4).

Code 1738 and an "X", entered on the SRS, will specify to test in accordance with MIL-A-3933.

Code 1739 and a value, entered on the SRS, will specify the number of cycles of connection and disconnection.

Code 1740 is the 1006 requirements code (5.4).

Code 1741 is the 1006 except requirements code (5.4).

Code 1742 and an "X", entered on the SRS, will specify that there shall be no evidence of excessive removal of material or lubrication during or after cycling.

5.19 Coupling Factor (Couplers)

Code 1745 is the 1006 test code (5.4).

Code 1746 is the 1006 except test code (5.4).

Code 1747 and an "X", entered on the SRS, will specify to test in accordance with MIL-C-15370.

Codes 1748 and 1749 and values, entered on the SRS, will specify the frequency range in gigahertz for the determination of the coupling factor at mid-frequency of this range.

Code 1750 is the 1006 requirements code (5.4).

Code 1751 is the 1006 except requirements code (5.4).

Codes 1752 and 1753 and values, entered on the SRS, will specify the coupling factor and the tolerance limit respectively in db. If Code 1752 is used, it is mandatory that Code 1753 be used.

5.20 Coupling Variation (Couplers)

Code 1757 is the 1006 test code (5.4).

Code 1758 is the 1006 except test code (5.4).

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 1759 and an "X", entered on the SRS, will specify to test in accordance with MIL-C-15370.

Codes 1760 and 1761 and values, entered on the SRS, will specify the frequency range in gigahertz for the determination of coupling variation.

Code 1762 is the 1006 requirements code (5.4).

Code 1763 is the 1006 except requirements code (5.4).

Code 1764 and a value, entered on the SRS, will specify the variation in coupling in maximum db.

Code 1765 and a value, entered on the SRS, will specify the variation in coupling in plus or minus db.

5.21 Dial Calibration (Variable Attenuators)

Code 1767 is the 1006 test code (5.4).

Code 1768 is the 1006 except test code (5.4).

Code 1769 and an "X", entered on the SRS, will specify to test in accordance with MIL-A-24215.

Codes 1770 and 1771 are mandatory.

Code 1770 and a value, entered on the SRS, will specify the frequency in gigahertz at which the dial calibration check shall take place.

Code 1771 and a value, entered on the SRS, will specify the maximum attenuation in db for the dial calibration check.

Code 1772 is the 1006 requirements code (5.4).

Code 1773 is the 1006 except requirements code (5.4).

Code 1774 and a value, entered on the SRS, will specify the dial accuracy in plus or minus db.

Code 1775 and a value, entered on the SRS, will specify the dial accuracy in plus or minus percent.

Codes 1774 and 1775 shall not be used together.

5.22 Dielectric Withstanding Voltage (Reduced Barometric Pressure)

Code 4883 is the 1006 test code (5.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 4884 is the 1.006 except test code (5.4).

Code 6300 and an "X", entered on the SRS, will specify to test in accordance with Method 301 of MIL-STD-202.

Code 4886 and a letter, entered on the SRS, will specify the applicable test condition letter from Method 105 of MIL-STD-202. Code 4886 is mandatory.

Code 3277 and an "X", entered on the SRS, will specify that the specimen shall be mounted by any suitable method.

Code 3278 and an "X", entered on the SRS, will specify that the specimen shall be mounted by the normal method.

Code 6280 and a document designation, entered on the SRS, will specify the mounting method in accordance with the document (5.7).

Code 3280 and an "X", entered on the SRS, will specify that the test voltage shall be raised from zero to the required value instantaneously.

Code 3281 and a value, entered on the SRS, will specify the rate in volts per second to raise the test voltage from zero to the required value.

Code 4885 and a value, entered on the SRS, will specify the test voltage in volts dc.

Code 4849 and a value, entered on the SRS, will specify the test voltage in volts ac。

Code 4891 and a value, entered on the SRS, will specify the duration of test voltage application in seconds.

Code 6292 and an "X", entered on the SRS, will specify that the points of test voltage application shall be between mutually insulated parts.

Code 6293 and an "X", entered on the SRS, will specify that the points of test voltage application shall be between all insulated parts and ground.

Code 6294 and an "X", entered on the SRS, will specify that the points of test voltage application shall be between current carrying parts and case.

Code 4827 and a document designation, entered on the SRS, will specify the method of test voltage connection in accordance with the document (5.7).

Code 6310 and a value, entered on the SRS, will specify the maximum surge current in milliamperes.

Code 4907 is the 1006 requirements code (5.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 4908 is the 1006 except requirements code (5.4).

Code 4906 and an "X", entered on the SRS, will specify that there shall be no evidence of flashover, mechanical damage, arcing, or insulation breakdown.

Code 4894 and a value, entered on the SRS, will specify the maximum leakage current in milliamperes.

Code 4896 and a value, entered on the SRS, will specify the maximum leakage current in microampere.

Code 4901 and an "X", entered on the SRS, will specify that the component shall remain within tolerance.

Code 4902 and an "X", entered on the SRS, will specify that there shall be no degradation of component performance.

5.23 Dielectric Withstanding Voltage (Sea Level)

Code 4860 is the 1006 test code (5.4).

Code 4861 is the 1006 except test code (5.4).

Code 4862 and an "X", entered on the SRS, will specify to test in accordance with Method 301 of MIL-STD-202.

Code 4854 and a value, entered on the SRS, will specify the test voltage in volts. dc.

Code 4855 and a value, entered on the SRS, will specify the test voltage in volts ac.

Code 4867 and a value, entered on the SRS, will specify the duration of application of test voltage in seconds.

Code 3275 and an "X", entered on the SRS, will specify that the test voltage shall be raised from zero to the required value instantaneously.

Code 3276 and a value, entered on the SRS, will specify the rate in volts per second that the test voltage is to be raised from zero to the required value.

Code 4844 and an "X", entered on the SRS, will sepcify that the points of the test voltage application shall be between mutually insulated parts.

Code 4845 and an "X", entered on the SRS, will specify that the points of test voltage application shall be between all insulated parts and ground.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 4737 and a letter, entered *on* the SRS, will specify test condition letter, Method 112 of MIL-STD-202. To detail a seal test, Code 4737 is mandatory.

If test condition letter A or B is specified, Codes 4738 and/or 4739 may be used if exception to the parameters in the specified test condition letter are required. These codes and information concerning them are as follows:

Code 4738 and a media description, entered on the SRS, will specify the media to be used for the immersion bath. If Code 4738 is used, the use of Code 4739 is mandatory.

Code 4739 and a value, entered on the SRS, will specify the minimum bath temperature in degrees Celsius.

If test condition letter C is specified, Codes 4740 and 4741 are mandatory. Information concerning them is as follows:

Code 4740 and a number, entered on the SRS, will specify the applicable procedure as specified in test condition letter C, Method 112 of MIL-STG-202.

Code 4741 and a value, entered on the SRS, will specify the leak rate sensitivity setting in ATM cc/see for the applicable leak detector in accordance with the procedure specified.

Code 4750 and a letter, entered on the SRS, will specify the gross leak test condition letter applicable after completion of procedure III or IV, test condition C, Method 112 of MIL-STD-202.

Code 4751 and a value, entered on the SRS, will specify the pressure in torr to which the chamber is to be evacuated for procedure IV of test condition C, Method 112 of MIL-STD-202. Do not use Code 4751 with Code 4735.

Code 4735 and a value, entered on the SRS, will specify the pressure in kilopascals to which the chamber is to be evacuated for Procedure IV, test condition C, Method 112 of MIL-STD-202. Do not use Code 4735 with Code 4751.

Code 4752 and a value, entered on the SRS, will specify the duration in minutes of reduced pressure for procedure IV of test condition C of Method 112 of MIL-STD-202.

Code 4743 and an “X”, entered on the SRS, will specify that any suitable mounting fixture may be used for test condition letters D or E, Method 112 of MIL-STD-202.

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 3196 and an “X”, entered on the SRS, will specify that insulation esistance shall be measured after the test.

Code 4744 is the 1006 requirements code (5.4).

Code 4745 is the 1006 except requirements code (5.4).

Code 4746 and an “X”, entered on the SRS, will specify that the leak ate measured shall be not greater than the leak rate sensitivity specified. nis code is intended for use when test condition letter C is specified, ut. may be used with any test condition letter, Method 112 of MIL-STD-202.

Code 4748 and an “X”, entered on the SRS, will specify that bubbles ndicative of leakage shall not be observed. This code is applicable to 11 test condition letters.

Code 3197 and a value, entered on the SRS, will specify the minimum nsulation resistance in megohms.

code 4758 and an “)(”, entered on the SRS, will specify that the part hall remain within tolerance.

.49 Sensitivity of Attenuation (Fixed Attenuators)

Code 1993 is the 1006 test code (5.4).

Code 1994 is the 1006 except test code (5.4).

Code 1995 and an “X”, entered on the SRS, will specify to test in ccordance with MIL-A-3933.

Codes 1996 through 2201 and 2005 are mandatory.

Code 2005 and an “X”, entered on the SRS, will specify the minimum requency as direct current during measurement of attenuation.

Codes 1996 and 1997 and values, entered on the SRS, will specify the requency range extremes in gigahertz for measurement of attenuation. Code 896 will specify the lower extreme; Code 1997 will specify the higher extreme.

Code 1998 and a value, entered on the SRS, will specify the full input ower in watts during attenuation measurement.

Code 1999 and a value, entered on the SRS, will specify the reference ower in watts during attenuation measurement.

Code 2000 and a value, entered on the SRS, will specify the minimum emperature in degrees Celsius during attenuation measurement.

upersedes page 5-52 of 31 December 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 4714 and an “X”, entered on the SRS, will specify to test in accordance with Method 107 of MIL-STD-202.

Code 4715 and a letter, entered on the SRS, will specify the applicable test condition letter.

Code 4719 and a document designation, entered on the SRS, will specify mounting shall be in accordance with the document (5.7).

Code 4720 is the 1006 requirements code (5.4).

Code 4722 is the 1006 except requirements code (5.4).

Code 4723 and an “X”, entered on the SRS, will specify no evidence of mechanical damage. This code is mandatory when requirements after the thermal shock test are to be detailed.

Code 3220 and a value, entered on the SRS, will specify the maximum attenuation in db.

Codes 3221 and 3222 and values, entered on the SRS, will specify the attenuation range in db.

Code 3223 and a value, entered on the SRS, will specify the maximum attenuation change in db that exhibits the stability of attenuation.

Code 3224 and a value, entered on the SRS, will specify the accuracy of the dial assembly in plus or minus db.

Code 3225 and a value, entered on the SRS, will specify the dial assembly accuracy measurement frequency in gigahertz. If Code 3224 is used, it is mandatory that Code 3225 be used.

Code 3226 and a value, entered on the SRS, will specify the accuracy of the dial assembly in plus or minus percent.

Code 3227 and a value, entered on the SRS, will specify the dial assembly accuracy measurement frequency in gigahertz. If Code 3226 is used, it is mandatory that Code 3227 be used.

Codes 3224 and 3225 are not to be used with Codes 3226 and 3227.

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 3228 and a value, entered on the SRS, will specify the maximum insertion loss in db.

Code 4728 and a value, entered on the SRS, will specify the minimum insulation resistance in megohms.

Code 3230 and an "X", entered on the SRS, will specify the power handling test shall be performed.

Code 3231 and a value, entered on the SRS, will specify the maximum resetability error in plus or minus db.

Code 3232 and a number, entered on the SRS, will specify the maximum VSWR.

Code 3233 and an "X", entered on the SRS, will specify that the part shall be within tolerance and shall meet design or performance characteristics.

5.56 Vibration, High Frequency

Code 1445 is the 1006 test code (5.4).

Code 1446 is the 1006 except test code (5.4).

Code 1447 and an "X", entered on the SRS, will specify to test in accordance with Method 204 of MIL-STD-202. To detail the high frequency vibration test, Code 1447 and Code 1448 are mandatory.

Code 1448 and a letter, entered on the SRS, will specify the applicable test condition letter as selected from Method 204 of MIL-STD-202.

There are three codes available to specify the method of mounting. Only one may be used. These codes and information concerning them follows:

Code 4708 and an "X", entered on the SRS, will specify that normal usage mounting means shall be used.

Code 4707 and a document designation, entered on the SRS, will specify to mount in accordance with the document (5.7).

Code 4709 and an "X", entered on the SRS, will specify that any suitable mounting method may be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

There are two codes available to specify the method of determining mechanical resonance. Only one of the codes may be entered. These codes and information concerning them are as follows:

Code 1533 and an "X", entered on the SRS, will specify that mechanical resonance shall be monitored visually by means of a strobotac.

Code 1534 and an "X", entered on the SRS, will specify that mechanical resonance shall be monitored by electrical output indicators.

Code 1442 and a letter, entered on the SRS, will specify the applicable test circuit letter from Method 310 of MIL-STD-202.

Code 1444 and a letter, entered on the SRS, will specify the applicable test condition letter from Method 310 of MIL-STD-202 that defines the maximum allowable time-duration of contact opening or closing during monitoring. The use of Codes 1442 and 1444 are mandatory.

Code 3243 and an "X", entered on the SRS, will specify the seal test shall be performed after vibration.

Code 1454 is the 1006 requirements code (5.4).

Code 1455 is the 1006. except requirements code (5.4).

Code 1456 and an "X", entered on the SRS, will specify no evidence of physical damage. This code is mandatory when requirements after the high frequency vibration test are to be detailed.

Code 3244 and an "X", entered on the SRS, will specify there shall be no leakage as detected by the continuous escaping of bubbles.

Code 3235 and a value, entered on the SRS, will specify the maximum attenuation in db.

Codes 3236 and 3237 and values, entered on the SRS, will specify the attenuation range in db.

Code 3238 and a value, entered on the SRS, will specify the maximum attenuation change in db that exhibits the stability of attenuation.

Code 3239 and a value, entered on the SRS, will specify the maximum insertion loss in db.

Code 3240 and a value, entered on the SRS, will specify the minimum insulation resistance in megohms.

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 3241 and a value, entered on the SRS, will specify the maximum resetability error in plus or minus db.

Code 3242 and a number, entered on the SRS, will specify the maximum VSWR.

Code 1480 and an "X", entered on the SRS, wi 11 specify that the part shall remain within tolerance.

5.57 Vibration. Low Frequencv

Code 1465 is the 1006 test code (5.4).

Code 1466 is the 1006 except test code (5.4).

Code 1467 and an "X", entered on the SRS, will specify to test in accordance with Method 201 of MIL-STD-202. To detail-the low frequency vibration test, Code 1467 is-mandatory.

Code 4690 and an "X", entered on the SRS, will specify to test in accordance with MIL-A-38728.

Code 4973 and a value, entered on the SRS, will specify the vibration time in minutes in each of three axes. Codes 4973 and 1470 are not to be used together.

Code 1470 and a value, entered on the SRS, will specify the duration in hours of vibration per axis. This code should only be used when the required vibration per axis is other than two hours as specified in Method 201 of MIL-STD-202.

Code 1491 and a letter, entered on the SRS, will specify the applicable test circuit letter from Method 310 of MIL-STD-202. The use of this code is mandatory.

Code 1492 and a letter, entered on the SRS, will specify the applicable test condition letter from Method 310 of MIL-STD-202 that defines the maximum allowable time-duration of contact opening or closing during monitoring. The use of this code is mandatory.

There are three codes available to specify the method of mounting. Only one may be used. These codes and information concerning them are as follows:

Code 4731 and an "X", entered on the SRS, will specify any suitable mounting method may be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 4730 and an "X", entered on the SRS, will specify normal mounting means shall be used.

Code 4729 and a document designation, entered on the SRS, will specify to mount in accordance with the document (5.7).

There are three codes available to specify the direction of motion. These may be used as required.

Code 4978 and an "X", entered on the SRS, will specify that the direction of motion shall be 90 degrees from the center line of the most sensitive axis.

Code 4979 and an "X", entered on the SRS, will specify that the direction of motion shall be on the center line of the most sensitive axis.

Code 4995 and a document designation, entered on the SRS, will specify that the direction of vibration motion shall be in accordance with the document (5.7).

Code 1472 and a value, entered on the SRS, will specify the electrical load in ohms.

Code 3245 and an "X", entered on the SRS, will specify that a pressurization test shall be performed after the vibration test.

Code 3246 and a value, entered on the SRS, will specify the total displacement of the component in inches during vibration as specified in MIL-A-38728.

Codes 3247 and 3248 and values, entered on the SRS, will specify the vibration frequencies in hertz. If Code 3246 is used, it is mandatory that Codes 3247 and 3248 be used.

Code 1474 is the 1006 requirements code (5.4).

Code 1475 is the 1006 except requirements code (5.4).

Code 1476 and an "X", entered on the SRS, will specify no evidence of physical damage. This code is mandatory when requirements after the high frequency vibration test are to be detailed.

Code 3250 and an "X", entered on the SRS, will specify that there shall be no leakage as detected by the continuous escaping of bubbles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 3251 and a value, entered on the SRS, will specify the maximum attenuation in db.

Codes 3252 and 3253 and values, entered on the SRS, will specify the attenuation range in db.

Code 3254 and a value, entered on the SRS, will specify the maximum change in attenuation in db that exhibits the stability of attenuation.

Code 3255 and a value, entered on the SRS, will specify the maximum insertion loss in db.

Code 3256 and a value, entered on the SRS, will specify the minimum insulation resistance in megohms.

Code 3257 and a value, entered on the SRS, will specify the maximum resetability error in plus or minus db.

Code 3258 and a number, entered on the SRS, will specify the maximum VSWR.

Code 1480 and an "X", entered on the SRS, will specify that the part shall remain within tolerance.

5.58 Vibration, Random

Code 1425 is the 1006 test code (5.4).

Code 1426 is the 1006 except test code (5.4).

Code 1427 and an "X", entered on the SRS, will specify to test in accordance with Method 214 of MIL-STD-202. To detail the random vibration test, Codes 1427 and 1428 are mandatory.

Code 1428 and a number and letter, entered on the SRS, will specify the applicable test condition number and letter as selected from Method 214 of MIL-STD-202. Enter the number (I or II) and follow with "the letter, for example, 1B or IIK.

It is mandatory that one duration of application per axis be specified. Do not use Code 1438 with Code 1431. Information concerning them is as follows:

Code 1438 and a value, entered on the SRS, will specify the duration in minutes of the random excitation per axis. The options are 3 or 15 minutes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 1431 and a value, entered on the SRS, will specify the duration in hours of the random excitation per axis. The options are 1.5 and 8 hours.

There are three codes to specify the monitoring instrumentation of the excitation. Only one may be selected.

Code 1452 and an "X", entered on the SRS, will specify that any suitable system may be used to monitor excitation.

Code 1453 and an "X", entered on the SRS, will specify the use of a calibrated ac to dc converter and a strip chart recorder to monitor excitation.

Code 1459 and an "X", entered on the SRS, will specify the use of a calibrated oscilloscope to monitor excitation.

Code 1430 and a value, entered on the SRS, will specify the quantity of vibration monitoring test points.

Codes 1439 or 1462 may be used to specify the location of the test point(s).

Only one of the two following codes is to be used:

Code 1439 and an "X", entered on the SRS, will specify that the location of vibration monitoring points shall be any suitable location.

Code 1462 and an "X", entered on the SRS, will specify that the location of vibration monitoring points shall be as close as practical to the test specimen,

There are three codes available to specify the method of mounting. Only one may be used. These codes and information concerning them follows:

Code 4976 and an "X", entered on the SRS, will specify normal mounting means shall be used.

Code 4975 and a document designation, entered on the SRS, will specify to mount in accordance with the document. The applicable test name from the referenced document should be entered in addition to the document designation (5.7).

Code 4977 and an "X", entered on the SRS, will specify any suitable mounting method may be used.

Code 3260 and an "X", entered on the SRS, will specify that a pressurization test is required.

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 1434 is the 1006 requirements code (5.4).

Code 1435 is the 1006 except requirements code (5.4).

Code 1436 and an "X", entered on the SRS, will specify no evidence of physical damage. This code is mandatory when requirements after the random vibration test are to be detailed.

Code 3261 and an "X", entered on the SRS, will specify that there shall be no leakage as detected by the continuous escaping of bubbles.

Code 3262 and a value, entered on the SRS, will specify the maximum attenuation in db.

Codes 3263 and 3264 and values, entered on the SRS, will specify the attenuation range in db.

. Code 3265 and a value, entered on the SRS, will specify the maximum attenuation change in db that exhibits the stability of attenuation.

Code 3266 and a value, entered on the SRS, will specify the maximum insertion loss in db.

Code 1441 and a value, entered on the SRS, will specify the minimum insulation resistance in megohms.

Code 3268 and a value, entered on the SRS, will specify the maximum resetability error in plus or minus db.

Code 3269 and a number, entered on the SRS, will specify the maximum VSWR.

Code 3270 and an "X", entered on the SRS, will specify that the part shall be within tolerance and shall meet design or performance characteristics.

5.59 Voltage Standing Wave Ratio

Code 2018 is the 1006 test code (5.4).

Code 2019 is the 1006 except test code (5.4).

Code 2020 and a document designation, entered on the SRS, will specify that testing shall be performed in accordance with the methods and conditions specified in the document (5.7).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 2022 and a number, entered on the SRS, will specify the reflection coefficient indicated on the ratio meter during the measurement of VSWR by a reflectometer system.

Code 2021 and an "X", entered on the SRS, will specify the test frequency as direct current during measurement of VSWR.

Codes 2023 and 2024 and values, entered on the SRS, will specify the test frequency in gigahertz during measurement of VSWR.

Code 2025 is the 1006 requirements code (5.4).

Code 2026 is the 1006 except requirements code (5.4).

Codes 2027 through 2030 and Code 3150 are to be used for attenuators only.

Code 2027 and a number, entered on the SRS, will specify the maximum VSWR as determined by the use of Table III.

Code 2028 and a number, entered on the SRS, will specify the maximum VSWR at minimum attenuation.

Code 2029 and a number, entered on the SRS, will specify the maximum VSWR at 50 percent of the rated attenuation range.

Code 2030 and a number, entered on the SRS, wil 1 specify the maximum VSWR at maximum attenuation.

Code 3150 and a number, entered on the SRS, wil 1 specify the maximum VSWR as measured by the reflectometer system with a reflection coefficient "P".

Codes 3151 and 3152 are to be used for adapters only.

Code 3151 and a number, entered on the SRS, will specify the maximum VSWR over the specified frequency band.

Code 3152 and a number, entered on the SRS, will specify the maximum VSWR at 50 percent of the specified frequency band.

Codes 3153, 3154 and 3155 are to be used for couplers only.

Code 3153 and a number, entered on the SRS, will specify the maximum" VSWR at the input of the primary line.

Supersedes page 5-65 of 31 December 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 3154 and a number, entered on the SRS, will specify the maximum VSWR at the secondary line waveguide output.

Code 3155 and a number, entered on the SRS, will specify the maximum VSMR at the secondary line coaxial output. Code 3154 is not to be used with Code 3155.

Code 3156 is for switches only.

Code 3156 and a number, entered on the SRS, will specify the maximum VSWR over the specified frequency band.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.12.4	Power Coupling	
	Transmitted maximum (db)	1651
	Cross-coupling maximum (db)	1652
	Reflected maximum (db)	1653
5.12.5	*Power Rating	
	Primary average (watts)	1655
	Primary peak (kilowatts)	1656
	Secondary average reflected (watts)	1657
5.12.6	Isolation	
	Minimum (db)	1658
5:12.7	Frequency Sensitivity	
	(± db)	1659
5.12.8	Tracking,	
	Maximum (db)	1660
5.12.9	Anplitude Equality	
	output to output (± _ db)	1661

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.12.10	Phase Equality	
	(Select one)	
	output to output (± _____ degrees)	1662
	output to output (± _____ radians)	1663
5.12.11	Mounting Method	
	(Select one)	
	Any acceptable	1664
	Bolts	J 665
	Brackets	1666
	Clamps	1667
	Clips	1668
	Connectors	1669
	Screws	1670
	Studs	1671
5.13	SWITCHES	
5.13.1	*Actuation	
	(Select one)	
	Manual	1675
	By motor	1676
	By solenoid	1677

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.14 (Cont)	Altitude (Cont)	
	(Select one requirement)	
	Requirement(s) per 1006 document	3027
	Requirement(s) per 1006 document except	3028
	Requirement(s) as follows:	
	No degradation of performance	3029
	Test performance requirements	
	(Select one or more requirements)	
	Attenuation maximum (db)	3031
	Insertion loss maximum (db)	3032
	VSWR (maximum)	3033
5.15	Attenuation (Fixed and Variable Attenuators)	
	(Select one test method)	
	Test per 1006 document	1698
	Test per 1006 document except ____.	1699
	Test per MIL-A-3933	1700
	Attenuation Accuracy	Table II

Reprinted without change .

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.15 (Cont)	Attenuation (Fixed and Variable Attenuators (Cont)	
	Test per MIL-A-24215	1701
	Attenuation shall be measured at minimum, 50 percent, and maximum attenuation.	1703
	Test per MIL-A-46853	1702
	Test pad number one attenuation value (db)	1704
	Test pad number two attenuation value (db)	1705
	Impedance value of test cables (ohms)	1706
	(Select one requirement)	
	Requirement(s) per 1006 document	1707
	Requirement(s) per 1006 document except _____.	1708
	Requirements as follows:	
	The measured attenuation shall be	
	*_____ maximum db	1709
	*_____ minimum db	1710
	*Frequency band of	
	DC	1716
	_____ minimum GHz	1711
	*_____ maximum GHz	1712

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST. (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.20 (Cont)	Coupling Variation (Couplers) (Cont)	
	Test as follows:	
	Test frequency range	
	* _____ minimum GHz	1760
	* _____ maximum GHz	1761
	(Select one requirement)	
	Requirement(s) per 1006 document	1762
	Requirement(s) per 1006 document except .	1763
	Requirement(s) as follows:	
	Coupling variation	
	_____ db maximum	1764
	*+-- db	1765
5.21	Dial Calibration (Variable Attenuators)	
	(Select one test method)	
	Test per 1006 document	1767
	Test per 1006 document except .	1768
	Test per MIL-A-24215	
	Check dial calibration at	
	* ____ GHz and at	1770
	* ____ maximum db attenuation	1771

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.21 (Cont)	Dial Calibration (Variable Attenuators) (Cont)	
	(Select one requirement)	
	Requirement(s) per 1006 document	1772
	Requirement per 1006 document except _____.	1773
	Requirement(s) as follows:	
	(Select one)	
	Dial accuracy	
	± _____. _____ db	1774
	Dial accuracy	
	± _____ percent	1775
5.22	Dielectric Withstanding Voltage (Reduced Barometric Pressure)	
	(Select one test method)	
	Test per 1006 document	4883
	Test per 1006 document except _____.	4884
	Test per MIL-STD-202, Method 301	6300
	MIL-STD-202, Method 105 *Test condition letter	4886

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
5.48 (Cont)	Seal (Cont)	
	Measurements after test	
	Insulation resistance	3196
	(Select one requirement)	
	Requirement(s) per 1006 document	4744
	Requirement(s) per 1006 document except _.	4745
	Requirement(s) as follows:	
	Evidence of leakage (Select one)	
	A/W test method sensitivity	4746
	No visible bubbles indicative of leakage	4748
	Requirements after test	
	Minimum insulation resistance (megohms)	3197
	The part shall remain within tolerance	4758
5.49	Sensitivity of Attenuation (Fixed Attenuators)	
	(Select one test method)	
	Test per 1006 document	1993
	Test per 1006 document except _.	1994

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.49 (Cont)	Sensitivity of Attenuation (Fixed Attenuators) (Cont)	
	Test per MIL-A-3933	1995
	Attenuation measurements	
	*At minimum frequency (de)	2005
	*At minimum frequency (GHz)	1996
	*At maximum frequency (GHz)	1997
	*At full input power (watts)	1998
	*At the reference power (watts)	1999
	*At minimum temperature (deg C)	2000
	*At maximum temperature (deg C)	2001
	(Select one requirement)	
	Requirement(s) per 1006 document	2002
	Requirement(s) per 1006 document except _____.	2003
	Requirement(s) as follows:	
	Change in attenuation shall not" exceed _____ db	2004
5.50	Shock (Variable Attenuators)	
	(Select one test method)	
	Test per 1006 document	3200
	Test per 1006 document except _____.	3201
	Test per MIL-A-38728	3202

Supersedes page 5-122 of 31 December 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.55 (Cont)	Thermal Shock (Cont)	
	Attenuation range	
	* . _ _ db	3221
	*to . _ db	3222
	Attenuation stability (db change)	3223
	Dial accuracy (Select one)	
	+ _____ db	3224
	*at _ _ GHz	3225
	+ _ . percent	3226
	*at _ . GHz	3227
	Maximum insertion loss (db)	3228
	Minimum insulation resistance (megohms)	4728
	Power handling capacity	3230
	Maximum Resetability error (± db)	3231
	Maximum VSWR	3232
	The part shall be within tolerance and shall meet design or performance characteristics.	3233

Supersedes page 5-129 of 31 December 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.56	Vibration, High Frequency	
	(Select one test method)	
	Test per 1006 document	1445
	Test per 1006 document except _.	1446
	Test per MIL-STD-202 Method 204	1447
	*Test condition letter	1448
	Method of mounting	
	(Select one)	
	Any suitable mounting method	4709
	Normal means	4708
	Mount in accordance with (5.7)	4707
	Method of determining mechanical resonance	
	(Select one)	
	Visually by means of a strobotac	1533
	Electrical output indicators	1534

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.56 (Cont)	Vibration. High Frequency (Cont)	
	Monitoring during test per MIL-STD-202. Method 310.	
	*Test circuit number	1442
	*Test condition letter	1444
	Measurements after the test shall be in accordance with requirements selected.	
	Perform seal test after vibration	3243
	(Select one requirement)	
	Requirement(s) per 1006 document	1454
	Requirement(s) per 1006 document except .	1455
	Requirement(s) as follows:	
	*No evidence of physical damage	1456
	No leakage as detected by escaping bubbles	3244
	Test performance requirements (Select one or more requirements)	
	Maximum attenuation (db)	3235
	Attenuation range	
	*___ . . db	3236
	*to _ . db	3237

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
5.56 (Cont)	Vibration, High Frequency (Cont)	
	Attenuation stability (db change)	3238
	Maximum insertion loss (db)	3239
	Minimum insulation resistance (megohms)	3240
	Maximum resetability error (± db)	3241
	Maximum VSWR	3242
	The part shall remain within tolerance	1480
5.57	Vibration, Low Frequency	
	(Select one test method)	
	Test per 1006 document	1465
	Test per 1006 document except .	1466
	Test per MIL-STD-202 Method 201	1467
	Test per MIL-A-38728	4690
	Test as follows:	
	Duration of vibration in each axis (Select one)	
	_____ minutes	4973
	_____ hours	1470

Supersedes page 5-132 of 31 December 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
5.57 (Cont)	Vibration, Low Frequency (Cont)	
	Monitoring during test per Method 310, MIL-STD-202	
	*Test circuit letter	1491
	*Test condition letter	1492
	Mounting method (Select one)	
	Any suitable method	4731
	Normal method	4730
	In accordance with (5.7)	4729
	Direction of motion	
	On center line of most sensitive axis	4979
	90 degrees from center line of most sensitive axis	4978
	Direction in accordance with (5.7)	4995
	Electrical load (ohms)	1472
	Pressurization test after vibration test	3245
	Total displacement (inches)	3246
	*at _____ Hz and	3247
	*at _____ Hz	3248

Supersedes page 5-133 of 31 December 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.57 (Cont)	Vibration, Low Frequency (Cont)	
	Measurements after the test shall be in accordance with the requirements selected.	
	(Select one requirement)	
	Requirement(s) per 1006 document	1474
	Requirement(s) per 1006 document except .	1475
	Requirement(s) as follows:	
	*No evidence of physical damage	1476
	No leakage as detected by escaping bubbles.	3250
	Test performance requirements (Select one or more requirements)	
	Maximum attenuation (db)	3251
	Attenuation range	
	*_____ dt)	3252
	*to _____ db	3253
	Attenuation stability (db change)	3254
	Maximum insertion loss (db)	3255
	Minimum insulation resistance (megohms)	3256

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.58 (Cont)	Vibration, Random (Cont)	
	Test performance requirements (Select one or more requirements)	
	Maximum attenuation (db)	3262
	Attenuation range	
	*_ _ db	3263
	*to _ _ db	3264
	Attenuation stability (db change)	3265
	Maximum insertion loss (db)	3266
	Minimum insulation resistance (megohms)	1441
	Maximum resetability error (± db)	3260
	Maximum VSWR	3269
	The part shall be within tolerance and shall meet design or performance characteristics.	3270
5.59	Voltage Standing Wave Ratio	
	(Select one test method)	
	Test per 1006 document	2018
	Test per 1006 document except .	2019
	Test per (see 5.7)	2020

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
5.59 (Cont)	Voltage Standing Wave Ratio (Cont)	
	Test as follows:	
	Test per VSWR Test Table III	Table III
	(Enter applicable codes and values on SRS from Table III	
	Measure VSWR by reflectometer system	
	Ratio meter indication	
	*Reflection coefficient (P)	2022
	VSMR measurement frequency range	
	Dc	2021
	_- - GHz minimum	2023
	* _____ GHz maximum	2024
	(Select one requirement)	
	Requirement(s) per 1006 document	2025
	Requirement(s) per 1006 document except _,	2026
	Requirement(s) as follows:	
	Attenuators	
	Maximum VSWR	
	per Table 111	2027
	-at minimum attenuation	2028

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.