FED. SUP CLASS
9510




TABLE I. DASH NUMBERS.

DASH NO	A	HEAT TREATMENT	FORMING PROCESS (SEE REQT 3)	ADDITIONAL REQT (SEE REQT 4)
001	.375	ANNEALED	H	
003	.375	ANNEALED	C	
005	.375	ANNEALED	C	
007	.375	HARDENED AND TEMPERED	C	
009	.438	ANNEALED	C	
011	.438	NORMALIZED	C	
013	.500	ANNEALED	C	
015	.500	ANNEALED	H	
017	.500	HARDENED AND TEMPERED	C	
019	.500	NORMALIZED	C	
021	.562	ANNEALED	C	
023	.625	ANNEALED	C	
025	.625	NORMALIZED	C	
027	.625	NORMALIZED AND TEMPERED	C	
029	.688	ANNEALED	C	
031	.750	ANNEALED	C	
033	.750	HARDENED AND TEMPERED	C	
035	.750	NORMALIZED	C	
037	.875	ANNEALED	H	
039	.875	NORMALIZED	C	
041	1.000	ANNEALED	C	
043	1.000	ANNEALED	H	po or sb
045	1.000	NORMALIZED	C	
047	1.000	ANNEALED	H	
049	1.125	ANNEALED	C	
051	1.125	NORMALIZED	C	
053	1.250	ANNEALED	C	
055	1.250	ANNEALED	H	
057	1.250	HARDENED AND TEMPERED	C	
059	1.250	NORMALIZED	C	
061	1.375	ANNEALED	C	
063	1.500	ANNEALED	C	
065	1.500	NORMALIZED	C	
067	1.750	ANNEALED	C	
069	1.750	NORMALIZED	H	
071	2.000	ANNEALED	H	
073	2.000	ANNEALED	C	
075	2.000	NORMALIZED	H	
077	2.250	NORMALIZED	C	
079	2.500	ANNEALED	C	
081	2.500	NORMALIZED	H	
083	2.500	NORMALIZED	H	
085	3.000	ANNEALED	H	
087	3.000	NORMALIZED	H	
089	3.500	NORMALIZED	H	
091	3.500	NORMALIZED	H	
093	4.000	NORMALIZED	H	
095	4.500	NORMALIZED	H	po or sb
097	5.000	ANNEALED	H	

USER ACTIVITIES:
NAVY-MC,OS

REVIEWER ACTIVITIES:
AIR FORCE-84
DLA-IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

APPROVED 9 October 1984 REVISED

P.A.	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
AS		BAR, METAL, SQUARE, ALLOY STEEL 4130 CHROME-MOLYBDENUM (AIRCRAFT QUALITY)	MS14295
Other Cust MR 99			
PROCUREMENT SPECIFICATION: MIL-S-6758	SUPERSEDES:		PAGE 1 OF 2

DD FORM 1 MAY 73 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 9510-0421

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:39Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

1. MATERIAL. ALLOY STEEL 4130 (UNS G41300), AS SPECIFIED IN PROCUREMENT DOCUMENT.


2. LENGTH STANDARD LENGTH OF SQUARE BAR IS 10 FEET MINIMUM, 12 FEET MAXIMUM.

3. FORMING PROCESS. COLD DRAWN - CODE "C"
HOT ROLLED - CODE "H"

4. ADDITIONAL REQUIREMENTS. PICKLED OVERALL - CODE "po"
SANDBLASTED OVERALL - CODE "sb"

5. PART NUMBER. THE PART NUMBER CONSISTS OF THE BASIC MS NUMBER, PLUS A FORMING PROCESS CODE, PLUS A DASH NUMBER FROM TABLE I.

EXAMPLE: MS14295H001



6. MARKING. IRON AND STEEL PRODUCTS SHALL BE MARKED IN ACCORDANCE WITH FED-STD-183 WITH THE EXCEPTION THAT A PART NUMBER FROM THIS MILITARY STANDARD SHALL BE INCLUDED AS PART OF THE IDENTIFICATION MARKING.

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.

2. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BIDS, OR REQUEST FOR PROPOSAL, EXCEPT THE REFERENCED ADOPTED INDUSTRY DOCUMENTS SHALL GIVE THE DATE OF THE ISSUE ADOPTED.

3. FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

APPROVED 9 October 1984 REVISED

USER ACTIVITIES:
NAVY-MC,OS

REVIEWER ACTIVITIES:
AIR FORCE-84
DLA-IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P.A.	AS	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
Other Cust	MR 99		BAR, METAL, SQUARE, ALLOY STEEL 4130 CHROME-MOLYBDENUM (AIRCRAFT QUALITY)	MS14295
PROCUREMENT SPECIFICATION: MIL-S-6758		SUPERSEDES:		PAGE 2 OF 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:39Z
Check the source to verify that this is the current version before use.