THIS SPECIFICATION IS APPROVED FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE

THE REQUIREMENTS FOR ACQUIRING THE PRODUCT(S) DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DODISS SPECIFIED IN THE SOLICITATION: MIL-N-25027

DD Form 672, MAY 88

PREVIOUS EDITION IS OBSOLETE

PREPARING ACTIVITY: DLA-IS

CUSTODIANS: ARMY- AV
AIR FORCE- 11
DLA-

NAVY- AS

REVIEW: CR, MI, 99 (D)

USER:

PROJECT NUMBER: 5310-2048

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

MILITARY SPECIFICATION SHEET

TITLE
NUT, SELF-LOCKING, PLATE, SIDE BY SIDE, REDUCED RIVET SPACING, LOW HEIGHT, STEEL, 125 KSI FTU, 450F

SPECIFICATION SHEET NUMBER
MS21086 26 MAR 95
REV D

SUPERSEDING
MS21086 C 1 FEB 94 (SEE NOTE 5)

AMSC- N/A

FSC 5310

INCH-POUND

(D) DENOTES CHANGE(S)

Page 1 of 2

CONFIGURATION OF NUT OPTIONAL WITHIN THE LIMITATIONS IMPOSED BY DIMENSIONS AND REQUIREMENTS SPECIFIED HEREIN.




TABLE I. DASH NUMBERS AND DIMENSIONS

DASH NUMBERS				T THREAD SIZES	A	B		2/ C	øD	F	øG	1/ H	(D) J	3/ øK	øP	V	W	AXIAL STRENGTH LBS/MIN	WEIGHT LBS/100
PLAIN RIVET HOLES		COUNTERSUNK OR DIMPLED RIVET HOLES																	
NON-DRY FILM LUBRICANT	DRY FILM LUBRICANT	NON-DRY FILM LUBRICANT	DRY FILM LUBRICANT		MAX	MAX	MIN	±.005	MIN	MIN	±.010	MAX	±.002	+.005 -.000	MAX	MAX	MAX		
-08	L08	-08K	L08K	.164-32 UNJC-3B	.486	.297	.235	.234	.168	.100	.200	.250	.219	.099	.248	.047	.437	1,720	.23
-3	L3	-3K	L3K	.190-32 UNJF-3B	.521	.328	.298	.250	.194	.100	.200	.250	.219	.098	.274	.047	.437	2,460	.28
-4	L4	-4K	L4K	.250-28 UNJF-3B	.591	.414	.380	.281	.254	.100	.200	.281	.219	.098	.344	.055	.437	4,580	.45
-5	L5	-5K	L5K	.3125-24 UNJF-3B	.747	.505	.475	.359	.317	.125	.230	.328	.269	.130	.417	.065	.537	7,390	.78
-6	L6	—	—	.375-24 UNJF-3B	.856	.614	.580	.414	.379	.125	.230	.344	.269	.130	.505	.075	.537	11,450	1.05

1/ MINIMUM "H" NOT SPECIFIED, LIMITED ONLY BY STRENGTH REQUIREMENTS OF SPECIFICATION.
2/ CENTER OF THE TAPPED HOLE SHALL NOT DEVIATE IN ANY DIRECTION FROM THE CENTER OF THE PLATE NUT AS DETERMINED BY THE RIVET HOLES BY MORE THAN .005.
3/ DIMPLED RIVET HOLE TOLERANCE FOR "øK" IS +.015 -.000.

Form Approved
OMB No. 0704-0188

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:26Z
Check the source to verify that this is the current version before use.

THE REQUIREMENTS FOR ACQUIRING THE PRODUCT(S) DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DODISS SPECIFIED IN THE SOLICITATION: MIL-N-25027

THIS SPECIFICATION IS APPROVED FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE.

Form Approved
OMB No. 0704-0188

REQUIREMENTS:

1. MATERIAL: CARBON STEEL, COMPOSITIONS 1035 (UNS G10350), 1040 (UNS G10400), AND 1050 (UNS G10500) IN ACCORDANCE WITH ASTM A827 OR QQ-S-700; 1042 (UNS G10420), IN ACCORDANCE WITH ASTM A29. ALLOY STEEL, GRADES 4130 (UNS G41300), 4340 (UNS G43400) AND 8740 (UNS G87400), IN ACCORDANCE WITH ASTM A29.
2. FINISH: CADMIUM PLATE IN ACCORDANCE WITH QQ-P-416 TYPE II, CLASS 2. FOR DRY FILM LUBRICATED NUTS, THE TYPE AND CLASS ARE OPTIONAL IF THE NUTS MEET THE SALT SPRAY REQUIREMENTS OF QQ-P-416 TYPE II.
3. DIMENSIONING AND TOLERANCING: DIMENSIONING AND TOLERANCING SHALL BE IN ACCORDANCE WITH ANSI Y14.5M.
4. HARDNESS: 49 HRC, MAX.
5. THREADS: THREADS PER LUBRICATION IN ACCORDANCE WITH MIL-S-8879.
6. SURFACE TEXTURE: SURFACE TEXTURE, UNLESS OTHERWISE SPECIFIED, SHALL NOT EXCEED 125 MICROINCHES, IN ACCORDANCE WITH ANSI/ASME B46.1.
7. LUBRICANT: DRY FILM LUBRICANT APPROVED IN ACCORDANCE MIL-N-25027. NON-DRY FILM LUBRICANTS SHALL BE SOLUBLE IN THE CLEANER SPECIFIED IN MIL-S-8802.
8. EDGES: BREAK ALL SHARP EDGES AND REMOVE ALL BURRS.
9. COUNTERBORE: ON SIZE .164 AND LARGER, THREAD RELIEF SHALL BE .062 MINIMUM.
10. PART NUMBER: THE PART NUMBER SHALL CONSIST OF THE BASIC MS NUMBER FOLLOWD BY A DASH NUMBER FROM TABLE I.

EXAMPLE: MS21086L4K
- L4K — DASH NUMBER
- MS21086 — BASIC MS NUMBER

MS21086L4K INDICATES: NUT, SELF-LOCKING, PLATE, SIDE BY SIDE, REDUCED RIVET SPACING, LOW HEIGHT, STEEL; 125 KSI Ftu, 450° F; .250-28 UNJF-3B, DRY FILM LUBRICANT; COUNTERSUNK OR DIMPLED HOLES.

NOTES

1. ALL DIMENSIONS ARE IN INCHES.
2. (D) IN THE EVENT OF A CONFLICT BETWEEN THE TEXT OF THIS DOCUMENT AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS DOCUMENT SHALL TAKE PRECEDENCE.
3. (D) UNLESS OTHERWISE SPECIFIED, ISSUES OF REFERENCED DOCUMENTS ARE THOSE IN EFFECT AT THE TIME OF SOLICITATION.
4. DESIGN AND USAGE LIMITATIONS: THESE NUTS ARE DESIGNED TO DEVELOP THE TENSILE STRENGTH OF BOLTS AND SCREWS WITH AN ULTIMATE TENSILE STRENGTH OF 125 KSI BASED ON THE CROSS SECTION AREA AT THE BASIC ROOT DIAMETER OF THE THREADS. THESE NUTS ARE DESIGNED TO BE USED ON 3A EXTERNAL THREADS. THES NUTS SHALL BE USED IN ACCORDANCE WITH THE LIMITATIONS OF MS33588. ONLY NUTS FOR WHICH THESE ARE QUALIFIED PRODUCTS LISTED ON QPL 25027 SHALL BE USED.
5. MS21086 SUPERSEDES NAS1067 IN PART.

INTERCHANGEABILITY RELATIONSHIP

MS21086 NUTS CAN UNIVERSALLY REPLACE NAS1067 NUTS OF LIKE MATERIAL, THREAD SIZE, PLATING LUBRICANTS (DRY FILM OR NON-DRY FILM), RIVET SPACING AND FASTENING METHOD (PLAIN RIVET HOLES; DIMPLED OR COUNTERSUNK RIVET HOLES OR PROJECTION WELDING), BUT THESE NAS1067 NUTS CANNOT UNIVERSALLY REPLACE MS21086 NUTS.

INTERCHANGEABILITY TABLE

CANCELLED PART NUMBERS	SUBSTITUTIVE PART NUMBERS
NAS1067X08	MS21086-08
NAS1067X08K	MS21086-08K
NAS1067A08	MS21086L08
NAS1067A08K	MS21086L08K
NAS1067X3	MS21086-3
NAS1067X3K	MS21086-3K
NAS1067A3	MS21086L3
NAS1067A3K	MS21086L3K
NAS1067X4	MS21086-4
NAS1067X4K	MS21086-4K
NAS1067A4	MS21086L4
NAS1067A4K	MS21086L4K
NAS1067X5	MS21086-5
NAS1067X5K	MS21086-5K
NAS1067A5	MS21086L5
NAS1067A5K	MS21086L5K
NAS1067X6	MS21086-6
NAS1067A6	MS21086L6

PREPARING ACTIVITY: DLA-IS
CUSTODIANS: ARMY - AV NAVY - AS
AIR FORCE - 11 DLA -
REVIEW: CR, MI, 99 (D)
USER
PROJECT NUMBER: 5310-2048

MILITARY SPECIFICATION SHEET

TITLE
NUT, SELF-LOCKING, PLATE, SIDE BY SIDE, REDUCED RIVET SPACING, LOW HEIGHT, STEEL, 125 KSI Ftu, 450°F

SPECIFICATION SHEET NUMBER
MS21086 28 MAR 95 REV D

SUPERSEDING
MS21086 C 1 FEB 94 (SEE NOTE 5)

AMSC - N/A FSC 5310

DISTRIBUTION STATEMENT
A. Approved for public release; distribution is unlimited

DD Form 672, MAY 88

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:26Z
Check the source to verify that this is the current version before use.