CCC–P–86a
AMENDMENT—2
AUGUST 11, 1954

SUPERSEDING
Amendment—1
1 June 1951

FEDERAL SPECIFICATION

PADDING, LAUNDRY (STITCHED-COTTON-ROVING)

This amendment, which forms a part of Federal Specification CCC–P–86a, dated 28 July 1949, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

Page 1, paragraph 2.1: Delete and substitute:

2.1 The following Federal Specification, of the issue in effect on date of invitation for bids, forms a part of this specification:

CCC–T–191—Textile Test Methods.

(Activities outside the Federal Government may obtain copies of Federal Specifications and Standards as outlined under "General Information" in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the GSA Regional Offices in Boston, New York, Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, Seattle, and Washington, D. C.

(Federal Government activities may obtain copies of Federal Specifications and Standards and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Page 1, paragraph 3.1.2: Delete and substitute:

3.1.2 *Thread.*—The thread used in joining the roving shall be of unbleached cotton of a quality and size to give an average breaking strength, skein test, of not less than 200 pounds, with a minimum breaking strength of 190 pounds per individual test.

Page 2, section 4: Following paragraph 4.1, add new paragraph 4.1.1 as follows:

4.1.1 *Thread.*—Not less than 500 yards of the same lot of thread used in fabricating the padding delivered, shall be furnished for test purposes by the contractor with each shipment.

Page 2, paragraph 4.3: Delete and substitute:

4.3 Tests.—The following methods described in Federal Specification CCC–T–191 shall be used in testing the padding and thread:

Test	Method No.
Standard conditions	Section 4
Weight per square yard	5041
Length	5010
Width	5020
Breaking strength (thread)	4104

Page 3, section 6: Following paragraph 6.2 continued insert new paragraph 6.3 as follows:

6.3 Transportation description.—The transportation description applicable to this item is:

Padding, laundry, (made wholly of cotton, cotton linters, sweepings, motes or card strippings), knitted, quilted or stitched, in the original piece.

Carload weight—Any Quantity.

Padding, cotton, not otherwise indexed, knitted, quilted or stitched.

Truckload weight 20,000 pounds.

Page 3, paragraphs 7.2.1 through 7.2.4.3: Delete and substitute the following:

312301—54—No. 43

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:28Z
Check the source to verify that this is the current version before use.

7.2.1 *Applicable specifications and standards.*

Military Specifications:

JAN–P–125—Packaging and Packing for Overseas Shipment — Barrier-Materials, Waterproof, Flexible.

MIL–B–3149—Baling of Clothing and Equipage.

Military Standards:

MIL–STD–105—Sampling Procedures and Tables for Inspection by Attributes.

MIL–STD–129—Marking for Shipment and Storage.

(Copies of specifications, standards, and publications required by the contractor in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

7.2.2 *Sampling, inspection, and test procedures.*

7.2.2.1 *Sampling.*—Sampling shall be conducted in accordance with Military Standard MIL–STD–105.

7.2.2.2 *Inspection.*—Inspection shall be made by the Government to determine compliance with this specification.

7.2.3 *Packaging, packing, and marking.*

7.2.3.1 *Packaging.*—The laundry padding shall be tightly rolled and securely fastened to prevent unrolling. Each roll shall be completely enclosed in a wrap of kraft paper having a minimum basis weight of 50 pounds per ream (24 x 36—500). For overseas shipment, each roll shall be enclosed in an additional wrap of type B-2, asphalt duplexed waterproof barrier-material made in conformance with the requirements of Military Specification JAN–P–125.

7.2.3.2 *Packing.*—Each roll, packaged as specified in 7.2.3.1, shall be inserted into a bias-sewn tubing of burlap, pre-sewn at one end and closed either by applying wire ties or sewing. The material and closure shall conform to the requirements outlined for baling of clothing and equipage in Military Specification MIL–B–3149. Compression, baling boards, and strapping need not be used.

7.2.3.3 *Marking.*—Marking shall be in accordance with Military Standard MIL–STD–129.

MILITARY INTEREST:
Army—Q
Navy—S
Air Force.

Page 4, bottom of page: Delete "For Sale" statement and substitute the following: "Copies of this specification may be purchased for 5 cents each."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.