FEDERAL SPECIFICATION

CARBON DISULFIDE, TECHNICAL GRADE

This amendment, which forms a part of Federal Specification O–C–131, dated 29 January 1952, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

Page 1, paragraph 2.1: Delete parenthetical "Copies" paragraph and substitute:

(Non-Government activities may obtain copies of Federal Specifications and Standards upon application accompanied by check, money order, cash, or Government Printing Office coupons, to the General Services Administration, Business Service Center, Region 3, Seventh and D Streets SW., Washington 25, D. C. This office will also honor deposit account numbers issued by the Government Printing Office. Copies of the Index of Federal Specifications and Standards may be obtained from the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C. Prices may be obtained from the Index of Federal Specifications and Standards or from the GSA Regional Offices.

(Single copies of this specification and other product specifications required by non-Government activities for bidding purposes are available without charge at the GSA Regional Offices in Boston, New York, Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, Seattle, and Washington, D. C.

(Government activities may obtain copies of Federal Specifications and Standards and the Index of Federal Specifications and Standards through departmental channels from the established sources of supply.)

Page 1, paragraph 2.2, bottom of first column insert the following:

A. S. T. M. Standards, Part 5.

(Copies of A. S. T. M. Standards may be obtained from the American Standards for Testing Material, 1916 Race Street, Philadelphia 3, Pa.)

Page 2, paragraph 4.2.3: Delete and substitute:

4.2.3 *Copper corrosion.*—The sample shall be tested by the A. S. T. M. Standard Method of Test D 849–47 for Copper Corrosion of Industrial Aromatic Hydrocarbons. The reflux condenser should be the water-cooled type. The water bath should be kept warm enough to cause gentle boiling. Examine for compliance with the requirements of table I.

Page 2, paragraph 5.2.1: Delete second paragraph (within quotations) and substitute:

"DANGER — EXTREMELY FLAMMABLE
VAPOR HARMFUL, POISON
HIGHLY VOLATILE

Keep away from fire sparks, or heated surfaces.

Store in cool place and keep container closed.

Use only with adequate ventilation.

Avoid breathing vapor.

Avoid contact with skin and eyes."

Page 3, following paragraph 6.3, insert new paragraphs 6.4 and 6.4.1:

6.4 Transportation description.

6.4.1 *The applicable transportation description, carload and truckload minimum weights are:*

Carbon bisulfide (carbon disulfide) (released valuation not to exceed 50 cents per pound)

Carload weight 30,000 pounds

Truckload weight 30,000 pounds.

Page 4, bottom of page: Delete "For sale" statement and substitute: Copies of this specification may be purchased for 5 cents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:12Z
Check the source to verify that this is the current version before use.