AMENDMENT

TO

INTERIM FEDERAL SPECIFICATION

SEAT, WATER CLOSET (LAND USE)

This amendment was developed by the General Services Administration, Federal Supply Service, Washington, D. C. 20406, based upon currently available technical information. The General Services Administration has authorized the use of this amendment as a valid exception to Interim Federal Specification WW-S-001912 (GSA-FSS), dated July 25, 1976.

PAGE 4

Paragraph 3.7, delete in its entirety and substitute the folowing:

"3.7 Flexural strength and load capability. Seats and covers shall not have a permanent set greater than 0.10 inch nor shall they fracture when tested in accordance with 4.4.3."

PAGE 5

Paragraph 4.2.1, delete in its entirety.

PAGE 6

Paragraph 4.4.3.2, delete in its entirety and substitute the following:

"4.4.3.2 Closed front seats. Fasten seat to water closet bowl or other suitable flat surface. Measure and record clear space between seat bottom and flat surface at a point half way between seat bumper and hinge on both sides of seat. Place a 300 pound load, distributed over both sides of seat, at points of measurement and hold load for one minute. Remove load and remeasure for conformance to 3.7."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:24Z
Check the source to verify that this is the current version before use.