AMENDMENT

TO

INTERIM FEDERAL SPECIFICATION

FLASHLIGHT, TRAFFIC

This amendment was developed by the General Services Administration, Federal Supply Service, Washington, D. C. 20405, based upon currently available technical information. The General Services Administration has authorized the use of this amendment as a part of Interim Federal Specification W-F-001247(GSA-FSS), dated November 17, 1967.

PAGE 3

Paragraph 3.3.2, delete and substitute:

3.3.2 Threads. All threads shall be of design and fit that may be screwed tight using a torque not exceeding 25 inch-pounds. Threads shall not strip or ride over those of a mating part when a torque of 75 inch-pounds is used.

PAGE 5

Paragraph 4.4.4, delete and substitute:

4.4.4 Threads. Starting with the case of the flashlight, disassembled, it shall be assembled applying a measured torque not exceeding 25 inch-pounds, to "screw-up," the caps and other threaded parts. The flashlight shall be examined to determine compliance with requirement of 3.3.2. A measure torque of 75 inch-pounds $\pm$ 1/2 inch-pound shall be applied to each of the threaded parts of the case and the flashlight shall then be examined for compliance with the stated requirements of 3.2.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:34Z
Check the source to verify that this is the current version before use.