AMENDMENT

TO

INTERIM FEDERAL SPECIFICATION

FLASHLIGHT, RIGHT ANGLE

This amendment was developed by the Standardization Division, General Services Administration, Federal Supply Service, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this amendment as a valid exception to Interim Federal Specification W-F-001316(GSA-FSS), dated December 9, 1971.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B or C, as specified (see 6.2).

5.1.1 Level A. Each flashlight shall be individually packaged in accordance with submethod IC-2 of MIL-P-116.

5.1.1.1 Intermediate packaging. Twelve flashlights of one stock number, as specified in 5.1.1, shall be intermediate packaged in a close-fitting box conforming to PPP-B-636, W6c.

5.1.2 Level B. Each flashlight shall be packaged in a close-fitting box conforming to PPP-B-566, PPP-B-665, or PPP-B-676. The box shall be closed and secured to prevent accidental opening.

5.1.2.1 Intermediate packaging. Twelve flashlights of one stock number packaged, as specified in 5.1.2, shall be intermediate packaged in a close-fitting box conforming to PPP-B-566, PPP-B-665, or PPP-B-676. Each box shall be closed and secured to prevent accidental opening.

5.1.3 Level C. Flashlights shall be packaged in accordance with the supplier's commercial practice.

5.2 Packing. Packing shall be level A, B or C, as specified (see 6.2).

5.2.1 Level A. Intermediate packages of like description, in quantities, as specified (see 6.2), shall be packed in a close-fitting box conforming to PPP-B-601, overseas type, or PPP-B-621, class 2. The box shall be closed, waterproofed and strapped in accordance with the appendix to the applicable box specification. When the gross weight exceeds 250 pounds, skids shall be provided in accordance with the applicable box specification.

5.2.2 Level B. Six intermediate packages (72 flashlights) shall be packed in a close-fitting box conforming to PPP-B-636, class domestic. The box shall be in accordance with the appendix to PPP-B-636.

5.2.3 Level C. The flashlights, packaged, as specified in 5.1, shall be packed in containers to assure carrier acceptance and safe arrival at destination in compliance with Uniform Freight Classification Rules or National Motor Freight Classification Rules.

5.3 Marking. In addition to any special marking required by the contract or order, the interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123 or MIL-STD-129, as applicable.

6.2(f): Delete and substitute:

(f) Quantity of intermediate packages required, shipping container (see 5.2.1).

Source: https://assist.dla.mil - Downloaded: 2026-02-27T11:34Z
Check the source to verify that this is the current version before use.