INACTIVE FOR NEW DESIGN AS OF 13 JULY 1995

INCH-POUND

MIL-M-38510/115A
AMENDMENT 1
05 SEPTEMBER 1995

MILITARY SPECIFICATION

MICROCIRCUITS, LINEAR, NEGATIVE, VOLTAGE REGULATORS, MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/115A, dated 04 September 1989, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 6

TABLE I. Device type 02. Output noise voltage test (V_{NO}), delete the max limit of "250 µV rms" and substitute "600 µV rms".

PAGE 7

TABLE I. Device type 03. Output noise voltage test (V_{NO}), delete the max limit of "300 µV rms" and substitute "700 µV rms".

PAGE 8

TABLE I. Device type 04. Output noise voltage test (V_{NO}), delete the max limit of "500 µV rms" and substitute "1000 µV rms".

PAGE 30

FIGURE 13. Voltage start-up test circuit. Note 2, delete the second sentence and substitute the following; "Measurements shall be made in the interval 0.5 ms to 10 ms after the start of the pulse."

PAGE 38

TABLE III. Test no. 60. Delete the max limit of "250 µV rms" and substitute "600 µV rms".

PAGE 42

TABLE III. Test no. 57. Delete the max limit of "300 µV rms" and substitute "700 µV rms".

PAGE 46

TABLE III. Test no. 60. Delete the max limit of "500 µV rms" and substitute "1000 µV rms".

AMSC N/A
FSC 5962

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:23Z
Check the source to verify that this is the current version before use.

at 120 Hz: 4.6 ohms per 100 feet

Dc resistance (maximum

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Navy - OS, SH
Air Force - 11, 19, 85, 99

Civil Agency Coordinating Activity:

NASA - NA

Preparing activity:
DLA - ES

Agent:
DLA - ES

(Project 5962-1552)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:23Z
Check the source to verify that this is the current version before use.