INCH-POUND

MIL-M-38510/119A
AMENDMENT 1
09 Jan 1995

MILITARY SPECIFICATION

MICROCIRCUITS, LINEAR, LOW POWER, LOW NOISE, BI-FET
OPERATIONAL AMPLIFIERS, MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/119A, dated 07 August 1987 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2.1, Add footnote for device type 06 as follows "Devices may be monolithic or they may consist of two separate independent die."

PAGE 3

3.1, Detail specifications, delete in its entirety and substitute "3.1 Item requirements. The individual item requirements shall be in accordance with MIL-M-38510, and as specified herein. The individual item requirements for devices marked with the "Q" certification mark shall be in accordance with MIL-I-38535 and as specified herein or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not effect the form, fit, or function as described herein.

3.4, Electrical performance characteristics, delete in its entirety and substitute "For dual and quad packages, the idle devices shall be connected as grounded followers or in the case of devices maintained in servo test loops, the idle devices shall have their outputs forced to ground via the output control voltage."

4.1, Sampling and inspection, delete in its entirety and substitute "4.1 Sampling and Inspection. Sampling and inspection procedures shall be in accordance with MIL-M-38510 and methods 5004, 5005, and 5007, as applicable, of MIL-STD-883, except as modified herein. For devices marked with the "Q" certification mark, sampling and inspection procedures shall be in accordance with MIL-I-38535 or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not effect the form, fit, or function as described herein.

PAGE 5

Table I, add new footnote "1/" to the conditions column.
Table I, Input offset current test, footnote "1/" will be renumbered as footnote "2/".
Table I, Input bias current test, footnote "2/" will be renumbered as footnote "3/".
Table I, Input bias current test, footnote "3/" will be renumbered as footnote "4/".
Table I, Input voltage common mode rejection test, footnote "4/" will be renumbered as footnote "5/".
Table I, Adjustment for input offset voltage test, footnote "5/" will be renumbered as footnote "6/".
Table I, Output short circuit current (for positive output) test, footnote "6/" will be renumbered as footnote "7/".

AMSC N/A
FSC 5962

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-21T13:25Z
Check the source to verify that this is the currentversion before use.

Table I, Input bias current test, delete in its entirety and substitute the following:

"

Input bias current 3/, 4/	$+I_{IB}$, $-I_{IB}$	V_{CC} = ±15 V, V_{CM} = +11 V, t ≤ 25 ms	T_J = +25°C	All	-200	1,200	pA
			T_J = +125°C	All	-10	70	nA
		V_{CC} = ±15 V V_{CM} = 0 V, t ≤ 25 ms	T_J = +25°C	All	-200	+200	pA
			T_J = +125°C	All	-10	50	nA
		V_{CC} = ±15 V, V_{CM} = -11 V, t ≤ 25 ms	T_J = +25°C	All	-400	200	pA
			T_J = +125°C	All	-10	50	nA

".

Table I, add new footnote "1/" to the conditions column.
Table I, Output short circuit current (for negative output) test, footnote "6/" will be renumbered as footnote "7/".
Table 1, Open loop voltage gain (single ended) test, delete in its entirety and substitute the following:

"

Open loop voltage gain (single ended) 8/	$A_{VS(+)}$	V_{OUT} = 0 V to 10 V, R_L = 10 kΩ	T_A = +25°C	01, 02, 03	5		V/mV
			T_A = -55°C, +125°C	01, 02 03	4		
		V_{OUT} = 0 V to 10 V, R_L = 2 kΩ	T_A = +25°C	04, 05, 06	50		
			T_A = -55°C, +125°C	04, 05 06	25		
	$A_{VS(-)}$	V_{OUT} = -10 V to 0 V, R_L = 10 kΩ	T_A = +25°C	01, 02, 03	5		
			T_A = -55°C, +125°C	01, 02 03	4		
		V_{OUT} = -10 V to 0 V, R_L = 2 kΩ	T_A = +25°C	04, 05, 06	50		
			T_A = -55°C, +125°C	04, 05 06	25		

".

Table I, Open loop voltage gain (single ended), A_{VS}, test, footnote "7/" will be renumbered as footnote "8/".

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:25Z
Check the source to verify that this is the current version before use.

PAGE 7

Table I, add new footnote "1/" to the conditions column.
Table I, Channel separation test, footnote "8/" will be renumbered as footnote "9/".
Footnotes, Add new footnote as follows, "1/ For devices marked with the "Q" certification mark, the parameters listed herein may be guaranteed if not tested to the limits specified in accordance with the manufacturer's QM plan."
Footnote "1/" will be renumbered as footnote "2/".
Footnote "2/" will be renumbered as footnote "3/".
Footnote "3/" will be renumbered as footnote "4/".
Footnote "4/" will be renumbered as footnote "5/".
Footnote "5/" will be renumbered as footnote "6/".
Footnote "6/" will be renumbered as footnote "7/".
Footnote "7/" will be renumbered as footnote "8/".
Footnote "8/" will be renumbered as footnote "9/".

PAGE 9

Figure 1, device types 03 and 06, cases C and D, pin 11, delete "V-/GND" and substitute "V-".

PAGE 12

Figure 4, Test circuit for burn-in and steady state life tests, delete "Conditions @ T_A = +125°C" and substitute "Conditions @ $T_A \geq$ +125°C".

PAGE 18

Figure 9, Test circuit for settling time, delete note 4 in its entirety and substitute "4. Settling time t_s, measured on pin 5, is the interval during which the summing mode is not nulled to within ±5 mV."

PAGE 26

Footnote 1/, add the following sentence, "For devices marked with the "Q" certification mark, the parameters listed herein may be guaranteed if not tested to the limits specified in accordance with the manufacturer's QM plan."
Footnote 7/, delete in its entirety and substitute "7 For device types 02, 03, 05, and 06 maximum limit shown is for 1 operating amplifier only, this value is double for the dual device (i.e. 2 x 3.5 = 7 mA at 25°C and 125°C (i.e. 2 x 4.0 = 8 mA at -55°C), quadruple for the quad devices."

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI, SM
Navy - SH, OS, TD, MC, CG, AS
Air Force - 19, 85, 99
DLA - ES

Civil Agency Coordinating Activity:
NASA-NA

Preparing activity:
DLA-ES

Agent:
DLA - ES

(Project 5962-1406)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:25Z
Check the source to verify that this is the current version before use.