MILITARY SPECIFICATION

MICROCIRCUITS, LINEAR, CMOS
NEGATIVE LOGIC, ANALOG SWITCH,
MONOLITHIC SILICON

This amendment forms a part of Military Specification MIL-M-38510/123A, dated 21 September 1982, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 5

TABLE I, V_{ISO}, conditions column: Delete "(see 4.4.4b)" and substitute "(see 4.4.1d, 4.4.3d, and 4.4.4b)". Make this same change in V_{CT} and V_{CTE} conditions columns.

PAGE 6

* 3.7, line 2; delete "57" and substitute "82".

* TABLE II, delete and substitute:

" TABLE II. Electrical test requirements.

MIL-STD-883 test requirements	Subgroups (see table III)	
	Class S	Class B
Interim electrical parameters (pre burn-in) (method 5004)	1	1
Final electrical parameters (method 5004)	1*,2,3,9	1*,2,3,9
Group A test requirements (method 5005)	1,2,3,4***, 9,10,11, (12,13,14)****	1,2,3,4***, 9,10,11, (12,13,14)****
Group C end-point and group B class S, electrical parameters (method 5005)	1,2,3, and table IV delta limits	1 and table IV delta limits
Additional electrical subgroups for group C periodic inspection	N/A	(12,13,14)*****
Group D end-point electrical parameters (method 5005)	1, 2, 3, (12,13,14)**	1

* PDA applies to subgroup 1 (see 4.2c).

** See 4.4.4b.

*** Subgroup 4, see 4.4.1c.

**** See 4.4.1d.

***** See 4.4.3d."

FSC 5962

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:27Z
Check the source to verify that this is the current version before use.

PAGE 28

TABLE III, test nos. 121 through 125, terminal conditions: Delete "4/" and "5/" (all columns).

* 4.2a, add the following: "NOTE: Burn-in circuit resistor tolerances for figures 4, 5 and 6 shall be ±10%."

* 4.4.1c, add the following sentence: "Subgroup 4 shall be performed using a sample of 5 devices with no failures allowed."

PAGE 37

Add new paragraph 4.4.1d as follows:

"d. Subgroups 12, 13, and 14 shall be added to group A inspection as specified in table III herein. These subgroups shall be performed for initial qualification only using a sample of five devices for each device type submitted to group A inspection, with no failures allowed. If not more than one failure is found in the first sample of five, a second sample of five is permitted with no further failures allowed."

PAGE 38

* Delete 4.4.2c in its entirety.

Add new paragraph 4.4.3d as follows:

"d. A special subgroup shall be added to group C inspection for class B and C devices only and it shall consist of subgroups 12, 13, and 14 of group A inspection as specified in table III herein. This special subgroup shall be performed on each device type that is qualified from those listed in 1.2.1 herein. After initial qualification, the special subgroup shall be performed periodically on a single device type selected from those device types previously qualified. A sample of five devices (of the device type to be inspected) shall be chosen and submitted to test with no failures allowed. If not more than one failure is found in the first sample of five, a second sample of five is permitted with no further failures allowed. When more than one device type is qualified, the single device type selected shall be a different device type for each subsequent periodic inspection until all qualified device types have been inspected. The sequence of single device types shall be repeated to fulfill the periodic inspection requirement."

4.4.4b, delete and substitute:

"b. A special subgroup shall be added to group D inspection for class S devices only and it shall consist of subgroups 12, 13, and 14 of group A inspection as specified in table III herein. This special subgroup shall be performed on each device type that is qualified from those listed in 1.2.1 herein. After initial qualification, the special subgroup shall be performed periodically on a single device type selected from those device types previously qualified. When more than one device type is qualified, the single device type selected shall be a different device type for each subsequent periodic inspection until all qualified device types have been inspected. The sequence of single device types shall be repeated to fulfill the periodic inspection requirement."

PAGE 39

* Delete 4.5.3: Delete in its entirety.

*TABLE V: Delete in its entirety.

*FIGURE 17: Delete in its entirety.

PAGE 40

* 4.7: Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 202610-21T13:27Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ER
Navy - EC
Air Force - 17
NASA - NA

Review activities:
Army - AR, MI
Navy - OS, SH
Air Force - 11, 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC

Agent:
DLA - ES

Preparing activity:
NASA - NA

(Project 5962-0608)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:27Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:27Z
Check the source to verify that this is the current version before use.