INCH-POUND

MIL-DTL-3943/166C
19 February 2010
SUPERSEDING
MIL-DTL-3943/166B
9 December 1998

DETAIL SPECIFICATION SHEET

DECORATION, AERIAL ACHIEVEMENT MEDAL, CIVILIAN, AIR FORCE

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.

OBVERSE

REVERSE

MATERIAL: Nickel Silver

FINISH: Silver Plated, Oxidized, Buffed Relieved, Matte Finish and shall match The Institute of Heraldry (TIOH) Metal Finish Chip number 14.

DIMENSIONS:
HEIGHT (including lug): 1-3/4 inches (REF)
WIDTH (overall): 1-3/4 inches (REF)
THICKNESS (at wing tips): 0.125 inch $\pm$ 0.010 inch

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:13Z
Check the source to verify that this is the current version before use.

2. Decoration set shall consist of a regular size medal, a service ribbon, and a lapel button all packaged in a presentation case conforming to MIL-C-14633, Type XVI with a Type XVI, Class 1 or 3 pad.

3. The ribbon for the pendant drape and service ribbon shall conform to MIL-DTL-11589/390.

4. The lapel button shall conform to MIL-DTL-11484/225.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activities:
Air Force - 99
DLA - CT

(Project No. 8455-2010-090)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:13Z
Check the source to verify that this is the current version before use.