NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/65F
11 May 1999
SUPERSEDING
MIL-DTL-3943/65E
1 May 1997

DETAIL SPECIFICATION SHEET

DECORATION, AWARD FOR VALOR, FEDERAL AVIATION ADMINISTRATION

Inactive for new design after 14 January 1999.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

OBVERSE

REVERSE

MATERIAL:

BASE: Gilding Metal
DEVICE: Red Brass

FINISH:

BASE: Hard Enameled, Gold Plated, Rose Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 20.
DEVICE: Gold Plated, Rose Gold Plated, Polished Highlights.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T23:14Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

BASE:
HEIGHT (including lug): 1-5/8 inches (REF)
DIAMETER: 1-1/2 inches (REF)
THICKNESS (on lettering): 0.125 inch ± 0.005 inch

DEVICE:
DIAMETER (world): 11/16 inch (REF)
THICKNESS (thickest point): 0.150 inch ± 0.005 inch

ASSEMBLED THICKNESS (thickest point): 0.275 inch + 0.010 inch

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub and die.

2. Enameled areas shall be as indicated. The colors shall conform to TIOH Hard Enamel Color Chip Numbers listed below.

COLOR	CHIP NO.
Blue	18
White	28

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer. When epoxy resin is used in lieu of hard enamel, the material requirement shall be gilding metal or red brass.

4. The device shall be soft soldered to the base in the location shown.

5. Decoration set shall consist of a regular size medal and a service ribbon all packaged in a presentation case conforming to MIL-DTL-14633, Type XV, Style 1 with a Class 1 or 1A pad.

6. The ribbon for the pendant drape and service ribbon shall conform to MIL-DTL-11589/169.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T23:14Z
Check the source to verify that this is the current version before use.

Custodians:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0978)

Civil Agency Coordinating Activities:
DOT - ACO

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T23:14Z
Check the source to verify that this is the current version before use.