MIL-C-12517 A(EL)
13 September 1965
Superseding
MIL-C-12517 (SigC)
4 March 1953

MILITARY SPECIFICATION

CASE, HYDROGEN GENERATOR SET (CASE CY-219( )/TMQ-3)

1. SCOPE

1.1 This specification covers one type of Plywood Case Designated as Case CY-219( )/TMQ-3, for transporting components and running spare parts of Hydrogen Generator Set AN/TMQ-3.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-B-601	Boxes, Wood, Cleated-Plywood
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	Box, Fiberboard
PPP-T-76	Tape, Pressure - Sensitive Adhesive Paper

MILITARY

MIL-P-116	Preservation, Methods of.
MIL-M-13231	Marking of Electronic Items.
MIL-F-14072	Finishes for Ground Signal Equipment.

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking of Shipments.

FSC-3655

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:54Z
Check the source to verify that this is the current version before use.

DRAWINGS

ELECTRONICS COMMAND

SC-DL-86464 Case CY-219( )/TMQ-3

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer. Both the title and number or symbol should be stipulated when requesting copies.

3. REQUIREMENTS

3.1 Description. - Case CY-219( ) TMQ-3 is a Plywood Case compartmented to hold 4 Hydrogen Generator ML-303/TM, Manifold ML-344/TMQ-3, Hose ML-81 and running spare parts. Metal reinforced on all edges and corners. Has 1 carrying handle and secured by 4 trunk catches. Dimensions approximately 12 in. x 18 in. x 27 in; Weight approximately 20 pounds.

3.2 Preproduction Samples. - The contractor shall furnish two preproduction samples for approval, if required by the invitation for bids and contract.

3.3 Construction. - Case CY-219( ) TMQ-3 shall be constructed in accordance with Drawing and Data List SC-DL-86464.

3.4 Parts, materials, and processes; general. - Parts, materials and processes shall be such as to enable the equipment to meet its performance and other requirements, as specified herein.

3.5 Ruggedness. - The case shall meet the bounce and shock test of Table 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:54Z
Check the source to verify that this is the current version before use.

TABLE 1 - BOUNCE & SHOCK

Paragraph Heading	Test Paragraph	
Bounce	4.9	No physical damage except surface abrasions.
Shock, drop	4.10	No damage which will limit proper use, i.e., splitting, or checking, loosening of catches or hinges or any departure from the usual shape sufficient to prevent installation of equipment.

3.6 Finish. - The Case CY-219 ( ) TMQ-3 shall be finished in accordance with MIL-F-14072 and the equipment drawings. (See 4.4)

3.7 Marking. - Marking shall conform to MIL-M-13231 and the equipment drawings. (See 4.4)

3.8 Preconditioning. - The equipment shall be capable of meeting the requirements herein without subsequent processing after subjection to the bounce preconditioning of 4.6.

3.9 Fit of components. - The Case shall be capable of meeting the test specified in 4.8.

3.10 Interchangeability. - Like units, assemblies, subassemblies, and replacable parts shall be physically and functionally interchangeable, without modification of such items or of the equipment. (See 4.11) Individual items shall not be hand-picked for fit or performance; however, matched pairs or sets, when permitted, may be interchangeabl e as such. Reliance shall not be placed on any unspecified dimension, rating, characteristic, etc.

3.11 Workmanship. - The Case shall be manufactured and assembled in accordance with the applicable portions of the following paragraphs herein:

3.3 Construction
3.4 Parts, materials and processes; general
3.6 Finish
3.7 Marking

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:54Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. - Unless otherwise specified in the contract, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Classification of inspection. - Inspection shall be classified as follows:

(a) Preproduction inspection (does not include preparation for delivery) (See 4.3)

(b) Inspection covered by subsidiary documents. (See 4.4)

(c) Quality conformance inspection.

(1) Quality conformance inspection of equipment before preparation for delivery. (See 4.5)

(2) Quality conformance inspection of preparation for delivery. (See 4 12)

4.3 Preproduction inspection. - This inspection will be performed by the Government unless otherwise specified in the contract. It shall consist of the preproduction inspection specified in table II, the inspection specified in the subsidiary documents covering the items listed in 4.4, and the inspection specified for group A and group B, (See tables III and IV respectively).

TABLE II - PREPRODUCTION INSPECTION

Inspection	Req. Para.	Insp. Para.
Bounce	3.5	4.9
Shock, drop	3.5	4.10

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:54Z
Check the source to verify that this is the current version before use.

4.4 Inspection covered by subsidiary documents. - The following shall be inspected under the applicable subsidiary documents as part of the inspection of equipment before preparation for delivery:

item	where required
Finish	3.6
Marking	3.7

4.5 Quality conformance inspection of equipment before preparation for delivery. - The contractor shall perform the inspection specified in 4.4 and 4.5.1 through 4.5.2. This does not relieve the contractor of his responsibility for performing any additional inspection which is necessary to control the quality of the product and to assure compliance with all specification requirements. The Government will review and evaluate the contractor's inspection procedures and examine the contractor's inspection records. In addition the Government--at its discretion--may perform all or any part of the specified inspections, to verify the contractor's compliance with specified requirements. (See 6.3.) Test equipment for Government verification inspection shall be made available by the contractor. Each unit which will be subjected to group A or group B, except preproduction samples, shall be preconditioned after final assembly. (See 3.8.)

4.5.1 Group A inspection. - This inspection including sampling, shall conform to Table III and the inspection procedures of Standard MIL-STD-105, using the general inspection levels.

TABLE III - GROUP A INSPECTION

Inspection	Req. Para.	Insp. Para.	AQL MAJOR	AQL MINOR
Visual-Mechanical	3.11	4.7	1%	4%

4.5.2 Group B Inspection. - This inspection including sampling, shall conform to Table IV and to the procedures for small sample inspection of MIL-STD-105. The AQL shall be 6.5 percent defective and the inspection level shall be S-4 for normal, tightened, and reduced inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:54Z
Check the source to verify that this is the current version before use.

TABLE IV - GROUP B INSPECTION

Inspection	Req. Para.	Insp. Para.
Fit of components	3.9	4.8
Interchangeability	3.10	4.11

4.6 Bounce preconditioning. - The unit, with shock mounts (if any) removed or blocked, shall be placed in its normal operation position on the table of the Package Tester, Type 1000-SC, as made by the L.A.B. Corporation, Skaneatales, New York, or equal. The package tester, shafts in phase, shall have a speed such that it is just possible to insert a 1/32-inch-thick strip of material under one corner or edge or the unit to a distance of 3 inches as the unit bounces. The unit shall be subjected to this preconditioning for 1 minute. After bounce preconditioning, the unit shall not be repaired, alined, cleaned, or otherwise changed prior to subjection to acceptance inspection.

4.7 Visual and mechanical inspection. - The Case shall be inspected for workmanship, mechanical fit, loose nuts, bolts and screws, marking and miscellaneous defects. All catches and hinges shall be checked for good mechanical fit.

4.8 Fit of components. - The Case shall be packed with the components to be housed in it to determine whether the components fit satisfactorily.

4.9 Bounce test. - The Case (with contained equipment), shall be placed on the table of the Package Tester as made by the L.A.B. Corporation, Summit, New Jersey, or equal, and shall be constrained from horizontal motion of more than 2 inches by suitable wooden fences. The package tester, shafts in phase, shall be operated at a speed of 285 r.p.m. + 1 percent for a total of 3 hours. During each 1/2 hour period of the test, the Case (with contained equipment) shall rest on a different face.

4.10 Drop test. - The Case (with contained equipment), shall be dropped a distance of 4 feet on each corner, edge, and face (total of 26 drops). Drops shall be made from a quick-release hook; an Acme Drop Tester, or equal; a conbur tester (10-degree inclined plane), or equal; or a basket-type pendulum tester. The floor or barrier receiving the impact shall be 2-inch fir, backed by concrete or a rigid steel frame.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:54Z
Check the source to verify that this is the current version before use.

4.11 Inspection for dimentional interchangeability. - The dimensions listed below shall be gaged or measured to determine conformance to the physical interchangeability requirements of 3.10. When a listed dimension is not within specified or design limits, it shall be considered a major defect.

(a) Dimensions of compartments, when such dimensions affect insertion of items specified in 3.1.

4.12 Quality conformance inspection of preparation for delivery. - Preparation for delivery shall be inspected in accordance with Specification MIL-P-116 to determine conformance to the requirements of section 5.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. -

5.1.1 Level A. - Case CY-219/TMQ-3, shall be preserved and packaged in accordance with the procedures specified for the designated methods as prescribed in specification MIL-P-116, and as follows:

5.1.1.1 Package each case Method IC-5, as follows; Cushion all protruding hardware and corners of the case with flexible corrugated paper securing the cushioning with suitable tape. Place each cushioned case within a W6C fiber board box, conforming to Specification PPP-B-636. Seal the entire box closure, corners and joints, with water-resistant, pressure-sensitive tape, conforming to Specification PPP-T-76.

5.1.2 Level B. - (Same as specified for Level A).

5.1.3 Level C. - Case CY-219/TMQ-3 shall be packaged in a manner that will afford adequate protection against corrosion, deterioration and damage during shipment from the supply source to the first receiving activity.

5.2 Packing. -

5.2.1 Case CY-219/TMQ-3, packaged as specified above shall be packed within the following type shipping containers, nailed wood, wood cleated plywood or fiberboard conforming to Specifications, PPP-B-621, PPP-B-601 or PPP-B-636. Shipping containers shall be closed and strapped as specified in the applicable box specification. The gross weight for fiberboard shall not exceed 65 pounds, wood boxes shall not exceed 200 .

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:54Z
Check the source to verify that this is the current version before use.

5.2.2 Level B. - Case CY-219/TMQ-3, shall be packed in shipping containers as specified in 5.2.1, except the containers shall be domestic type.

5.2.3 Level C. - Case CY-219/TMQ-3, shall be packed in a manner that will afford adequate protection against damage to the package and its contents during shipment from the supply source to the first receiving activity. Shipping containers shall comply with the rules and regulations of the common carrier as applicable to the mode of transportation.

5.3 Marking of unit packages and shipping containers shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. - Procurement documents should specify the following:

(a) Title, number, and date of this specification and any amendment thereto.
(b) Type required.
(c) Level of packaging and level of packing required for shipment. (Level A, level B, or level C.)
(d) The specific paragraphs of section 5 which are applicable to the particular procurement.
(e) Preproduction inspection
(1) Sample quantity (See 3.2)
(f) Marking and shipping of samples.
(g) Place of final inspection

6.2 The parenthesis in the nomenclature will be deleted or replaced by a letter identifying the particular design; for example: CY-219/TMQ-3. The contractor should apply for nomenclature in accordance with the applicable clause in the contract. (See 1.1)

6.3 Verification inspection. - Verification by the Government will be limited to the amount deemed necessary to determine compliance with the contract and will be limited in severity to the definitive quality assurance provisions established in this specification and the contract. The amount of verification inspection by the Government will be adjusted to make maximum utilization of the contractor's quality control system and the quality history of the product.

CUSTODIAN
ARMY-EL
REVIEW ACTIVITIES
AF-13,

PREPARING ACTIVITY
ARMY-EL
PROJECT NO. 3655-0016

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:54Z
Check the source to verify that this is the current version before use.

To detach this form, cut along this line

SPECIFICATION ANALYSIS SHEET

Form Approved Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION		
ORGANIZATION		CITY AND STATE
CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4 REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1426
1 APR 63

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:54Z
Check the source to verify that this is the current version before use.