MILITARY SPECIFICATION

HEADSETS ELECTRICAL (HEADSETS ELECTRICAL H-16( )/U AND HEADSET H-65( )/U)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for two types of headsets designated respectively as headsets electrical H-16( )/U and headset electrical H-65( )/U (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

NN-P-71	- Pallets, Materials Handling, Wood, Double Faced, Stringer Construction.
QQ-S-571	- Solder, Tin Alloy: Tin-Lead Alloy; and Lead Alloy.
QQ-S-781	- Strapping, Steel, Flat and Seals.
PPP-B-566	- Boxes, Folding, Paperboard.
PPP-B-585	- Boxes, Wood, Wirebound.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-B-676	- Boxes, Set-up.
PPP-T-60	- Tape: Packaging, Waterproof.
PPP-T-76	- Tape, Pressure-Sensitive Adhesive Paper, (For Carton Sealing).

MILITARY

MIL-T-27	- Transformers and Inductors (Audio, Power, and High-Power Pulse), General Specification for.
MIL-P-116	- Preservation-Packaging, Methods of.
MIL-T-152	- Treatment, Moisture-and Fungus-Resistant, of Communications, Electronic, and Associated Electrical Equipment.
MIL-P-642	- Plugs, Telephone, and Accessory Screws; General Specification for.
MIL-F-14072	- Finishes For Ground Signal Equipment.
MIL-C-45662	- Calibration System Requirements.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-147	- Palletized Unit Loads on 40" x 48" Pallets.
MIL-STD-202	- Test Methods for Electronic and Electrical Component Parts.
MIL-STD-454	- Standard General Requirements for Electronic Equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:52Z
Check the source to verify that this is the current version before use.

DRAWINGS

DEPARTMENT OF THE ARMY

SC-D-7724 - Receiver R-30-U
SC-D-14636 - Transformer
SC-DL-11534 - Drawing and Data List for Headset Electrical H-16( )/U.
SC-DL-11537 - Cord.
SC-DL-14630 - Cord.
SC-DL-14636 - Earcup MX-240( )/U and MX-239( )/U.
SC-DL-14647 - Headset H-16( )/U Frequency.
SC-DL-24222 - Drawing and Data List for Headset H-65( )/U.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Qualification. Headsets furnished under this specification shall be products which are qualified for listing on the applicable qualified products list at the time set for opening of bids (see 4.6 and 6.3).

3.2 Materials. Materials shall be as specified herein. However, when a definite material is not specified, a material shall be used which will enable the headsets to meet the performance requirements of this specification. Acceptance or approval of any constituent material shall not be construed as a guaranty of the acceptance of the finished product.

3.2.1 Metals. The metals used shall be of proper alloy and hardness necessary to provide the required strength and rigidity with the maximum strength to weight ratio. Metals shall be of a corrosion-resistant type or shall be treated in accordance with MIL-F-14072, type II (sheltered).

3.2.2 Fungus-resistant materials. Headsets shall be made of fungus-resistant materials as specified in requirement 4 of MIL-STD-454, or shall be treated to resist fungus growth as specified in MIL-T-152, type II.

3.2.3 Solder. Solder shall conform to composition Sn60 of QQ-S-571.

3.3 Design and construction.

3.3.1 Headsets. Headset H-16( )/U shall be constructed in accordance with drawing and data list SC-DL-11534. Headset H-65( )/U shall be constructed in accordance with drawing and data list SC-DL-24222.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:52Z
Check the source to verify that this is the current version before use.

3.3.2 Receiver R-30-U (see Electronics Command drawing SC-D-7724).

3.3.2.1 Receiver unit. The receiver unit shall consist of a diaphragm, permanent magnet and associated pole pieces, and coils or cords. The magnet pole pieces and coils shall be housed in a brass container. The back of the container shall be completely sealed.

3.3.2.2 Diaphragm. The diaphragm shall be constructed of Permendur or equivalent.

3.3.2.3 Permanent magnet. The permanent magnet shall be of precipitation-hardening alloy (alnico) or approved equivalent: cast or sintered, heat treated, and aged in accordance with the best commercial practice.

3.3.2.4 Coil. The coil of the receiver shall be wound with class HF (heavy) Formex wire, as made by the General Electric Company, or equivalent. The area of the wire shall be not smaller than 9.9 circular mils (No. 40 AWG). If coils are used in the construction of the receiver unit, the wire shall be continuous (without splice) from the start of the first coil to the end of the second coil.

3.3.3 Earcups. Earcups MX-239( )/U and MX-240( )/U shall be in accordance with SC-DL-14636.

3.3.4 Cord. The cord shall be in accordance with SC-DL-11537 and SC-DL-14630.

3.3.5 Plugs. Plugs PJ-054B and PJ-051 used in this equipment shall have been tested and have passed the qualification tests specified in MIL-P-642.

3.3.6 Spare inserts. Two spare inserts shall be furnished, packed in a fiberboard tube having a wall thickness of 1/16 inch and placed in a small paper envelope attached to the headset cord. Each envelope shall be marked as follows: "2 each, Insert for Headset." Envelope shall be 2 x 3 inches, flap unglued, and of a good grade manila.

3.3.7 Transformer. The transformer shall be in accordance with Electronics Command drawing SC-D-14636 and MIL-T-27.

3.4 Performance characteristics.

3.4.1 Headband. When tested as specified in 4.8.2, no permanent deformation or damage shall occur.

3.4.2 Frequency response. When tested as specified in 4.8.3, the average response in dB above .0002 Dyne per sq cm shall be as shown in table I. The acoustic output of each receiver unit and coupling tube assembly as indicated by the sound pressure measuring equipment, shall be not more than 4.0 dB below the average response given to table I for frequencies from 2,400 to 3,000 Hz. The maximum allowable difference in response between any two frequencies separated by 100 Hz shall be not more than 3.5 dB for any four frequencies in the range from 400 to 2,400 Hz. At all the other frequencies in this range, the difference in response shall be not more than 2.5 dB. In the range from 2,400 to 3,000 Hz the difference in response shall be not more than 5.0 dB.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:52Z
Check the source to verify that this is the current version before use.

TABLE I. Frequency response.

Frequency Hz	Average response in dB above .0002 dyne per sq cm.
400	115
600	115
800	114
1000	112
1200	112
1400	113
1600	115
1800	115
2000	112
2200	110
2400	108
2600	104
2800	97
3000	91

3.4.3 Impedance. When tested as specified in 4.8.4, the impedance of the transformer receiver unit combination shall be acceptable if the voltage is within the limits of 1.6 and 2.4 volts.

3.4.4 Acoustical quality (listening). When the earphone is tested as specified in 4.8.5, the acoustic output shall be free from serious objectionable distortion, spurious sounds, buzzing, or rattling sounds over the audio frequency range from 200 to 4,000 Hz.

3.4.5 Dielectric withstanding voltage. When the headset is tested as specified in 4.8.6, the cord shall withstand 1,000 volts dc applied between the tip of the plug and the metal portions of the headband for 1 minute. There shall be no arcing or breakdown of the insulation.

3.4.6 Insulation resistance. When the headset is tested as specified in 4.8.7, the insulation resistance shall be not less than 1 megohm.

3.4.7 Overvoltage/endurance. When tested as specified in 4.8.8, there shall be no audible rattles or other signs of failure, and the frequency response shall not vary more than ±3 dB from the values shown in table I.

3.4.8 Immersion. When the headset is tested as specified in 4.8.9, there shall be no more than 2 or 3 drops of water having leaked into the earcup casting cavity. Upon reassembly the headset shall be operative.

3.4.9 Bounce. When tested as specified in 4.8.10, there shall be no mechanical damage and the degradation in response shall not exceed ±3 dB from the values shown in table I.

3.4.10 Cord test. When the headset is tested as specified in 4.8.11, the cord shall be capable of withstanding a pull of 12 pounds without resultant damage to cord or plug. The dc resistance of the cord when checked during continuity shall be as follows:

(a) Headset H-16( )/U. Between tip and sleeve of plug - Not more than 0.13 ohms.
(b) Headset H-65( )/U.
  (1) Between tip and sleeve of plug - Not more than 0.82 ohms.
  (2) Between the ring and sleeve - Not more than 0.84 ohms.

3.4.11 Random drop. When the headset is tested as specified in 4.8.12, there shall be no mechanical failure such as cracking or breaking of parts. Minor chipping of plastic parts shall not constitute a failure. The degradation in response shall not exceed ±3 dB from the values shown in table I.

3.4.12 Thermal shock. When tested as specified in 4.8.13, there shall be no evidence of warping or mechanical damage. The degradation in response of the earphones shall not exceed ±3 dB from the values shown in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:52Z
Check the source to verify that this is the current version before use.

3.4.13 Moisture resistance. When the headset is tested as specified in 4.8.14, there shall be no loose or deformed parts or other damage. The degradation in response of the earphone shall not exceed ±3 dB from the values shown in table I.

3.4.14 Salt spray (corrosion). When tested as specified in 4.8.15, there shall be no evidence of harmful corrosive action or damage. Following test, the degradation in response shall not exceed ±3 dB from the values shown in table I.

3.4.15 Sand and dust. When tested as specified in 4.8.16, there shall be no damage to the headset that would impair its operation, nor shall there be a degradation of response of more than ±3 dB from the values shown in table I.

3.5 Marking. Headsets shall be marked in accordance with MIL-STD-130, with the type designation and the manufacturer's name or symbol.

3.6 Workmanship. Headsets shall be manufactured and processed to be uniform in quality and shall be free from defects that will affect life, serviceability, or appearance. Headsets shall provide satisfactory performance and shall not adversely affect the performance of the radio receiver or wire equipment in which the headset is intended to be used, when interconnected with and operated as part of that equipment.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Test equipment and inspection facilities. Test and measuring equipment and inspection facilities of sufficient accuracy, quality and quantity to permit performance of the required inspection shall be established and maintained by the supplier. The establishment and maintenance of a calibration system to control the accuracy of the measuring and test equipment shall be in accordance with MIL-C-45662.

4.2 Classification of inspection. The inspections herein are classified as follows:

(a) Materials inspection (see 4.3).
(b) Components inspection (see 4.4).
(c) Qualification inspection (see 4.6).
(d) Quality conformance inspection (see 4.7).

4.3 Materials inspection. Materials inspection shall consist of certification supported by verifying data that the material listed in table II, used in fabricating the earphone element, is in accordance with the specification prior to such fabrication.

TABLE II. Materials inspection.

Material	Requirement paragraph	Applicable specification
Solder	3.2.3	QQ-S-571

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:52Z
Check the source to verify that this is the current version before use.

4.4 Components inspection. Components inspection shall consist of certification supported by verifying data that the components listed in table III, used in the headsets, are in accordance with the applicable referenced document.

TABLE III. Components inspection.

Component	Requirement paragraph	Applicable document
Earcup MX-239( )/U and MX-240( )/U	3.3.3	SC-DL-14636
Cord	3.3.4	SC-DL-11537 SC-DL-14630
Plugs	3.3.5	MIL-P-642
Transformer	3.3.7	MIL-T-27 SC-D-14636

4.5 Inspection conditions. Unless otherwise specified herein, all inspections shall be performed in accordance with the test conditions specified in the "GENERAL REQUIREMENTS" of MIL-STD-202.

4.6 Qualification inspection. Qualification inspection shall be performed at a laboratory acceptable to the Government (see 6.3) on sample units produced with equipment and procedures normally used in production.

4.6.1 Sample size. Six headsets shall be subjected to qualification inspection.

4.6.2 Inspection routine. The sample shall be subjected to the inspections specified in table IV in the order shown. All sample units shall be subjected to the inspections of group I. The sample shall then be divided equally into two groups of three units each and subjected to the inspection for their particular group.

TABLE IV. Qualification inspection.

Examination or test	Requirement paragraph	Method paragraph
Group I		
Visual and mechanical examination	3.2 to 3.3.7 incl, 3.5 and 3.6	4.8.1
Headband test	3.4.1	4.8.2
Frequency response	3.4.2	4.8.3
Impedance	3.4.3	4.8.4
Acoustical quality (listening)	3.4.4	4.8.5
Group II		
Dielectric withstanding voltage	3.4.5	4.8.6
Insulation resistance	3.4.6	4.8.7
Overvoltage/endurance	3.4.7	4.8.8
Immersion	3.4.8	4.8.9
Bounce	3.4.9	4.8.10
Group III		
Cord test	3.4.10	4.8.11
Random drop	3.4.11	4.8.12
Thermal shock	3.4.12	4.8.13
Moisture resistance	3.4.13	4.8.14
Salt spray (corrosion)	3.4.14	4.8.15
Sand and dust	3.4.15	4.8.16

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:52Z
Check the source to verify that this is the current version before use.

4.6.3 Failures. One or more failures shall be cause for refusal to grant qualification approval.

4.6.4 Retention of qualification. To retain qualification, the supplier shall forward a report at 12-month intervals to the qualifying activity. The qualifying activity shall establish the initial reporting date. The report shall consist of:

(a) A summary of the results of the tests performed for inspection of product for delivery, (components inspection, groups A and B), indicating as a minimum the number of lots that have passed and the number that have failed. The results of tests of all reworked lots shall be identified and accounted for.
(b) A summary of the results of tests performed for qualification verification inspection (group C), including the number and mode of any subgroup failures. The summary shall include results of all qualification verification inspection tests performed on completed lots during the 12-month period. If the summary of the test results indicates nonconformance with specification requirements, and corrective action acceptable to the qualifying activity has not been taken, action may be taken to remove the failing product from the qualified products list.

Failure to submit the report within 60 days after the end of each 12-month period may result in loss of qualification for the product. In addition to the periodic submission of inspection data, the supplier shall immediately notify the qualifying activity at any time that the inspection data indicates noncompliance of product to meet the requirements of this specification.

In the event that no production occurred during the reporting period, a report shall be submitted certifying that the company still has the capabilities and facilities necessary to produce the item. If during two consecutive reporting periods there has been no production, the manufacturer may be required, at the discretion of the qualifying activity, to submit the products to testing in accordance with the qualification inspection requirements.

4.7 Quality conformance inspection.

4.7.1 Inspection of product for delivery. Inspection of product for delivery shall consist of components inspection (see table III), and groups A and B inspections.

4.7.1.1 Inspection lot. An inspection lot shall consist of all headsets of the same type designation, produced under essentially the same conditions, and offered for inspection at one time.

4.7.1.2 Group A inspection. Group A inspection shall consist of the examination and test specified in table V, in the order shown.

4.7.1.2.1 Sampling plan. Statistical sampling and inspection shall be in accordance with MIL-STD-105 for general inspection level II. The acceptable quality level (AQL) shall be as specified in table V. Major and minor defects shall be as defined in MIL-STD-105.

4.7.1.2.2 Rejected lots. If an inspection lot is rejected, the supplier may rework it to correct the defects, or screen out the defective units, and resubmit for reinspection. Resubmitted lots shall be inspected using tightened inspection. Such lots shall be separate from new lots, and shall be clearly identified as reinspected lots.

TABLE V. Group A inspection.

Examination or test	Requirement paragraph	Test method paragraph	AQL (percent defective)	
			Major	Minor
Visual and mechanical	3.2 to 3.3.7 incl, 3.5 and 3.6	4.8.1	1.0	4.0
Headband test	3.4.1	4.8.2	1.0	4.0
Acoustical quality 1/	3.4.4	4.8.5	1.0	none

1/ 100 percent inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:52Z
Check the source to verify that this is the current version before use.

4.7.1.3 Group B inspection. Group B inspection shall consist of the tests specified in table VI, and shall be made on sample units which have been subjected to and have passed the group A inspection.

4.7.1.3.1 Sampling plan. The sampling plan shall be in accordance with MIL-STD-105 for special inspection level S-4. The AQL shall be 6.5 percent defective.

4.7.1.3.2 Rejected lots. If an inspection lot is rejected, the supplier may rework it to correct the defects, or screen out the defective units, and resubmit for reinspection. Resubmitted lots shall be inspected using tightened inspection. Such lots shall be separate from new lots, and shall be clearly identified as reinspected lots.

TABLE VI. Group B inspection.

Examination or test	Requirement paragraph	Test method paragraph
Frequency response Impedance	3.4.2 3.4.3	4.8.3 4.8.4

4.7.1.3.3 Disposition of sample units. Sample units which have passed all the group B inspection may be delivered on the contract or purchase order, if the lot is accepted and the sample units are still within specified electrical tolerances.

4.7.2 Group C inspection. Group C inspection shall consist of the examinations and tests specified in table VII, in the order shown. Group C inspection shall be made on sample units selected from inspection lots which have passed the groups A and B inspection.

4.7.2.1 Sampling plan. Group C inspection shall be performed once each month on six sample units selected without regard to their quality from units produced during the period or each 2,000 units, whichever occurs first. The sample shall be divided equally into two groups and subjected to the tests of subgroups 1 and 2 of table VII.

4.7.2.2 Failures. If one or more sample units fail to pass group C inspection, the sample shall be considered to have failed.

4.7.2.3 Disposition of sample units. Sample units which have been subjected to group C inspection shall not be delivered on the contract or purchase order.

4.7.2.4 Noncompliance. If a sample fails to pass group C inspection, the supplier shall take corrective action on the materials or processes, or both, as warranted, and on all units of product which can be corrected and which were manufactured under essentially the same conditions, with essentially the same materials, processes, etc., and which are considered subject to the same failure. Acceptance of the product shall be discontinued until corrective action, acceptable to the Government, has been taken. After the corrective action has been taken, group C inspection shall be repeated on additional sample units (all inspection, or the inspection which the original sample failed, at the option of the Government). Groups A and B inspections may be reinstituted; however, final acceptance shall be withheld until the group C reinspection has shown that the corrective action was successful. In the event of failure after reinspection, information concerning the failure and corrective action taken shall be furnished to the cognizant inspection activity and the qualifying activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:52Z
Check the source to verify that this is the current version before use.

TABLE VII. Group C inspection.

Test	Requirement paragraph	Method paragraph
Subgroup I		
Dielectric withstanding voltage	3.4.5	4.8.6
Insulation resistance	3.4.6	4.8.7
Overvoltage/endurance	3.4.7	4.8.8
Immersion	3.4.8	4.8.9
Bounce	3.4.9	4.8.10
Subgroup II		
Cord test	3.4.10	4.8.11
Random drop	3.4.11	4.8.12
Thermal shock	3.4.12	4.8.13
Moisture resistance	3.4.13	4.8.14
Salt spray (corrosion)	3.4.14	4.8.15
Sand and dust	3.4.15	4.8.16

4.7.3 Inspection of preparation for delivery. The sampling and inspection of the preservation-packaging and interior package marking shall be in accordance with the group A and B quality conformance inspection requirements of MIL-P-116. The sampling and inspection of the packing and marking for shipment and storage shall be in accordance with the quality assurance provisions of the applicable container specification and the marking requirements of MIL-STD-129.

4.8 Methods of examination and test.

4.8.1 Visual and mechanical examination. Headsets, shall be examined to verify that the materials, design, construction, physical dimensions, finish, marking, and workmanship are in accordance with the applicable requirements (see 3.2 to 3.3.7 incl, 3.5 and 3.6).

4.8.2 Headband test (see 3.4.1). With the headband length adjusted for maximum headsize, pull the earcups apart until there is a distance of 11 inches between the lower inside edges of the cord clamps.

4.8.3 Frequency response (see 3.4.2). Earcup chassis assemblies shall be tested for response using the circuit and equipment shown on drawing SC-DL-14647. The voltage across the series combination of resistor and transformer primary winding shall be maintained constant at 4.0 volts for all frequencies in the test.

4.8.4 Impedance (see 3.4.3). After the sound pressure output of the receiver unit at 1,000 Hz has been determined, the voltage across the pin jacks of terminal block shall be measured.

4.8.5 Acoustical quality (listening) (see 3.4.4). A constant voltage having a root mean square (rms) value of 2.5 ±0.1 volts shall be applied to the earphones of the headset through the connector and the frequency varied continuously from 200 to 4,000 Hz and back to 200 Hz.

4.8.6 Dielectric withstanding voltage (see 3.4.5). The headset shall be tested in accordance with method 301 of MIL-STD-202. The following details shall apply:

(a) Test voltage - 1,000 volts.
(b) Nature of potential - 60 Hz.
(c) Points of application - On earphone between one of the terminals and the clamping ring, the metallic case, or other metallic surface which is not covered by a non-conducting coating. Simultaneously, the coil shall be excited with 9.5 volts rms at 200 Hz.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:52Z
Check the source to verify that this is the current version before use.

4.8.7 Insulation resistance (see 3.4.6). The headset shall be tested in accordance with method 302 of MIL-STD-202. The following details shall apply:

(a) Test potential - 500 volts ±10 percent at 60 Hz.
(b) Special preparations - The metal portion of the headband shall be clamped securely in such a way that the headband is effectively grounded. The test potential shall be applied to the tip of plug.
(c) Points of measurement - Between the tip of the plug and the metal portion of the headband.
(d) Electrification time - 1 minute.

4.8.8 Overvoltage/endurance (see 3.4.7). Ten volts at 400 Hz shall be applied directly across the earphone terminals for 10 hours. At the end of the test, the frequency response shall be measured as specified in 4.8.3.

4.8.9 Immersion (see 3.4.8). The headset shall be immersed in 6 inches of water for 10 minutes. After removal from the water, all exposed surfaces of the headset shall be wiped completely dry. The earcups shall be completely disassembled and examined for moisture.

4.8.10 Bounce (see 3.4.9). The equipment shall be placed on the table of the package tester as made by L.A.B. Corp., Skaneateles, N.Y., or equal. The equipment may be loosely constrained by wood cleats. The package tester, shafts in phase, shall be run at a speed of 285 revolutions per minute (rpm) ±1 percent for 3 hours. The equipment shall be examined for damage and the frequency response shall be measured as specified in 4.8.3.

4.8.11 Cord test (see 3.4.10). After the cord has been assembled with the headband and the terminal panels have been connected and molded in place, the completed cord assembly shall be tested for compliance with 3.4.5 and then tested for continuity. A longitudinal tension of 12 pounds shall be applied to the plug. After tension is released the assembly shall be examined to insure that there has been no slippage between the cordage and the plug. The cord assembly shall then be tested for continuity as follows:

4.8.11.1 Headset H-16( )/U. With both terminal boards as shown on drawing SC-DL-14630 shorted together the dc resistance between tip and sleeve of plug PJ-054B shall be measured, using a suitable ohmmeter.

4.8.11.2 Headset H-65( )/U. With both contacts on each terminal board as shown on drawing SC-DL-11537 shorted, using a suitable ohmmeter the dc resistance of the cord shall be measured.

4.8.12 Random drop (see 3.4.11). The entire headset shall be dropped on a concrete floor a distance of 6 feet above the floor. At the discretion of the supplier, the floor may be covered with one layer of floor tile. The headset shall be dropped one time in each of three planes for a total of three times. The frequency response shall be measured as specified in 4.8.3, and the headset shall be examined for damage.

4.8.13 Thermal shock (see 3.4.12). The equipment shall be tested in accordance with method 107 of MIL-STD-202. The following details shall apply:

(a) Test condition letter - A.
(b) Measurements after cycling - The equipment shall be examined for damage and the frequency response shall be measured as specified in 4.8.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:52Z
Check the source to verify that this is the current version before use.

4.8.14 Moisture resistance (see 3.4.13). The headset shall be tested in accordance with method 106 of MIL-STD-202. The following details shall apply:

(a) Mounting - Any convenient mounting with the front face of the earcups exposed and parallel with the vertical plane.
(b) Polarizing voltage - Not applicable.
(c) Step 7b - Not applicable.
(d) Final measurements - At the completion of the tenth cycle and following a 24-hour period at 25 ±5°C and 50 ±5 percent relative humidity, the headset shall be tested for frequency response in accordance with 4.8.3 and examined for loose or deformed parts or other damage.

4.8.15 Salt spray (corrosion) (see 3.4.14). Headsets shall be tested in accordance with method 101 of MIL-STD-202. The following details and exceptions shall apply:

(a) Applicable salt solution - 5 percent.
(b) Test condition letter - B.
(c) Additional conditioning - Headsets shall be dried for 48 hours at room ambient temperature and conditions.
(d) Measurements after drying period - As specified in 4.8.3.

4.8.16 Sand and dust (see 3.4.15). The headset shall be tested in accordance with method 110 of MIL-STD-202. The following details and exceptions shall apply:

(a) Test condition letter - B.
(b) Measurements after test - Examination for defects and the frequency response shall be measured as specified in 4.8.3 and the headset shall be examined for damage.

5. PREPARATION FOR DELIVERY

5.1 Preservation-packaging. Preservation-packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. Headsets shall be cleaned in accordance with MIL-P-116, process C-1.

5.1.1.2 Drying. Headsets shall be dried in accordance with MIL-P-116.

5.1.1.3 Preservative application. Preservatives shall not be used.

5.1.1.4 Unit packaging. Unless otherwise specified (see 6.2), headsets shall be individually packaged in accordance with MIL-P-116, submethod IA-15 insuring compliance with the general requirements paragraph under methods of preservation (unit protection) and the physical protection requirements therein. The container shall conform to PPP-B-566 or PPP-B-676.

5.1.1.5 Intermediate packaging. Not required.

5.1.2 Level C. Headsets shall be clean, dry and individually packaged in a manner that will afford adequate protection against corrosion, deterioration and physical damage during shipment from supply source to the first receiving activity.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. The packaged headsets shall be packed in fiberboard containers conforming to PPP-B-636, class weather resistant, style optional, special requirements. In lieu of the closure and waterproofing requirements in the appendix of PPP-B-636, closure and waterproofing shall be accomplished by sealing all seams, corners and manufacturer's joint with tape, two inches minimum width, conforming to PPP-T-60, class 1 or PPP-T-76. Banding (reinforcement requirements) shall be applied in accordance with the appendix to PPP-B-636 using nonmetallic or tape banding only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:52Z
Check the source to verify that this is the current version before use.

5.2.2 Level B. The packaged headsets shall be packed in fiberboard containers conforming to PPP-B-636, class domestic, style optional, special requirements. Closures shall be in accordance with the appendix thereto.

5.2.3 Level C. The packaged headsets shall be packed in shipping containers in a manner that will afford adequate protection against damage during direct shipment from the supply source to the first receiving activity. These packs shall conform to the applicable carrier rules and regulations.

5.2.4 Unitized loads. Unitized loads, commensurate with the level of packing specified in the contract or order, shall be used whenever total quantities for shipment to one destination equal 40 cubic feet or more. Quantities less than 40 cubic feet need not be unitized. Unitized loads shall be uniform in size and quantities to the greatest extent practicable.

5.2.4.1 Level A. Headsets, packed as specified in 5.2.1, shall be unitized on pallets in conformance with MIL-STD-147, load type I, with a fiberboard cap (storage aid 4) positioned over the load.

5.2.4.2 Level B. Headsets, packed as specified in 5.2.2, shall be unitized as specified in 5.2.4.1 except that the fiberboard caps shall be class domestic.

5.2.4.3 Level C. Headsets, packed as specified in 5.2.3, shall be unitized with pallets and caps of the type, size and kind commonly used for the purpose and shall conform to the applicable carrier rules and regulations.

5.3 Marking. In addition to any marking required by the contract or purchase order (see 6.2), each unit package, exterior container and unitized load shall be marked in accordance with MIL-STD-129.

5.4 General. Special requirements for Army procurements are specified in 5.4.2.

5.4.1 Exterior containers. Exterior containers (see 5.2.1, 5.2.2, and 5.2.3) shall be of a minimum tare and cube consistent with the protection required and shall contain equal quantities of identical stock numbered items to the greatest extent practicable.

5.4.2 Army procurements.

5.4.2.1 Level A unit packaging. MIL-P-116 submethod IC-2 shall be used in lieu of submethod IA-15 (see 5.1.1.4).

5.4.2.2 Level A and B packing. For level A packing when quantities per destination are less than a unitized load, the fiberboard containers shall not be banded but shall be placed in a close fitting box conforming to PPP-B-601, overseas type; PPP-B-621, class 2, style 4 or PPP-B-585, class 3, style 2 or 3. Closure and strapping shall be in accordance with the applicable container specification except that metal strapping shall conform to QQ-S-781, type I, finish A. When the gross weight exceeds 200 pounds or the container length and width is 48 x 24 inches or more and the weight exceeds 100 pounds, 3 x 4 inch skids (laid flat) shall be applied in accordance with the requirements of the container specification. If not described in the container specification, the skids shall be applied in a manner which will adequately support the item and facilitate the use of material handling equipment. For level B packing, fiberboard boxes shall be weather resistant as specified in level A and the containers shall be banded (see 5.2.1 and 5.2.2).

5.4.2.3 Level A and B unitization. For level A and B unitization, the fiberboard caps shall be weather resistant and softwood pallets conforming to NN-P-71, type IV, size 2 shall be used. The loads shall be bonded to the pallets by strapping conforming to QQ-S-781, type I, finish A or shrink film (see 5.2.4.1 and 5.2.4.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:52Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. Headset H-16( )/U is intended to be used in noisy locations such as tanks, tank destroyers, etc. Headset H-65( )/U is designed to be used with radar equipment where the operation is required to monitor two channels at the same time.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Levels of preservation-packaging and packing required (see 5.1 and 5.2).
(c) Method of preservation, if other than submethod IA-15 (see 5.1.1.4).
(d) Special marking, if required (see 5.3).

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are at the time set for opening of bids, qualified for inclusion in applicable qualified products list (QPL) whether or not such products have actually been so listed by that date. The attention of the suppliers is called to this requirement, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. The activity responsible for the qualified products list is the U.S. Army Electronics Command; however, information pertaining to qualification of products may be obtained from the Defense Electronics Supply Center (DESC-E), Dayton, Ohio 45444. Application for qualification tests shall be made in accordance with provisions governing qualification SD-6 (see 6.3.1).

6.3.1 Copies of "Provisions Governing Qualification SD-6" may be obtained upon application to Commanding Officer, Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

6.4 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Army -
Navy -
Air Force - 80
DSA - ES

User activities:
Army -
Navy - MC, AS, SH
Air Force -

Preparing activity:
Army - EL

Agent:
DSA - ES

(Project 5965-0103)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:52Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

☆ U.S. GOVERNMENT PRINTING OFFICE: 1973—714-866/3983 2-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:52Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Electronics Command
ATTN: AMSEL-RD-TS-S
Fort Mommouth, NM 07703

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:52Z
Check the source to verify that this is the current version before use.