MILITARY SPECIFICATION

SWITCHBOARD, TELEPHONE, MANUAL
SB-993( )/GT
(UNITS OF)

This amendment forms a part of Military Specification MIL-S-12479B(EL), dated 20 November 1963.

PAGE 8

4.7.1: Delete entire paragraph and substitute "Dielectric strength test. - (See 3.9.1) Subject the Adapter Connector U-184( )/GT to a potential of 400 volts either D.C. or peak 60 cycle A.C., for 10 seconds. Apply the potential between each terminal and the body of the plug, and then between each terminal connected together and the body of the plug. There shall be no visible evidence of breakdown or damage.".

4.7.2, line 3: Delete "less" and substitute "greater".

4.7.3: Delete entire paragraph and substitute "Visual signal operation test. - Apply 85 volts r.m.s., 17-20 cycles alternating current to the terminals of a completed Adapter, Connector U-184( )/GT with a non-inductive 9,000 ohm resistor across its terminals and a non-inductive 4,400 ohm resistor in series with the voltage source. Determine that the glow lamp provided in the adapter flashes continuously as required in 3.9.3.".

Preparing Activity
Army CR

PROJECT NUMBER 5805-A303

☆ U.S. GOVERNMENT PRINTING OFFICE: 1981 0 — 703-023/6465

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:51Z
Check the source to verify that this is the current version before use.