MILITARY SPECIFICATION

SPRAYER, PESTICIDE, FRAME-MOUNTED:

GASOLINE-ENGINE-DRIVEN, MIST AND SOLID STREAM,

360 GPH

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a 360-gallon-per-hour (gph) reciprocating-piston-pump-type, gasoline-engine-driven, frame-mounted, mist and solid stream, pesticide sprayer.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICAIONS

MILITARY

MIL-P-514	- plates, Identification, Instruction and Marking, Blank.
MIL-T-704	- Treatment and Painting of Materiel.
MIL-L-2104	- Lubricating Oil, Internal Combustion Engine, Tactical Service.
MIL-F-3541	- Fittings, Lubrication.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 3740

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:53Z
Check the source to verify that this is the current version before use.

MIL-G-3859	Grease Guns, Hand-Operated, Lever, Push and Screw Type.
MIL-G-10924	Grease, Automotive and Artillery.
MIL-S-12651	Sprayers, Packaging of.
MIL-G-23827	Grease, Aircraft and Instrument, Gear and Actuator Screw.
MIL-L-46167	Lubricating Oil, Internal Combustion Engine, Arctic.

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.
MIL-STD-130	Identification Marking of US Military Property.
MIL-STD-461	Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference.
MIL-STD-781	Reliability Tests: Exponential Distribution.
MIL-STD-1188	Commercial Packaging of Supplies and Equipment.
MIL-STD-1410	Methods for Selection of Industrial Engines for End Item Application.
MIL-STD-1474	Noise Limits for Army Materiel.

(Copies of specifications and standards required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

J429 - Mechanical and Material Requirements for Externally Threaded Fasteners.
J1046 - Exterior Sound Level for Small Engine Powered Equipment.

(Application for copies should be addressed to the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D380 - Rubber Hose, Testing.

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:53Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

AMERICAN WELDING SOCIETY, INC. (AWS)

D1.1 - Structural Welding Code, Section 5, Qualification.

(Application for copies should be addressed to the American Welding Society, Inc., 2501 N.W. 7th Street, Miami, FL 33125.)

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section IX, Welding Qualifications.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The sprayer shall be frame mounted to include carrying handles and hand crank hose reel mounted to the frame. The sprayer shall be pressurized by a piston-type pump that will be on the frame with the sprayer and shall be driven by a gasoline powered engine. The frame mounted sprayer system shall also include a pulsation dampening device, spray gun assembly, pressure relief valve, by-pass hose, suction hose with strainer, discharge hose, and engine fuel tank. A liquid reservoir tank will not be includes in the sprayer system. The weight of the sprayer and all components shall not exceed 300 pounds.

3.2 First article. when specified (see 6.2), the contractor shall furnish sample unit(s) for first article inspection and approval (see 4.3 and 6.4).

3.3 Material. All pesticide conveying parts shall be made of stainless steel, nylon, polyethylene, viton, polytetrafluroethylene, or other suitable corrosion resistant materials. Material not definitely specified shall be of best quality used for the purpose in commercial practice for similar applications. Material shall be free from all defects and imperfections that might affect the serviceability of the finished product (see 6.7).

3.4 Identical items. All sprayer units furnished under a specific contract shall be physically and mechanically identical, in that all parts, components,

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:53Z
Check the source to verify that this is the current version before use.

accessories, and subassemblies shall be interchangeable on all sprayer units. No deviation shall be acceptable without prior written approval from the contracting officer.

3.5 Capacity. The sprayer shall be capable of dispensing not less than 360 gallons per hour (gph) of liquid pesticide material at not less than 400 pounds per square inch (psi). The pressure gage shall have a range of 0 to 800 psi. The spray gun assembly shall be capable of operating at a pressure range of 0 to 800 psi with solid stream orifice adjustment. Two sets of three interchangeable nozzle tips or discs, with orifice sizes capable of solid stream dispersal of 56 through not less than 360 gph shall be provided with each unit. The discharge hose shall be at least 50 feet in length with a diameter of not less than 0.5 inch. The suction and bypass hoses shall be a minimum of 16 feet each. The suction hose shall be noncollapsible and not less than 1.5 inches in diameter. The bypass hose shall be not less than 1.5 inches in diameter.

3.6 Function. The sprayer system shall be capable of dispensing liquid pesticide material without malfunction of any component or control or leakage of air or liquid and shall meet all provisions of this specification.

3.7 Operation. The spray gun assembly shall be heavy duty, with trigger handle control and be capable of being coupled to the discharge hose. The sprayer shall be capable of operation when mounted on a carrier vehicle which is moving on unimproved roads and cross-country trails.

3.8 Performance. The sprayer shall perform as follows:

a. Operate continuously (except for refueling) in an operational mode for the hours as specified in Section 4, using water or other liquid specified by the Government as spray material. The rate of spraying shall be varied during testing but will involve operating the sprayer at maximum pressure and application rate for not less than 8 hours and dispensing a minimum of 2500 gallons of spray material. The spray pattern produced shall vary from a wide angle mist to a solid stream.
b. Comply with the Environmental Protection Agency (EPA) requirements for dispensing registered pesticides labeled for pest control by liquid mist or solid stream dispersal as well as the Occupational Safety and Health Administration (OSHA) requirements for protection of Personnel operating the system.

3.8.1 Burst pressure. Any component or system pressurized shall be able to withstand a burst pressure of four times the maximum operating Pressure (see 4.5.2.5) or for pressure greater than 15 psi shall bear the appropriate ASME Code Symbol.

3.9 Noise limits.

3.9.1 Personnel noise. The noise level at the operator's station shall not exceed 85 dB(A) when tested in accordance with 4.5.2.8.1.

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:53Z
Check the source to verify that this is the current version before use.

3.9.1.1 Precautions (noise). Hearing caution signs shall be posted on equipment if the sound level exceeds 85dB(A) at the operator's position. Noise level of 85dB(A) may only be exceeded when it is beyond the present state-of-the-art. Caution signs, if required, shall state "CAUTION, HEARING PROTECTION REQUIRED WITHIN (SPECIFY) FEET". Specify the maximum distance in feet 85dB(A) is measured from the equipment. Plates shall be in accordance with MIL-P-514, Type III, Composition C, of Type I, Grade A, Class 1 materiel.

3.9.2 Exterior noise. The sprayer's noise level shall comply with MIL-STD-1474 when tested in accordance with 4.5.2.8.2.

3.10 Reliability. The specified Mean-Time-Between Failure (MTBF) shall be 120 hours when the sprayer is tested as specified in 4.5.2.9.

3.11 Maintenance ratio. The sprayer shall have a maintenance ratio of not more than 0.025. Maintenance ratio is defined as the ratio of the total active maintenance man-hours required (scheduled and unscheduled) to the total operating time. Man-hours for repair of replaced components and scheduled before-and-after operation checks are excluded. A maintenance schedule shall be furnished prior to the start of any testing (see 4.5.2.10).

3.12 Engine. For the purpose of selecting the engine, the sprayer shall be classified as a class I end item in accordance with MIL-STD-1410. The gasoline engine including all systems components and accessories, shall conform to MIL-STD-1410, Class 1, except as otherwise specified herein. The engine shall be not less than 5 horsepower and shall be capable of operating under all conditions specified herein when using fuels and lubricants specified herein and in MIL-STD-1410. @

3.12.1 Electromagnetic interference characteristics. When specified (see 6.2), the electromagnetic interference emission characteristics of the sprayer shall conform to MIL-STD-461, Class II (see 4.5.2.7).

3.12.2 Fuel tank. A fuel tank, sufficient to operate the engine not less than 60 minutes without refueling, and fuel lines shall be furnished. The fuel tank shall be located where spills or overflows cannot contact electrical components or hot surfaces.

3.13 Lubrication.

3.13.1 Lubricants. When applicable, the sprayer shall operate as specified herein when serviced with the following military lubricants:

Engine: MIL-L-2104 or MIL-L-46167.

Grease Lubrication: MIL-G-10924 or MIL-G-23827.

3.13.2 Lubrication fittings. Lubrication fittings shall conform to NIL-F-3541, Type I, II, or III. Fittings shall be located in a protected position and shall be accessible to a hand-operated grease gun conforming to

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:53Z
Check the source to verify that this is the current version before use.

MIL-G-3859 with a 10-inch flexible extension. Accessibility to fittings shall be provided without the removal or adjustment of accessories or parts. Panels and plates equipped with hand-operable, quick-disconnect fasteners may be removed to provide accessibility.

3.14 Treatment and painting. The portions of the sprayer normally painted shall be cleaned, treated, and painted in" accordance with MIL-T-704, Type A, color as specified (see 6.2).

3.15 Identification marking. The sprayer shall be identified in accordance with MIL-STD-130. The marking shall be applied to the sprayer on plates conforming to MIL-P-514, Type 1, Style 1, Composition C, of Type I, Grade A, Class 1 material, 0.020 inch thick.

3.16 Workmanship. The sprayer shall be clean and free from sand, dirt, fins, pits, scale, rust, burrs, sharp edges, cracks, poor or unsound welds, or any other defect that could impair its performance or serviceability.

3.16.1 Metal fabrication. Metal used in fabrication shall be free from kinks and sharp bends. The straightening of material shall be done by methods that will not cause injury to the material. Corners shall be square and true. Flame cutting, using tips suitable for the thickness of the steel may be employed instead of shearing and sawing. All bends shall be made with controlled means to insure uniformity of size and shape. Precaution shall be taken to avoid overheating. Heated steel shall be allowed to cool slowly. External surfaces shall be free of burrs, sharp edges and corners, except when sharp edges or corners are required or where they are not detrimental to safety.

3.16.2 Bolted connections. Boltholes shall be accurately formed and shall have the burrs removed. Washers or lockwashers shall be provided where necessary. Matching thread areas securing bolts conforming to SAE J429 or cap-screws shall be of sufficient strength to withstand the tensile strength of the bolt. All fasteners shall be correctly torqued and shall have full thread engagement. Bolts shall protrude not more than 2 full threads.

3.16.3 Welding. The surfaces of parts to be welded shall be free from rust, scale, paint, grease, mill scale that can be removed by chipping and wire brushing, and other foreign matter. Parent materials, weld filler metals, and fabrication techniques shall be as required to enable the sprayer to conform to the examination and test requirements specified in Section 4. Parts to be joined by fillet welds shall be brought into as close contact as possible and in no event shall be separated by more than 3/4 inch unless appropriate bridging techniques are used. Unless otherwise specified (see 6.2), the welding process used in fabrication of the sprayer shall be at the option of the contractor.

3.16.4 Welders. Before assigning any welder to manual welding work covered by this specification, the contractor shall provide the contracting officer with certification that the welder has passed qualification tests as prescribed by either of the following listed codes for the type of welding operations to be performed and that such qualification is effective as defined by the particular code:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:53Z
Check the source to verify that this is the current version before use.

Structural Welding Code, AWS D1.1, Qualification, Section 5.
Welding Qualifications of the ASME, Section IX.

* Contractors who only make horizontal welds need not qualify welders for "all position welding". Subject to approval by the Government, the contractor's standard welder qualification may be substituted in lieu of the above codes provided that the contractor's procedure is equivalent to the above codes. The contractor shall be responsible for determining that automatic welding equipment operators are capable of producing quality welds in accordance with AWS and ASME codes.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection comparison (see 4.6).
d. Inspection of packaging (see 4.7).

4.3 First article inspection. First article inspection shall be performed on one or more units (see 6.2). The inspection will be performed by the Government at a site selected by the Government. Failure of the first article to pass the examination and tests shall be cause for rejection. The first article may be a standard production unit from the contractor' s current inventory provided the unit meets the requirements of the specification and is representative of the manufacturing technique applicable to the remaining units to be furnished under the contract.

4.3.1 Examination. The first article sprayer shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The first article sprayer shall be tested as specified in 4.5.2. Failure of any test shall be cause for rejection.

4.4 Quality conformance inspection.

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:53Z
Check the source to verify that this is the current version before use.

4.4.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined for the major and minor defects specified in 4.5.1. AQL shall be 1.0 percent defective for major defects and 4.0 percent defective for minor defects.

4.4.3 Tests. Each sprayer shall be tested as specified in 4.5.2.3 except that pumping operations shall be conducted three times in lieu of 15 times and the operational time shall be 45 minutes in lieu of 8 hours- One out of every five units shall be tested as specified in 4.5.2.4. Failure of either of the tests shall be cause for rejection.

4.5 Inspection procedure.

4.5.1 Examinations The sprayer shall be examined as specified herein for the following defects:

Major

101. Assembly not complete or not correct.
102. parts or components missing or not as specified
103. Length of discharge, by-pass and suction hoses not as specified.
104. Material not as specified.
105. Lubrication devices not accessible or not as specified.
106. Electromagnetic interference suppression components and network not identical with approved model.
107. Safety provisions not as specified.
108. Leakage of any component.

Minor

201. Treatment and painting not as specified.
202. Identification marking not as specified.
203. Workmanship not as specified.

4.5.2 Tests.

4.5.2.1 Test preparation. Prior to the start of test, the sprayer shall be prepared in accordance with the manufacturer's instructions.

4.5.2.2 Road tests. Mount the sprayer on an appropriate vehicle and perform the following tests prior to the performance test specified in 4.5.2.3.

a. Unimproved roads. Drive the properly mounted sprayer 10 miles on unimproved roads at maximum safe speeds. The course shall consist of poorly maintained gravel and dirt roads with moderate washboarding, rutting, and occasional potholes. The sprayer will not be operated during this test.

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:53Z
Check the source to verify that this is the current version before use.

b. Cross-country trails with sprayer operating. The properly mounted sprayer shall be started up and adjusted for routine operation. The sprayer shall be operated continuously (except for refueling) in the nonspraying mode at designed operating engine speed for a 2-mile cross-country test in which the carrier vehicle will be driven at a safe speed, stopped, and the sprayer actuated to apply liquid for 3 - 5 minutes. This will be repeated 5 times. Inability of the sprayer to spray or failure of any component shall constitute failure of this test.

c. Failure of road tests. Examine the sprayer at the completion of each phase of the road test. The breaking or loosening of any fitting, seal, or other component that would cause the sprayer to malfunction shall constitute failure of any specified road test.

4.5.2.3 Performance. The sprayer shall pump liquid from the liquid tank at pump level through the spray gun with the bypass valve closed for a period of not less than 5 minutes. This procedure shall be repeated not less than 15 times, and the priming, pressure, and capacity of the pump shall be determined. The spray-gun valve shall be closed, the bypass valve shall be opened, and the liquid shall be pumped continuously for not less than 8 hours from the liquid tank, through the pump, and back to the tank. Inability of the pump to prime itself, discharge capacity of less than 360 gph at 400 psi, inability to build up a pressure of 200 psi within 1 minute with the spray-gun valve open, or leakage at the pump or fittings shall constitute failure of this test.

4.5.2.4 Spray gun assembly. One hundred gallons of liquid shall be pumped through the spray gun at a pressure of 800 psi by a pressure source other than the pump, and the spray gun valve shall be turned on and off four times and examined. Cracking, splitting, or leakage of any component of the spray gun assembly shall constitute failure of this test.

4.5.2.5 Burst pressure. Hydrostatic pressure shall be applied as specified in ASTM D380 to determine conformance to the requirements of 3.8.1. A certificate of compliance shall be acceptable as proof that the product being offered meets the requirements of 3.8.1., provided the contractor furnishes actual test results, acceptable to the Government, indicating that tests have been performed to substantiate the certification. The certificate shall state that the tests described in this paragraph have been performed on products manufactured from the same material and manufacturing process as the items being offered and that any proposed changes in material or process will be promptly reported to the Government. The Government reserves the right to require additional testing and certification by the contractor when such changes are made or when otherwise deemed necessary. For pressures greater than 15 psi, the appropriate ASME code symbol shall be acceptable evidence of compliance.

4.5.2.6 Hose. Samples of hose, not less than 3 feet long, shall be subjected to a hydrostatic pressure of not less than 1200 psi for a period of not less than 1 minute. Any leaks, splits, collapse or permanent deformation shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:53Z
Check the source to verify that this is the current version before use.

4.5.2.7 Electromagnetic interference. The sprayer shall be tested to determine compliance with 3.12.1. The contractor shall furnish the contracting officer a report of tests required by MIL-sTD-461. Disapproval of the report shall constitute failure of this test.

4.5.2.8 Noise level measurement.

4.5.2.8.1 Personnel noise testing. The sprayer shall be tested in accordance with the provisions of MIL-STD-1474 for steady-state noise at personnel-occupied areas. Noise levels shall be taken while the system is at maximum rated output. The data should include dB(A) levels and octave band pressure levels taken at the operator's station. Duty cycle testing shall not be used.

4.5.2.8.2 Exterior noise testing. The sprayer shall be tested in accordance with the provisions for exterior noise of MIL-STD-1474. Test procedure SAE J1046 may be used as an alternate procedure.

4.5.2.8.3 Hazard precautions. Should the noise level exceed 85dB(A) at any operator position, and the excess noise level can be documented as being clearly beyond the stat-of-the-art, failure to provide the precautions specified in 3.9 shall constitute failure of this test.

4.5.2.9 Reliability. Using the MTBF specified in 3.10, the sprayer system shall be tested as specified herein with "accept" or "reject" criteria in accordance with MIL-STD-781, Test Plan IV. Mean-time-between-failure (MIBF) shall be 120 hours or better when the sprayer is tested as specified herein. MTBF shall be defined as the total number of test hours the sprayer is operating divided by the total number of failures during the measurement interval. Testing will continue until either an accept or reject decision is reached. A failure is defined as any malfunction that causes inability to commence spraying operation, cessation of spraying operation, degradation below the operating conditions required to continue testing, or safety hazard to personnel or equipment that cannot be corrected within 1 hour using controls, tools, or parts available at the test facility. Repair manuals, spare parts, and special tools shall be furnished prior to the start of any testing.

4.5.2.9.1 Test procedure. The sprayer shall be prepared for test in accordance with the provisions of 4.5.2.1 and tested in accordance with the provisions of 4.5.2.3. The sprayer shall be tested for a minimum of 250 hours of operation.

4.5.2.10 Maintenance support evaluation. Maintenance operation testing shall be accomplished to determine conformance to 3.11. Failure of the support elements to maintain the sprayer as specified shall constitute failure of this test. Errors or inadequacies in the manuals shall not be considered in assessing the maintenance ratio or the MTBF.

4.6 Inspection comparison. The Government may select sprayers at any time during the contract production period and subject these sprayers to the examination specified in 4.5.1 and the tests specified in 4.5.2 to determine conformance to the requirement of this specification. The inspection will be

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:53Z
Check the source to verify that this is the current version before use.

performed by the Government, at a site selected by the Government, on sprayers selected at random from those which have been accepted by the Government and will not include the previously inspected first article sprayers. In addition to any test specified as part of the inspection comparison, the Government reserves the right to conduct any and all other tests contained in this specification as part of the inspection comparison, and failure of such additional tests shall have the same effect as failure of those tests specified as inspection comparison.

4.6.1 Inspection failure. Failure of an inspection comparison sprayer to meet any requirement specified herein during and as a result of the examination and test specified in 4.6 shall be cause for rejection of the inspection comparison sprayer and shall be cause for refusal by the Government to continue acceptance of production sprayers until evidence has been provided by the contractor that corrective action has been taken to eliminate the deficiencies. Correction of such deficiencies shall be accomplished by the contractor at no cost to the Government on sprayers previously accepted and produced under the " contract. Any deficiencies found as a result of the inspection comparison will be considered prima facie evidence that all sprayers accepted prior to the completion of inspection comparison are similarly deficient unless evidence to the contrary is furnished by the contractor and such evidence is acceptable to the contracting officer.

4.7 Inspection of packaging. The preservation, packing and marking for level A or level B shall be examined and tested to determine compliance with the quality assurance provisions of MIL-S-1265L. The preservation, packing and marking for commercial shall be examined to determine compliance with MIL-STD-1188.

5. PACKAGING

5.1 Preservation. Preservation shall be level A, level B or commercial as specified (see 6.2).

5.1.1 Level A. Each complete sprayer shall be preserved in accordance with the level A preservation and packaging requirements of MIL-S-12651.

5.1.2 Level B. Each complete sprayer shall be preserved in accordance with the level B preservation and packaging requirements of MIL-S-12651.

5.1.3 Commercial. Each complete sprayer shall be preserved in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be level A, level B, or commercial as specified (see6.2).

5.2.1 Level A. Sprayers preserved as specified in 5.1, shall be packed in accordance the level A packing requirements of MIL-S-12651.

5.2.2 Level B. Sprayers preserved as specified in 5.1, shall be packed in accordance the level B packing requirements of MIL-S-12651.

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:53Z
Check the source to verify that this is the current version before use.

5.2.3 Commercial. Sprayers preserved as specified in 5.1, shall be packed in accordance with MIL-STD-1188.

5.3 Marking.

5.3.1 Military. Marking for military levels of protection (level A or B) shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Marking for commercial packaging shall be in accordance with MIL-STD-1188

6. NOTES

6.1 Intended use. The sprayer is intended to be used for handling all types of liquid pesticides.

6.2 Ordering data. Procurement documents should specifiy the following:

a. Title, number and date of this specification.
b. Date of issue of DoDISS applicable and exceptions thereto (see 2.1.1).
c. When sample units will be required for first article inspection and number of units required (see 3.2, 4.3 and 6.4).
d. When electromagnetic interference suppression is required (see 3.12.1).
e. Color required (see 3.14).
f. When welding process will not be at the option of the contractor (see 3.16.3).
g. Degree of preservation and degree of packing required (see 5.1 and 5.2).

6.3 Contract data requirements. When this specification is used in a procurement which incorporates a DD Form 1423 and invokes the provisions of paragraph 7-104.9(n) of the DAR, the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the Contract Data Requirements List (DD Form 1423) incorporated into the contract. When the provisions of DAR 7.104.9(n) are not invoked, the data shall be delivered in accordance with the contract requirements.

6.3.1 Data. The contracting officer should make provisions in the contract that the manufacturer provide a detailed operator's manual with each unit which includes installation, maintenance and operational instructions. The contracting officer should also assure that the manufacturer provides a detailed parts list, applicable to the model furnished, with each unit which includes parts numbers and the supply source for each.

6.4 First article. When a first article is required, it will be tested and approved under the appropriate provisions of paragraph 7-104.55 of the Defense Acquisition Regulation (DAR). The first article may be a standard production item from the contractor's current inventory as specified in 4.3. The first article should consist of the number of units specified (see 6.2). The contracting officer should include specific instructions in all procurement instruments, regarding arrangements for examinations, test and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:53Z
Check the source to verify that this is the current version before use.

6.5 Noise limits. When the noise level of the sprayer exceeds 85 dB(A), the appropriate discussion of the noise hazard in accordance with MIL-STD-1474 (MANUALS Paragraph) must include the requirement for hearing protection, the noise level of the sprayer, the distance from the sprayer at which 85 dB(A) will always be met, and what operational situation or system configuration will reduce the level to 85 dB(A).

6.6 Provisioning. The contracting officer should include provisioning requirements for repair parts and maintenance tools as necessary (including any special tools), and instructions on shipment of sprayers.

6.7 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.3).

6.8 Materiel deterioration prevention and control (MADPAC). The contracting officer should consider for inclusion in all applicable invitations for bid, requests for proposal, and contracts the following statement:

"The technical proposal shall provide assurance that all system/item parts shall be fabricated from compatible materials, suitably finished, to provide protection from corrosion and other forms of materiel deterioration. The assurance shall be in the form of a finish plan, utilizing state-of-art technology, which clearly identifies the specific finish or treatment to be used on the various components and assemblies, to provide protection against the various forms of materiel deterioration in the applicable operating and storage environments to which they may be exposed."

Custodians:
Army - ME
Navy - YD
Air Force - 99

Review activities:
Army - MD
Navy - MS
Air Force - 84
DLA - CS

User activity:
Navy - MC

Preparing activity:
Army - ME

Project 3744)-0111

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:53Z
Check the source to verify that this is the current version before use.

,RTMENT OF THE ARMY

OFFICIAL BUSINESS
.TY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY MOBILITY EQUIPMENT RESEARCH
AND DEVELOPMENT COMMAND
ATTN: DRDME-DS
FORT BELVOIR, VA 22060

Source: https://assist.dla.mil -- Downloaded: 202640-17T22:53Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-S-12511G Sprayer, Pesticide, Frame-Mounted: Gasoline-Engine-Driven, Mist and Solid Stream, 360 GPH

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202640-17T22:53Z
Check the source to verify that this is the current version before use.