INCH-POUND

MIL-T-12474D
30 September 1992
SUPERSEDING
MIL-T-12474C
31 March 1967

MILITARY SPECIFICATION

TABLE, DINING, 4-SEAT CAPACITY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type and size, 4-seat capacity dining table (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5017 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7105

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:51Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-26 - Bag, Plastic (General Purpose)
PPP-B-601 - Boxes, Wood, Cleated-Plywood
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner
PPP-B-636 - Boxes, Shipping, Fiberboard

STANDARDS

FEDERAL

FED-STD-141 - Paint, Varnish, Lacquer and Related Materials: Methods of Inspection, Sampling and Testing

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-130 - Identification Marking of U.S. Military Property
MIL-STD-147 - Palletized Unit Loads
MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking and Waterproofing; With Appropriate Test Methods

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-8-102 - Table, Dining, 4-Seat Capacity
5-8-130 - Table, Dining, 4-Seat Capacity, Method of Packing

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: SATNC-UX, Natick, MA 01760-5017.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:51Z
Check the source to verify that this is the current version before use.

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

UNITED STATES DEPARTMENT OF COMMERCE PUBLICATIONS

Product Standard PS-1 - Soft wood Plywood, Construction and Industrial

(Application for copies of Department of Commerce publications should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

NATIONAL ELECTRICAL MANUFACTURERS' ASSOCIATION (NEMA)

Publication LD-3 High Pressure Decorative Laminate

(Application for copies should be addressed to the National Electrical Manufacturers' Association, 2101 L Street N.W., Suite 300, Washington, DC 20037.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 707 - Cellulose Acetate Butyrate Molding and Extrusion Compounds
D 905 - Strength Properties of Adhesive Bonds In Shear By Compression Loading
D 3951 - Standard Practice for Commercial Packaging
D 4442 - Direct Moisture Content Measurement of Wood and Wood Base Material

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

HARDWOOD PLYWOOD MANUFACTURERS ASSOCIATION (HPMA)

HP-1 - Interim Voluntary Standard for Hardwood and Decorative Plywood
FE-86 - Voluntary Standard for Formaldehyde Emissions From Hardwood Plywood, Wall Paneling, Wood Composition Wall Paneling and Panels Having Face Veneers

(Application for copies should be address to the Hardwood Plywood Manufacturers Association, P.O. Box 2789, Reston, VA 22090.)

(Non-Government standards and other publications are normally available from organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:51Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Material. The materials shall conform to the referenced specifications and requirements specified herein. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.2.1 Lumber. Lumber shall be kiln-dried without brashness, case-hardening or honeycombing, to a moisture content of from 5 to 9 percent at time of fabrication as determined in accordance with 4.4.1.2.1. The lumber shall be plain or quarter sawn. The wood components shall be free from defects, except that the following will be permitted: (1) Sound, tight knots not exceeding 1/4 inch in greatest dimension and not less than 10 inches apart, (2) Sap stain or discoloration, provided that no more than two such defects appear in any one table; (3) Not more than two wormholes, 1/16 inch or less in diameter, provided that they are in a concealed surface. Slope (or divergence) of grain shall not exceed 1 inch in 10 inches on any one surface of a part.

3.2.1.1 Species and densities of lumber. Lumber shall be of any of the species listed in table I. When tested as specified in 4.5.1, the density of the species of lumber tested shall be equal to or greater than the density shown in table I. Densities shown in table I are based on oven dry weight and volume.

TABLE I. Species and densities of lumber

Species	Density (Pounds per cubic foot)
Alder, red	24.1
Ash, white	32.6
Beech	37.5
Birch, sweet yellow	37.0
Elm, American	30.8
Elm, cedar	30.8
Elm, rock	37.1
Elm, winged	30.8
Hackberry	31.5
Hickory	37.0
Holly	34.2

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:51Z
Check the source to verify that this is the current version before use.

TABLE I. Species and densities of lumber (cont'd)

Species	Density (Pounds per cubic foot)
Maple, big leaf	28.6
Maple, hard	38.2
Maple, silver	28.6
Oak, red or white	37.1
Pecan	38.7
Sweetgum red or sap	28.5
Sycamore	30.2

3.2.2 Plywood panels. Plywood panels shall be constructed of hard wood veneers, a combination of hard wood and soft wood veneers, or a combination of hard wood veneers and lumber core, as specified below. Face and back veneers for all constructions shall be close grained hard wood conforming to grades 1 or 2 veneers of Hardwood Plywood Manufacturers Association HP-1. The veneers shall be of such thickness as required to produce the finished top size and to produce a balanced panel to prevent warping.

3.2.2.1 Hard wood plywood panels. Hard wood plywood panels using all hard wood veneers shall be 5 ply minimum and shall be constructed in accordance with type II, grade 1 or 2 of HPMA HP-1.

3.2.2.2 Combination soft wood and hard wood plywood panels. Combination soft wood and hard wood plywood panels shall be either 5 or 7 ply and shall have inner plies of soft wood conforming to Group 1 interior type, grade A-B of Department of Commerce Product Standard PS-1.

3.2.2.3 Combination hard wood veneers and lumber core. Combination hard wood veneers and lumber core plywood panels shall be 3 ply minimum and shall be constructed with a lumber core of medium or low density hard wood, or Idaho or Ponderosa Pine, Spruce, or similar low density soft wood. Construction of the lumber core shall be in accordance with regular grade of HPMA HP-1. After lumber core has been glued, and prior to surfacing, the moisture content shall be stabilized to not less than 5 and not more than 9 percent when tested as specified in 4.4.1.2.1. Hard wood face and back veneer shall be as specified in 3.2.2. Crossbands, when used, shall be hard wood veneers conforming to grade 1 or 2 of HPMA HP-1. Veneers shall have an interior type bond and lumber core may be glued in accordance with manufacturer's standard practice.

3.2.2.4 Formaldehyde emission requirements. All plywood and wood veneered/plastic laminated panels shall meet Voluntary Standard HPMA FE-86 on formaldehyde emissions with the following changes:

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:51Z
Check the source to verify that this is the current version before use.

Under section III, Formaldehyde Emission Standards, Product Category, change "Industrial Panels" to "Furniture Panels greater than 0.25 inches thick, such as top panels." Formaldehyde emission requirements do not apply to hardboard panels.

3.2.3 Laminated, thermo-setting, decorative sheet. The laminated, thermo-setting, decorative sheet shall be not less than 0.05 inch thick and shall conform to type I (general purpose type) of National Electrical Manufacturers' Association (NEMA) Publication LD-3. The surface of the sheet shall have a satin finish. The color and grain shall be maple (see 6.3) and shall be approved by the contracting officer. Only one pattern shall be used in a single contract.

3.2.4 Backing sheets. The backing sheet shall be not less than 0.020 inch thick and conform to the type used in industry practice.

3.2.5 Cellulose acetate butyrate, extruded. The extruded, cellulose acetate shall conform to Group 1, Grade 2, Class 1 of ASTM D 707.

3.2.6 Adhesives. Adhesives shall be used for all assembly joints and for bonding the high pressure decorative laminate to the table top. The adhesive used shall have a minimum average block shear strength of 2,800 psi when tested as specified in 4.5.3. Hardwood plywood panels shall have a Type II bond or better in accordance with HPMA HP-1 when tested as specified in 4.5.3.

3.2.7 Glides. Glides shall be commercial type, of the size and construction shown on Drawing 5-8-102, fabricated of corrosion-resisting steel, or case hardened steel with a nickel or chromium protective coating. Glides shall be provided with a rubber insulator or cushion to protect the table against jars and vibration.

3.2.8 Hardware, miscellaneous. Bolts, washers, screws, rods, clips, cornerbracket (when used), and brads shall be steel, of the types and sizes specified on Drawing 5-8-102. All miscellaneous hardware shall be zinc or cadmium plated.

3.2.9 Lacquer or varnish. The lacquer or varnish shall be not less than 21 percent nonvolatile content just prior to application, when tested as specified in 4.4.1.1.

3.3 Construction. Tables shall be constructed in accordance with the design, details, dimensions, and materials, as shown on Drawing 5-8-102 and as specified herein. At the option of the contractor, the alternate corner construction shown on Drawing 5-8-102 may be used; and in lieu of the 12 steel clips used to secure the table top frame assembly, either of the following alternate methods may be used:

(a) Three screws through each apron into table top (total of 12 screws.)
(b) Two screws through each apron and two screws through each corner block into table top (total of sixteen screws).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:51Z
Check the source to verify that this is the current version before use.

When either of the above alternate methods is used, the screw holes in the aprons and corner blocks may be countersunk not greater than 1 inch. The table, when placed on a flat level surface, shall be rigid, shall not rock greater than 1/16 inch, and the table top shall be parallel within 3/16 inch to the flat level surface.

3.3.1 Sanding. All exposed surfaces of wood components shall be sanded smooth.

3.3.2 Gluing. The adhesive specified in 3.2.6 shall be used for all assembly joints. The adhesive shall be applied to joint surfaces in an adequate and uniform manner as recommended by the adhesive manufacturer. Open and closed assembly time and pressure shall be in accordance with the adhesive manufacturer's recommendations.

3.4 Component details.

3.4.1 Table top. The table top shall be fabricated from plywood specified in 3.2.2. A laminated, thermo-setting, decorative sheet specified in 3.2.3 shall be bonded to the top surface of the plywood panel. At the time of bonding, the moisture content of the plywood panel shall be from 5 to 9 percent as determined in accordance with 4.4.1.2.1. A backing sheet specified in 3.2.4 shall be bonded to the bottom surface of the plywood panel. All bonding shall be in accordance with 3.3.2. The sides of the plywood panel shall be edged with molding specified in 3.4.2. No seams or gaps shall appear on the face surfaces of the laminated, thermo-setting, decorative sheets. All edges shall be beveled or chamfered as shown on Drawing 5-8-102. The face surfaces of the laminated, thermo-setting, decorative sheets shall be free from mars; patched blistered, or rough areas; chips, cracks, pin holes and scratches. There shall be no delamination between the laminated, thermo-setting, decorative sheets and the plywood core. When viewed at a distance of 5 feet, discoloration, spotting, streaking, staining, surface waviness, swells, lapping of printed layer, depression mold marks, plywood imperfections and grain shall not be visible in the laminated, thermo-setting, decorative sheet. There shall be no warp greater than 1/8 inch in length or width of table top.

3.4.2 Molding. The molding, as shown on the drawing, shall be butyrate, plastic, flat profile as specified in 3.2.5. Molding shall be one piece, properly bent to the radii of the corners of the table top. The ends of the molding shall be cut square and shall be butt jointed. The molding shall be attached to the top by imbedding the barbed section into the saw kerf slot in the edge of the top in such a manner that there shall be no open gaps between the top edge of the molding and the edge of the laminated, thermo-setting, decorative sheet. In addition to the barbs, the molding shall be secured in place to the top with not less than one brad on either side of the joint. Brads shall be driven from the underside of the table top and through the barbed tongue of the molding. Molding is to be hand trimmed in such a manner to produce an eased edge. The molding shall be of a solid color to harmonize with the laminated, thermo-setting decorative sheet on the top, and shall be approved by the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 202640-17T22:51Z
Check the source to verify that this is the current version before use.

3.4.3 Aprons. Aprons shall be made from wood specified in 3.2.1. Only one specie of wood shall be used on a table. Aprons shall be either one piece, or edge glued using strips not less than 1-1/2 inch wide, providing a suitable grain match is achieved.

3.4.4 Legs. Legs shall be made from wood specified in 3.2.1, and shall be of the same specie as used for the aprons (see 3.4.3). Legs shall be either one piece, or laminated stock with no lamination less than 3/4 inch thick.

3.4.5 Corner blocks. Corner blocks shall be made from one piece of wood specified in 3.2.1 and shall be securely glued and screwed in place as shown on the drawing. When the alternate corner construction is used (see 3.3), the alternate corner bracket as shown on the drawing shall be used.

3.5 Finish. All of the wood surfaces shall be finished as specified in 3.5.1 through 3.5.3.

3.5.1 Appearance. The appearance of the legs and outer surfaces of the apron shall be uniform and the color shall match the laminated, thermo-setting, decorative sheet used on the table top (see 6.4).

3.5.2 Sanding. Prior to finishing, exposed surfaces of the legs and outer faces of the aprons shall be sanded smooth with a 5/0 or finer sandpaper, followed by thorough cleaning to remove sanding dust.

3.5.3 Finishing. After sanding, the legs and outer faces of the aprons shall be stained. Pores shall be filled if open grain wood is used. A coat of sanding sealer shall be applied. Lacquer or varnish specified in 3.2.9 shall then be applied in two full coats with intermediate drying. Sanding shall be done during finishing as required to produce a smooth finish. After four hours aging, a test portion of the final finish shall show no imprint when tested as specified in 4.5.2.1, and no spotting or softening when tested as specified in 4.5.2.2. A full coat of the same lacquer or varnish shall be applied to the accessible surfaces of corner blocks, lower edges and inner faces of aprons, sufficient in thickness to produce a gloss or semigloss appearance when dry.

3.6 Marking for identification. The underside of the table top shall be marked for identification in accordance with MIL-STD-130. The letters U.S. shall be not less than 1 inch high and all other markings shall be not less than 1/4 inch high.

3.7 Workmanship. Dining tables shall be free from defects such as fractures, splits, punctures, or dents. There shall be no sharp edges, slivers, burrs, or projections. The end item shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:51Z
Check the source to verify that this is the current version before use.

3.7.1 Glides. Glides shall be fastened to the table legs so that the bottom of the legs rest against the insulator or cushion to protect the table against jars and vibration.

3.7.2 Gluing. The outside of the glue joints shall be wiped free of excess glue.

3.7.3 Screws, wood and machine. Wood and machine screws shall be inserted the full depth.

3.7.4 Application of finish. The finish applied to the end item shall be continuous, smooth, adherent, without discoloration or foreign material embedded, and contain no runs, wrinkles, drops, streaks or excess of this film, or no film.

4. QUALITY ASSURANCE

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to the prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in manufacturing process necessary to ensure compliance with all dimensional requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:51Z
Check the source to verify that this is the current version before use.

4.1.3 Certificates of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3, 4.4.4 and 4.4.5, and shall be tested for the characteristics specified in 4.4.6. Any noncompliance shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.1 Component and material certification. A certificate of compliance may be acceptable as evidence that lacquer or varnish conforms to the requirement in 3.2.9 and that the adhesive conforms to the requirement in 3.2.6.

4.4.1.2 Component testing.

4.4.1.2.1 Testing of moisture content and density of lumber. The density of the lumber specified in 3.2.1 shall be tested as specified in 4.5.1. Moisture content of lumber specified in 3.2.1 and plywood panels specified in 3.4.1 shall be performed in accordance with ASTM D 4442. The sample unit shall be one piece of lumber and one plywood table top, as applicable. Sample units shall be obtained from each lot of lumber or each lot of plywood panels. A minimum of three determinations shall be made on one plywood sample piece, one near the edge of each unit and one at the center. The inspection level shall be S-1 with an acceptable quality level (AQL) of 4.0 defects, expressed in terms of defects per hundred units.

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table II. The lot size shall be expressed in units of assembled tables. The sample unit shall be one assembled table. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 4.0 for total (major and minor combined) defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:51Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects

Examine	Defect	Classification Major	Classification Minor
Finish:			
Legs and aprons (exposed surfaces)	Does not correspond to approved standard color panel for color-texture-gloss	101	
	Light or dark color areas, spotted (visible at 5 feet)		201
	Area of no lacquer or varnish film		202
	Finish peeling, flaking or blistered	102	
	Finish cracked, checked, or wrinkled		203
	Open grain, filler material does not fill pores or wood (when applicable)		204
	Soft runs, sags or is tacky	103	
	Hard runs or sags over 1 inch long	104	
	Finish rough or gritty, or dirt or foreign matter imbedded in finish		205
	Touchup or burn-in not neat, wrong color, not smooth (visible at 5 feet)		206
Aprons and corner blocks (unexposed surfaces)	Not finished as specified	105	
	Coating not glossy or semi-gloss, or is tacky		207
Metal retaining clips, glides, corner brackets (when applicable)	Coating not of specified type or is missing	106	
	Area of no coating		208
	Flaking, peeling or blistered	107	
Molding	Ends of the molding not properly butted, less than 1 brad on either side of butt joint	108	
	Gap between edge of the molding and top of laminated thermo-setting decorative sheet	109	
	Edge of molding not properly trimmed to ease edge with top	110	
	Color does not harmonize with color of laminated thermo-setting or laminated sheet		209
	Not satin finish, or color does not correspond to approved standard panel as to texture-color-gloss	111	

Source: https://assist.dla.mil -- Downloaded: 202640-17T22:51Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Finish (cont'd):			
Quality of wood components (aprons, legs, and corner blocks)	Wood grain match of edge glued components do not harmonize (when applicable)		210
	End split or cracked	112	
	Check or split over 1 inch in length (except at ends of components	113	
	Check or split up to and including 1 inch in length (except at ends of components)		211
	Honeycomb, casehardening, brashness, shake, loose or torn grain, loose or unsound knot, or knot hole		212
	Sound tight knot 1/4 inch in greatest dimension on exterior surfaces		213
	Any two sound tight knots less than 10 inches apart on exterior surface of apron rail		214
	Open hole, gouge, or other open defects on unexposed surfaces not filled or patched (when applicable)		215
	Hole, dent, gouge, or patch on exposed surface	114	
	Incipient decay or rot	115	
	Bark, bark pocket, pitch, or gum pocket over 1 inch long on exposed surface (visible at 5 feet)	116	
	Worm holes on exposed surface		216
	More than two worm holes, or over 1/16 inch in diameter on exposed surfaces	117	
	Slivered edges	118	
	Wood surfaces checked or torn out, or chipped or damaged edges on exposed surfaces	119	
	Slope of grain greater than 1 inch in 10 inches on any one surface of component		217

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:51Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Finish (cont'd):			
Quality of wood components (aprons, legs, and corner blocks) (cont'd)	Void in glue line (not burned-in) on exposed surfaces		218
	Open glue joint	120	
	Surface of glued up components uneven with each other on exposed surface or contains surfacing skip caused by lack of wood		219
	Wave of uneven sanding or machine marks on exposed surface (visible at 5 feet)		220
Construction and workmanship:			
Table top with aprons (assembled)	Component missing (except screw, or retainer clip)	121	
	Table top warped over 1/8 inch in width or length	122	
	Overhand of table top out of alignment with faces of apron by more than 1/8 inch		221
	Face or backing sheet omitted	123	
	Face sheet not of one piece construction	124	
	Edge of face sheet not beveled or chamfered as specified, or is rough, chipped, nicked, or gouged		222
	Face sheet marred, patched, cracked, chipped out, blistered, pitted, pin holes, rough areas, or not bonded to plywood	125	
	Backing sheet gouged, blistered, pitted, pin holes, rough areas, or not bonded to plywood		223
	Face sheet.discolored, spotted, streaked, stained, surface waviness, lapping, depressions, mold marks, plywood imperfections, or grains reproduction (visible at 5 feet)		224
	One hole missing in corner block, or holes mispositioned		225

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:51Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction and workmanship (cont'd):			
Table top with aprons (assembled) (cont'd)	More than one hole missing or mispositioned in corner block	126	
	Corner block not glued and attached by screws in groove in apron		226
	Corner block loose (when applicable), screw holes not countersunk, one screw missing or mispositioned, or not drawn tight		227
	Metal corner bracket fractured, cracked, or malformed (when applicable)	127	
	End of corner bracket not recessed into groove in apron as specified (when applicable)		228
	Corner bracket loose (when applicable), one screw missing or mispositioned, or not drawn tight		229
	More than one screw missing in corner block or corner bracket	128	
	Gap over 1/8 inch between underside of table top and top of corner block or bracket		230
	Corner block or corner bracket protrudes below bottom edge of apron over 1/32 inch		231
	Screw point protrudes through face of apron from corner block or corner bracket	129	
	Face sheet of top bulged from screw or brad (when applicable)	130	
	Face sheet of top pierced or split from screw or brad (when applicable)	131	
	Apron loose, method of attachment not as specified, warped more than 1/8 inch in length (examine visually, or groove for retainer clip not as specified		232
	Apron not tight to underside of table top by more than 1/16 inch any location	132	
	Apron not tight to underside of table top by more than 1/32 inch and up to and including 1/16 inch, or more than 10 inches in length		233

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:51Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction and workmanship (cont'd):			
Table top with aprons (assembled) (cont'd)	Molding wrong size or type, method of attaching not as specified, loose or not securely fastened, consists of more than two pieces around table top, or is malformed		234
	Molding cracked or fractured	133	
	Molding wrinkled at corners (visible at 5 feet)		235
	Open joint of more than 1/32 inch between molding and edge of face sheet (except at corners)		236
	Open joint of more than 1/16 inch between molding and edge of face sheet at radius of corners		237
	Butt joint at ends of molding open more than 1/32 inch		238
	Any opening between molding and edge of face sheet over 2 inches in length		239
	Retainer clip does not fit into groove in apron		240
	One metal retainer clip missing		241
	More than one metal retainer clip missing	134	
Screws and brads (In retainer clips, aprons, and underside of table top)	One or more screws or brads missing or loose		242
	Not of specified type or size		243
	Brads not driven from underside side of table top through barbed tongue of molding		244
	Head of brad protrudes (not driven flush)		245
	Screws, brads, or retainer clip not in specified location		246
	Loose in leg, misposition, locating screw loose, or rod projects above top of leg		247
	Locating screw not type or size specified or missing		248

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:51Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction and workmanship (cont'd):			
Glides, leg	Missing	135	
	Not type or size specified; are loose, improperly positioned, damaged or cracked; rubber cushion split, cut or malformed		249
	Rubber cushion missing		250
Metal components	Any sharp or burred edge or projection which may cause injury or damage to clothing	136	
Identification marking	Missing, incorrect, illegible, incomplete, or wrong location		251

4.4.4 Assembly examination. The dining table assembly shall be examined for defects listed in table III. The lot size shall be expressed in terms of unassembled tables. The sample unit shall be one unassembled table. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

TABLE III. Assembly characteristic defects

Examine	Defect	Classification Major	Minor
Ease of assembly and fit of components	Legs not easily assembled, i.e. assembly requires realignment of parts, enlargement of holes, use of hammer, drift pin, or mechanical means other than wrench assembling legs	101	
	Cannot attach leg bolt to leg	102	
	Head of leg bolt cannot be drawn up tight	103	
	Evidence of galling or seizure when drawing up bolt		201
	Legs protrude beyond corner of table top	104	
	Leg visibly not splayed as specified		202

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:51Z
Check the source to verify that this is the current version before use.

TABLE III. Assembly characteristic defects (cont'd)

Examine	Defect	Classification Major	Minor
Ease of assembly and fit of components (cont'd)	Table not rigid when on flat surface	105	
	Legs uneven, i.e. table rocks more than 1/16 inch on flat surface		203
	Table top not parallel with floor (level surface) by more than 3/16 inch		204

4.4.5 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on Drawing 5-8-102. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimensions not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of assembled tables. The sample unit shall be one assembled table. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.6 End item testing. The end item shall be tested for the characteristics listed in table IV. The lot size shall be expressed in units of completely assembled tables. The sample unit for each test shall be one completely assembled table. The inspection level shall be S-2. Any test failure shall be cause for rejection of the lot.

TABLE IV. End item tests

Characteristic	Requirement paragraph	Test method
Finish-print resistance	3.5.3	4.5.2.1
Finish-hot water resistance	3.5.3	4.5.2.2

4.4.7 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence or method of application

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:51Z
Check the source to verify that this is the current version before use.

Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling Bulged or distorted container
Content	Number of tables per container is more or less than required

4.4.8 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet patterns not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

4.5 Methods of inspection.

4.5.1 Wood density test. Wood density shall be calculated as oven dry weight and volume. Machine a sample of wood so that its dimensions can readily be computed. Place the sample in a drying oven, maintained at a temperature of 212° to 221°F, until the sample reaches a constant weight. Measure the dimensions of the sample and calculate the oven dry volume in cubic inches. The density (pounds per cubic foot) can then be determined as follows:

$$\frac{\text{Oven dry weight in pounds}}{\text{Oven dry volume in cubic inches}} \times \frac{1728 \text{ cubic inches}}{1 \text{ cubic foot}}$$

Any nonconformance with requirement in 3.2.1.1 shall constitute failure of this test.

4.5.2 Finish tests. Prior to testing, the finish shall be thoroughly cleaned with xylol or mineral spirits. The test shall be made not less than 4 hours after application of the final finish.

Source: https://assist.dla.mil -- Downloaded: 20261010-17T22:51Z
Check the source to verify that this is the current version before use.

4.5.2.1 Print resistance test. The finish shall be tested in accordance with Method No. 6211 of FED-STD-141. At room temperature and humidity a pressure of 1 psig shall be applied for not less than 4 hours. Any nonconformance with the no imprint requirement of 3.5.3 shall constitute failure of this test.

4.5.2.2 Hot water resistance test. Twenty-five cc of water ($137^{o} \pm 2^{o}F$), shall be poured on a level finished surface and allowed to cool to room temperature, after which the water shall be wiped from the surface. Any nonconformance with the no spotting or softening requirements of 3.5.3 shall constitute failure of this test.

4.5.3 Adhesive test. The average block shear strength of the adhesives shall be determined in accordance with ASTM D 905. Rerun test if the average block shear strength of all samples is below 2,800 psi, there is a 10% or greater difference between high and low specimen values, and at least one test specimen broke at more than 2,800 psi. Disregard a test specimen in computing the average if it breaks at less than 2,800 psi and has a 50% or more wood failure. Failure to meet the requirement in 3.2.6 shall be cause for rejection of the adhesive.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A preservation. The table shall be disassembled (knocked down) for shipment. The legs and hardware shall be detached. Detached hardware shall be placed in a cotton drawstring bag or a plastic bag conforming to type I or II, style 1, minimum thickness of 0.003 inch, of PPP-B-26. Each leg shall be sleeved, or wrapped, with 40-pound basis weight kraft paper and then overwrapped with cushioning material. The four wrapped legs, laid flat, alternated end for end, along with the detached hardware, shall be packed in a snug-fitting corrugated fiberboard box conforming to style RSC or OPF, type CF, class domestic, variety SW of PPP-B-636. All finished surfaces of the table top and apron shall be completely covered with 40-pound basis weight kraft paper and then covered with cushioning material to provide built-up cushioning not less than 3/4 inch thick. The cushioning blanket shall be secured to the underside of the table as shown on Drawing 5-8-130. All cushioning and blocking, as shown on Drawing 5-8-130, shall conform to MIL-STD-1186.

5.1.1.1 Unit packing. Each table, preserved as specified in 5.1.1, shall be unit packed in accordance with Drawing 5-8-130. The inverted table top shall be placed in a fiberboard box conforming to style FTC, type CF (variety SW) or SF, class domestic, grade 200 of PPP-B-636, except that the dimensional limitations be waived. The fiberboard box containing the legs shall be positioned within the apron and blocked or braced as necessary to immobilize the table and fill voids in the box. A corrugated fiberboard pad, 1/8 inch less than the length and width of the box, shall be placed over the inverted table.

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:51Z
Check the source to verify that this is the current version before use.

5.1.2 Commercial preservation. Tables (knocked down) shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A packing. Two tables preserved and unit packed in accordance with 5.1, shall be packed in a snug-fitting cleated plywood shipping container conforming to overseas type, style A or I, grade A or B, type 1 load of PPP-B-601, or a nailed wood shipping container conforming to class 2, style 1, grade A or B, load type 1 of PPP-B-621. The inside dimensions of the shipping container shall approximate 42 inches in length, 42 inches in width, and 12 inches in depth. Each shipping container shall be closed in accordance with the appendix of the container specification.

5.2.2 Level B packing. Each table preserved as specified in 5.1, shall be packed in accordance with 5.1.1.1, except that the fiberboard shipping container shall be grade 275. The inside dimensions of the shipping container shall approximate 41 inches in length, 41 inches in width, and 5-1/2 inches in depth. Shipping containers shall be closed and reinforced in accordance with the appendix of PPP-B-636.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s or V4s container fabricated in accordance with PPP-B-636 and closed in accordance with method III, as specified in the appendix.

5.2.3 Commercial packing. Tables, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), tables packed as specified in 5.2 shall be palletized in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with straps in accordance with bonding means C and D or film bonding means F or G, as applicable. Pallet pattern shall be number 83 in accordance with the appendix of MIL-STD-147.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers and unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

5.4.1 Additional marking. The top panel shall be plainly marked as follows:

FURNITURE

FRAGILE, HANDLE WITH CARE

TOP

THIS SIDE UP

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:51Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The table is intended for use in military dining halls with the dining chair covered by MIL-C-12475.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3 and 6.3).
d. Levels of preservation and packing (see 5.1 and 5.2).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
f. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Federal Acquisition Regulation (FAR) 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Color and grain of maple sheets. The following patterns are indicative of the color and grain of maple, laminated, thermo-setting, decorative sheets required for the table tops. The listing is intended to be descriptive rather than restrictive, and samples of similar patterns may be submitted to the contracting officer for approval:

Micarta	-	96-M-34 - Plank Rock Maple
Formica	-	1728-91-58 or 44-115-58
Pioneer	-	W0640 - Oiled Oak
Wilsonart	-	7902-13 - Planked Maple

6.5 Subject term (key word) listing.

Furniture
Wood

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:51Z
Check the source to verify that this is the current version before use.

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Air Force - 99

Review activity:

Air Force - 84

User activity:

Navy - MC

Civil agency coordinating activity:

GSA - FSS

Preparing activity:

Army - GL

(Project 7105-0255)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:51Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-T-12474D	1992 September 30

3. DOCUMENT TITLE

TABLE, DINING, 4-SEAT CAPACITY

4. NATURE OF CHANGE (*Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.*)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	e. DATE SUBMITTED (YYMMDD)

7. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON/DSN
U.S. Army Natick RD&E Center	508-651-4531	256-4531
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: SATNC-UXT Natick, MA 01760-5017	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89... Previous editions are obsolete. 198/2

Source: https://assist.dla.mil -- Downloaded: 2026-10-17 22:51:2
Check the source to verify that this is the current version before use.