INCH-POUND

MIL-DTL-32415
06 August 2012

DETAIL SPECIFICATION

DUMMY CAP, BLASTING: NON-ELECTRIC, 5 MINUTE INERT TIME FUSE DELAY-M32

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1. Scope. This specification describes the requirements and verification methods for the DUMMY CAP, BLASTING: non-electric, 5 minute inert time fuse delay, M32.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-1168 - Ammunition Lot Numbering
MIL-STD-1916 - DOD Preferred Methods for Acceptance of Products

(Copies of these documents are available online at https://assist.dla.mil/quicksearch/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

Comments, suggestions, or questions on this document should be addressed to: Commander, US Army ARDEC, Attn: RDAR-QES-E, Picatinny Arsenal, New Jersey 07806-5000 or emailed to ardecstdzn@conus.army.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC: 1375

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:18Z
Check the source to verify that this is the current version before use.

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC) DRAWINGS

8830953	- Cup
13030291	- Dummy cap, blasting: non-electric, 5 minute inert time fuse delay, M32 assembly

(Copies of the above drawings are available from U.S. Army RDECOM-ARDEC, ATTN: RDAR-EIS-PE, Bldg. 12, Picatinny Arsenal, NJ 07806-5000 or by email at pica.drawing.request@conus.army.mil .)

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1. Required inspections.

3.1.1. First article. When specified, a sample shall be subjected to the first article inspection in accordance with 4.2.

3.1.2. Conformance inspection. A sample of the M32 shall be subjected to conformance inspection in accordance with 4.3.

3.2. Materials, components, and assemblies. All materials, components and assemblies shall comply with the requirements of 13030291.

3.3. Dummy blasting cap attachment integrity. The dummy blasting cap shall not separate from the dummy fuse after exposure to not less than a 15 pound axial force for not less than 5 seconds.

3.4. Storage temperatures. The M32 shall show no evidence of material degradation after exposure to the temperature range of -65ºF to 165ºF.

3.5. Ammunition lot numbering. Ammunition lot numbers shall be assigned in accordance with MIL-STD-1168.

3.6. Workmanship. All parts and assemblies shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil, corrosion products and other foreign matter. The dummy time fuse shall have no pin holes, bubbles, breaks, discontinuity, kinks, twists, burrs, or similar defects. The dummy blasting cap shall not be cracked, bulged, scratched, or deformed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:18Z
Check the source to verify that this is the current version before use.

3.7. Markings. All markings shall be smooth, uniform, unsmeared in appearance and free of conspicuously ragged edges. There shall be no bleeding of color markings to the extent that there is a mottled or streaky appearance. The markings shall show no lifting, wrinkling, or other visible effect on the plastic's surface. The markings shall be applied on clean, dry surfaces that shall be free of dirt, oil, grease, water, corrosion, or other foreign matter. All required markings shall be present, neat, legible, only where specified, and sharply defined.

4. VERIFICATION

TABLE I. Requirement/verification cross reference matrix.

Method of verification 1 - Analysis 2 - Demonstration 3 - Examination 4 - Test		Classes of verification A – First article B – Conformance						
Section 3	Description	Verification Methods				Verification Class		Section 4
		1	2	3	4	A	B	
3.1.1	First article inspection			X	X	X		4.2
3.1.2	Conformance inspection			X	X		X	4.3
3.2	Materials, components, and assemblies			X		X	X	4.3.3.1; 4.3.3.2
3.3	Dummy blasting cap attachment integrity				X	X	X	4.4
3.4	Storage temperatures				X	X		4.5
3.5	Ammunition lot numbering			X		X	X	4.3.2
3.6	Workmanship			X		X	X	4.3.2
3.7	Markings			X		X	X	4.3.2

4.1. Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2).

b. Conformance inspection (see 4.3).

4.2. First article inspection. When specified, a sample shall be subjected to first article verification in accordance with Table II.

4.2.1. First article rejection. If any assembly, component, or test specimen fails to comply, the sample and first article shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:18Z
Check the source to verify that this is the current version before use.

TABLE II. First article inspections and tests.

Examination or test	Drawing	Sample size	Requirement paragraph	Verification
Cup	8830953	20	3.2	4.3.3.1
M32 Assembly	13030291	30 [1/]		
Examination for defects		30 [1/]	3.2	4.3.3.2
Dummy blasting cap attachment integrity		30 [1/]	3.3	4.4
Storage temperatures		15 [1/] at hot 15 [1/] at cold	3.4	4.5

Notes:
[1/] A total of 30 samples shall be sequentially subjected to the following, in the order listed: conformance inspections, storage temperature conditioning, and the dummy blasting cap attachment integrity test.

4.3. Conformance inspection.

4.3.1. Conformance rejection. If any assembly, component or test specimen fails to comply with the requirements, the lot from which the sample was taken shall be rejected.

4.3.2. Inspection lot formation. Inspection lots shall conform to the requirements of MIL-STD-1916. In addition inspection lots shall contain materials from not more than of one lot interfix number from one manufacturer.

4.3.3. Inspection requirements by classification of characteristics.

a. For the conformance inspection paragraphs 4.3.3.1 through 4.3.3.2, the definitions of critical, major and minor defects are provided in paragraph “Definitions” of MIL-STD-1916.

b. The acceptance criteria for sampling inspection shall be in accordance with the levels provided in conformance examination/test paragraph and MIL-STD-1916.

4.3.3.1 Cup.			Drawing Number 8830953 Next Higher Assembly 13042834	
	Examination	Conformance Criteria	Requirement Paragraph	Paragraph Reference/ Inspection Method
Critical	None defined.			
Major				
101	Cup split or cracked	Level II	3.2	Visual
102	Outside diameter, max.	Level II	3.2	Gage
Minor				
201	Poor workmanship	Level I	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:18Z
Check the source to verify that this is the current version before use.

4.3.3.2. Dummy cap, blasting: non-electric, 5 minute inert time fuse delay, M32.	Drawing Number 13030291
	Next Higher Assembly

	Examination and Tests	Conformance Criteria[1/]	Requirement Paragraph	Paragraph Reference/ Inspection Method
Critical	None defined.			
Major				
101	Blasting cap attachment integrity test	10 [2/]	3.3	4.4
102	Cup split or cracked	Level II	3.2	Visual
103	Dummy cap hole diameters (.125 +.005/-.001)	Level II	3.2	Gage
104	Number of holes in dummy cap incorrect	Level II	3.2	Visual
105	Hole locations (.80+/-.03 and .40 +/-.03)	Level II	3.2	Gage
Minor				
201	Distances of crimps from blasting cap edge (.125 +.025/-.000)	Level I	3.2	Gage
202	Crimp widths (.125 +/-.015)	Level I	3.2	Gage
203	Crimp diameters (.185 +.005/.002)	Level I	3.2	Gage
204	Fuse color incorrect	Level I	3.2	Visual
205	Fuse marking color incorrect	Level I	3.2	Visual
206	Distances between marks (18.00 +.50/-.25)	Level I	3.2	Visual
207	Fuse outer diameter (.200 +/-.005)	Level I	3.2	Gage
208	Dummy cap color incorrect	Level I	3.2	Visual
209	Markings missing, illegible, or incorrect	Level I	3.7	4.7
210	Poor workmanship	Level I	3.6	Visual

Notes:
[1/] All samples may be returned to the lot after successful test completion.
[2/] If one (1) or more fails to comply with the specified requirement, the lot shall be rejected.

4.4. Blasting cap attachment integrity test. The test shall be conducted on the M32. Secure the dummy blasting cap. Apply the specified axial load to the dummy time fuse for the specified length of time. Verify that the dummy blasting cap remains attached to the dummy time fuse. Visually verify the M32 remains in compliance with the workmanship and marking requirements. The samples and lot shall be rejected if the dummy blasting cap detaches from the dummy time fuse.

4.5. Storage temperature test. The test shall be conducted on the unpackaged M32. The samples tested at hot shall be conditioned at no less than 165ºF. The samples tested at cold shall be conditioned at no greater than -65ºF. The samples shall be conditioned at hot/cold for no less than 72 hours. After conditioning, the samples shall be returned to uncontrolled ambient temperature and stabilized for no less than 4 hours. Visually verify the M32 remains in compliance with the workmanship and marking requirements. The samples and lot shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:18Z
Check the source to verify that this is the current version before use.

rejected if the M32 does not remain in compliance with the workmanship or marking requirements.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of material is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service of Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The M32 is an inert replica of the M14 and is used to train both the M14 (5 minute delay) and M18 (20 minute delay). The M14 and M18 are used to initiate all past and current fielded and developmental demolition items such as explosives, shaped charges, and cratering charges.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification, and of all reference documents cited in section 2 and applicable documents from section 6.

b. Requirement for first article inspection.

c. Requirement for conformance inspection.

d. Packaging requirements exist for this item.

e. Packaging inspection requirements exist for the packaging of this item in accordance with 13026892. Detailed directions and additional information may be obtained from RDAR-QEM-G.

f. Requirement for ammunition data cards as specified in MIL-STD-1168.

g. Requirement for acceptance inspection equipment (AIE).

h. Requirement for ammunition lot numbering per MIL-STD-1168.

6.3 Subject term (key word) listing.
Demolition
Modernized Demolition Initiators (MDI)
M14
M18

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:18Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AR
Navy - OS
Air Force – 70

Review activities:
Army – AV, MI,
Navy – AS, NP
Air Force – 11, 99

Preparing activity:
Army-AR
(Project 1375-2012-011)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:18Z
Check the source to verify that this is the current version before use.