MIL-C-21100C
13 December 1985
SUPERSEDING
MIL-C-21100B
22 June 1971
(See 6.5)

MILITARY SPECIFICATION

CLEANER, VACUUM INDUSTRIAL, EXTERNAL FILTER TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers external filter type, industrial tank model vacuum cleaners for removing dirt, dust, and other dry particles by suction or blowing action with a filter bag which is attached to the exhaust port of the unit.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

J-C-175 - Cable Assembly, Power, Electrical, for 125-Volt, 250-Volt, and 125/250-Volt, 50-60 Hz, Equipment.
W-C-596 - Connector, Electrical, Power, General Specification for.
W-C-596/13 - Connector, Plug, Electrical, General Purpose, Hospital Grade Grounding, 2 Pole, 3 Wire, 15 Amperes, 125 Volts, 50/60 Hertz.
CC-M-1807 - Motors, Alternating Current, Fractional and Integral Horsepower (500 hp and Smaller).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Naval Sea Systems Command, SEA 55Z3, Department of the Navy, Washington, DC 20362-5101 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of the this document or by letter.

FSC 7910

DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-E-16298 - Electric Machines Having Rotating Parts and Associated Repair Parts: Packaging of.
MIL-O-16485 - Ohmmeters, Insulation Resistance-Indicating, Portable.

STANDARDS

MILITARY

MIL-STD-130 - Identification Marking of US Military Property.
MIL-STD-461 - Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference.
MIL-STD-740 - Airborne and Structureborne Noise Measurements and Acceptance Criteria of Shipboard Equipment.

(Copies of specifications and standards required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3 and 6.3).

3.2 Materials. The materials shall be as specified herein. Materials not definitely specified shall be of the quality best suited for the purpose intended.

3.2.1 Recovered materials. Unless otherwise specified herein, all equipment, material, and articles incorporated in the products covered by this specification shall be new and may be fabricated using materials produced from recovered materials to the maximum extent practicable without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of unused or rebuilt products is allowed under this specification unless otherwise specifically specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

3.3 Design and stability.

3.3.1 Design. The vacuum cleaner shall be a portable unit. It shall be constructed in such a manner that it may be used as a shoulder mounted blowing unit or vacuum cleaner, when the shoulder strap is attached. It shall also be used as a floor vacuum. It shall comprise only the following subassemblies as specified herein: tank assembly, cover, fan and motor assembly, switch, external filter bag, cable, shoulder harness, and accessory tools.

3.3.2 Stability. The assembled cleaner shall operate at full capacity, without loss of power, when inclined at an angle of 15 degrees in any direction from the normal horizontal position under all conditions of operation.

3.4 Dimensional and weight limits. The assembled cleaner, with the filter bag detached shall not exceed 24 inches in length, 24 inches in width, and 35 inches in height. The weight of the assembled cleaner including the filter bag, cord and plug attachments shall not exceed 75 pounds.

3.5 Tank assembly.

3.5.1 Construction. The tank shall be of steel, so drawn, or formed and welded as to make an upright cylindrical or square container.

3.5.2 Reinforcing details. The gauge of steel used and reinforcing details such as hoops or ribbing, if any, shall render the tank rigid: to maintain its shape under normal usage; to support firmly the cover assembly and provide an effective vacuum seal between the tank and the cover; to support the hardware attachments (see 3.5.5) without pulling out; and to provide a receptacle for chips, filings, and other metallic and coarse litter.

3.5.3 Capacity. The tank shall have a capacity of not less than 1800 cubic inches (in^3).

3.5.4 Treatment for corrosion resistance. Unless corrosion-resistant steel is provided (see 6.2.1), all surfaces of the tank shall be treated, coated, or enameled to resist corrosion. Inner walls and bottom shall be smooth surfaced to assist in easy cleaning.

3.5.5 Mounting of tank and hardware. The tank shall be mounted on four swivel type ball bearing casters and shall be provided with the following:

(a) Two chest handles or other means for lifting.
(b) Clamping or locking devices needed to secure the cover assembly to the tank.
(c) Vacuum intake port fitting.

3.6 Cover fan and motor assembly.

3.6.1 Cover. The cover shall combine the function of top seal to the tank and firm support for fan, motor, switch, and exhaust port fitting. The cover shall be of steel so formed as to fit the tank snugly when locked in place. If made of other than corrosion-resistant steel, it shall be treated to provide rust resistance as specified in 3.5.4. Gasket seal as necessary shall be provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

3.6.2 Fan. The fan shall be of rugged construction, so designed and mounted that it shall run freely under load without excessive or objectionable vibration. Octave band sound pressure levels resulting from operation shall not exceed the specified airborne acceptance sound pressure levels when tested as specified in 4.5.5.

3.6.2.1 The fan, when powered as specified herein, shall develop a vacuum of not less than 33 inches of water with 5/8-inch orifice when tested as specified in 4.5.3.

3.6.2.2 Fan and exhaust port air passages and impellers shall be smooth so that dirt adherence to the surfaces shall be reduced to a minimum.

3.6.2.3 Airborne noise levels. Airborne noise levels shall not exceed the values shown in table I when tested in accordance with 4.5.5.

TABLE I. Airborne acceptance sound pressure levels in decibels (dB) re: 0.0002 microbar.

Octave band center frequency (Hz)									
Hz	31.5	63	125	250	500	1000	2000	4000	8000
dB	91	88	85	82	79	76	73	70	67

3.7 Motor. The motor shall conform to CC-M-1807 and the following classification:

Type - universal.
Voltage - 115 volts (V) alternating current (ac) and direct current (dc).
Frequency - 60 hertz (Hz).
Enclosure - protected.
Duty rating - continuous.
Ambient temperature - 40 degrees celsius (°C).

3.7.1 The continuous duty rating shall be not less than 1 horsepower (hp). The motor shall have ball bearings with means for lubrication.

3.7.2 The motor shall pass the tests for insulation resistance (to be not less than 2 megohms), and dielectric strength in 4.5.6 and 4.5.7, respectively.

3.7.3 Brush accessibility. Convenient access shall be provided for inspection and replacement of brushes.

3.8 Switch. A switch for operating the cleaner shall be mounted on the cover, fan, and motor assembly. It shall be of quick-break design and shall provide two switch positions, "ON" and "OFF".

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

3.9 External filter bag. The external filter bag shall be the sole medium in the vacuum system. The weight of the bag shall be 10 ounces per square yard. The external filter bag shall be a porous cloth bag for collecting light dust. One end of the external filter bag shall have a metal coupling to mate with the exhaust port. The other end of the external filter bag shall have an opening of 7 inches nominal to facilitate emptying the bag. Closure shall be by means of a metal bag clamp. A metal rod shall be provided to add support to the bag when in use. The overall surface area of the external filter bag shall be not less than 850 square inches (in^2).

3.10 Cable. Each cleaner shall be provided with a cord assembly in accordance with J-C-175 except that the cable shall be 25 feet in length. The connector plug shall be either a molded-on type in accordance with type I of J-C-175, or an attachable type including a cord grip conforming to W-C-596/13 as specified (see 6.2.1).

3.11 Electromagnetic emissions. The electromagnetic emissions shall not exceed the limits specified in MIL-STD-461. The mounting of any noise suppression accessories shall be such that an electrical shock hazard is not introduced (see 4.5.9).

3.12 Attachments. The following attachments shall be supplied with each cleaner:

1 - length oil-resistant hose, 1-1/2 inches in diameter, 6 feet in length, with swivel connections at the tank.
1 - length oil-resistant hose, 1-1/2 inches in diameter, 10 feet in length, with swivel connections at the tank.
1 - length oil-resistant hose, 1-1/2 inches in diameter, 25 feet in length, with swivel connections at the tank.
2 - large dust bags (including one bag with assembled cleaner).
1 - metal nozzle, 5 inches in length, with shortened connection for 1-1/2 inch diameter hose.
2 - brushes, 6 inches in width, for attachment to 5-inch nozzle.
1 - floor nozzle, 12 inches in width.
1 - blowing nozzle (nonconducting).
2 - round nozzles with brushes, 3 inches in diameter, 45 degree bend.
1 - metal connector (for floor nozzle).
1 - extension piece (nonconducting), 40 to 46 inches in length, 1-1/2 inches in diameter (in two pieces).
1 - metal box for attachments and repair parts. The 10-foot and 25-foot lengths of hose and the metal connector need not be contained in the metal box.
1 - brush (for 12-inch floor nozzle).

3.13 Identification plates. Identification plates in accordance with MIL-STD-130 shall be furnished and mounted on the cleaner. These identification plates shall conform to the following:

(a) Material - As required, except that aluminum alloy and plastic materials will not be permitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

(b) Required information:
Cleaner, vacuum, industrial tank type
Type, external filter _____
Operating voltage _____
Horsepower _____
R/min _____

Military Specification MIL-C-21100
Stock number _____
Manufacturer's part number _____
Serial number _____
Contract or order number _____
Manufacturer's name or trademark _____
U.S. property _____

3.14 Technical manuals. Two copies of the manufacturer's standard operating and maintenance instructions shall be packed with each cleaner. Included with the manuals shall be complete factory parts lists, with list of accessories and repair parts furnished with each cleaner.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3)
(b) Quality conformance inspection (see 4.4)

4.3 First article inspection. First article inspection shall consist of the examinations and tests specified in 4.5 and the results recorded (see 6.2.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Lot. For purposes of sampling, a lot shall consist of all cleaners of the same type offered for delivery at one time.

4.4.2 Sampling.

4.4.2.1 Sampling for group A examination and tests. A random sample of cleaners shall be selected from each lot and shall be subjected to the group A examination and tests specified in 4.4.3 with lot acceptance based on table II.

TABLE II. Sampling for group A examination and tests.

Number of cleaners in lot	Number of cleaners in sample	Number of equipments nonconforming on any group A examination and test	
		Acceptance number	Rejection number
15 and under	10	0	1
16 to 40	15	0	1
41 to 110	25	0	1
111 to 300	35	1	2
301 to 500	50	1	2
501 and over	75	2	3

4.4.2.2 Sampling for group B tests. A random sample of cleaners shall be selected from each lot in accordance with table III and shall be subjected to each of the group B tests specified in 4.4.4.

TABLE III. Sampling for group B tests.

Number of cleaners in lot	Number of cleaners in sample	Number of equipments nonconforming on any group B examination and test	
		Acceptance number	Rejection number
15 and under	2	0	1
16 to 25	3	0	1
26 to 40	5	0	1
41 to 110	7	0	1
111 to 300	10	0	1
301 to 500	15	1	2
501 and over	25	2	3

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

4.4.2.3 Sampling for group C tests. A sample number of cleaners shall be selected from each lot in accordance with table IV and shall be subjected to the group C tests specified in 4.4.5.

TABLE IV. Sampling for group C tests.

Number of cleaners in lot	Number of cleaners for the group C tests
110 and under	1
111 to 500	2
501 and over	3

4.4.3 Group A examination and tests. Each of the sample cleaners selected in accordance with 4.4.2.1 shall be subjected to the examination and tests in accordance with table V. The results of examination and each test shall be compared with requirements of this specification. Failure to conform to the requirements of this specification for any group A examination or tests shall be counted as a defect, and the cleaner shall be rejected. If the number of such nonconforming cleaners in any sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

4.4.4 Group B tests. Each of the sample cleaners selected in accordance with 4.4.2.2 shall be subjected to the tests in accordance with table V, and the results of each test compared with the specification requirements. Failure to conform to the specification requirements for any group B test shall be counted as a defect and the cleaner shall be rejected. If the number of such nonconforming cleaners in any sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

4.4.5 Group C tests. Each of the sample cleaners selected in accordance with 4.4.2.3 shall be subjected to the tests in accordance with table V, and the results of each test compared with the specification requirements. In the event of any failure to conform to the specification requirements for the group C tests, the contractor shall correct the cause for failure and repair the deficiency in any cleaner not yet shipped.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

TABLE V. Quality conformance inspection.

Examination or test	Requirement paragraph	Examination or test paragraph
Group A		
Examination	3.2, 3.3, 3.4, 3.5, 3.6, 3.8, 3.9, 3.10, 3.12, 3.13	4.5.1
Short operation	3.7	4.5.2
Insulation resistance	3.7.2	4.5.6
Dielectric strength	3.7.2	4.5.7
Electromagnetic emissions (one unit)	3.11	4.5.9
Group B		
Operative	3.6.2.1	4.5.3
Temperature measurements	3.7	4.5.4
Airborne noise	3.6.2.3	4.5.5
Group C		
Stability	3.3.2	4.5.8

4.5 Examination and test procedures.

4.5.1 Examination. Each sample cleaner shall be subjected to a thorough examination to determine that the cleaner is in strict conformance with this specification regarding materials, dimensions, weights, design, and any other requirements not involving tests.

4.5.2 Short operation test. Each of the sample cleaners shall be subjected to a short operation test for a few minutes.

4.5.3 Operative tests. The cleaner shall be subjected to one 6-1/2 hour continuous run at normal full-load operating conditions, at 115 V, 60 Hz ac. The degree of vacuum of the cleaner shall be determined during this run. A pipe 4 inches in diameter and 12 inches in length shall be attached to the end of the 25-foot length of hose furnished with the cleaner. The pipe end which is not attached to the hose shall be fitted with a 5/8-inch diameter, round, sharp-edged orifice. The difference in water level in the two columns of a manometer connected at approximately the center of the pipe length shall be considered as the suction of the cleaner.

4.5.4 Temperature measurements. Temperature measurements shall be taken during the progress of the run specified in 4.5.3 and after shutdown to determine compliance with the temperature rise limits of CC-M-1807.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

4.5.5 Airborne noise. During the operative tests of 4.5.3, airborne noise sound pressure level tests shall be conducted. The test procedure shall be in accordance with MIL-STD-740. During the noise tests, the cleaner shall be operated at normal full load operating conditions. The octave band sound pressure levels produced shall not exceed those as specified in table I (see 3.6.2.3).

4.5.6 Insulation resistance test (cold). The insulation resistance test shall be conducted to determine compliance with 3.7.2. The measurement shall be made with all circuits connected together. Insulation resistance shall be measured with an insulation-resistance indicating instrument conforming to MIL-O-16485. The time of test voltage application shall be 60 seconds. The temperature of the windings at the time of the test shall be measured and recorded. Insulation-resistance measurements shall be corrected to 25°C. Corrections shall be made on the basis of insulation resistance doubling for each 15°C decrease in temperature. The relative humidity at the time of the test shall be measured and recorded.

4.5.7 Dielectric strength test. Each sample cleaner shall be subjected to an ac potential of 900 V for 60 seconds, applied between the current carrying parts and the frame. The radio shielding accessories may be disconnected for this test.

4.5.8 Stability. Stability operation test shall be conducted on the cleaner inclined at an angle of 15 degrees in any direction from the normal horizontal position and at both no load and full load.

4.5.9 Electromagnetic emissions. Electromagnetic emissions test shall be conducted in accordance with type IIB equipment requirements of MIL-STD-461 to determine compliance with 3.11. The leakage current with cleaner plugged in shall not exceed 4.99 milliamperes (mA) either with switch "ON" or "OFF".

4.6 Inspection of packaging. Sample packages and packs, and the inspection of the preservation-packaging, packing and marking for shipment and storage shall be in accordance with the requirements of section 5 and the documents specified therein.

5. PACKAGING

(The packaging requirements specified herein apply only for direct Government acquisition. For the extent of applicability of the packaging requirements of referenced documents listed in section 2, see 6.4.)

5.1 Packaging, packing, and marking. Cleaners, attachments, technical manuals, and repair parts shall be cleaned, preserved, and packaged level A or C, and packed level A, B, or C, as specified (see 6.2.1) and marked in accordance with MIL-E-16298.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. Vacuum cleaners covered by this specification are intended for removing dirt, dust and other dry particles or debris in all general light industrial or housekeeping functions.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) When first article inspection is required (see 3.1).
(c) Whether corrosion-resistant steel will be provided (see 3.5.4).
(d) Type of power cord assembly required (see 3.10).
(e) Level of packaging and packing required (see 5.1).

6.2.2 Data requirements. When this specification is used in an acquisition and data are required to be delivered, the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DoD FAR Supplement, Part 27, Sub-Part 27.410-6 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification are cited in the following paragraph.

Paragraph no.	Data requirement title	Applicable DID no.	Option
4.3	First article inspection report	DI-T-4902	---

(Data item descriptions related to this specification, and identified in section 6 will be approved and listed as such in DoD 5000.19L., Vol. II, AMSDL. Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

6.2.2.1 The data requirements of 6.2.2 and any task in sections 3, 4, or 5 of this specification required to be performed to meet a data requirement may be waived by the contracting/acquisition activity upon certification by the offeror that identical data were submitted by the offeror and accepted by the Government under a previous contract for identical item acquired to this specification. This does not apply to specific data which may be required for each contract regardless of whether an identical item has been supplied previously (for example, test reports).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

6.3 First article. When a first article inspection is required, the item should be a first article sample. The first article should consist of a sample lot. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.4 Sub-contracted material and parts. The packaging requirements of referenced documents listed in section 2 do not apply when material and parts are acquired by the contractor for incorporation into the equipment and lose their separate identity when the equipment is shipped.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Navy - SH
Air Force - 99

Review activities:
Navy - SH
Air Force - 84

User activity:
Navy - MC

Preparing activity:
Navy - SH
(Project 7910-0063)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-21100C	CLEANER, VACUUM INDUSTRIAL, EXTERNAL FILTER TYPE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

COMMANDER
NAVAL SEA SYSTEMS COMMAND (SEA 55Z3)
DEPARTMENT OF THE NAVY
WASHINGTON, DC 20362-5101

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

COMMANDER
NAVAL SEA SYSTEMS COMMAND (SEA 55Z3)
DEPARTMENT OF THE NAVY
WASHINGTON, DC 20362-5101

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.