INCH-POUND
MIL-C-21100D
4 October 1990
SUPERSEDING
MIL-C-21100C
13 December 1985
(See 6.8)

MILITARY SPECIFICATION

CLEANER, VACUUM INDUSTRIAL, EXTERNAL FILTER TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers external filter type, industrial tank model vacuum cleaners for removing dirt, dust, and other dry particles by suction or blowing action, with a filter bag which is attached to the exhaust port of the unit.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

J-C-175 - Cable Assembly, Power, Electrical, for 125-Volt, 250-Volt, and 125/250-Volt, 50-60 Hz, Equipment.
W-C-596 - Connector, Electrical, Power, General Specification for.
W-C-596/13 - Connector, Plug, Electrical, General Purpose, Hospital Grade Grounding, 2 Pole, 3 Wire, 15 Amperes, 125 Volts, 50/60 Hertz.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Naval Sea Systems Command, SEA 55Z3, Department of the Navy, Washington, DC 20362-5101 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7910
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

FEDERAL - Continued

CC-M-1807 - Motors, Alternating Current, Fractional and Integral Horsepower (500 hp and Smaller).
PPP-F-320 - Fiberboard, Corrugated and Solid Sheet Stock (Container Grade), and Cut Shapes.

MILITARY

MIL-P-15024 - Plates, Tags and Bands for Identification of Equipment.
MIL-P-15024/5 - Plates, Identification.
MIL-E-16298 - Electric Machines Having Rotating Parts and Associated Repair Parts: Packaging of.
MIL-O-16485 - Ohmmeters, Insulation Resistance-Indicating, Portable.
MIL-L-19140 - Lumber and Plywood Fire Retardant Treated.

STANDARDS

MILITARY

MIL-STD-461 - Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference.
MIL-STD-462 - Electromagnetic Interference Characteristics; Measurement of.
MIL-STD-740 - Airborne and Structureborne Noise Measurements and Acceptance Criteria of Shipboard Equipment.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Document Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Non-Government publications. The following document forms a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

F 1166 - Standard Practice for Human Engineering Design for Marine Systems, Equipment and Facilities

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.5) in accordance with 4.3.

3.2 Materials. The materials shall be as specified herein. Materials not definitely specified shall be of the quality best suited for the purpose intended.

3.2.1 Recovered materials. Unless otherwise specified herein, all equipment, material, and articles incorporated in the products covered by this specification shall be new and may be fabricated using materials produced from recovered materials to the maximum extent practicable without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products is allowed under this specification unless otherwise specifically specified.

3.3 Design and stability.

3.3.1 Design. The cleaner shall be designed in accordance with the Human Engineering criteria specified in ASTM F1166. The cleaner shall be a portable unit comprised of only the following subassemblies: tank assembly, cover, fan and motor assembly, control switch, external filter bag, cable, and accessory tools. The cleaner's design shall incorporate the maintainability requirements specified in ASTM F1166 and shall permit safe and efficient performance by the 5th percentile female to the 95th percentile male as specified in ASTM F1166.

3.3.2 Stability. The assembled cleaner shall operate at full capacity, without loss of power, when inclined at an angle of 15 degrees in any direction from the normal horizontal position under all conditions of operation.

3.4 Dimensional and weight limits. The assembled cleaner, with the filter bag detached shall not exceed 24 inches in length, 24 inches in width, and 35 inches in height. The weight of the assembled cleaner including the filter bag, cord and plug attachments shall not exceed 75 pounds.

3.5 Tank assembly. Tank assembly shall be in accordance with 3.5.1 through 3.5.5.

3.5.1 Construction. The tank shall be of steel, so drawn, or formed and welded as to make an upright cylindrical or square container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

3.5.2 Reinforcing details. The gauge of steel used and reinforcing details such as hoops or ribbing, if any, shall render the tank rigid: to maintain its shape under normal usage; to support firmly the cover assembly and provide an effective vacuum seal between the tank and the cover; to support the hardware attachments (see 3.5.5) without pulling out; and to provide a receptacle for chips, filings, and other metallic and coarse matter.

3.5.3 Capacity. The tank shall have a capacity of not less than 1800 cubic inches (in^3).

3.5.4 Treatment for corrosion resistance. Unless corrosion-resistant steel is provided (see 6.2), all surfaces of the tank shall be treated, coated, or enameled to resist corrosion. Inner walls and bottom shall be smooth surfaced to assist in easy cleaning.

3.5.5 Mounting of tank and hardware. The tank shall be mounted on four swivel type ball bearing casters and shall be provided with the following:

(a) Two chest handles or other means of lifting, in accordance with handle and grasp area requirements specified in 38.5 of ASTM F1166.
(b) Clamping or locking devices needed to secure the cover assembly to the tank.
(c) Vacuum intake port fitting.

3.6 Cover fan and motor assembly. The cover fan and motor assembly shall be in accordance with the requirements in 3.6.1 through 3.6.2.3.1.

3.6.1 Cover. The cover shall combine the function of top seal to the tank and firm support for fan, motor, switch, and exhaust port fitting. The cover shall be of steel so formed as to fit the tank snugly when locked in place. If made of other than corrosion-resistant steel, it shall be treated to provide rust resistance as specified in 3.5.4. Gasket seal, as necessary, shall be provided.

3.6.2 Fan. The fan shall be of rugged construction, so designed and mounted that it shall run freely under load without excessive or objectionable vibration. Octave band sound pressure levels resulting from operation shall not exceed the specified allowable acceptance sound pressure levels when tested as specified in 4.6.3.

3.6.2.1 Degree of vacuum. The fan, when powered as specified herein, shall develop a vacuum of not less than 33 inches of water with 5/8-inch orifice when tested as specified in 4.6.1.

3.6.2.2 Exhaust port and impellers. Fan and exhaust port air passages and impellers shall be smooth so that dirt adherence to the surfaces shall be reduced to a minimum.

3.6.2.3 Airborne noise levels. Airborne noise levels shall not exceed the values shown in table I when tested in accordance with 4.6.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

TABLE I. Airborne acceptance sound pressure levels in decibels (dB) re: 0.0002 microbar.

	Octave band center frequency (Hz)								
Hz	31.5	63	125	250	500	1000	2000	4000	8000
dB	91	88	85	82	79	76	73	70	67

3.6.2.3.1 Sound pressure level. Machines emitting 85 decibels ("A" weighted) (85 dBa) or greater shall be labeled in accordance with OPNAVINST 5100.23.

3.7 Motor. The motor shall conform to CC-M-1807 and the following classification:

Type	- universal.
Voltage	- 115 volts (V) alternating current (ac) and direct current (dc).
Frequency	- 60 hertz (Hz).
Enclosure	- protected.
Duty rating	- continuous.
Ambient temperature	- 40 degrees Celsius (°C).
Maximum current drawn	- 15 Amps.

3.7.1 Continuous duty rating. The continuous duty rating shall be not less than 1 horsepower (hp). The motor shall have ball bearings with accessible means for lubrication (see 3.3.1).

3.7.2 Insulation resistance and dielectric strength. The motor shall pass the tests for insulation resistance (to be not less than 2 megohms), and dielectric strength in 4.6.4 and 4.6.5, respectively.

3.7.3 Brush accessibility. Access shall be provided for inspection and replacement of brushes in accordance with 3.3.1 and the arm and hand access requirements specified in ASTM F1166.

3.8 Control switch. A control switch shall be mounted on the cover, fan and motor assembly. It shall provide two positions, "on" and "off". The control switch shall be capable of being quickly turned on or off, but shall not be susceptible to inadvertent action.

3.9 External filter bag. The external filter bag shall be the sole medium in the vacuum system. The weight of the bag shall be 10 ounces per square yard. The external filter bag shall be a porous cloth bag for collecting light dust. One end of the external filter bag shall mate with the exhaust port. The other end of the external filter bag shall have an opening of 7 inches nominal to facilitate emptying the bag. Closure shall be by means of a metal bag clamp. A metal rod shall be provided to add support to the bag when in use. The overall surface area of the external filter bag shall be not less than 850 square inches (in^2).

Source: https://assist.dla.mil -- Downloaded: 2026l0-19T08:54Z
Check the source to verify that this is the currentversion before use.

3.10 Cable. Each cleaner shall be provided with a cord assembly in accordance with J-C-175 except that the cable shall be 50 feet in length. The connector plug shall be either a molded-on type in accordance with type I of J-C-175, or an attachable type including a cord grip conforming to W-C-596 and W-C-596/13 as specified (see 6.2).

3.11 Electromagnetic emissions. The electromagnetic emissions shall not exceed the limits specified in MIL-STD-461. The mounting of any noise suppression accessories shall be such that an electrical shock hazard is not introduced (see 4.6.7).

3.12 Attachments. The following attachments shall be furnished with each cleaner:

1 - length oil-resistant hose, 1-1/2 inches in diameter, 6 feet in length, with swivel connections at the tank.
1 - length oil-resistant hose, 1-1/2 inches in diameter, 10 feet in length, with swivel connections at the tank.
1 - length oil-resistant hose, 1-1/2 inches in diameter, 25 feet in length, with swivel connections at the tank.
2 - large dust bags (including one bag with assembled cleaner).
1 - metal nozzle, 5 inches in length, with shortened connection for 1-1/2 inch diameter hose.
2 - brushes, 6 inches in width, for attachment to 5-inch nozzle.
1 - floor nozzle, 12 inches in width.
1 - blowing nozzle (nonconducting).
2 - round nozzles with brushes, 3 inches in diameter, 45 degree bend.
1 - metal connector (for floor nozzle).
1 - extension piece (nonconducting), 40 to 46 inches in length, 1-1/2 inches in diameter (in two pieces).
1 - metal box for attachments and repair parts. The 10-foot and 25-foot lengths of hose and the metal connector need not be contained in the metal box.
1 - brush (for 12-inch floor nozzle).

3.13 Identification plates. Identification plates in accordance with MIL-P-15024 and MIL-P-15024/5 shall be furnished and mounted on the cleaner. These identification plates shall conform to the following:

(a) Material - As required, except that aluminum alloy and plastic materials will not be permitted.

(b) Required information:

Cleaner, vacuum, industrial tank type _____
Type, external filter _____
Operating voltage _____
Horsepower _____
R/min _____
Military Specification MIL-C-21100
Stock number _____
Manufacturer's part number _____

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

Serial number _____
Contract or order number _____
Manufacturer's name or trademark _____
U.S. property _____

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of the manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept decfective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 First article inspection. First article inspection shall consist of the examinations specified in 4.5 and tests specified in 4.6.1 through 4.6.7.

4.4 Quality conformance inspection. Quality conformance inspection shall be as specified in 4.4.1 through 4.4.5.

4.4.1 Lot. For purposes of sampling, a lot shall consist of all cleaners of the same type offered for delivery at one time.

4.4.2 Sampling. Sampling for group A, B, and C examinations and tests shall be as specified in 4.4.2.1 through 4.4.5.

4.4.2.1 Sampling for group A examination and tests. A random sample of cleaners shall be selected from each lot and shall be subjected to the group A examination and tests specified in 4.4.3 with lot acceptance based on table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

TABLE II. Sampling for group A examination and tests.

		Number of equipments nonconforming on any group A examination and test	
Number of cleaners in lot	Number of cleaners in sample	Acceptance number	Rejection number
15 and under	10	0	1
16 to 40	15	0	1
41 to 110	25	0	1
111 to 300	35	1	2
301 to 500	50	1	2
501 and over	75	2	3

4.4.2.2 Sampling for group B tests. A random sample of cleaners shall be selected from each lot in accordance with table III and shall be subjected to each of the group B tests specified in 4.4.4.

TABLE III. Sampling for group B tests.

		Number of equipments nonconforming on any group B examination and test	
Number of cleaners in lot	Number of cleaners in sample	Acceptance number	Rejection number
15 and under	2	0	1
16 to 25	3	0	1
26 to 40	5	0	1
41 to 110	7	0	1
111 to 300	10	0	1
301 to 500	15	1	2
501 and over	25	2	3

4.4.2.3 Sampling for group C tests. A sample number of cleaners shall be selected from each lot in accordance with table IV and shall be subjected to the group C tests specified in 4.4.5.

TABLE IV. Sampling for group C tests.

Number of cleaners in lot	Number of cleaners for the group C tests
110 and under	1
111 to 500	2
501 and over	3

Source: https://assist.dla.mil -- Downloaded: 202610-19T08:54Z
Check the source to verify that this is the current version before use.

4.4.3 Group A examination and tests. Each of the sample cleaners selected in accordance with 4.4.2.1 shall be subjected to the examination and tests in accordance with table V. The results of examination and each test shall be compared with the requirements of this specification. Failure to conform to the requirements of this specification for any group A examination or test shall be counted as a defect, and the cleaner shall be rejected. If the number of such nonconforming cleaners in any sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

4.4.4 Group B tests. Each of the sample cleaners selected in accordance with 4.4.2.2 shall be subjected to the tests in accordance with table V, and the results of each test compared with the specification requirements. Failure to conform to the specification requirements for any group B test shall be counted as a defect and the cleaner shall be rejected. If the number of such nonconforming cleaners in any sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

4.4.5 Group C tests. Each of the sample cleaners selected in accordance with 4.4.2.3 shall be subjected to the tests in accordance with table V, and the results of each test compared with the specification requirements. In the event of any failure to conform to the specification requirements for the group C tests, the contractor shall correct the cause for failure and repair the deficiency in any cleaner not yet shipped.

TABLE V. Quality conformance inspection.

Examination or test	Requirement	Examination or test
Group A		
Examination	3.2, 3.3, 3.4, 3.5, 3.6 3.8, 3.9, 3.10, 3.12, 3.13	4.5
Insulation resistance	3.7.2	4.6.4
Dielectric strength	3.7.2	4.6.5
Electromagnetic emissions (one unit)	3.11	4.6.7
Group B		
Operative	3.6.2.1	4.6.1
Temperature measurements	3.7	4.6.2
Airborne noise	3.6.2.3	4.6.3
Group C		
Stability	3.3.2	4.6.6

4.5 Examinations. Each sample cleaner shall be subjected to a thorough examination to determine that the cleaner is in strict conformance with this specification regarding materials, dimensions, weights, design, and any other requirements not involving tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

4.6 Tests. Tests shall be as specified in 4.6.1 through 4.6.7.

4.6.1 Operative tests. The cleaner shall be subjected to one 6-1/2 hour continuous run at normal full-load operating conditions, at 115 V, 60 Hz ac. The degree of vacuum of the cleaner shall be determined during this run. A pipe 4 inches in diameter and 12 inches in length shall be attached to the end of the 25-foot length of hose furnished with the cleaner. The pipe end which is not attached to the hose shall be fitted with a 5/8-inch diameter, round, sharp-edged orifice. The difference in water level in the two columns of a manometer connected at approximately the center of the pipe length shall be considered as the suction of the cleaner and shall not be less than 33 inches.

4.6.2 Temperature measurements. Temperature measurements shall be taken during the operative tests of 4.6.1 and after shutdown to determine compliance with the temperature rise limits of CC-M-1807.

4.6.3 Airborne noise. During the operative tests of 4.6.1, airborne noise sound pressure level tests shall be conducted. The test procedure shall be in accordance with MIL-STD-740. During the noise tests, the cleaner shall be operated at normal full load operating conditions. The octave band sound pressure levels produced shall not exceed those as specified in table I (see 3.6.2.3).

4.6.4 Insulation resistance test (cold). The insulation resistance test shall be conducted to determine compliance with 3.7.2. The measurement shall be made with all circuits connected together. Insulation resistance shall be measured with an insulation-resistance indicating instrument conforming to MIL-O-16485. The time of test voltage application shall be 60 seconds. The temperature of the windings at the time of the test shall be measured and recorded. Insulation-resistance measurements shall be corrected to 25°C and shall not be less than 2 megohms. Corrections shall be made on the basis of insulation resistance doubling for each 15°C decrease in temperature.

4.6.5 Dielectric strength test. Each sample cleaner shall be subjected to an ac potential of 900 V for 60 seconds, applied between the current carrying parts and the frame. The radio shielding accessories may be disconnected for this test.

4.6.6 Stability. Stability operation test shall be conducted on the cleaner inclined at an angle of 15 degrees in any direction from the normal horizontal position and at both no load and full load.

4.6.7 Electromagnetic emissions. Electromagnetic emissions testing shall be conducted in accordance with MIL-STD-462 to determine compliance with the group I, UM05 equipment requirements specified in MIL-STD-461.

4.7 Inspection of packaging. Sample packages and packs, and the inspection of the preservation, packing and marking for shipment, stowage, and storage shall be in accordance with the requirements of section 5 and the documents specified therein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

5. PACKAGING

(The packaging requirements specified herein apply only for direct Government acquisition. For the extent of applicability of the packaging requirements of referenced documents listed in section 2, see 6.7.)

5.1 Packaging requirements. Cleaners, attachments, technical manuals and repair parts shall be preserved level A or C and packed level A, B or C as specified (see 6.2) and marked in accordance with MIL-L-16298 and shall include bar codes and applicable packaging acquisition options therein as specified (see 6.2). In addition, for Navy acquisitions, the following applies:

a. Navy fire-retardant requirements.

1. Lumber and plywood. Unless otherwise specified see 6.2, all lumber and plywood including laminated veneer material used in shipping container construction members, blocking, bracing, and reinforcing shall be fire-retardant treated material conforming to MIL-L-19140 as follows:

Levels A and B - Type II - weather resistant.
Category I - general use.

Level C - Type I - nonweather resistant.
Category I - general use.

2. Fiberboard. Unless otherwise specified (see 6.2), fiberboard used in the construction of class-domestic, nonweather resistant fiberboard and cleated fiberboard boxes including interior packaging forms shall meet the flamespread and the specific optic density requirements of PPP-F-320 and amendments thereto.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. Vacuum cleaners covered by this specification are intended for removing dirt, dust and other dry particles or debris in all general light industrial or housekeeping functions.

6.2 Acquisition requirements. Acquisition documents must specify the following:

(a) Title, number, and date of this specification.
(b) Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
(c) If first article inspection is required (see 3.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

(d) Whether corrosion-resistant steel will be provided (see 3.5.4).
(e) Type of power cord assembly required (see 3.10).
(f) Level of preservation and packing required (see 5.1).
(g) When fire retardant materials are not required (see 5.1).

6.3 Consideration of data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Descriptions (DIDs) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/provided and that the DIDs are tailored to reflect the requirements of the specific acquisition. To ensure correct contractual application of the data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DOD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

Reference paragraph	DID number	DID title	Suggested tailoring
4.3	DI-MISC-80653	Test reports	-----

The above DIDs were those cleared as of the date of this specification. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DIDs are cited on the DD Form 1423.

6.4 Technical manuals. The requirement for technical manuals should be considered when this specification is applied on a contract. If technical manuals are required, military specifications and standards that have been cleared and listed in DOD 5010.12L, Acquisition Management Systems and Data Requirements Control List (AMSDL) must be listed on a separate Contract Data Requirements List (DD Form 1423), which is included as an exhibit to the contract. The technical manuals must be acquired under separate contract line item in the contract.

6.5 First article. When first article inspection is required, the contracting officer should provide specific guidance to offerors whether the item(s) should be a preproduction sample, a first article sample, a first production item, a sample selected from the first lot production items, a standard production item from the contractors current inventory (see 3.1), and the number of items to be tested as specified in 4.3. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.

6.6 Subject term (key word) listing.

Bag, filter
Fan, cover
Impellers

6.7 Sub-contracted material and parts. The packaging requirements of referenced documents listed in section 2 do not apply when material and parts are acquired by the contractor for incorporation into the equipment and lose their separate identity when the equipment is shipped.

6.8 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Navy - SH
Air Force - 99

Review activity:
Air Force - 84

User activity:
Navy - MC

Preparing activity:
Navy - SH
(Project 7910-0072)

Source: https://assist.dla.mil -- Downloaded: 202610-19T08:54Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-C-21100D	90/10/04

3. DOCUMENT TITLE
CLEANER, VACUUM INDUSTRIAL, EXTERNAL FILTER TYPE

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
Technical Point of Contact (TPOC): Mr. Jim Brechka (NAVSSES 074) PLEASE ADDRESS ALL CORRESPONDENCE AS FOLLOWS:	(1) Commercial TPOC: 215-443-7653	(2) AUTOVON 443-7653
c. ADDRESS (Include Zip Code) Commander, Naval Sea Systems Command Department of the Navy (SEA 55Z3) Washington, DC 20362-5101	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 — Previous editions are obsolete. — 198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:54Z
Check the source to verify that this is the current version before use.