MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

LENSES, FILTERS, AND MIRRORS (OPTICAL)

TO ALL HOLDERS OF DOD-STD-35-120(MI):

1. THE FOLLOWING PAGES OF DOD-STD-35-120(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
v	18 SEPTEMBER 1992	v	17 JULY 1978
1	18 SEPTEMBER 1992	1	17 JULY 1978
2	18 SEPTEMBER 1992	2	17 JULY 1978
3	18 SEPTEMBER 1992	3	17 JULY 1978
4	18 SEPTEMBER 1992	4	17 JULY 1978
5	18 SEPTEMBER 1992	5	17 JULY 1978
6	18 SEPTEMBER 1992	6	17 JULY 1978
11	18 SEPTEMBER 1992	11	17 JULY 1978
12	18 SEPTEMBER 1992	12	17 JULY 1978
35	17 JULY 1978	(Reprinted without change)	
36	18 SEPTEMBER 1992	36	17 JULY 1978
37	18 SEPTEMBER 1992	37	17 JULY 1978
38	18 SEPTEMBER 1992	38	17 JULY 1978
39	18 SEPTEMBER 1992	39	17 JULY 1978
40	17 JULY 1978	(Reprinted without change)	
57	17 JULY 1978	(Reprinted without change)	
58	18 SEPTEMBER 1992	58	17 JULY 1978
59	18 SEPTEMBER 1992	59	17 JULY 1978
60	18 SEPTEMBER 1992	60	17 JULY 1978
65	17 JULY 1978	(Reprinted without change)	
66	18 SEPTEMBER 1992	66	17 JULY 1978
67	18 SEPTEMBER 1992	67	17 JULY 1978
68	17 JULY 1978	(Reprinted without change)	

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
73	18 SEPTEMBER 1992	73	17 JULY 1978
74	18 SEPTEMBER 1992	74	17 JULY 1978
75	18 SEPTEMBER 1992	75	17 JULY 1978
76	18 SEPTEMBER 1992	76	17 JULY 1978
77	18 SEPTEMBER 1992	77	17 JULY 1978
78	17 JULY 1978 (Reprinted without change)		
81	17 JULY 1978 (Reprinted without change)		
82	18 SEPTEMBER 1992	82	17 JULY 1978
83	18 SEPTEMBER 1992	83	17 JULY 1978
84	18 SEPTEMBER 1992	84	17 JULY 1978

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of DOD-STD-35-120(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army-MI

Review activities:
Army-AT, AV, CR, ER
ME, MR, SC

User activity
Army - AR

Preparing activity:
Army - MI

(Project EGDS-A456)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

CONTENTS

			Page
Paragraph	1.	SCOPE	1
	1.1	General	1
	1.2	Purpose	1
	1.3	Utilization	1
	1.4	Military Specification Exception Title Index	1
	2.	APPLICABLE DOCUMENTS	5
	2.1	Government documents	5
	2.2	Non-Government publications	6
	3.	DEFINITIONS	7
	4.	GENERAL REQUIREMENTS	9
	4.1	Introduction	9
	4.2	Specification Requirement Sheet (SRS)	9
	4.3	Configuration	9
	4.3.1	Dimensions	9
	4.3.2	Illustrations	9
	4.4	Units of measure	9
	5	DETAILED REQUIREMENTS	11
	5.1	Introduction	11
	5.2	MSE Formats	11
	5.3	Referenced documents	11
	5.4	Deleted	11
	5.5	Tabulation	12
	5.6	Keyword Code Index (KCI) and Standard Paragraphs	15
	5.6.1	Interrelationship of Codes	15
	5.6.2	Automatic MSE Data	15
	5.6.3	DOD-STD-35 Tables	15

TABLES

Table	I.	Title Index	2
	II.	Deleted	12
	III.	Tabulation Candidates	13

APPENDICES

Appendix	A.	Illustrations	139
	B.	Characteristic Code Index	145
		Index	153

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 General. This dash-numbered part of the Automated Engineering Document Preparation System (AEDPS), provides detailed requirements for the preparation of Military Specification Exception (MSE) documentation for Lenses, Filters, and Mirrors (Optical).

1.2 Purpose. This military standard provides the necessary information to prepare a Specification Requirement Sheet (SRS) which will be used to generate an MSE by automated data processing.

1.3 Utilization. General instructions, quality assurance provisions, packaging, and notes, applicable to all AEDPS dash-numbered parts have been included in the basic document (DOD-STD-35) to avoid redundancy. Unless otherwise specified in this dash-numbered part, the following list contains additional subjects that are applicable to all AEDPS dash-numbered parts and are included in DOD-STD-35:

a. Writing Methodology
b. Document and Part Numbering
c. Applicable Documents
d. Single and Multi-item Specifications (Tabulation)
e. Keyword Code Index (KCI)
f. General Requirements of AEDPS

1.4 Military Specification Exception Title Index. The title code for an MSE shall be selected from one of the MSE titles listed in the Title Index (see table I). Data bases have been established for the generation of MSE's for the MSE titles indicated. If a suitable title code is not contained in the Title Index, leave the title code spaces on the SRS blank, and attach a request for the assignment of a title code. Include in the request the desired title and the base document identifier. A code will be assigned and the code, title, and base document will be made a part of the Title Index.

One of the six-digit codes listed in the Title Index, entered on an SRS, will specify that the title of the MSE will be the title shown in the Title Index.

Each MSE title listed in the Title Index is compatible with the document(s) listed with that title under base document. The list of base documents may or may not be a complete listing. The information shown under coverage is intended for the user's reference; when more than one document is listed for an MSE title, this information will be found useful in determining which of the documents is most suitable for use as the base document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

The MSE title may or may not be the same as the title used in DODISS, FIIG, or the base document. In general, the MSE title uses the basic federal item name listed in Cataloging Handbook H6. However, titles with additional modifying and identifying words are provided to assist in defining the scope of the MSE. Also, less restrictive titles are provided to prevent exclusion of items.

TABLE I. TITLE INDEX

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
LENSES	905001	MIL-L-4352	TRIAL LENS SET GUN CAMERA LENSES
		MIL-L-5630	BEACON LIGHT LENS AND DOVER
		MIL-L-10114	3 PLY LENS, CYLINDRICAL
		MIL-L-11931	COPYING LENS
		MIL-F-16377	LIGHT LENSES AND GLOBES
		MIL-L-24560	LIGHTS AND GLASSWARE
		A-A-53088	GLASS LENS OPHTHALMIC
		MIL-L-22257	TV LENS SYSTEM
		A-A-51334	OPHTHALMIC LENS MEASURING INST.
		A-A-53088	NEUTRAL ABSORP. OPHTHALMIC LENS
		A-A-51707	PLASTIC LENS; OPHTHALMIC
		A-A-54008	RED DIPLOPIA TEST LENS

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
LENSES (CONT)	905001 (CONT)	A-A-53088	ONE PIECE LENS BLANK, BIFOCAL
		MIL-L-38169	GOGGLE AND VISOR LENSES
		MIL-L-50064	SIMPLE LENSES OPHTHALMIC
		MS16867	GLASS MARINE LENSES
		MS17998	NAVIGATIONAL LIGHTS, LENSES
		MS25391	DOUBLE BEAM LENS
		MS35420	BLACKOUT LENS
		MS35421	MARKER LIGHT LENS
FILTERS	905002	MIL-F-2763	BINOCULAR FILTER
		MIL-F-9329	PHOTOGRAPHIC LIGHT FILTERS
		MIL-F-12716	LAMINATED LIGHT FILTERS, TELESCOPIC
		MIL-F-13455	BLACKOUT LIGHT FILTER
		MIL-F-21241	FINISHED COLOR FILTERS
		MIL-F-21424	POLARIZING FILTERS
		MIL-F-45289	INFRARED FILTER INTERFERENCE
		MIL-F-52393	INFRARED FILTER KIT
		MIL-F-55608	INFRARED FILTER INTERFERENCE
		MIL-F-55614	INFRARED FILTER INTERFERENCE

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
FILTERS (CONT)	905002 (CONT)	MIL-F-83236	SIGNAL LIGHT FILTER
		MS24489	MARKER LIGHT FILTER
		MS24502	MARKER LIGHT FILTER
		MS51600	OPTICAL INSTRUMENT LIGHT FILTER
MIRRORS	905003	DD-M-411	FRAMED PLATE GLASS MIRRORS
		GGG-M-350	INSPECTION MIRROR
		MIL-M-1715	GLASS, TRIPLE-SECTION, FULL-LENGTH MIRROR
		MIL-M-13508	FRONT SURFACED ALUMINIZED MIRROR
		MIL-M-18371	EMERGENCY SIGNALING MIRRORS

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-C-25050	Colors, Aeronautical Lights and Lighting Equipment, General Requirements For

STANDARDS

FEDERAL

FED-STD-595	Colors

MILITARY

MIL-STD-35	Automated Engineering Document Preparation System, Basic
MIL-STD-150	Photographic Lenses
MIL-STD-810	Environmental Test Methods
MIL-STD-1241	Optical Terms and Definitions
MIL-STD-1278	Filters, Light, Photographic

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation.

ASTM D 785	Rockwell Hardness of Plastics and Electrical Insulating Materials
ASTM D 792	Standard Methods of Test for Specific Gravity and Density of Plastics by Displacement
ASTM D 2240	Standard Method of Test for Indentation Hardness of Rubber and Plastics by Means of a Durometer
ASTM E 380	Metric Practice Guide

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103.)

ANSI C 29.1	American National Standard Test Methods for Electrical Power Insulators

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, N. Y. 10018.)

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:03Z
Check the source to verify that this is the current version before use.

5. DETAILED REQUIREMENTS

5.1 Introduction. This section provides instructions for completion of the SRS and references for instructions on specific requirements contained in DOD-STD-35.

5.2 MSE formats. AEDPS has the capability to prepare a six-section or a single-section document. The six-section document appears similar to a six-section military specification. The single-section document appears similar to a military specification sheet. Specification requirements described in DOD-STD-35 are applicable to either of the formats selected. It is mandatory that one of the two following codes and an "X" be entered on the SRS to create the desired MSE format:

a. 0700 for a six-section format

b. 0800 for a single-section format

5.3 Referenced documents. Section 2 of the MSE may contain a list of all referenced documents within Sections 3, 4, and 5 of the MSE. Instructions for referencing documents to appear in Section 2 of the forthcoming MSE are contained in DOD-STD-35.

5.4 Deleted

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

5.5 Tabulation. Instructions for tabulation are provided in DOD-STD-35. Table III provides codes for column headings which may be used for Lenses, Filters, and Mirrors (Optical) characteristics. When different units of measure within one system (U.S. or SI) are available for specifying a characteristic, only one of the units may be tabulated; e.g. either ounces or pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1612	INDEX OF REFRACTION SHALL BE 1612.
1613	PLUS INDEX OF REFRACTION TOLERANCE SHALL BE 1613.
1614	MINUS INDEX OF REFRACTION TOLERANCE SHALL BE 1614.
1615	TEMPERATURE SHALL BE 1615 DEGREE(S) CELSIUS.
1616	SPECIFIC GRAVITY SHALL BE 1616.
1617	PLUS SPECIFIC GRAVITY TOLERANCE SHALL BE 1617.
1618	MINUS SPECIFIC GRAVITY TOLERANCE SHALL BE 1618.
1619	TEMPERATURE SHALL BE 1619 DEGREE(S) CELSIUS.
1620	LENS POWER SHALL BE 1620 DIOPTER(S).
1621	LENS POWER SHALL BE 1621 PER METER.
6943	MINIMUM WEIGHT PER UNIT. THE WEIGHT PER UNIT SHALL BE NOT LESS THAN 6943 OUNCE(S).
6945	MINIMUM WEIGHT PER UNIT. THE WEIGHT PER UNIT SHALL BE NOT LESS THAN 6945 GRAM(S).

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DESIGN AND CONSTRUCTION (CONT)	
WEIGHT (CONT)	
MAXIMUM WEIGHT PER UNIT (SELECT ONE)	
U.S.	
(OUNCES)	7022
SI	
(GRAMS)	7021
ABRASION	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1641
AS FOLLOWS:	1642
NO MAJOR DAMAGE TO RUBBED AREA.	1643
NO REMOVAL OF COATING.	1644
MAXIMUM HAZE (PERCENT)	1645
MAXIMUM REDUCTION IN REFLECTANCE (PERCENT)	1646
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1648
PER (DOC DES)	1649

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
7022	MAXIMUM WEIGHT PER UNIT. THE WEIGHT PER UNIT SHALL BE NOT GREATER THAN 7022 OUNCE(S).
7021	MAXIMUM WEIGHT PER UNIT. THE WEIGHT PER UNIT SHALL BE NOT GREATER THAN 7021 GRAM(S).
1641	ABRASION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1641.
1642	ABRASION. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1643	THERE SHALL BE NO MAJOR DAMAGE TO RUBBED AREA(S).
1644	THERE SHALL BE NO REMOVAL OF THE COATING.
1645	HAZE SHALL BE NOT GREATER THAN 1645 PERCENT.
1646	REDUCTION IN REFLECTANCE SHALL BE NOT GREATER THAN 1646 PERCENT.
1648	ABRASION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1648.
1649	ABRASION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1649.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
ABRASION (CONT)	
TEST METHODS (CONT)	
PER MIL-L-38169.	1651
RUBBING CYCLES (NUMBER)	1652
RUBBING LENGTH (SELECT ONE)	
(INCHES)	1653
(CENTIMETERS)	1654
ERASER FORCE (SELECT ONE)	
(POUNDS)	1655
(KILOGRAMS)	1656
ACCELERATION	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	6272
NO EVIDENCE OF PHYSICAL DAMAGE.	6273
REMAIN WITHIN SPECIFIED TOLERANCE.	6277
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	6250

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1651	ABRASION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-L-38169.
1652	THERE SHALL BE 1652 RUBBING CYCLE(S).
1653	RUBBING LENGTH SHALL BE 1653 INCH(S).
1654	RUBBING LENGTH SHALL BE 1654 CENTIMETER(S).
1655	ERASER FORCE SHALL BE 1655 POUND(S).
1656	ERASER FORCE SHALL BE 1656 KILOGRAM(S).
6272	ACCELERATION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 6272.
6273	ACCELERATION. THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.
6277	ITEM(S) SHALL REMAIN WITHIN SPECIFIED TOLERANCE.
6250	ACCELERATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 6250.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
ACCELERATION (CONT)	
TEST METHODS (CONT)	
PER MIL-STD-810, METHOD 513.	6252
*A LEVEL (G's)	6275
*VEHICLE CATEGORY (SELECT ONE)	
AIRPLANE.	6240
HELICOPTER.	6241
MANNED AEROSPACE VEHICLE.	6242
AIR LAUNCHED MISSILE.	6243
GROUND LAUNCHED MISSILE.	6244
PROCEDURE NUMBER (ROMAN NUMERAL)	6256
TEST TIME (MINUTES)	6259
BOILING	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1661

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1781	COATING/PLATING. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1781.
1782	COATING/PLATING. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH DD-M-411.
1783	SILVER PLATING THICKNESS SHALL BE NOT LESS THAN 1783 MICROINCH(S).
1784	SILVER PLATING THICKNESS SHALL BE NOT LESS THAN 1784 MICROMETER(S).
1785	COPPER BACKING PLATING THICKNESS SHALL BE NOT LESS THAN 1785 MICROINCH(S).
1986	COPPER BACKING PLATING THICKNESS SHALL BE NOT LESS THAN 1786 MICROMETER(S).
1791	COATING/PLATING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1791.
1792	COATING/PLATING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH DD-M-411.
1793	PAINT SOLVENT 1793 SHALL BE USED TO EXPOSE THE COPPER PLATING.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
COLORFASTNESS TO LIGHT	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1796
NO EVIDENCE OF PEELING, WARPING, CRACKING, CRAZING, OR OPTICAL DEFECTS.	1797
MINIMUM SPECTRAL TRANSMITTANCE (PERCENT)	1798
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1801
PER (DOC DES)	1802
DISTANCE BETWEEN LENS AND LAMP (SELECT ONE)	
(INCHES)	1803
(CENTIMETERS)	1804
LENS TEMPERATURE	
MINIMUM (DEGREES CELSIUS)	1805
MAXIMUM (DEGREES CELSIUS)	1806

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1796	COLORFASTNESS TO LIGHT. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1796.
1797	COLORFASTNESS TO LIGHT. THERE SHALL BE NO EVIDENCE OF PEELING, WARPING, CRACKING, CRAZING, OPTICAL DISTORTION OF THE CRITICAL AREA, OR ANY OTHER OPTICAL DEFECTS.
1798	SPECTRAL TRANSMITTANCE SHALL BE NOT LESS THAN 1798 PERCENT.
1801	COLORFASTNESS TO LIGHT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1801.
1802	COLORFASTNESS TO LIGHT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1802.
1803	DISTANCE BETWEEN LENS AND LAMP SHALL BE 1803 INCH(S).
1804	DISTANCE BETWEEN LENS AND LAMP SHALL BE 1804 CENTIMETER(S).
1805	LENS TEMPERATURE SHALL BE NO LESS THAN 1805 DEGREE(S) CELSIUS.
1806	LENS TEMPERATURE SHALL BE NOT GREATER THAN 1806 DEGREE(S) CELSIUS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DEFINITION/PARALAX/RESOLUTION	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ___	1811
AS FOLLOWS:	1812
NO IMPAIRMENT OF DEFINITION.	1813
NO VISIBLE PARALAX.	1814
MINIMUM RESOLVING POWER (LINES PER MILLIMETER)	1815
NO DIFFUSED OR SCATTERED LIGHT.	1816
MAXIMUM LIMIT OF RESOLUTION (SECONDS OF ARC)	1817
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ___	1821
PER MIL-F-21241.	1822

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

DEVIATION TABLE

APERTURE DIAMETER		DEVIATION
INCHES	MILLIMETERS	MINUTES OF ARC
3000	3001	3002
3003	3004	3005
3006	3007	3008
3009	3010	3011
3012	3013	3014

1846 DEVIATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1846.

1847 DEVIATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-F-2763.

1848 DEVIATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-F-9329.

1849 DEVIATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE DEVIATION TABLE.

1856 DIFFUSION ENAMEL. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1856.

1857 DIFFUSION ENAMEL. THERE SHALL BE NO LOOSENING, SOFTENING, OR OTHER DISSOLUTION OF ENAMEL.

1861 DIFFUSION ENAMEL. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT 1861.

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DIFFUSION ENAMEL (CONT)	
TEST METHODS (CONT)	
PER (DOC DES)	1862
MINIMUM SUBMERSION DURATION (MINUTES)	1863
DISTORTION/IMAGE QUALITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ___	1866
AS FOLLOWS:	1867
NO IMPAIRMENT OF RESOLUTION OR PARALLAX.	1868
NO TANGENTIAL DISTORTION.	1869
MAXIMUM ASTIGMATISM DIFFERENCE (DIOPTERS)	1870
MAXIMUM DISTORTION (SELECT ONE)	
(MILLIMETERS)	1871
(MICRONS)	1872
(DIOPTERS)	1873
MAXIMUM RADIAL DISSTORTION (MILLIMETERS)	1874
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ___	1876

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1862	DIFFUSION ENAMEL. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1862.
1863	SUBMERSION DURATION SHALL BE NOT LESS THAN 1863 MINUTE(S).
1866	DISTORTION/IMAGE QUALITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1866.
1867	DISTORTION/IMAGE QUALITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1868	THERE SHALL BE NO IMPAIRMENT OF RESOLUTION OR PARALLAX.
1869	THERE SHALL BE NO TANGENTIAL DISTORTION.
1870	ASTIGMATISM DIFFERENCE SHALL BE NOT GREATER THAN 1870 DIOPTER(S).
1871	DISTORTION SHALL BE NOT GREATER THAN 1871 MILLIMETER(S).
1872	DISTORTION SHALL BE NOT GREATER THAN 1872 MICRON(S).
1873	DISTORTION SHALL BE NOT GREATER THAN 1873 DIOPTER(S).
1874	RADIAL DISTORTION SHALL BE NOT GREATER THAN 1874 MILLIMETER(S).
1876	DISTORTION/IMAGE QUALITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1876.

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DISTORTION/IMAGE QUALITY (CONT)	
TEST METHODS (CONT)	
PER DOCUMENT (DOC DES)	1877
APERTURE DIAMETER (SELECT ONE)	
(INCHES)	1878
(MILLIMETERS)	1879
TELESCOPE POWER (NO.)	1880
DIOPTOMETER POWER (NO.)	1881
TARGET DISTANCE (SELECT ONE)	
(FEET)	1882
(METERS)	1883
EXPOSURE CYCLE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ___	1886
AS FOLLOWS:	1887
NO DELAMINATION, FOGGING, CRAZING, OR CORROSION.	1888
NO OBSTRUCTION OR DISTORTION OF VISION.	1889

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1901	FLATNESS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1901.
1902	FLATNESS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-M-18371.
4760	FUNGUS. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4760.
4761	FUNGUS. ALL EXTERNAL MATERIALS SHALL BE NONNUTRIENT TO FUNGUS GROWTH OR SHALL BE SUITABLY TREATED TO RETARD FUNGUS GROWTH. THE MANUFACTURER SHALL VERIFY BY CERTIFICATION THAT ALL EXTERNAL MATERIALS ARE FUNGUS RESISTANT OR SHALL PERFORM THE FUNGUS TEST. WHEN THE FUNGUS TEST IS PERFORMED, THERE SHALL BE NO EVIDENCE OF FUNGUS GROWTH ON THE EXTERNAL SURFACES.
4762	FUNGUS. ALL EXTERNAL MATERIALS SHALL BE NONNUTRIENT TO FUNGUS GROWTH OR SHALL BE SUITABLY TREATED TO RETARD FUNGUS GROWTH. THERE SHALL BE NO EVIDENCE OF FUNGUS GROWTH ON THE EXTERNAL SURFACES.
4754	FUNGUS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4754.
4755	FUNGUS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 508 OF MIL-STD-810.
4756	TEST PERIOD SHALL BE 4756 DAY(S).

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
HARDNESS	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1906
AS FOLLOWS:	1907
BARCOL HARDNESS	
MINIMUM (NO.)	1908
MAXIMUM (NO.)	1909
ROCKWELL HARDNESS	
MINIMUM (NO.)	1910
MAXIMUM (NO.)	1911
HARDNESS (NAME)	1912
MINIMUM (NO.)	1913
MAXIMUM (NO.)	1914
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1921
PER ASTM D 785.	1923
PER ASTM D 2240.	1924

Source: https://assist.dla.mil -- Downloaded: 20260-23T21:03Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1906	HARDNESS. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1906.
1907	HARDNESS. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1908	BARCOL HARDNESS SHALL BE NOT LESS THAN 1908.
1909	BARCOL HARDNESS SHALL BE NOT GREATER THAN 1909.
1910	ROCKWELL HARDNESS SHALL BE NOT LESS THAN 1910.
1911	ROCKWELL HARDNESS SHALL BE NOT GREATER THAN 1911.
1912	1912 HARDNESS SHALL APPLY.
1913	HARDNESS SHALL BE NOT LESS THAN 1913.
1914	HARDNESS SHALL BE NOT GREATER THAN 1914.
1921	HARDNESS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1921.
1923	HARDNESS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM D 785.
1924	HARDNESS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM D 2240.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
HOMOGENEITY (CONT)	
TEST METHODS (CONT)	
PER MIL-STD-1278.	1947
TEST METHOD IX.	1948
TEST METHOD X.	1949
HUMIDITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4798
NO EVIDENCE OF CORROSION OR PHYSICAL DAMAGE.	4799
NO DEGRADATION OF PERFORMANCE.	4815
REMAIN WITHIN SPECIFIED TOLERANCE.	4791
MINIMUM REFLECTANCE (PERCENT)	1968
NO EVIDENCE OF LAMINATION SEPARATION.	1969
NO EVIDENCE OF CORROSION OR PITTING.	1970
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4788

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
4853	HUMIDITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 103 OF MIL-STD-202.
4890	TEST CONDITION LETTER 4890 SHALL APPLY.
4871	HUMIDITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 507 OF MIL-STD-810.
4767	PROCEDURE NUMBER I SHALL APPLY.
4796	SPECIMEN(S) SHALL BE EXPOSED TO EXTREME HIGH TEMPERATURE BEFORE TESTING.
4777	SPECIMEN(S) SHALL BE EXPOSED TO 4777 DEGREES CELSIUS BEFORE TESTING.
4778	DURATION OF EXPOSURE TO EXTREME TEMPERATURE SHALL BE 4778 HOUR(S).
4800	THERE SHALL BE 4800 TEST CYCLE(S).
4816	DURATION OF THE TEST SHALL BE 4816 HOUR(S).
1976	IMPACT. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1976.
1977	IMPACT. THERE SHALL BE NO EVIDENCE OF CRACKS, CHIPS, OR FRACTURES.

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
IMPACT (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ___	1981
PER MIL-L-10114.	1982
PER (DOC DES)	1983
DIAMETER OF STEEL BALL (SELECT ONE)	
(INCHES)	1984
(CENTIMETERS)	1985
HEIGHT OF DROP (SELECT ONE)	
(INCHES)	1986
(CENTIMETERS)	1987
RUBBER GASKET THICKNESS (SELECT ONE)	
(INCH)	1988
(CENTIMETERS)	1989
WEIGHT OF STEEL BALL (SELECT ONE)	
(OUNCES)	1990
(GRAMS)	1991

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1981	IMPACT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1981.
1982	IMPACT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-L-10114.
1983	IMPACT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1983.
1984	DIAMETER OF THE STEEL BALL SHALL BE 1984 INCH(S).
1985	DIAMETER OF THE STEEL BALL SHALL BE 1985 CENTIMETER(S).
1986	HEIGHT OF DROP SHALL BE 1986 INCH(S).
1987	HEIGHT OF DROP SHALL BE 1987 CENTIMETER(S).
1988	RUBBER GASKET THICKNESS SHALL BE 1988 INCH(S).
1989	RUBBER GASKET THICKNESS SHALL BE 1989 CENTIMETER(S).
1990	WEIGHT OF STEEL BALL SHALL BE 1990 OUNCE(S).
1991	WEIGHT OF STEEL BALL SHALL BE 1991 GRAM(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
IMPACT (CONT)	
PER (DOC DES) (CONT)	
TEST TEMPERATURE	
MINIMUM (DEGREES CELSIUS)	1992
MAXIMUM (DEGREES CELSIUS)	1993
LEAKAGE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1996
NO EVIDENCE OF LEAKAGE.	1997
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2001
PER MIL-L-10114.	2002
DIFFERENTIAL PRESSURE (SELECT ONE)	
(PSID)	2003
(PASCALS)	2004
DURATION (MINUTES)	2005

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.