MILITARY SPECIFICATION

MINE, METAL PARTS FOR
MINES : BLU-91/B AND BLU-92/B

This specification is approved for use by the U.S. Army Armament Research and Development command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not normally covered by drawings and provides quality assurance provisions for the fabrication and packaging of the metal parts for the Mines: Antitank, BLU-91/B, and Antipersonnel, BLU-92/B.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

ML-C-5541 - Chemical Conversion Coatings on Aluminum and Aluminum Alloys
MIL-A-48078 - Ammunition. Standard Quality Assurance Provision, General Specification for

FEDERAL

QQ-P-35 - Passivation Treatments for Corrosion Resisting Steel
TT-C-490 - Cleaning Method and Pretreatment of Ferrous Surfaces for Organic Coatings

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

FSC: 1345

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:59Z
Check the source to verify that this is the current version before use.

MIL-STD-1188- Commercial Packaging of Supplies and Equipment

DRAWINGS (See 6.5)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9292715 - Cover
9292716 - Housing Aeroballistic
9292723 - Clip, Borerider
9328744 - Pin, Borerider
9292731 - Fastener, Push-on
9332383 - Spacer End Cover Assembly

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

ASTM B 117 Standard Method of Salt Spray (Fog) Testing
ASTM E 18 Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Components and assemblies. The parts shall comply with all requirements specified on drawings listed in paragraph 2.1 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Salt spray. The designated parts shall withstand exposure to salt spray when tested as specified in 4.5.2.

3.4 Hardness. The Push-on Fastener, Dwg 9292731, shall pass the hardness test as specified in 4.5.3.

3.5 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.6 Workmanship. All part and assemblies shall be fabricated, and assembled in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent . All required markings shall be neat and sharply defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:59Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the contracting officer for evaluationin accordance with provisions of 4.3.2. The First Article sample shall consist of the following items in sample quantities as indicated:

Part Description	Drawings	Quantity
Cover	9292715	10
Housing, Aeroballistic	9292716	10
Clip, Borerider	9292723	10
Pin, Borerider	9328744	10
Fastener, Push-on	9292731	15
Cover Assembly	9332379	10
Cover, Spacer	9332382	10
Spacer, Lens	9332380	10
Eyelet, Borerider	9332381	10
Spacer End Cover Assembly	9332383	10

4.3.2 Inspection to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:59Z
Check the source to verify that this is the current version before use.

TABLE I. First Article Inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63508(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
	Metal Parts For Mines: BLU-91/B and BLU-92/B				See below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cover (Dwg. 9292715)				
	Examination for defects	10		3.2	4.4.2.1
	Housing, Aeroballistic (Dwg. 9292716)				
	Examination for defects	10		3.2	4.4.2.2
	Clip, Borerider (Dwg. 9292723)				
	Examination for defects	10(a)		3.2	4.4.2.3
	Salt spray test	10(a)		3.3	ASTM B 117
	Pin, Borerider (Dwg. 9328744)				
	Examination for defects	10(a)		3.2	4.4.2.4
	Salt spray test	10(a)		3.3	ASTM B 117
	Fastener, Push-on (Dwg. 9292731)				
	Examination for defects	10(a)		3.2	4.4.2.5
	Salt spray test	10(a)		3.3	ASTM B 117
	Hardness	5		3.4	ASTM E 18
	Cover, Spacer (Dwg. 9332382)				
	Examination for defects	10		3.2	4.4.2.6

NOTES: (a) These shall be the same 10 assemblies.

DRDAR-Q Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 7 which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 20260-23T02:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	Metal Parts For Mines: BLU-91/B and BLU-92/B				See below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Evelet, Borerider (Dwg. 9332381)				
	Examination for defects	10		3.2	4.4.2.7
	Cover Assembly (Dwg. 9332379)				
	Examination for defects	10		3.2	4.4.2.8
	Spacer, Lens (Dwg. 9332380)				
	Examination for defects	10		3.2	4.4.2.9
	Spacer End Cover Assy (Dwg. 9332383)				
	Examination for defects	10		3.2	4.4.2.10

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:59Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. (See MIL-A-48078). Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:59Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63508(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Cover				9292715
					NEXT HIGHER ASSEMBLY 9292710/9330381
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Length of oval holes (4)		0.40%	3.2	Gage
103	Width of oval holes (4)		0.40%	3.2	Gage
104	Thickness		0.40%	3.2	Gage
105	Height of tab		0.40%	3.2	Gage
106	Width of tab		0.40%	3.2	Gage
107	Depth of offset		0.40%	3.2	Gage
108	Distance from outside diameter to offset		0.40%	3.2	Gage
109	True position of oval holes (4)		0.40%	3.2	Gage
110	True position of tabs (4)		0.40%	3.2	Gage
111	Small hole		0.40%	3.2	Gage
112	Small hole angle		0.40%	3.2	Gage
113	Dim. "H"		0.40%	3.2	Gage
Minor					
201	Protective finish missing or improper		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES: Used on AP & AT mines.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:59Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63508(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9292716
4.4.2.2	Housing, Aeroballistic				NEXT HIGHER ASSEMBLY 9292710
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Height		0.40%	3.2	Gage
102	Width		0.40%	3.2	Gage
103	Length		0.40%	3.2	Gage
104	True position of width to Datum A		0.40%	3.2	Gage
105	True position of length to Datum A		0.40%	3.2	Gage
106	Datum A, inside diameter of ribs		0.40%	3.2	Gage
107	Outside diameter of mine sleeve		0.40%	3.2	Gage
108	Height of "S"		0.40%	3.2	Gage
109	Radius of "S" (2 places)		0.40%	3.2	Gage
110	Diameter of rivet hole (2 places)		0.40%	3.2	Gage
111	Location of rivet hole (2 places)		0.40%	3.2	Gage
112	Wall thickness		0.40%	3.2	Gage
Minor					
201	Width of clip slot		0.65%	3.2	Gage
202	True position of clip slot		0.65%	3.2	Gage
203	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

DRDAR- (orm 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 7 (hich is Obsolete (

Source: https://assistdocs.com - Downloaded: 20240723102392
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63508(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Clip, Borerider		9292723
			NEXT HIGHER ASSEMBLY 9292710

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Width		0.40%	3.2	Gage
102	Length from tip of wind tabs to edge of hinge joint		0.40%	3.2	Gage
103	Length of hinge joint		0.40%	3.2	Gage
104	Height of hinge joint (2 places)		0.40%	3.2	Gage
105	Hinge pin cutout radius (2 places)		0.40%	3.2	Gage
106	Hinge pin cutout location (2 places)		0.40%	3.2	Gage
107	Length from edge to center of hinge pin cutout (2 places)		0.40%	3.2	Gage
108	Length of hinge pin cutout tab (2 places)		0.40%	3.2	Gage
109	Depth of bow undersize		0.40%	3.2	Gage
110	Salt spray test	5		3.3	4.5.2
Minor					
201	Wind tab tip bend radius		0.65%	3.2	Gage
202	Width of wind tab		0.65%	3.2	Gage
203	Material thickness		0.65%	3.2	Gage
204	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

DRDAR-QA Form 160, Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T02:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63508(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Pin, Borerider	1 OF 1	9328744
			NEXT HIGHER ASSEMBLY: 9292710

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter		0.40%	3.2	Gage
102	Length		0.40%	3.2	Gage
103	Chamfer		0.40%	3.2	Gage
104	Salt spray test	5		3.3	4.5.2
Minor					
201	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63508(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Fastener, Push-on				9292731
					NEXT HIGHER ASSEMBLY
					9292710
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Depth of bow		0.40%	3.2	Gage
102	Hardness test	5		3.4	4.5.3
103	Salt spray test	5		3.3	4.5.2
Minor					
201	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T02:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63508(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Cover, Spacer	1 OF 1	9332382
			NEXT HIGHER ASSEMBLY: 9332379

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter (O.D.)		0.40%	3.2	Gage
102	Inside diameter		0.40%	3.2	Gage
103	Height		0.40%	3.2	Gage
104	Protective finish missing or improper	(a)	-	3.2	Visual
105	Hole location		0.40%	3.2	Gage
106	Hole diameter		0.40%	3.2	Gage
107	Location of O.D. with respect to datum A		0.40%	3.2	Gage
Minor					
201	Thickness		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES: (a) Sampling and rejection in accordance with QQ-P-35.
Used on AT mine only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Eyelet, Borerider				9332381
					NEXT HIGHER ASSEMBLY 9332379
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter		0.40%	3.2	Gage
102	Length		0.40%	3.2	Gage
103	Flare missing or improper		0.40%	3.2	Gage
104	Protective finish missing or improper	(a)	-	3.2	Visual
Minor					
201	Flange diameter		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES: (a) Sampling and rejection in accordance with QQ-P-35. Used on AT mine only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:59Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63508(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.8	Cover Assembly		9332379
			NEXT HIGHER ASSEMBLY 9332383

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Location of borerider eyelet with respect to datum A		0.40%	3.2	Gage
102	Braze joint inadequate		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES: Used on AT mine only.

DRDAR-(rm 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 7(ich is Obsolete (

Source: https://assist.dla.mil -- Downloaded: 2020-07-31T02:39Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63508(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.9	Spacer, Lens		9332380
			NEXT HIGHER ASSEMBLY 9332383

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Diameter of S&A cavity		0.40%	3.2	Gage
103	Depth of S&A cavity		0.40%	3.2	Gage
104	Length of propellant cavity		0.40%	3.2	Gage
105	Width of propellant cavity		0.40%	3.2	Gage
106	Depth of propellant cavity		0.40%	3.2	Gage
107	Overall height		0.40%	3.2	Gage
108	Spherical radius		0.40%	3.2	Gage
109	Width of space cup slot		0.40%	3.2	Gage
110	Depth of space cup slot		0.40%	3.2	Gage
111	Location of S&A flat		0.40%	3.2	Gage
112	Hole diameter		0.40%	3.2	Gage
113	Hole location		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES: Used on AT mine only.

DRDAR-QA Form 160, Jul 77 Replaces SARPA-QA Form 2542 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63508(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Spacer End Cover Assembly		9332383
			NEXT HIGHER ASSEMBLY 9330380

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Height, max		0.40%	3.2	Gage
102	Adhesive material missing or improperly applied (not 360°)		0.40%	3.2	Visual
103	Location of borerider eyelet to datum A		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES: Used on AT mine only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:59Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment (gage) required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1, and the test method paragraph (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and 6.3 herein.

4.5 Test methods and procedures

4.5.1 Salt spray test. The applicable parts shall be tested in accordance with ASTM-B-117 using a 5% salt solution and with the requirements specified on the applicable drawings and specifications. The rejection criteria shall be as specified in the applicable specifications. Assemblies subjected to this test shall not be returned to the lot.

4.5.2 Hardness test. A sample of five (5) push-on fasteners shall be selected from each lot or heat treat batch and tested for hardness in accordance with ASTM-E-18. The lot or heat treat batch shall be rejected if any sample fails to meet the hardness requirement specified on the drawing.

5. PACKAGING

5.1 Preservation-packaging. Packaging shall be Level B in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be Level B in accordance with MIL-STD-1188.

5.3 Marking. Marking shall be Level B in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The metal parts covered by this specification are intended for assembly of the BLU-91/B Anti-tank, and BLU-92/B Antipersonnel Mines .

6.2 Ordering data. Procurement documents shall specifiy the following:

a. Title, number, and date of this specification.

b. Provisions of MIL-A-48078.

c. Provisions for submission of first article samples.

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Submit equipment designs as required, to Comnander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAT-1, Dover, New Jersey 07801.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:59Z
Check the source to verify that this is the current version before use.

6.4 Distribution of ammunition data cards. Distribution of data cards shall include the following: Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAT-M, Dover, New Jersey 07801.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Techincal data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing Activity
Army-AR

Project Number: 1345-A170

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:59Z
Check the source to verify that this is the current version before use.

...TMENT OF THE ARMY

OFFICIAL BUSINESS
... PRIVATE USE $300

POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Armament R&D Command
Attn: DRDAR-GAA
Dover, New Jersey 07801

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:59Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:59Z
Check the source to verify that this is the current version before use.