MIL-O-52724A(ME)
1 May 1980
SUPERSEDING
MIL-O-52724(ME)
7 February 1972

MILITARY SPECIFICATION

OILERS, HAND, PLASTIC

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers plastic containers with a spout for dispensing lubricating oils under pressure.

1.2 Classification. The oilers shall be of the following sizes (see 6.2):

Size 1 - 8 ounce capacity.
Size 2 - 16 ounce capacity.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

FSC 4930

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:30Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

L-P-390	- Plastic, Molding and Extrusion Material Polyethylene and Copolymers (Low, Medium and High Density).
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.

MILITARY

MIL-L-2104	- Lubricating Oil, Internal Combustion Engine, Tactical Service.
MIL-L-46167	- Lubricating Oil, Internal Combustion Engine, Arctic.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

SOCIETY OF THE PLASTICS INDUSTRY (SPI)

Technical Bulletin SP-410, Dimensions for Plastic Bottles.

(Application for copies should be addressed to the Society of The Plastics Industry, 355 Lexington Avenue, New York, NY 10017).

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T21:30Z
Check the source to verify that this is the currentversion before use.

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Description. The oilers shall consist of a translucent polyethylene body with a removable straight or angle spout as specified (see 6.2) with a removable cap. The oiler shall be operated by hand pressure and shall eject oil as specified herein at temperatures specified herein.

3.2 First article. When specified (see 6.2), the contractor shall furnish one or more oilers for first article inspection and approval (see 4.3 and 6.3).

3.3 Material. Material shall be as specified herein. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.4).

3.4 Construction. The oilers with a straight or angle spout and spout cap shall be translucent polyethylene conforming to L-P-390, Type 1, Class L, Grade 2. The oiler may be cylindrical or oval, shall have a flat bottom, and shall be of one-piece seamless construction.

3.5 Graduations. The oiler shall be graduated in increments of 2 ounces.

3.6 Threads. All threaded parts shall be in accordance with the SPI Technical Bulletin SP-410.

3.7 Spout and spout cap.

3.7.1 Straight. The straight spout shall be one-piece molded construction of the same material as the container. One end shall be threaded for not less than one complete thread engagement with the container, and the spout end shall be capable of securing the spout cap. The length of the straight spout shall be not more than 1-1/2 inches, and the opening at the smallest diameter shall be 1/32 inch nominal. The straight spout with spout cap properly attached shall not leak, crack, or become separated when tested as specified in 4.5.2.

3.7.2 Angle. The angle spout shall be one-piece molded construction of the same material as the container. One end shall be threaded for not less than one complete thread engagement with the container and the spout

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:30Z
Check the source to verify that this is the current version before use.

end shall be capable of securing the spout cap. The length of the spout shall be not more than 3 inches, and the opening at the smallest diameter shall be 1/32 inch nominal. The spout shall be bent 30 degrees from the longitudinal axis with the bend starting at the middle of the spout. The spout with spout cap properly attached shall not leak, crack, or become separated when tested as specified in 4.5.2.

3.7.3 Spout cap. The spout cap shall be reusable, and one-piece molded construction; it shall be capable of being attached to the closure spout and shall not crack or separate from the spout or allow the spout to leak when tested as specified in 4.5.2.

3.8 Performance. The oiler shall be filled with oil conforming to MIL-L-46167. With the spout cap removed, and with pressure applied by squeezing the oiler by hand, the oiler shall emit a steady flow of oil when in a horizontal position at temperature range of minus 25° F to plus 125° F. The oiler shall dispense 75 percent of the contents. The remaining 25 percent shall be dispensed with the oiler spout in a downward position, when tested as specified in 4.5.2.3.

3.9 Durability. The oiler shall not crack, break or leak when tested as specified in 4.5.2.2.

3.10 Chemical resistance. The oiler shall not crack, craze, darken, or show signs of chemical corrosion when tested as specified in 4.5.2.

3.11 Identification and marking. The oiler shall be identified in accordance with MIL-STD-130.

3.12 Sizes.

3.12.1 Size 1. The Size 1 oiler shall have a capacity of 8 ounces with a threaded neck in accordance with SPI SP-410, Size 24 straight or angle spout. The oiler shall be not more than 3-1/2 inches in width when constructed in an oval shape, or 2-1/2 inches in diameter when constructed in a cylindrical shape; the height including the spout, shall be not more than 7 inches.

3.12.2 Size 2. The Size 2 oiler shall have a capacity of 16 ounces with a threaded neck in accordance with SPI SP-410, Size 28 threaded straight or angle spout. The oiler shall be not more than 4-1/4 inches in width when constructed in an oval shape, or 3-1/4 inches in diameter when constructed in a cylindrical shape; the height, including the spout, shall be not more than 10 inches.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:30Z
Check the source to verify that this is the current version before use.

3.13 Workmanship.

3.13.1 Finish. The finish of the oilers shall be smooth, and the surface shall be free from ridges and pinch-off flash, flow marks, or depressions.

3.13.2 Freedom from defects. The oilers shall be free from bubbles, cracks, pinholes, dirt, foreign matter, warpage, chipped edges, blisters, scratches, and other defects which could affect serviceability or appearance.

3.13.3 Uniformity. The oilers shall be uniform in color, texture, finish and physical properties.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Material inspection. The contractor is responsible for insuring that materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).
(c) Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. The first article oilers shall be examined as specified in 4.5.1. Presence of one or more defect shall be cause for rejection.

4.3.2 Tests. The first article oilers shall be tested as specified in 4.5.2.1 through 4.5.2.3. Failure of any test shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:30Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination and tests shall be in accordance with MIL-STD-105.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined for the defects specified in 4.5.1. AQL shall be 6 percent defective.

4.4.3 Tests. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2.1. AQL shall be 6.5 percent defective.

4.5 Inspection procedure.

4.5.1 Examination. The oilers shall be examined as specified herein for the following defects:

101. Material not as specified.
102. Oilers not one-piece seamless construction or bottom not flat.
103. Graduations not as specified.
104. Threads of oiler neck and spout not as specified.
105. Threads distorted or containing sharp edges.
106. Straight spout not as specified.
107. Angle spout not as specified.
108. Spout cap missing or not as specified.
109. Identification marking missing, incomplete, or illegible.
110. Dimensions not as specified for the applicable size.
111. Workmanship not as specified.

4.5.2 Tests.

4.5.2.1 Leakage complete assembly. The oiler shall be filled with Grade 10 oil conforming to MIL-L-2104, completely assembled, and positioned with the spout facing downward for a period of 1 hour. Nonconformance to 3.7.1, 3.7.2, 3.7.3, or 3.10 shall constitute failure of this test.

4.5.2.2 Drop. The oiler shall be filled with oil conforming to MIL-L-46167, completely assembled and dropped from not less than 4 feet on a flat concrete surface. After being subjected to a temperature of minus 25° F for a period of 24 hours:

(a) Drop the oilers 3 times to impact upon a side.
(b) Drop the oilers 3 times to impact on the bottom.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:30Z
Check the source to verify that this is the current version before use.

Nonconformance to 3.7.1, 3.7.2, 3.7.3, 3.9, or 3.10 shall constitute failure of this test.

4.5.2.3 Dispensing. The oiler shall be filled with oil conforming to MIL-L-46167 and subjected to a minus 25° F temperature for a period of 24 hours. After conditioning, the oiler shall be held in the horizontal position and operated by hand until the flow of oil ceases. Measure the oil remaining in the oiler. Point the spout downward and operate the oiler by hand. Nonconformance to 3.7.1, 3.7.2, 3.7.3, 3.8 or 3.10 shall constitute failure of this test.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

112.	Containers not as specified for Level A.
113.	Oilers of unlike description preserved together for Level A.
114.	Quantities preserved together are not as specified for Level A.
115.	Strapping not as specified.
116.	Marking missing, illegible, incorrect, or incomplete.

5. PACKAGING

5.1 Preservation. Preservation shall be Level A or Commercial as specified (see 6.2).

5.1.1 Level A. The oilers of like description shall be preserved together in quantities of 12 in a close-fitting box conforming to PPP-B-636, W6c.

5.1.2 Commercial. The oilers shall be preserved in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be Level A, Level B or Commercial as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:30Z
Check the source to verify that this is the current version before use.

5.2.1 Level A. The oilers of like description preserved as specified in 5.1, shall be packed in close-fitting boxes conforming to PPP-B-601, Overseas Type, style optional. Box closure and strapping shall be in accordance with the appendix to the box specification.

5.2.2 Level B. Packing shall be as specified for Level A except that boxes shall be Domestic Type.

5.2.3 Commercial. The oilers of like description, preserved as specified in 5.1 shall be packed in accordance with MIL-STD-1188.

5.3 Marking.

5.3.1 Military packaging. Marking shall be in accordance with MIL-STD-129.

5.3.2 Commercial packaging. Marking shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The oilers covered by this specification are intended to dispense lubricating oils.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Size oiler required (see 1.2).
(c) Type of spout required (see 3.1).
(d) When first article is required for inspection and approval and number of oilers required (see 3.2, 4.3, and 6.3).
(e) Degree of preservation and degree of packing required (see 5.1 and 5.2).

6.3 First article. When a first article is required, it shall be tested and approved under the appropriate provisions of paragraph 7-104.55 of the Armed Services Procurement Regulations. The first article should be a preproduction model. The first article should consist of one or more units. The contracting officer should include specific instructions in all procurement instruments, regarding arrangements for examinations, test, and approval of the first article.

6.4 Recycled material. It is encouraged that recycled material be used, when practical, as long as it meets the requirements of this specification (see 3.3).

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:30Z
Check the source to verify that this is the current version before use.

Custodian:
Army - ME

Review activity:
DLA - CS

Preparing activity:
Army - ME

Project 4930-A220

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:30Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:30Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-O-52724A(ME) Oilers, Hand, Plastic

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:30Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
USA Mobility Equipment R&D Command
ATTN: DRDME-DE/DS
Ft. Belvoir, VA 22060

FOLD

☆ U.S. GOVERNMENT PRINTING OFFICE: 1980—603-121/2354 2-1

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:30Z
Check the source to verify that this is the current version before use.