MIL-P-60053 (MU)
11 September 1964

MILITARY SPECIFICATION

PRIMER, PERCUSSION, M1A2
LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of percussion primer designated as Primer, Percussion, M1A2.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116	- Preservation, Methods of
MIL-P-223	- Powder, Black
MIL-A-2550	- Ammunition and Special Weapons, General Specification for
MIL-P-20449	- Primer, Percussion, M61, Loading, Assembling and Packing
MIL-I-45208	- Inspection Requirements, General Specification for
MIL-I-45607	- Inspection Equipment, Supply and Maintenance of

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-1235	- Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

FSC: 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:07Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

8839453 - Primer, Percussion, M1A2 Assembly
8858938 - Box, Packing, For Primers M1B1A2 or M1B2
8858940 - Box Set-up, For Primers M1B1A2 or M1B2

PUBLICATIONS

ORDNANCE CORPS

IEL-8839453 - Index of Inspection Equipment Lists

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement and functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material.-Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Percussion primer.-The percussion primer shall comply with all requirements specified on Drawing (dwg.) 8839453, and with all requirements specified in applicable specifications.

3.3 Head assembly

3.3.1 Non-functioning.-The head assemblies shall not function under an applied energy value of 47.52 inch-ounces, minimum (min.), when tested as specified in 4.3.1.1.

3.3.2 Functioning.-The head assemblies shall function under an applied energy value of 159.20 inch-ounces, maximum (max.), when tested as specified in 4.3.1.2.

3.4 Primer assembly

3.4.1 Functioning.-The primer assembly shall function without audible hangfire, when tested as specified in 4.3.2.

Source: https://assist.dla.mil -- Downloaded: 20261O-23T00:07Z
Check the source to verify that this is the current version before use.

3.4.2 Pressure resistance.-The primer assemblies shall withstand a pressure of 40,000 plus or minus 4,000 pounds per square inch without evidence of rupture, or any part of the primer becoming detached, when tested as specified in 4.3.2.

3.5 Moisture content of black powder.-The moisture content of the black powder at the loading station, at the time of loading shall not exceed 0.5 percent, when tested as specified in 4.3.3.

3.6 Workmanship.-All parts shall be free of burrs, chips, dirt, grease, cracks, rust, corrosion and other foreign material. The cleaning method used shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents used.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Contractor quality assurance system.-The contractor shall provide and maintain an effective quality assurance system in compliance with the requirements of Specification MIL-I-45208. The contractor's quality assurance system shall contain a procedure for the reporting of critical defectives found during the course of his inspection and during inspection by the Government. Any critical defect encountered, unless annotated by an asterisk (*) to the right of the characteristic code number (see 6.2), will be reported within 48 hours. A monthly summary report covering those critical defects annotated by an asterisk will be furnished. The agencies to whom the reports will be furnished are identified in paragraph 6.6. The reports shall contain, as a minimum, the following information:

a. Contractor and contract number.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:07Z
Check the source to verify that this is the current version before use.

b. Number and revision date of specification.
c. Characteristic code number.
d. Lot or serial number.
e. Number of defectives found.
f. Assignable cause or analysis of occurrence.
g. Corrective action taken or recommended. When the corrective action is beyond the control of the contractor or the scope of the contract, the report shall contain the contractor's recommendation to the Government.

4.1.2 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all quality assurance provisions of the approved current written description of the system.
b. Number of units of product inspected.
c. Results obtained for all inspection performed.
d. Drawing, specification number and date, together with an identification and date of changes.
e. Certificates of compliance on all material purchased by the contractor when such material is controlled by Government specifications referenced in any of the contractual documents.
f. Number of items in the lot.
g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantited by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.3 Government verification.-Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be in accordance with Specification MIL-I-45208 and will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:07Z
Check the source to verify that this is the current version before use.

to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 Inspection provisions

4.2.1 Lot formation.-A lot shall consist of loaded percussion primers produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting performance safety, or fit, as determined by the Government shall not be cause for changing the lot number. Lots shall be submitted for inspection in accordance with Standard MIL-STD-105 (or Standard MIL-STD-1235, when applicable). Each lot shall contain:

a. Metal parts of one lot interfix number from one manufacturer.

b. Black powder of one lot number from one manufacturer.

c. Primers, Percussion, M61 of one lot interfix number from one manufacturer.

4.2.2 Examination.-Inspection for Critical defects shall be 100 percent. Sampling plans and procedures for Major and Minor defects shall be in accordance with Standard MIL-STD-105 except that continuous sampling plans in accordance with Standard MIL-STD-1235 may be used if approvd by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to individual characteristics listed using an AQL of 0.65 percent for each minor defect and an AQL of 0.40 percent for each major defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 Head, prior to assembling battery cup and firing plug (see dwg. 8839453).

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical: None defined			
Major:	AQL 0.40 percent		
101.	Percussion element missing, cocked or inverted.....	Visual	01001

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:07Z
Check the source to verify that this is the current version before use.

Minor:	AQL 1.0 percent		
201.	Seal between percussion element assembly and head assembly missing or incomplete.....	Visual	01002
202.	Evidence of poor workmanship (see 3.6).....	Visual	01003

4.2.2.2 Head, prior to assembling to body (see dwg.8839453).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Firing plug or battery cup above flush with surface of head.....	Straight-edge	02001*
Major:	AQL 0.65 percent		
101.	Firing plug missing, cocked or inverted.....	Visual	02002
102.	Flash hole in head completely obstructed.....	Visual	02003
103.	Battery cup loose or missing.....	Visual-Manual	02004

Minor: None defined

4.2.2.3 Body, prior to assembly of liner (see dwg.8838089 covering a detail of dwg. 8839453).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Any flash hole missing from body.....	Gage	03001*

Major: None defined

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:07Z
Check the source to verify that this is the current version before use.

Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.6)	Visual	03002

4.2.2.4 Body, prior to assembling head assembly (see dwg. 8839453).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Weight of charge	Balance	04001
102.	Liner fails to cover all holes	Visual	04002
Minor:	AQL 0.65 percent		
201.	Foreign matter in charge	Visual	04003

4.2.2.5 Assembly (see dwg. 8839453).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Head assembly loose on body	Manual	05001
*102.	Any flash hole not completely sealed	Visual	05002
Minor:	AQL 2.5 percent		
201.	Total length, max	Gage	05003
202.	Diameter of flange, max	Gage	05004
203.	Crimp of body to head missing or incomplete	Visual	05005
204.	Marking misleading or unidentifiable	Visual	05006
205.	Evidence of poor workmanship (see 3.6)	Visual	05007

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:07Z
Check the source to verify that this is the current version before use.

*Sketches 1, 2, and 3 on Figure 1 indicate acceptable primers. Furthermore, a primer with holes displaying the conditions 4, 5 and 6 may be classed acceptable provided that the visible liner is thoroughly impregnated with paint or lacquer and not more than 20 percent of the holes have this condition.

4.2.2.6 Set-up box, prior to sealing (see dwg. 8858940).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major: None defined			
Minor:	AQL 1.5 percent		
201.	Any packing material missing.....	Visual	06001
202.	Separator damaged to extent that primers touch each other.....	Visual	06002
203.	Primer missing.....	Visual	06003

4.2.2.7 Set-up box, sealed (see dwg. 8858940).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major:	AQL 0.40 percent		
101.	Sealing strip torn, badly wrinkled, incomplete or otherwise fails to seal box completely.....	Visual	07001
102.	Carton torn, cut or punctured.....	Visual	07002
Minor: None defined			

4.2.2.8 Sealed barrier bag (see dwg. 8858940)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:07Z
Check the source to verify that this is the current version before use.

Major:	AQL 0.40 pencent		
101.	Seal improper or incomplete.....	Visual	08001
102.	Bag punctured, torn or cut.....	Visual	08002
Minor:	AQL 0.65 percent		
201.	Marking misleading or unidentifiable.....	Visual	08003

4.2.2.9 Packing box, prior to sealing (see dwg. 8858938).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Carton missing.....	Visual	09001
Minor:	None defined		

4.2.2.10 Packing box, sealed (see dwg. 8858938).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Box broken, board loose or protruding nail.....	Visual	10001
102.	Strapping missing, broken or loose.....	Visual-Manual	10002
Minor:	AQL 1.5 percent		
201.	Marking misleading or unidentifiable.....	Visual	10003
202.	Strapping improperly engaged or mislocated.....	Visual	10004
203.	Contents loose.....	Manual	10005

4.2.3 Testing

4.2.3.1 Head assembly

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:07Z
Check the source to verify that this is the currenversion before use.

4.2.3.1.1 Non-functioning (see 3.3.1) Critical defect - Code No. 02005.*

4.2.3.1.1.1 Beginning with the first lot produced, and continuing until three consecutive lots have complied with the acceptance criteria specified, a sample of 150 head assemblies shall be randomly selected from each lot for the test. If any sample fails to comply with requirement the lot shall be rejected. The test shall be performed as specified in 4.3.1.1.

4.2.3.1.1.2 After three consecutive lots have met the criteria of 4.2.3.1.1.1, a sample of 50 head assemblies shall be randomly selected from each lot for this test. If one or more primers fails to comply with the applicable requirement, the lot shall be rejected. The test shall be performed as specified in 4.3.1.1 using equipment in accordance with 4.2.4. Primers subjected to this test shall be destroyed.

4.2.3.1.2 Functioning (see 3.3.2) Major defect - Code No. 02006.

4.2.3.1.2.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified two hundred and fifty samples shall be randomly selected from each lot for this test. If three or more primers fail to comply with the applicable requirements, the lot shall be rejected. If one or two defects are found, a second sample of five hundred primers shall be tested. If the combined number of defectives in both the first and second sample is three or more, the lot shall be rejected. The test shall be performed as specified in 4.3.1.2 using equipment in accordance with 4.2.4.

4.2.3.1.2.2 After three consecutive lots have met the criteria of 4.2.3.1.2.1, a sample of 125 primers shall be randomly selected from each lot for this test. If two or more primers fail to comply with the applicable requirement, the lot shall be rejected. If only one defect is found, a second sample of 250 primers shall be tested. If the combined number of defectives in both the first and second sample is two or more, the lot shall be rejected. The test shall be performed as specified in 4.3.1.2 using equipment in accordance with 4.2.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:07Z
Check the source to verify that this is the current version before use.

4.2.3.2 Primer assembly functioning and pressure resistance (see 3.4) Major defect - Code No. 00008.-A sample of 25 primers shall be selected from each lot for this test. If any primer fails to comply with the applicable requirement, the lot shall be rejected. The test shall be performed as specified in 4.3.2 using equipment that is in accordance with 4.2.4.

4.2.3.3 Check test for deterioration of Primer, Percussion (M61 Assembly).-If the total elapsed time between original acceptance of the M61 primer lot and the assembly of that lot into the M1A2 primer exceeds two years, or if the M61 primers have been subjected to adverse conditions for any period of time since previous test, the M61 primer lot shall be subjected to and must satisfactorily pass the check test for deterioration specified in Specification MIL-P-20449 immediately before the M61 primer lot is assembled into the M1A2 primers (see 6.4).

4.2.3.4 Moisture content of black powder (see 3.5) Major defect - Code No. 11001.-A sample of one primer body, prior to assembly to the head, shall be randomly selected from each eight hours production. The black powder shall be tested as specified in 4.3.3 and any failure to comply with the applicable requirement shall be cause for rejection of the eight hours production represented by the sample.

4.2.3.5 Heat seal test of sealed bag (see dwg. 8858940 Major defect Code No. 12001, Sampling acceptance criteria and testing procedures for this test shall be as required in Specification MIL-P-116)

4.2.4 Inspection Equipment.-Index of Inspection Equipment Number IEL 8839453 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.2.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the IEL may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:07Z
Check the source to verify that this is the current version before use.

parts, inspection of items at overhaul, general maintenance of equipment, contruction, survey and wherever inspection equipment drawings are needed.

4.2.4.2 Supply and Maintenance.-Supply and maintenance of the equipment listed on the IEL shall be in accordance with Specification MIL-I-45607.

4.2.4.3 Government use of contractor's inspection and test equipment.-The contractor shall make available to the Government all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment, and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

4.3 Test methods and procedures

4.3.1 Head assembly

4.3.1.1 Non-functioning.-The loaded heads, prior to assembling to the body, shall be assembled into the test fixture (see 4.2.4). A steel ball weighing a min. of 7.92 ounces shall be dropped from a height to give the required impact force (approximately 6 inches).

4.3.1.2 Functioning.-The test shall be performed as specified in 4.3.1.1 except that the weight of the ball shall be 7.96 ounces max., and the height shall be adjusted to give the required impact force (approximately 20 inches).

4.3.2 Primer assembly functioning and pressure resistance.-The loaded primer assemblies shall be assembled into the test fixture (see 4.2.4). The fixture shall be activated and observation shall be made for firing and audible hangfire. Upon completion of firing the primer shall be removed and observation shall be made for ruptured and broken or detached parts. (see 6.7).

4.3.3 Determination of moisture content of black powder.-The moisture content of the black powder shall be determined in accordance with the procedure specified in Specification MIL-P-223.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:07Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging

5.1.1 Level C.-The primers shall be preserved and packaged in accordance with dwg. 8858940.

5.2 Packing

5.2.1 Level C.-The cartons shall be packed in accordance with dwg. 8858938.

5.3 Marking.-Marking shall be in accordance with dwgs. 8858940 and 8858938.

5.4 Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Specification MIL-A-2550.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify title, number and date of this specification.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the referenced Inspection Equipment Lists (IEL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.7.

6.3.1 Inspection equipment lists.-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (OO Form 1242-3) the numbers of drawings of existing equipment designs or codes as indicated in paragraph 6.3.2. Design action required of the contractor with respect to the different types of drawings that may be listed is described in paragraphs 6.3.3 and 6.3.4. Action required by the contractor with respect to commercial inspection equipment is described in 6.3.5. The contractor will be required to prepare detailed drawings in accordance with 6.3.6 for all the equipment coded as "Contractor Design" in the number column. These contractor

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:07Z
Check the source to verify that this is the current version before use.

designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3, 6.3.4, 6.3.5 and 6.3.6 will be designed in the IEL by the following codes:

CDAF - Contractor's design responsibility on Army format in accordance with MIL-D-45608.
CDCF - Contractor's design responsibility on contractor format.
AD - Army design.
ADMU - Army design, mandatory for use.
CE - Commercial equipment.
SCD - Specification control drawing.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications, mandatory and non-mandatory. When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.4 Specification control drawing.-Specification control drawings depict the minimum equipment requirements in outline, descriptive, diagramatic or pictorial form only and specify the required performance or other characteristics. Contractors must prepare detaled drawings (see 6.3.6) of their designs in support of specification control drawings. These contractor prepared designs must be approved by the Government prior to the fabrication or procuring of the equipment. Commercial equipment meeting the requirements of specification control drawings may be approved if described in sufficient detail to permit identification and evaluation by the Government. Designs shall be submitted for approval as specified in 6.3.7.

Source: https://assist.dla.mil -- Downloaded: 20261O-23T00:07Z
Check the source to verify that this is the current version before use.

6.3.5 Commercial equipment.-Commercial equipment is inspection equipment that has universal application for a specific function. It is comprised of items commonly used by industry and Government. Contractors are not required to furnish drawings of commercial inspection equipment, but a list of such equipment must be approved by the Government. Lists shall be submitted for approval to the inspection element of the agency administering the contract.

6.3.6 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Contractor designs identified as CDCP may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above. Contractor designs identified as CDAF shall comply with the format and requirements of MIL-D-45608, and in addition, contain the detail and information specified above.

6.3.7 Submission of contractor designs.-Designs shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND. Design review will normlly be accomplished within one month after receipt by Picatinny Arsenal. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs.

6.4 Cost of check tests.-The contracting officer will arrange for the contractor to be reimbursed for the expense incurred in the performance of the check test. The test shall be conducted at Government expense without cost to the contractor who loaded the M61 primer or the contractor loading and assembling the M1A2 primer, and shall not constitute a basis for rejection against either contractor, except where deterioration has occurred as a direct result of carelessness in handling, storage, etc, while the primers were under the jurisdiction of either contractor.

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:07Z
Check the source to verify that this is the currentversion before use.

6.5 Check test for possible deterioration of percussion artillery primers.-The following tests are designed to prevent the loading of artillery primers which have deteriorated into a major ammunition item. The test shall be performed on artillery primers from each lot which has been stored under normal conditions for more than two years or under adverse conditions for any period of time. If the specification for the ammunition item into which the artillery primers are loaded does not require that the check test be performed, the contracting officer should insert a provision for the performance of the check test in the contract.

6.5.1 Head assembly

6.5.1.1 Non-functioning (see 3.3.1).-The sampling for the test shall be in accordance with Table I. Any head assembly which fails to comply with the applicable requirements shall be classed defective. The test shall be performed as specified in 4.3.1.1, except that the body and the head assembly shall be separated in a manner that will not damage the head assembly to the extent that the validity of the test results would be questionable. All head assemblies so tested shall be scrapped.

TABLE I

Sample	Sample Size	Combined Samples Size	Acceptance Number	Rejection Number
First	20	20	*	2
Second	20	40	*	2
Third	20	60	0	2
Fourth	20	80	1	3
Fifth	20	100	1	3
Sixth	20	120	1	3
Seventh	20	140	2	3

*No acceptance on this sample

6.5.1.2 Functioning (see 3.3.2).-The sampling plan for the test shall be in accordance with Table II. Any head assembly which fails to comply with the applicable requirement shall be rejected. The test shall be performed as specified in 4.3.1.2, except that the

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:07Z
Check the source to verify that this is the current version before use.

body and the head assembly shall be separated in a manner that will not damage the head assembly to the extent that the validity of the test results would be questionable.

TABLE II

Sample	Sample Size	Size	Combined Samples Acceptance Number	Combined Samples Rejection Number
First	75	75	*	2
Second	75	150	0	3
Third	75	225	0	3
Fourth	75	300	1	4
Fifth	75	375	2	5
Sixth	75	450	2	5
Seventh	75	525	4	5

*No acceptance on first sample

6.5.2 Moisture content of black powder.-A sample of 25 primers shall be selected for this test. The black powder shall be removed from the body by any suitable means. **The moisture content of the powder shall be determined in accordance with the methods specified in Specification MIL-P-223. If the moisture content of the powder tested exceeds 0.7 percent, the lot of primers shall be rejected.

**Since black powder is hygroscopic, it is advisable to place the powder in a dry, air-tight container immediately upon removal, and to run the determination as soon as possible thereafter.

6.6. Critical defect report

6.6.1 Submission of critical defect reports.-For U. S. Army Munitions Command procurement, one copy of each critical defect report will be furnished the cognizant Government inspection agency; the Army Ammunition Procurement and Supply Agency, ATTN: SMUAP-RO; Picatinny Arsenal, ATTN: SMUPA-ND.

6.6.2 Reporting to other services.-For other than U. S. Army Munitions Command procurements, critical defect reporting shall be as prescribed by the contracting officer.

6.7 Test Fixture.-In the event the test fixture is not available, primer may be fired at a Proving Ground in loaded cartridges for which the primer is intended.

Custodian:
Army-MU

Preparing Activity:
Army-MU

Project No. 1390-A409

Project Number: 1390-A409

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:07Z
Check the source to verify that this is the current version before use.

ARTILLERY PRIMERS
STANDARDS FOR PAINT CONDITIONS IN FLASH HOLES




FIGURE 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:07Z
Check the source to verify that this is the current version before use.

To detach this form, cut along this line

SPECIFICATION ANALYSIS SHEET

Form Approved Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO (IF "YES", IN WHAT WAY?

4. REMARKS (*Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity*)

SUBMITTED BY (*Printed or typed name and activity*) | DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4883, WHICH IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:07Z
Check the source to verify that this is the current version before use.