MIL-T-81187 (AS)

1 July 1966

MILITARY SPECIFICATION

TRANSMITTER, RATE OF FUEL FLOW,
SYNCHRO TYPE, MS90361

This specification has been approved by the Naval
Air Systems Command, Department of the Navy

1 SCOPE

1.1 Scope - This specification covers design and all performance requirements for synchro type rate of fuel flow transmitters up to 5000 PPH maximum.

1.2 Classification - The transmitters shall be classified as shown on MS90361.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on the date of invitation for bids, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-P-116	Preservation, Methods of
MIL-E-5272	Environmental Testing Aeronautical and Associated Equipment, General Specification for
MIL-T-5350	Transmitters, Synchro Operated Aircraft, General Specification for
MIL-J-5624	Jet Fuel, Grades JP-4 and JP-5
MIL-S-6872	Soldering Process, General Specification for
MIL-I-81186	Indicator, Rate of Fuel Flow, Synchro Type

FSC 6620

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:04Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MIL-STD-130	Identification Marking of U S Military Property
MIL-STD-781	Reliability Tests Exponential Distribution
MIL-STD-794	Parts and Equipment Procedures for Packaging and Packing of
MS90361	Transmitter, Rate of Fuel Flow, Synchro Type

2.2 Availability of documents - When requesting any of the applicable documents, refer to both title and number. Copies of this specification and applicable documents may be obtained upon application to the Commanding Officer, Naval Supply Depot, Code 1051, 5801 Tabor Avenue, Philadelphia, Pennsylvania 19120.

3. REQUIREMENTS

3.1 Qualification - The transmitters furnished under this specification shall be a product, samples of which have been tested and have passed the Qualification Tests specified herein, and has been listed on or approved for listing on the applicable qualified products list.

3.2 General - The requirements of MIL-T-5350 are applicable as requirements of this specification. Additional requirements shall be as specified herein.

3.3 Design and construction - The transmitter shall produce a synchro output signal representative of the rate of fuel flow through a range as classified on MS90361 The synchro signal shall operate one or two indicators designed in accordance with MIL-I-81186. The transmitter shall prevent small variations of flow rate from causing objectionable oscillations in indicator readings.

3.3.1 Case - The outline dimensions of the transmitter shall conform to MS90361.

3.3.2 Transmitter calibration - The fuel flow transmitter shall be calibrated for rate of flow in pounds per hour (PPH) using fuel which complies with MIL-J-5624. A commercial fuel of higher flash point may be used for testing purposes

3.3.3 Operating pressure - The transmitter shall operate with fuel pressure up to 600 psi and be capable of withstanding an internal pressure of 1000 psi without damage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:04Z
Check the source to verify that this is the current version before use.

3.3.4 Temperature range - The transmitter shall withstand an ambient operating temperature range of -55° to +121° C.

3.3.5 Mechanical stop - Mechanical stop shall be provided within the transmitter to limit the rotation of the synchro to a point just above and just below the scale of the applicable indicator of MIL-I-81186.

3.3.6 Weight - The weight of the complete transmitter shall not exceed 2.75 pounds.

3.3.7 Mounting - The transmitter mounting holes shall be located as shown in MS90361

3.3.8 Flow direction - The direction of fuel flow through the transmitter shall be permanently and legibly marked by an arrow as shown in MS90361.

3.4 Electrical requirements -

3.4.1 Input power requirements - The transmitter shall operate on AC power (single phase) 26V ±10 percent, 400 cps ±5 percent, 1 watt maximum

3.4.2 Wiring - The external and internal wiring shall be as specified in MIL-T-5350. The electrical connector shall be as shown on MS90361.

3.5 Performance - The transmitter shall perform satisfactorily when subjected to the tests specified in Section 4 of this specification

3.5.1 Reliability -

3.5.1.1 Operational Stability - The equipment shall operate with satisfactory performance, continuously or intermittently for a period of at least 1200 hours without the necessity for the readjustment of any controls which are inaccessible to the operator during normal use.

3.5.1.2 Reliability in Mean Time Between Failure (MTBF) - The transmitter shall have 1200 hours of mean (operating) time between failures when tested and accepted as outlined under the requirements of 4.4.3.

3.6 Identification of product -

3.6.1 Nameplate - A nameplate shall be securely attached to the exterior of the case and shall be marked in accordance with the requirements of MIL-STD-130 except that the FSN shall be omitted.

3.7 Soldering - Soldering shall be performed in accordance with MIL-S-6872.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:04Z
Check the source to verify that this is the current version before use.

3.8 Workmanship - The transmitter, including all parts and accessories, shall be constructed and finished in a thoroughly workmanlike manner. Particular attention shall be paid to neatness and thoroughness of soldering, wiring, impregnation of coils, marking of parts and assemblies, plating, painting, riveting, machine-screw assemblage, welding and brazing, and freedom of parts from burrs and sharp edges.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Classification of inspection - Inspection of the transmitter shall be classified as follows

(a) Qualification inspection Qualification inspection consists of examinations and tests performed on sample transmitters submitted for approval as a qualified product.

(b) Quality conformance inspection - Quality conformance inspection consists of examinations and tests performed on transmitters manufactured and submitted for acceptance under contract.

4.3 Qualification inspection - The qualification inspection of the transmitter shall consist of all the examinations and tests of this specification performed in the order specified under the paragraph headed Inspection methods and shall include the reliability test for the Reliability Qualification Phase Unless otherwise stated in the contract the tests of the Reliability Sampling Phase only are required.

4.3.1 Qualification inspection sample - Qualification inspection samples shall consist of three transmitters manufactured in accordance with this specification. The transmitters submitted for qualification inspection shall have been previously subjected only to the Individual inspections The samples shall be forwarded at the contractor's expense to the laboratory designated in the Letter of Authorization

4.3.1.1 Qualification inspection samples identification - The qualification inspection samples shall be plainly identified by durable tags, securely

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:04Z
Check the source to verify that this is the current version before use.

attached, and marked with the following information:

Sample for Qualification Inspection
TRANSMITTER, RATE OF FUEL FLOW,
_____ to ____ PPH, SYNCHRO TYPE
Submitted by (Manufacturer's name, date)
for Qualification Inspection in accordance
with Specification MIL-T-81187 under
authorization (reference letter authorizing
tests)

4.4 Quality conformance inspection - The Quality conformance inspection shall consist of the Individual inspection, the Sampling plans, and the Reliability assurance tests of this specification. The contractor shall furnish all samples and shall be responsible for accomplishing all the inspections. Sampling plan B inspections shall be conducted at a Government laboratory designated by the procuring activity. Quality conformance inspection, except for Sampling plan B, shall be under the supervision of the Government quality control representative. The contractor shall furnish test reports showing quantitative results for all tests required by this specification, signed by an authorized representative of the contractor or laboratory as applicable Acceptance or approval of material during the course of manufacture shall in no case be construed as a guarantee of the acceptance of the finished product.

4.4.1 Individual inspection - Each transmitter submitted for acceptance shall be subjected to the Individual inspection. This inspection shall determine compliance with the requirements of material, workmanship, operational adequacy, and reliability. As a minimum, each transmitter accepted shall have passed the following inspections (Inspections marked * are from MIL-T-5350)

*Detail examination
Scale error at room temperature
Leakage
Pressure drop
Position error
*Dielectric strength

4 4.2 Sampling plans - The Sampling plans shall consist of Sampling plan A and Sampling plan B inspections The inspection samples selected for sampling tests shall first have passed the Individual inspections. The inspection samples which have been subjected to Sampling plan A inspection shall not be delivered on contract until they have been refurbished (see 6 1) and resubmitted and passed all the Individual inspections. Inspection samples which have been subjected to the Sampling plan B inspection shall not be delivered on contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:04Z
Check the source to verify that this is the current version before use.

4.4.2.1 Sampling plan A sample selection - Sampling plan A samples shall be selected at random in accordance with the following schedule

Quantity Offered for Acceptance	Quantity to be Selected for Inspection
First 15	(See Note)
Next 50	1
Next 75	1
Next 100	1
Each additional 200 or fraction thereof	1

NOTE: When Sampling plan B is invoked, the quantity shall be zero. When Sampling plan B is to be omitted, the quantity shall be one.

When a defective transmitter occurs, no items from those still on hand or later produced shall be accepted until the extent and cause of failure has been determined and appropriately corrected. In addition when a failure occurs, shift to one sample out of fifteen (when Sampling plan B is omitted) and proceed as indicated.

4.4.2.1.1 Sampling plan A inspection - Each sample selected for Sampling plan A inspection shall be subjected to the following tests (Inspections marked * are from MIL-T-5350).

High temperature operation
Low temperature operation
Voltage and frequency variation
*Electrical characteristics (see para 4.6.10)
*Mechanical characteristics
Damping
Vibration

4.4.2.2 Sampling plan B instructions - Two transmitters shall be selected at random from the first 15 produced on contract and submitted within 10 days after manufacture. These samples shall be forwarded at the contractor's expense to a Government laboratory designated by the procuring activity. Each sample shall be plainly identified by a durable tag, securely attached and marked with the following information

TRANSMITTER RATE OF FUEL FLOW,
_____ to_____ PPH, SYNCHRO TYPE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:04Z
Check the source to verify that this is the current version before use.

Submitted by (Manufacturer's name, date)
for Production Acceptance Sampling Plan B
inspection, in accordance with Contract/
order No.
Manufacturer's part number _____

4.4.2.2.1 Sampling plan B inspection - Each sample selected for Sampling plan B inspection shall be subjected to the following tests

Sampling plan A
High temperature exposure
Low temperature exposure
Temperature shock
Contaminated fuel operation
Aromatic fuel
Internal examination

4.4.3 Reliability Assurance Tests - Reliability Assurance Tests shall be conducted using MIL-STD-781. Qualification Phase and Sampling Phase Tests shall be conducted Equipments selected for reliability assurance tests shall first have passed the Individual tests.

4.4.3.1 Reliability Qualification Phase - Prior to Qualified Products Listing (see 4.3), a minimum of three (3) equipments shall be tested as outlined in MIL-STD-781, under the section entitled "Qualification Phase of Production Reliability Tests" The maximum number of equipments to be used shall be those listed in Table 5 of MIL-STD-781. For the Qualification Phase, Test Level E shall be used except that the temperature shall be -30° C to +38° C and cycled on a daily basis 25° C, -30° C, 25° C, 38° C, etc each temperature condition for approximately twenty-four hours The Accept-Reject Criteria for Test Plan I shall be used

4.4.3.2 Reliability Sampling Phase Tests - Samples of the equipment shall be tested as outlined in MIL-STD-781, under the Section entitled "Sampling Phase of Production Reliability Tests' For the Sampling Phase, Test Level E shall be used with the same exception as in 4 4 3.1 The Accept-Reject Criteria for Test Plan II shall be used to determine the length of the tests (until an accept or reject decision is reached).

4 4 3 2 1 Lot size for Sampling Phase - The entire contract quantity (with the exception of those equipments used in the Qualification Phase) shall be considered one lot The test program shall start the first month after the Qualification Phase has been completed Samples shall be selected and placed on test in the same manner as though one month's production was a lot The samples shall be tested until an accept or reject decision is reached. In the meantime other equipments constructed

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:04Z
Check the source to verify that this is the current version before use.

shall be shipped. The test results shall be summarized monthly for the procuring activity. The procuring activity reserves the right to stop the acceptance of equipment at any time after one or more reject decisions have been reached, pending a review of the contractor's efforts to improve the equipment, the equipment parts, the equipment quality control, etc., so that the entire contract quantity will show an accept decision

4.4.3.3 Test details - The test details such as the length of the test cycle, the length of the heat portion of the cycle, the performance characteristics to be measured, special failure criteria, preventive maintenance to be allowed during the test, etc., shall be part of the test procedures to be submitted to and approved by the procuring activity prior to the beginning of the Qualification Test Phase of the Reliability Assurance Tests The following paragraphs shall be considered minimum conditions and shall apply to both the Qualification and Sampling phases.

4.4.3.3.1 Duty cycle - The duty cycle shall consist of applying the following flow rates, in the following order, in the course of each hour 10, 50, 80, 50 and 10 percent, approximately, of maximum range A variable speed motor shall be used to drive the fluid at these flow rates. The transmitter shall be energized and wired to an indicator in accordance with MIL-I-81186

4.4.3.3.2 Performance characteristics to be measured - The Scale error at room temperature test, described under Inspection methods, shall be conducted at least once each week

4.4.3.3.3 Failure criteria - Whenever performance characteristics fall below the acceptance requirements (4.4.3.3.2), at least one failure has occurred If subsequent analysis reveals that several parts have deteriorated, each should be counted a failure, unless one part caused the other parts to fail.

4.4.3.3.4 Preventive maintenance - No preventive maintenance may be accomplished on samples while they are on test.

4.4.3.3.5 Disposition of samples upon completion of tests - Any sample tested other than those tested under the Reliability Qualification Phase, may be delivered on contract provided it meets all the following requirements

(a) It is representative of production units currently being accepted

(b) It is in "good as new" condition or has been refurbished. (See 6.1)

(c) It is otherwise satisfactory.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:04Z
Check the source to verify that this is the current version before use.

4.5 Inspection conditions - With the following exceptions or additions, the Test conditions shall be as specified in MIL-T-5350.

4.5.1 Power - Unless otherwise specified, the transmitter shall be operated on 26 ±0.5 V, 400 ±5 cps power

4.5.2 Attitude - Unless otherwise specified, the transmitter shall be tested in its normal operating position

4.5.3 Test fuel - Unless otherwise specified the test fuel shall have the properties of one of the following.

*Specific gravity 68°F/60°F	Kinematic Viscosity @ 100 ±2° F (Centistokes)
0.775 ±.020	0.920 ± 020
0.823 ± 020	1.650 ± 030

*The actual value of the sample used shall be known, and maintained, within ±0.005.

4.6 Inspection methods -

4.6.1 Detail examination - The detail examination test of MIL-T-5350 shall apply

4.6.2 Scale error at room temperature - Scale error of the transmitter shall be determined at the test points specified in Table I with both increasing and decreasing rates of flow. This test shall be conducted with the transmitter connected to the master indicator and the power supply. In no event shall either the upscale or downscale readings exceed the scale error tolerance specified in Table I

TABLE I

Percent of Max Fuel Flow	Tolerances ±percent of actual flow		
	Room Temperature (25° C)	High Temperature +38° C Low Temperature -38° C	Aromatic Fuel
10	20.0	30	30
20	6.0	12	12
30	3.0	5	5
40	2.0	3	5
50	1.6	3	5
60	1.6	3	5
70	1.8	[illegible]	5
80	2.0	3	5
90	2.0	3	6
100	2.0	3	6

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:04Z
Check the source to verify that this is the current version before use.

4.6.3 Leakage - A pressure of 1000 psi shall be applied to the transmitter hydrostatically and held for 1 minute. No leakage or damage to the transmitter shall be incurred.

4.6.4 Pressure drop - The pressure drop within the transmitter, when measured with a differential pressure gage connected across the inlet and outlet ports, or by a method approved by the procuring activity, and with a flow rate of 100 percent maximum should not exceed 3.0 psi for units with maximum flow ranges up through 3500 PPH and 5.0 psi for transmitters with maximum flow ranges of 3501 through 5000 PPH

4.6.5 Position error - The transmitter scale error at room temperature test shall be repeated with the transmitter mounted in each of three mutually perpendicular axes including the manufacturer's recommended mounting position The error introduced in the scale by changing the position of the transmitter from that recommended by the manufacturer for correct installation, to any other position shall not exceed 1 percent of full scale reading

4.6 6 Dielectric strength - The dielectric strength test of MIL-T-5350 shall apply.

4.6.7 High temperature - The transmitter shall be subjected to a temperature of +38° C (+100° F) for a period of two hours and while still at this temperature shall be tested for scale error The fuel shall also be at this specified temperature. The scale error shall not exceed the tolerances specified in Table I. The transmitter shall then be subjected to, and meet, the requirements of the Scale error at room temperature test

4 6.8 Low temperature - The transmitter shall be subjected to a temperature of -38° C(-36.4° F) for a period of two hours and while at this temperature the transmitter shall be tested for scale error with fuel at -38° C (-36 4° F) The scale error shall not exceed the tolerances specified in Table I The transmitter shall then be subjected to, and meet, the requirements of the Scale error at room temperature test.

4.6.9 Voltage and frequency variation - The transmitter shall be operated at a fuel flow rate of approximately 80 percent maximum and a scale reading taken when the voltage and frequency are within the limits specified under Inspection conditions. Under the same condition of fuel flow the voltage and frequency shall be adjusted as listed and respective scale readings taken

Percent Volts	Percent Frequency
90	95
110	105
90	105
110	95

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:04Z
Check the source to verify that this is the current version before use.

No one of the latter four readings shall differ from the first reading by more than 0.5 percent full scale.

4.6.10 Electrical characteristics - The transmitter shall pass the electrical characteristics test of MIL-T-5350 except that the power requirements shall be 26 V ±10 percent, 400 cps ±5 percent, 1 watt maximum. The subparagraph "Open secondary" shall not apply. The transmitter shall also be subjected to, and meet, the requirements of the following test.

4.6.10.1 Effect of lead length - The indication shall not change more than one degree of arc when the lead length of the leads between the indicator and transmitter is changed from 5 to 100 feet of No. 20 wire. For this test the A pins of both transmitter and indicator shall be grounded to simulate aircraft installed conditions.

4.6.11 Mechanical characteristics - The transmitter shall pass the mechanical characteristics test of MIL-T-5350.

4.6.12 Damping - Damping shall be considered satisfactory if small changes in flow rate do not cause oscillations in excess of ±2 percent and if these oscillations do not persist more than 5 seconds after the final indication is recorded. Oscillations at steady flow rate shall not be discernible.

4.6.13 Vibration - The transmitter shall be filled with fluid and mounted on a vibration stand. The transmitter shall then be subjected to the vibration of Procedure XII, MIL-E-5272, except that all vibration shall be at room temperature. During vibration it shall be connected to a test indicator and energized. After vibration, it shall be subjected to the Scale error at room temperature test and meet the requirements specified therein. No sticking, excessive friction, or any other failure shall occur as a result of this test.

4.6.14 High temperature exposure - The transmitter, without test fuel, shall be placed in a test chamber. The internal temperature of the chamber shall be raised to and maintained at 121° C (249.8° F). After 24 hours exposure to this temperature, the transmitter shall be returned to room temperature and examined for physical defects. After a minimum of 4 hours at room temperature it shall be subjected to and shall meet the requirements of the Scale error at room temperature test. There shall be no physical defects due to the high temperature exposure.

4.6.15 Low temperature exposure - The transmitter, without test fuel, shall be placed in a test chamber. The internal temperature of the chamber shall be lowered to and maintained at -65° C (-85° F) for a period of 72 hours. It shall then be raised to and maintained at -55° C (-67° F) for 24 hours. The transmitter shall then be returned to room temperature and inspected for physical defects. After a minimum of 4 hours at room temperature it shall be subjected to

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:04Z
Check the source to verify that this is the current version before use.

and shall meet the requirements of the Scale error at room temperature test. There shall be no physical defects caused by the low temperature exposure.

4.6.16 Temperature shock - The transmitter shall be tested in accordance with Procedure I of MIL-E-5272. After completion of the test the transmitter shall be inspected for cracks, and rupture of material. The transmitter shall be tested for scale error at room temperature and shall not exceed the scale error tolerance specified in Table I

4.6.17 Contaminated fuel operation - Test fuel containing dirt to the extent of 80 grams of foreign matter to 1000 gallons of fuel shall be circulated through the transmitter at approximately 65 percent maximum range for one hour. A scale and friction error test shall then be made with the contaminated fuel and operation shall be satisfactory and within the room temperature tolerances. This foreign matter shall be considered to consist of not less than 68 percent SiO_2 and shall have a particle size analysis as shown in Table II

TABLE II

Particle Size Analysis

Foreign Particle Size, Microns	Percent of Total Weight
0 - 5	39 ±2
5 - 10	18 ±3
10 - 20	16 ±3
20 - 40	18 ±3
over 40	9 ±3
Through a 200 mesh screen	100 percent

4.6.18 Humidity - The humidity test of MIL-T-5350 shall apply

4.6.19 Salt spray - The salt spray test of MIL-T-5350 shall apply

4.6.20 Aromatic fuel - The transmitter shall be tested as specified for the Scale error at room temperature test except that the fuel used shall have a specific gravity of 0.740 ±0.010 77°F/60°F and shall contain 35 to 40 percent aromatics. The scale error when using aromatic fuel shall not exceed the tolerances specified in Table I The fuel shall then be allowed to flow for approximately one hour, at a flow rate of approximately 50 percent maximum The Internal examination test shall then be conducted and the requirements, therein, shall apply.

4.6.21 Internal examination - The case of the transmitter shall be opened and the internal mechanism examined. Any deterioration or damage which could in any manner prevent the transmitter from meeting operation or maintenance requirements during service life shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:04Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging - The transmitter shall be packaged in accordance with MIL-STD-794, Level A or C as specified in contract or order. For Level A packaging the method of preservation shall be in accordacne with MIL-P-116, Method IC-1 without preservative compound The container shall be reuseable.

5.2 Packing - The transmitter snall be packed in accordance with MIL-STD-794 Level A, B or C as specified in contract or order

5 3 Marking - The interior and exterior containers shall be marked as specified in MIL-STD-794.

5.3.1 Precautionary marking - The following precautionary markings shall appear on two opposite sides of each interior package and shipping container wherever practicable

FRAGILE
DELICATE INSTRUMENTS
HANDLE WITH CARE

5 4 Reinspection dates - Reinspection marking shall be as specified by the procuring agency.

6. NOTES

6.1 The Notes specified in MIL-T-5350 shall apply except for the following

(a) Intended use - The transmitters covered by this specification are intended for use in aircraft to sense fuel flow rates and to transmit this information to a fuel flow indicator.

(b) Definitions - The following definitions are in addition to those specified in MIL-T-5350.

(1) Good as new - "Good as new" shall mean transmitters operated less than 10 percent of this specified MTBF operation.

(2) Refurbished - "Refurbished" shall mean that the transmitter has been completely overhauled with all component parts meeting current parts standards and the transmitter shall have been subjected to, and met, all the requirements of a new transmitter.

6.2 Qualification - With respect to products requiring qualification,

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:04Z
Check the source to verify that this is the current version before use.

awards will be made only for such products as have, prior to the time set for the opening of bids, been tested and approved for inclusion in the applicable Qualified Products List whether or not such products have actually been so listed by that date. The attention of the suppliers is called to this requirement and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government, tested for qualification, in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. The activity responsible for the Qualified Products List is the Naval Air Systems Command, Department of the Navy, Washington, D C., 20360

6.3 Precedence of documents - When the requirements of the contract, this specification, or applicable subsidiary specifications are in conflict, the following precedence shall apply:

(a) Contract - The contract shall have precedence over any specification.

(b) This specification - This specification shall have precedence over all applicable subsidiary specifications. Any deviation from this specification, or from subsidiary specifications where applicable shall be specifically approved in writing by the procuring activity.

(c) Referenced specifications - Any referenced specification shall have precedence over all applicable subsidiary specifications referenced therein. All referenced specifications shall apply to the extent specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:04Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost Comments and the return of this form will be appreciated Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*

SPECIFICATION

MIL-T-81187(AS) TRANSMITTER, RATE OF FUEL FLOW, SYNCHRO TYPE, MS90361

ORGANIZATION *(Of submitter)*	CITY AND STATE

CONTRACT NO	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3 IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4 REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 APR 63 1426

C-8279

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:04Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
Naval Air Systems Command
Washington, D. C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

NAVAL AIR SYSTEMS COMMAND (AIR-52021)
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:04Z
Check the source to verify that this is the current version before use.