NOT MEASUREMENT SENSITIVE

MIL-DTL-11589/119F
15 September 1995
SUPERSEDING
MIL-R-11589/119E
30 March 1993

DETAIL SPECIFICATION SHEET

RIBBON, PHILIPPINE DEFENSE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11589 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

COLOR PATTERN SIZE: Regular FINISH: Moire

| TOTAL WIDTH | WIDTH OF STRIPES INCHES & METRIC | FUNCTION OF STRIPES | COLOR & CABLE NUMBER STRIPES | FILLING YARN |
|---|---|---|---|---|
| | 1/32 (0.8 mm) | Edge & Binder | Scarlet HL 67111 | |
| | 7/32 (5.6 mm) | Ground | Scarlet HL 67111 | |
| | 5/32 (4.0 mm) | Ground | White HA 67101 | |
| 1-3/8 | 9/16 (14.2 mm) | Ground | Scarlet HL 67111 | White HA 67101 |
| (35.0 mm) | 5/32 (4.0 mm) | Ground | White HA 67101 | |
| 1/ | 7/32 (5.6 mm) | Ground | Scarlet HL 67111 | |
| | 1/32 (0.8 mm) | Edge & Binder | Scarlet HL 67111 | |

1/ Three five-pointed white stars, each star 5/32 inch (4.0 cm) in diameter and with 2 rays pointed downward shall be located in the center of the red stripe to form an equilateral triangle measuring 9/32 inch (7.1 cm) on each side. The center of each star shall be located in the points of the equilateral triangle. The triangular group of stars is formed from a filling effect design or screen printed at the option of the manufacturer. Each triangular design of white stars shall be 1-1/4 inches (31.8 cm) apart measured from center to center with a cutting mark (white thread) midway between each group of stars.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T19:01Z
Check the source to verify that this is the current version before use.

COLOR PATTERN SIZE: Streamer FINISH: Moire

| TOTAL WIDTH | WIDTH OF STRIPES INCHES & METRIC | FUNCTION OF STRIPES | COLOR & CABLE NUMBER STRIPES | FILLING YARN |
|---|---|---|---|---|
| | 1/32 (0.8 mm) | Edge & Binder | Scarlet HL 67111 | |
| | 15/32 (12.0 mm) | Ground | Scarlet HL 67111 | |
| | 5/16 (7.9 mm) | Ground | White HA 67101 | |
| 2-3/4 | 1-1/8 (28.6 mm) | Ground | Scarlet HL 67111 | White HA 67101 |
| (70.0 mm) | 5/16 (7.9 mm) | Ground | White HA 67101 | |
| 2/ | 15/32 (12.0 mm) | Ground | Scarlet HL 67111 | |
| | 1/32 (0.8 mm) | Edge & Binder | Scarlet HL 67111 | |

2/ Three five-pointed white stars, each star 5/16 inch (8.0 cm) in diameter, shall be located in the center of the red stripe to form an equilateral triangle measuring 9/16 inch (14.3 cm) on each side. The center of each star shall be located in the points of the equilateral triangle. The triangular group of stars is formed from a filling effect design or screen printed at the option of the manufacturer. The first triangular group shall be 18 inches (457.2 cm) from a cutting mark (white thread) measured to the vertical center of the triangle; the second triangular group shall be 41 inches (1041.4 cm) from the first group, center to center; the third triangular group shall be 36 inches ((914.4 cm) from the second groups, center to center and so on with a 41 - 36 - 41 - 36 inch (1041.4 - 914.4 - 1041.4 - 914.4 cm) pattern repeat with a cutting mark (white thread) midway between the groups which are 36 inches (914.4 cm) apart.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 45
Navy - NU
Coast Guard - CG

Review activities:
Air Force - 32, 82, 99
Navy - MC
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0815)



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T19:01Z
Check the source to verify that this is the current version before use.