MIL-D-22955(SHIPS)
AMENDMENT - 1
9 October 1962

MILITARY SPECIFICATION

DOMES, SONAR, STEEL, TYPES CW-553/SQS, CW-554/SQS AND CW-559/SQS AND MOUNTINGS, SONAR DOME, MT-2327/SQS, MT-2328/SQS AND MT-2369/SQS

This amendment forms a part of Military Specification MIL-D-22955 (Ships), 15 September 1961.

Pages 3 and 4, paragraph 3.2, item (g): Delete and substitute: "flush on both sides and edges, and shall be provided by the contractor in one continuous length. The fairing strip shall be given one."

Pages 3 and 4, paragraph 3.2, item (i), line 1: Delete "9/16" and substitute ."9/32".

Page 5, after paragraph 3.2.1, add:

"3.2.2 Mounting bolts and nuts.- The mounting bolts attached to mountings MT-2327/SQS and MT-2328/SQS, and the mounting nuts attached to mounting MT-2369/SQS shall be tack-welded to their respective mountings at each accessible flat."

Page 5, paragraph 3.4, line 2: Delete "1/32" and substitute "3/64".

Page 5, paragraph 3.5, line 2: Delete "1/32" and substitute "3/64".

Page 5, paragraph 3.6: Delete and substitute:

"3.6 Interchangeability.- All domes and mountings of the same type produced under the contract or order shall be interchangeable with each other and shall match the applicable Government furnished bolting circle template (3.6.1) after all structural welding has been completed."

Page 5, paragraph 3.7, line 3: Delete "3/16" and substitute "3/64".

Page 5, paragraph 3.8, second sentence: Delete and substitute: "Variations in the prevailing contour of the entire dome and mounting shall not exceed plus or minus 1/16-inch over any 6-inch square. In addition, variations in the prevailing contour of the forward half of the dome and mounting shall not exceed 1/64-inch in any 2-inch square."

FSC 5845

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:57Z
Check the source to verify that this is the current version before use.

Page 6, paragraph 3.11: Delete.

Page 8, paragraph 3.13, last sentence: Delete and substitute: "Attachment to the dome shall be accomplished by means of weld or solder. Attachment to the mounting shall be accomplished after the mounting is painted by means of corrosion-resisting rivets or screws."

Page 9, paragraph 4.1: Delete and substitute:

4.1 Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. The government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Page 9, paragraph 4.3.1: Delete and substitute:

"4.3.1 All welds not specified in 4.3 shall be examined on a sample basis sufficient to assure high quality workmanship (see 3.16). Welds on the vertical chocks, located between mounting bolts, shall not protrude beyond the dome's contour. Clearance in this area is necessary to allow subsequent installation of the fairing strip by the installing activity."

Page 10, paragraph 4.4: Delete.

Page 10, paragraph 4.5, line 3: Delete and substitute: "dome and mounting exterior shall be made with particular attention to the spot".

Page 11, paragraph 4.7, line 3: Delete and substitute: "forward half of the dome and mounting. With the shoulder of the gauge resting on the".

Page 11, paragraph 4.9: Add "These weights shall be determined for one equipment only of each type produced under the contract or order."

Page 11, paragraph 4.10: Delete and substitute:

"4.10 Determining interchangeability. - A drill jig which matches the Government furnished template (see 3.6.1) shall be used while drilling all bolt holes for mounting of the transducer (not including the underwater telephone) and the dome. Other methods which assure accurate location of mounting holes must be approved by the bureau or agency concerned. Actual interchange of mountings and domes of the same type shall be made, when deemed necessary by the Government representative, to assure compliance with the interchangeability requirements of 3.6."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:57Z
Check the source to verify that this is the current version before use.

Page 11, paragraph 4.11, line 2: Delete and substitute: "compliance with 3.4, 3.5 and 3.7. The surface being examined shall be placed on a plate or series of plates, the flatness of which has been previously assured. Any space between this flat surface and the surface being examined shall not exceed 3/32 inch."

Page 11, paragraph 4.12: Delete and substitute:

"4.12 The examinations called for in 4.5 through 4.8 shall be made after the air test and any subsequent repairs (see 4.3).

"4.13 Flange contours.- Tolerances for the outer edge of the dome and mounting flanges are given on the respective manufacturing drawings. Maintaining flange contours within these tolerances shall be accomplished by either fabricating mountings and domes while firmly attached to a fixture having the proper contour, or by checking each mounting and dome against such a fixture subsequent to all structural welding."

Preparing activity:
Navy - Ships
(Project 5845-N255Sh)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:57Z
Check the source to verify that this is the current version before use.