MILITARY SPECIFICATION
CARTRIDGE, IMPULSE, M94 ASSEMBLY

1. SCOPE

1.1 This specification covers Cartridge, Impulse, M94 for use with propellant actuated devices in aircrew emergency escape systems.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-A-2550	- Ammunition and Special Weapons, General Specification for
MIL-E-5272	- Environmental Testing, Aeronautical and Associated Equipment, General Specification for
MIL-C-60539	- Coating Anodic, Conventional for Aluminum and Aluminum Alloys

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-413	- Visual Inspection Guide for Rubber "O" Rings
MS 28741	- Hose Assembly, Detachable End Fitting, Medium Pressure

DRAWINGS

Munitions Command

D8596708	- Cartridge, Impulse, M94 Assembly

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

C8797725 - Carton, Packing, Ammunition for Cartridge, Impulse M94
C8797267 - Box, Packing, Ammunition for Cartridge, Impulse M94
IEL8596708 - Inspection Equipment List for Cartridge, Impulse M94

(Copies of specification, standards, drawings and publications required by suppliers in connection with specific procurement functions shall be obtained from the procuring activity or as directed by the contracting office.)

2.2 Other publications.-The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bid or request for proposal shall apply.

ASA B46.1 - Surface Texture

(Application for copies should be addressed to the American National Standards Institute (ANSI) 1430 Broadway, New York, N.Y. 10018)

3. REQUIREMENTS

3.1 General.-Materials, parts and assemblies shall conform to the applicable drawings and referenced specifications.

3.2 Protective finish.-Protective finish shall be in accordance with MIL-C-60539.

3.3 Vibration.-The assembled cartridge shall withstand vibration as prescribed in MIL-E-5272, Procedure XII, without evidence of any disintegration of the primer, propellant, igniter or derangement of any components.

3.4 Functional.

3.4.1 The cartridge shall not fail to fire.

3.4.2 Ballistics.-The cartridge, when assembled into an acceptable M15 Thruster, and fired at -65°F to -70°F, 65° to 75°F and 160° to 165°F, shall produce a thrust sufficient to propel an eleven (11) pound mass along a horizontal plane, shearing a shear pin with a shear value of 3750 pounds, simultaneously overcoming a 2250 pound resistive load from zero inches stroke to a minimum of 4.42 inch stroke. Time from initiation of cartridge to completion of stroke shall be not less than 120 milliseconds or more than 750 milliseconds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

3.4.2.1 Initiation.-The thruster shall be fired by a source delivering an output equal to that of an M3A1 Initiator at the end of 15 feet of aircraft hose, size 4, in accordance with MS28741 at 70° ± 5°F.

3.5 Workmanship.-Workmanship shall be in accordance with the requirements of the applicable drawings, referenced specifications and the following:

3.5.1 Metal defects.-The metal part shall be free from cracks, splits, cold shuts, inclusions, porosity or other metal defects.

3.5.2 Burr.-The part shall not have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.5.3 Foreign matter.-The part or assembly shall not contain chips, dirt, grease, oil, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.-Reference shall be made to MIL-STD-109 to define the quality assurance terms used.

4.1.2 Inspection.-Inspection shall be in accordance with MIL-A-2550.

4.2 First article sample.

4.2.1 Initial production sample.-At the beginning of regular production, a sample shall be submitted in accordance with contract requirements and shall consist of 21 assembled cartridges for ballistics, 5 assembled cartridges for sealant application tests, and 10 sets of unassembled components (including explosive components for visual and dimensional examination and tests.) The sample shall be manufactured using the same materials, equipment, processes and procedures as used in regular production. All parts and materials, including packaging and packing, shall be the same as used for regular production and shall be obtained from the same source of supply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

4.2.1.1 Examination and test.-After inspection and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specification at a Government laboratory or such other facility specified in the contract.

4.2.1.2 Ballistics.-The sample for ballistic test shall be temperature conditioned and tested to determine compliance with 3.4.2. The sample for firing shall consist of the following:

TABLE I

Temperature	Not Vibrated	Vibrated
-65°F to -70°F	3	4
65°F to 75°F	3	4
160°F to 165°F	3	4

4.2.1.3 Initial production sample failure.-Failure of the sample to comply with the requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection provisions.

4.3.1 Lot.

4.3.1.1 Submission of product.-The product shall be submitted in accordance with MIL-STD-105.

4.3.1.2 Size of lot.-A lot shall consist of an identifiable group of metal parts assemblies consisting of:

a. Components produced by a homogeneous process
b. Propellant from not more than one lot
c. Primers from not more than one lot
d. Igniters from not more than one lot

4.3.2 Examination.-One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plans and associated criteria in Table II and III. For an individual defect (single characteristic), the criteria in Table II shall be used. For total defects within a major or minor group, the criteria in Table III shall be used. All nonconforming material shall be rejected. The roughness comparison specimens prescribed

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

4.3.2 (Cont'd)

by ASA B46.1 shall be used as a basis of comparison for surface roughness determination. Inspection for rubber O-rings shall be in accordance with MIL-STD-413. Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter.

TABLE II

Lot Size	Sample Size	Major Accept	Major Reject	Minor Accept	Minor Reject
1 - 300	100% Examination	-	-	-	-
301 - 1300	110	1	2	2	3
1301 - 3200	150	2	3	3	4
3201 - 8000	225	3	4	4	5
8001 - 22000	300	4	5	5	6

TABLE III
Total Allowable Defects Per Sample Size

Sample Sizes for Major Defects	110	150	225	300
Number of Defects in Class				
2 - 3	1	2	3	4
4 - 7	2	3	4	5
8 - 19	3	4	5	7
20 - 43	4	5	8	10
Over 43	6	8	11	14
Sample Sizes for Minor Defects	**110**	**150**	**225**	**300**
Number of Defects in Class				
2 - 3	2	3	4	5
4 - 7	3	4	5	7
8 - 16	4	5	8	10
17 - 48	6	8	11	14
Over 48	8	11	17	20

4.3.2.1 Primer, Percussion, Drawing D10551686 covering a detail of Drawing D8596708.

Defect	Method of Inspection
CRITICAL	
1. Metal defective	Visual
2. Primer foil discolored	Visual
3. Mixed primers	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

4.3.2.1 (Cont'd)

Defect	Method of Inspection
MAJOR	
101. Burr	Visual
102. Foreign matter	Visual
MINOR	
None defined	

4.3.2.2 Plug, Firing, Drawing B8593498, covering a detail of Drawing D8596708.

CRITICAL	
1. Metal defective	Visual
2. Length of striker	Gage
MAJOR	
101. Diameter of body, large end, min.	Gage
102. Profile of striker	Gage
103. Burr	Visual
104. Foreign matter	Visual
MINOR	
201. Diameter of body,large end, max.	Gage
202. Diameter of body, small end	Gage
203. Total length	Gage
204. Length of body, small end	Gage
205. Surface finish improper	Visual

4.3.2.3 Ring, Retaining, Drawing B8593499, covering a detail of Drawing D8596708.

CRITICAL

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

4.3.2.3 (Cont'd)

Defects	Method of Inspection
MAJOR	
101. Concentricity of center hole with outside diameter	Gage
102. Diameter, O.D.	Gage
103. Diameter of center hole, max.	Gage
104. Metal defective	Visual
105. Protective finish inadequate or defective	Visual
106. Burr	Visual
107. Foreign matter	Visual
MINOR	
201. Diameter of center hole, min.	Gage
202. Thickness	Gage

4.3.2.4 Case, Cartridge, Drawing C8593736, covering a detail of Drawing D8596708.

CRITICAL	
1. Metal defective	Visual
MAJOR	
101. Concentricity of head with body	Gage
102. Flatness of base	Gage
103. Diameter of head min.	Gage
104. Thickness of base, min.	Gage
105. Thickness of sidewall, at head	Gage
106. Protective finish inadequate or defective	Visual
107. Burr or sharp corner	Visual
108. Foreign matter	Visual
MINOR	
201. Diameter of head, max.	Gage
202. Diameter of body	Gage
203. Total length	Gage
204. Location of datum diameter	Gage
205. Radius or chamfer missing or incorrect	Gage/Visual
206. Surface finish improper	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

4.3.2.5 Disc, Sealing, Drawing C8593494 covering a detail of Drawing D8596708.

Defect	Method of Inspection
CRITICAL	
1. None defined	
MAJOR	
101. Diameter, outside, min.	Gage
102. Diameter, center hole, max.	Gage
103. Metal defective	Visual
104. Protective finish, missing or inadequate	Visual
105. Burr	Visual
106. Foreign matter	Visual
MINOR	
201. Diameter, outside max.	Gage
202. Diameter, center hole, min.	Gage
203. Thickness	Gage
204. Diameter of stamp	Visual
205. Varnish, missing or inadequate	Visual
206. Marking missing, incorrect or illegible	Visual

4.3.2.6 Disc, Igniting, Drawing B8593355 covering a detail of Drawing D8596708.

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR	
101. Diameter, min.	Gage
102. Metal defective	Gage
103. Protective finish inadequate or defective	Visual
104. Burr	Visual
105. Foreign matter	Visual
MINOR	
None defined	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

4.3.2.7 Head Insert, Dwg. C8593741, covering a detail of Dwg. D8596708.

	Defect	Method of Inspection
CRITICAL		
	None defined	
MAJOR		
101.	Concentricity of large body with large cavity	Gage
102.	Concentricity of small cavitywith large cavity	Gage
103.	Perpendicularity of shoulder of large body with large body diam.	Gage
104.	Diameter of large cavity, max.	Gage
105.	Diameter of small cavity, max.	Gage
106.	Diameter of thru holes	Gage
107.	Length, large body, max.	Gage
108.	Diameter of large body, max.	Gage
109.	Surface finish large and small cavity and large body	Visual
110.	Metal defective	Visual
111.	Protective finish inadequate or defective	Visual
112.	Burr	Visual
113.	Foreign matter	Visual
MINOR		
201.	Diameter of large body, min.	Gage
202.	Diameter of large cavity, min.	Gage
203.	Diameter of small cavity, min.	Gage
204.	Depth of large cavity to chamfer	Gage
205.	Depth from face to bottom of small cavity	Gage
206.	Total length	Gage
207.	Length, large body, min.	Gage
208.	Diameter, small body	Gage
209.	Radius or chamfer missing or incorrect	Visual
210.	Surface finish improper, except as otherwise classified	Visual

4.3.2.8 Head, Drawing C8593740, covering a detail of Drawing D8596708.

CRITICAL		
	None defined	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

4.3.2.8 (Cont'd)

	Defect	Method of Inspection
MAJOR		
101.	Concentricity of flange with body diameter	Gage
102.	Concentricity of bore in flange with the body diameter	Gage
103.	Concentricity of counterbore of flange with the body diameter	Gage
104.	Perpendicularity of bottom of flange bore with diameter of flange bore	Gage
105.	Diameter of center cavity, max.	Gage
106.	Diameter of flange bore, max.	Gage
107.	Diameter of counterbore, flange, max.	Gage
108.	Diameter of flange	Gage
109.	Diameter of bore in bottom, max.	Gage
110.	Diameter of U'cut	Gage
111.	Diameter of body, max.	Gage
112.	Diameter of datum	Gage
113.	Total length, max.	Gage
114.	Surface finish of head face, improper	Visual
115.	Surface finish of diameter of bore in flange, improper	Visual
116.	Protective finish inadequate or defective	Visual
117.	Burr	Visual
118.	Foreign matter	Visual
MINOR		
201.	Diameter of center cavity, min.	Gage
202.	Diameter bore in flange, min.	Gage
203.	Diameter of counterbore, flange, min.	Gage
204.	Diameter of bore in bottom, min.	Gage
205.	Diameter of U'cut, min.	Gage
206.	Diameter of body, min.	Gage
207.	Length, total, min.	Gage
208.	Width of U'cut	Gage
209.	Thickness of flange	Gage
210.	Depth of counterbore in flange	Gage
211.	Depth to counterbore bottom	Gage
212.	Depth to end of center cavity	Gage
213.	Depth, of counterbore in front of U'cut	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

4.3.2.8 (Cont'd)

Defect	Method of Inspection
214. Configuration of U'cut	Gage
215. Radius missing or incorrect	Visual
216. Surface finish improper, except as otherwise classified	Visual

4.3.2.9 Head Assembly, Drawing C8593739, covering a detail of Drawing D8596708.

CRITICAL

1. Metal defective	Visual
2. Head insert not seated, flush or below surface "S"	Visual
3. Head not firmly seated against shoulder	Visual

MAJOR

101. Burr	Visual
102. Foreign matter	Visual

MINOR

201. Diameter of flange, max.	Gage

4.3.2.10 Spring, Retaining, Drawing B8593742, covering a detail of Drawing D8596708.

CRITICAL

None defined

MAJOR

101. Diameter, outside, min.	Gage
102. Thickness, max.	Gage
103. Width of gap when spring is compressed to specified O.D.	Gage
104. Metal defective	Visual
105. Protective finish inadequate or defective	Visual
106. Burr	Visual
107. Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

4.3.2.10 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Diameter, outside, max.	Gage
202. Thickness, min.	Gage

4.3.2.11 Cartridge, Impulse, M94 Assembly Drawing D8596708.

CRITICAL	
1. Metal defective	Visual
2. Primer not fully seated in primer pocket	X-ray 1/ Visual
3. Improper assembly	X-ray 1/ Visual
4. Any part missing	X-ray 1/ Visual
5. Marking missing, incorrect or illegible	Visual
MAJOR	
101. Concentricity of head with body	Gage
102. Location of datum diameter	Gage
103. Crimp missing, improper or defective	Gage
104. Sealant missing or improperly applied	Visual
MINOR	
201. Diameter of body, max.	Gage
202. Diameter of head, max.	Gage
203. Total length, max.	Gage
204. Moisture and fungus resistant varnish missing or inadequate	Visual

1/ The assembled cartridge shall be x-rayed with the long axis of the cartridge perpendicular to the rays of the machine. The x-ray negatives, properly identified, shall be forwarded to the procuring activity.

4.3.2.12 Carton, Packing, Ammunition For Cartridge Impulse M94, Drawing C8797725.

CRITICAL

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

4.3.2.12 (Cont'd)

Defect	Method of Inspection
MAJOR	
None defined	
MINOR	
201. Contents loose	Manual/Visual
202. Quantity of contents incorrect	Visual
203. Separation or filler missing	Visual
204. Heat sealer incomplete, loose or distorted	Visual
205. Cut or damaged through all impregnated layers	Visual
206. Marking missing, incorrect or illegible	Visual

4.3.2.14 Box, Packing, Ammunition For Cartridge Impulse M94 Drawing C8797267

CRITICAL	
None defined	
MAJOR	
None defined	
MINOR	
201. Contents loose	Manual/Visual
202. Box damaged	Visual
203. Contents of box exposed	Visual
204. Hardware missing, loose, broken or improperly engaged	Visual
205. Strapping missing, loose broken or improperly assembled	Visual
206. Marking missing, incorrect or illegible	Visual
207. Number of cartons incorrect	Visual
208. Car seal missing, unsealed or improperly positioned	Visual

4.3.3 Inspection testing.-The following tests shall be performed in accordance with the provisions of 4.4.

4.3.3.1 Protective finish.-Unless otherwise specified, sampling plans and procedures in determination of the acceptability of coated parts and articles submitted by a supplier shall be in accordance with provision set forth in MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

4.3.3.2 Vibration.-Twelve of the 21 cartridges of the initial production sample shall be subjected to vibration. The twelve cartridges shall then be x-rayed. Failure of any cartridge to comply with the requirements of 3.3 shall be cause for rejection of the lot. Any change in the process of a lot of primers in subsequent production shall be reason to select an additional sample of 12 cartridges for vibration tests.

4.3.3.3 Hardness.-Fifty units from each heat treated lot of components shall be tested. Failure of any unit to comply with the drawing requirements shall be cause for rejection of the lot of components.

4.3.3.4 Airtightness.-Each cartridge shall be subjected to the specified pressure differential. Failure to comply with the drawing requirements shall be cause for rejection of the lot of components.

4.3.3.5 Sealant application.-Five cartridges from each production lot shall be selected for this test. Failure of any cartridge to comply with the drawing requirements shall be cause for rejection of the lot of cartridges.

4.3.3.6 Functional.-The following test shall be performed by the Government:

4.3.3.6.1 Ballistics.-Twenty-one assembled cartridges from each production lot shall be functionally tested, as prescribed in Table IV. Failure of any cartridge to comply with the requirements of 3.4.2 shall be cause for rejection of the lot.

TABLE IV

Temperature	Sample Size
-65°F to -70°F	7
65°F to 75°F	7
160°F to 165°F	7

4.3.4 Inspection equipment.-The examination and tests shall be made using equipment listed on IEL-8596708.

4.4 Test method and procedures.

4.4.1 Protective finish.-Test procedures for protective finish shall be in accordance with MIL-C-60539. The cartridge case and head shall be sectioned longitudinally to better expose the significant surfaces to the salt spray.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

4.4.2 Vibration.-The method and procedure for performing the vibration test shall be in accordance with MIL-E-5272, Procedure XII.

4.4.3 Hardness.-A hardness testing machine shall be used for determining the hardness values specified on the applicable drawings.

4.4.4 Airtightness.-The method for determining airtightness shall be by use of the equipment listed on IEL-8596708.

4.4.5 Sealant application.-The cartridge shall be disassembled in such a manner that determination can be made that the sealant has been applied for the full length of the joining surfaces at the junction of the sealing disc and case sidewall and that the propellant is free of sealant.

4.4.6 Ballistics.-The cartridge shall be loaded into an acceptable M15 Thruster divided into 3 equal groups and temperature conditioned in accordance with Table IV. The cartridge shall be tested within 10 minutes after removal from the conditioning chamber. When this time is exceeded, the thruster shall be reconditioned in accordance with 4.4.6.1.

4.4.6.1 Temperature conditioning.-A standard M15 Thruster, loaded with a dummy M94 Cartridge, containing a temperature sensitive element shall be placed in the conditioning chamber at the same time as the samples. The conditioning time shall be a minimum of 1 hour longer than the time necessary to bring the element contained in the dummy cartridge to the required temperature.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking.-Packing and marking shall be in accordance with Drawings C8797267 and C8797725.

6. NOTES

6.1 Ordering Data.-Procurement documents should specify the title, number and date of this specification.

6.2 Ignition delay is defined as the time that elapses between the impact of the firing pin on the primer and the beginning of a continuous pressure rise on a pressure time record.

6.3 Storage and Shipping Information
Explosive Hazard Classification - Class 3
Storage Compatibility - Group B
Department of Transportation (DOT) Hazard Class; Class C

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

6.3 (Cont'd)

DOT Marking - "Explosive Power Device - Class C- Handle Carefully, Keep Fire Away".

Hazard notice.-The cartridge described herein and certain of its components are flammable and/or explosive and consequently present hazards in manufacture, handling, storage and shipment. The contractor should recognize these hazards and take appropriate measures to guard and protect against fire, explosion, adverse environment, corrosive atmosphere, rough handling and electrically induced incidents.

Custodian:

Army - MU

Preparing Activity:

Army - MU(FA)

Project No. 1377-A314

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
Department of the Army

OFFICIAL BUSINESS

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-J4000
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.