INCH-POUND



MIL-C-46274C
23 June 1992
SUPERSEDING
MIL-C-46274B(MU)
7 December 1971

MILITARY SPECIFICATION

# CARTRIDGE, IMPULSE, M94 ASSEMBLY

*This specification is approved for use by all Departments and Agencies of the Department of Defense.*

## 1. SCOPE

**1.1 Scope.** This specification covers the requirements for the M94 Impulse Cartridge (see 6.1).

## 2. APPLICABLE DOCUMENTS

### 2.1 Government documents.

**2.1.1 Specifications and standards.** The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplements thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

| | |
|---|---|
| MIL-A-2550 | Ammunition, General Specification For |
| MIL-A-8625 | Anodic Coatings, For Aluminum And Aluminum Alloy |

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, Standardization Branch (Code 8420), 101 Strauss Avenue, Indian Head, MD 20640-5035, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by sending a letter.

AMSC N/A FSC 1377

**DISTRIBUTION STATEMENT A:** Approved for public release; distribution is unlimited.

STANDARDS

MILITARY



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

| | |
|---|---|
| MIL-STD-105 | Sampling Procedures And Tables For Inspection By Attributes |
| MIL-STD-109 | Quality Assurance Terms And Definitions |
| MIL-STD-413 | Visual Inspection Guide For Elastomeric O-Rings |
| MIL-STD-453 | Inspection, Radiographic |
| MIL-STD-810 | Environmental Test Methods & Engineering Guidelines |
| MS-28741 | Hose Assembly, Detachable End Fitting, Medium Pressure |

(Unless otherwise indicated, copies of federal and military specifications and standards are available from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

**2.1.2 Other Government documents, drawings, and publications.** The following Government drawings form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation (see 6.2).

DRAWINGS

Naval Surface Warfare Center, Indian Head (CAGE Codes 19200 and 19203)

DL8596708 Cartridge, Impulse, M94 Assembly

| | |
|---|---|
| 8797725 | Box, Fiberboard (Inner), Packing, Ammunition, For Cartridge, Impulse M94 |
| 8797267 | Box, Packing, Ammunition, For Cartridge, Impulse M94 |
| 9224925 | Box, Fiberboard (Outer), Alternative Packing Ammunition, For Cartridge, Impulse M94 |

(Application for copies should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, Data Control Branch (Code 8410), Indian Head, MD 20640-5035.)

**2.2 Order of precedence.** In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

## 3. REQUIREMENTS

**3.1 First article.** When specified in the contract or purchase order, a first article sample shall be subjected to first article inspection (see 4.4, 6.2, and 6.3).



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

**3.2 Conformance to documents.** The M94 Impulse Cartridge covered by this specification shall be manufactured in accordance with DL8596708.

**3.3 Materials.** All materials used in the manufacture of the cartridges shall conform strictly to the specifications referred to on the respective drawings unless specific approval in writing covering a departure therefrom has been obtained from the cognizant Navy design activity prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

**3.4 Components.**

**3.4.1 Primary components.** For the purpose of this specification, the primer, igniter charge and the cartridge propellant charge are considered primary components. Only primary components from a single lot shall be used in a production lot of cartridges; however, one primary component production lot may be used in more than one cartridge production lot.

**3.4.1.1 Primer.** The primer shall conform to the applicable drawing and reference specification. Prior to assembly into a cartridge, the primer shall be visually examined in accordance with 4.6.2 and radiographically examined for defects as specified in 4.7.1.

**3.4.2 Hardness.** The hardness of each component part shall be in accordance with the applicable drawing (see 4.7.2).

**3.4.3 Protective finish.** The finish of each component part shall be in accordance with MIL-A-8625 and the applicable drawing (see 4.7.3).

**3.5 Assembly.**

**3.5.1 Radiographic examination.** Each cartridge assembly shall be radiographically examined for defects (see 4.7.4).

**3.5.2 Airtightness.** Each assembled cartridge shall exhibit no air leakage greater than $1 \times 10^{-4}$ standard cubic centimeters of air per second at a 14 psia pressure differential (see 4.7.5).

**3.5.3 Vibration.** The assembled cartridge shall withstand vibration as prescribed in MIL-STD-810, Method 514.3, Test Procedure I, Test Condition I-3.2.5 without evidence of any disintegration of the primer, propellant, or igniter, or derangement of any component (see 4.7.7 and 6.2).

**3.6 Functional requirements.**

**3.6.1 Primer sensitivity.** The primer shall fire when drop tested at an energy level of 120 inch-ounces in a sectioned cartridge void of igniter and propellant charge (see 4.7.8.1).

**3.6.2 Cartridge performance.**



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

**3.6.2.1 Misfires.** The cartridge shall not fail to fire.

**3.6.2.2 Ballistics.** The cartridge, when assembled into an acceptable M15 Thruster and fired at • 60• to • 70•F, 65• to 75•F, and 195• to 205•F, shall produce a thrust sufficient to propel an 11-pound mass along a horizontal plane, shearing a shear pin with a shear value of 3750 pounds, simultaneously overcoming a 2250-pound resistive load from zero inches stroke to a minimum of 4.42 inch stroke. Time from initiation of cartridge to completion of stroke shall be not less than 200 milliseconds or more than 750 milliseconds.

**3.6.2.3 Initiation.** The thruster shall be fired by a source delivering an output pressure of 700 + 25, • 0 pounds per sqaure inch gage (psig) at the end of 15 feet of aircraft hose, MS28741-4, at 70• ± 5•F.

**3.7 Workmanship.** Cartridges shall be free of cracks, splits, or other defects which might prevent proper mating with connecting parts or proper functioning of the device.

**3.7.1 Metal defects.** All components shall be free from cracks, splits, cold shuts, inclusions, porosity, or any similar defect.

**3.7.2 Burr.** No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

**3.7.3 Foreign matter.** No part or assembly shall contain chips, dirt, grease, rust, corrosion, or other foreign matter.

## 4. QUALITY ASSURANCE PROVISIONS

**4.1 Responsibility for inspection.** Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements (see 6.2).

**4.1.1 Responsibility for compliance.** All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements; however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

**4.1.2 Quality assurance terms and definitions.** Reference shall be made to MIL-STD-109 to define the quality assurance terms used.

**4.1.3 Inspections.** Inspections shall be in accordance with MIL-A-2550 and MIL-STD-453.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

**4.2 Classification of inspections.** The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4)
b. Quality conformance inspection (see 4.5)

**4.3 Inspection conditions.** Unless otherwise specified in the contract or purchase order (see 6.2), inspection conditions shall be as follows:

a. Temperature: Room ambient 20• to 25• C (68• to 77• F)
b. Altitude: Sea level
c. Humidity: 50 percent relative, maximum
d. Atmospheric: 14.7 psia

**4.4 First article inspection.** At the beginning of regular production, the contractor shall submit a first article sample to a Government approved facility for evaluation. The sample shall consist of 21 assembled cartridges for ballistics testing including 12 for vibration tests (to be selected from ballistic samples), 5 assembled cartridges for sealant tests, 10 sets of unassembled components for dimensional and visual examination, and a quantity in accordance with 4.4.2, i.e., cartridges assembled without the igniter and propellant charge for primer sensitivity test. The first article sample shall be manufactured using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be the same as used for regular production and shall be obtained from the same source of supply. When it becomes necessary to make a change in either the primer, propellant, or igniter lot after initial production, 12 assembled cartridges from the first production lot thereafter shall be tested in accordance with 4.7.7. The Government reserves the right to require new first article samples until an acceptable sample is submitted (see 6.3).

**4.4.1 Examination, tests, and facility.** After provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or other such facility specified in the contract (see 6.2).

**4.4.2 Sample size for primer sensitivity.** The number of cartridges assembled without igniter or propellant to be submitted for primer sensitivity tests shall be in accordance with table I.

TABLE I. Primer sensitivity.

| Lot Size | Sample Size |
|---|---|
| 3 to 15 | 3 |
| 16 to 25 | 4 |
| 26 to 40 | 5 |
| 41 to 65 | 7 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

| | |
|---|---|
| 66 to 110 | 10 |
| 111 to 180 | 15 |
| 181 to 300 | 25 |
| 301 to 500 | 30 |
| 501 to 800 | 35 |
| 801 to 1300 | 40 |
| Over 1300 | 50 |

**4.4.3 Temperature conditioning for ballistic test.** The sample shall be temperature conditioned and tested to determine compliance with 3.6.2.2. The sample for firing shall be conditioned to table II.

TABLE II. Temperature conditioning.

| Temperature (•F) | Not vibrated | Vibrated |
|---|---|---|
| -60 to -70 | 3 | 4 |
| 65 to 75 | 3 | 4 |
| 195 to 205 | 3 | 4 |

**4.4.4 First article failure.** Failure of the sample to comply with the requirements of the drawings and specifications shall result in first article sample disapproval.

**4.5 Quality conformance inspection.**

**4.5.1 Lot.**

**4.5.1.1 Submission of product.** The product shall be submitted in accordance with MIL-STD-105.

**4.5.1.2 Lot size.** The production lot size shall be as specified in the contract (see 6.2).

**4.5.2 Examination and tests.** The quality conformance sample shall be subjected to the examinations of 4.6 and all the test procedures of 4.7 except for 4.7.7.

**4.6 Examination.** All cartridges and components shall be examined visually and radiographically and characteristics defined in accordance with the applicable drawings. One hundred percent examination shall be performed for all critical defects. Examination for major or minor defects shall be performed on a defect basis in accordance with the classification of defects. Inspection for elastomeric O-rings shall be in accordance with MIL-STD-413. Four power (4X) magnification may be used in performing visual examination for such defects as burrs and foreign matter. When compliance is in doubt as a result of visual inspection, the characteristic shall be measured or gaged to determine acceptability. All nonconforming items shall be rejected.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

**4.6.1 Cartridge, Impulse, M94 Assembly, Drawing 8596708.**

| Characteristic | Defect | Method of Inspection |
|---|---|---|
| Critical | | |
| 1 | Any part missing | X-ray/Visual |
| 2 | Improper assembly | X-ray/Visual |
| 3 | Primer not properly seated | X-ray/Visual |
| 4 | Metal defective | Visual |
| 5 | Marking missing, incorrect, or illegible | Visual |
| Major | | |
| 101 | Concentricity of head with body | Gage |
| 102 | Crimp missing or improper | Visual |
| 103 | Sealant missing | Visual |
| 104 | Sealant in cavity | Visual |
| 105 | Foreign matter present | Visual |
| 106 | O-ring split, creaked, or cut | Visual |
| Minor | | |
| 201 | Diameter of body, max | Gage |
| 202 | Diameter of head, max | Gage |
| 203 | Total length, max | Gage |
| 204 | Location of datum diameter | Gage |
| 205 | Varnish missing or inadequate | Visual |
| 206 | Fold, wrinkle or bulge | Visual |

**4.6.2 Primer, Percussion, Drawing 10551686, covering a detail of 8596708.**

| | | |
|---|---|---|
| Critical | | |
| 1 | Improper assembly | Visual/X-ray |
| 2 | Any part missing | Visual/X-ray |
| 3 | Primer pellet broken, cracked, or dislodged | Visual |
| 4 | Metal defective | Visual |
| 5 | Primer foil discolored | Visual |
| 6 | Mixed primers | Visual |
| Major | | |
| 101 | Burr | Visual |
| 102 | Foreign matter present | Visual |

**4.6.3 Case, Cartridge, Drawing 8593736, covering a detail of Drawing 8596708.**

Critical
None defined



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

| | | |
|---|---|---|
| Major | | |
| 101 | Concentricity of large diameter with small diameter | Gage |
| 102 | Diameter of head, min | Gage |
| 103 | Thickness of base, min | Gage |
| 104 | Diameter of body, min | Gage |
| 105 | Thickness of sidewall, min | Gage |
| 106 | Straightness of base | Gage |
| 107 | Protective finish inadequate or defective | Visual |
| 108 | Foreign matter present | Visual |
| 109 | Burr or sharp corner | Visual |
| Minor | | |
| 201 | Small diameter, max | Gage |
| 202 | Large diameter, max | Gage |
| 203 | Total length | Gage |
| 204 | Location of datum diameter | Gage |
| 205 | Thickness of sidewall, max | Gage |
| 206 | Radius or chamfer missing or incorrect, except as otherwise classified | Visual |
| 207 | Surface finish improper | Visual |

**4.6.4 Sealing Disc, Drawing 8593494, covering a detail of Drawing 8596708.**

Critical
None defined

| | | |
|---|---|---|
| Major | | |
| 101 | Diameter, min | Gage |
| 102 | Marking missing, incorrect, or illegible | Visual |
| 103 | Metal defective | Visual |
| 104 | Protective finish inadequate or defective | Visual |
| 105 | Burr | Visual |
| 106 | Foreign matter present | Visual |
| Minor | | |
| 201 | Diameter, max | Gage |
| 202 | Thickness | Gage |
| 203 | Varnish missing | Visual |

**4.6.5 Head, Cartridge, Drawing 11731601, covering a detail of Drawing 8596708.**

| | | |
|---|---|---|
| Critical | | |
| 1 | Thickness of metallic web between flash hole and igniter cavity | Gage |
| Major | | |
| 101 | Concentricity of flange with body | Gage |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

| | | |
|---|---|---|
| 102 | Concentricity of counterbore with firing pin plug cavity | Gage |
| 103 | Concentricity of firing pin cavity with body | Gage |
| 104 | Concentricity of firing plug cavity with primer percussion cavity | Gage |
| 105 | Diameter of counterbore at flange end, max | Gage |
| 106 | Wall thickness, min | Gage |
| 107 | Surface finish firing plug cavity primer percussion cavity, and face of flange | Visual |
| 108 | Diameter of firing plug cavity | Gage |
| 109 | Diameter of percussion primer small cavity | Gage |
| 110 | Diameter of percussion primer large cavity | Gage |
| 111 | Metal defective | Visual |
| 112 | Protective finish inadequate or defective | Visual |
| 113 | Burr | Visual |
| 114 | Foreign matter | Visual |
| Minor | | |
| 201 | Diameter of counterbore at flange end, min | Gage |
| 202 | Total diameter | Gage |
| 203 | Depth of counterbore at flange end | Gage |
| 204 | Depth from flange face to bottom of firing plug cavity | Gage |
| 205 | Depth from flange face to bottom of larger percussion primer cavity | Gage |
| 206 | Diameter of body | Gage |
| 207 | Diameter at rear | Gage |
| 208 | Width of undercut, rear of percussion primer small cavity | Gage |
| 209 | Depth from rear face to bottom of igniter cavity | Gage |
| 210 | Width of undercut, rear of igniter cavity | Gage |
| 211 | Depth from rear face to start of igniter cavity | Gage |
| 212 | Width of spring retaining cavity | Gage |
| 213 | Width of flange | Gage |
| 214 | Diameter of spring retaining cavity | Gage |
| 215 | Chamfers and radius missing or incorrect | Visual |
| 216 | Surface finish improper except as otherwise specified | Visual |

### 4.6.6 Plug, Firing, Drawing 8593498, covering a detail of Drawing 8596708.

| | | |
|---|---|---|
| Critical | | |
| 1 | Length of striker tip, min | Gage |
| Major | | |
| 101 | Diameter of body, min | Gage |
| 102 | Profile of striker tip | Gage |
| 103 | Height of boss | Gage |
| 104 | Metal defective | Visual |
| 105 | Burr | Visual |
| 106 | Foreign matter present | Visual |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

| | | |
|---|---|---|
| Minor | | |
| 201 | Diameter of body, max | Gage |
| 202 | Diameter of boss | Gage |
| 203 | Total length | Gage |
| 204 | Length of striker tip, max | Gage |
| 205 | Surface finish improper | Visual |

**4.6.7 Ring, Retaining, Drawing 8593499, covering a detail of Drawing 8596708.**

Critical
None defined

| | | |
|---|---|---|
| Major | | |
| 101 | Concentricity of inside diameter with outside diameter | Gage |
| 102 | Outside diameter, min | Gage |
| 103 | Inside diameter, max | Gage |
| 104 | Metal defective | Visual |
| 105 | Protective finish inadequate or defective | Visual |
| 106 | Burr | Visual |

| | | |
|---|---|---|
| Minor | | |
| 201 | Outside diameter, max | Gage |
| 202 | Inside diameter, min | Gage |
| 203 | Thickness | Gage |
| 204 | Foreign matter present | Visual |

**4.6.8 Igniting Disc, Drawing 8593355, covering a detail of Drawing 8596708.**

Critical
None defined

| | | |
|---|---|---|
| Major | | |
| 101 | Diameter, min | Gage |
| 102 | Metal defective | Visual |
| 103 | Protective finish inadequate or defective | Visual |
| 104 | Burr | Visual |
| 105 | Foreign matter present | Visual |

| | | |
|---|---|---|
| Minor | | |
| 201 | Diameter, max | Gage |
| 202 | Thickness | Gage |

**4.6.9 Retaining Spring, Drawing 8593742, covering a detail of Drawing 8596708.**



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

Critical
None defined

Major

| | | |
|---|---|---|
| 101 | Thickness of wire, min | Gage |
| 102 | Metal defective | Visual |
| 103 | Protective finish inadequate or defective | Visual |
| 104 | Burr | Visual |
| 105 | Foreign matter present | Visual |

Minor

| | | |
|---|---|---|
| 201 | Diameter, free | Gage |
| 202 | Thickness of wire, max | Gage |
| 203 | Gap, min, when spring is compressed to specified outside diameter | Gage |

**4.6.10 Box, Fiberboard (Inner), Ammunition, Packing, Drawing 8797725.**

Critical
None defined

Major
None defined

Minor

| | | |
|---|---|---|
| 201 | Contents loose | Manual/Visual |
| 202 | Separator or filler missing | Visual |
| 203 | Heat sealer incomplete, loose, or distorted | Visual |
| 204 | Cut or damaged through impregnated box | Visual |
| 205 | Marking missing, incorrect, or illegible | Visual |

**4.6.11 Box, Ammunition, Packing, Drawing 8797267.**

Critical
None defined

Major
None defined

Minor

| | | |
|---|---|---|
| 201 | Contents loose | Manual/Visual |
| 202 | Strapping missing, loose, broken, or improperly assembled | Visual |
| 203 | Contents of box exposed | Visual |
| 204 | Box damaged | Visual |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

| | | |
|---|---|---|
| 205 | Marking missing, incorrect, or illegible | Visual |
| 206 | Number of cartons incorrect | Visual |

**4.6.12 Box, Fiberboard (Outer), Alternative, Drawing 9224945.**

Critical
None defined

Major
None defined

Minor

| | | |
|---|---|---|
| 201 | Contents loose | Manual |
| 202 | Box broken or damaged | Visual |
| 203 | Number of units contained incorrect | Visual |
| 204 | Marking missing, incorrect, or illegible | Visual |
| 205 | Tape incomplete | Visual |

**4.7 Test methods and procedures.**

**4.7.1 Primer x-ray.** Prior to assembly into the cartridge, the primer shall be radiographically examined in accordance with MIL-STD-453. Each primer shall be x-rayed on boards or trays with the cup side perpendicular to the rays. The x-ray negatives shall be identified by item nomenclature and by lot number. Primers are to be left mounted to the boards or trays until after the x-rays have been reviewed and defects identified to facilitate removal of defective units. After screening, the x-ray negatives with defectives identified, shall be forwarded to the engineering activity designated by the acquiring activity. Interpretation of the radiographic films shall verify the following:

Presence of Primer Charge
No Material Defects

**4.7.2 Hardness.** Ten units from each heat-treated lot of components shall be tested with a hardness tester. Failure of any unit to comply with the requirements of the drawings shall be cause for rejection of the lot of components.

**4.7.3 Protective finish.** Procedures for the determination of acceptability of coated parts shall be in accordance with the contract and MIL-A-8625.

**4.7.4 Radiographic examination.** All assembled cartridges shall be radiographically examined in accordance with MIL-STD-453. The cartridges shall be positioned on their sides for the most revealing exposure. All cartridges shall be identified with serial numbers prior to examination. The serial numbers shall be in consecutive order beginning with the number 001 in each production lot. The cartridges shall be arranged on trays or boards in consecutive numerical order, and each radiograph shall carry a permanent identification of the cartridges displayed thereon. The radiographic plate identification shall include item nomenclature, the complete lot number as stamped on the cartridges, the span of serial numbers displayed, and the contract number. Cartridges having any observable imperfections in assembly shall be cause for rejection.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

Radiographs of the entire production lot shall accompany the ballistic sample to the activity conducting the production lot acceptance test. Discontinuities in serial numbers shall be identified on the x-ray negative. Defective cartridges, found by the vendor, shall be clearly identified on the negative and those defectives removed from the production lot. The serial numbers shall be pen or ink stamped on the cartridge with approximately 1/8-inch-high characters. The serial numbers shall be located apart from the other cartridge markings (see 6.2).

**4.7.5 Airtightness.** Each cartridge shall be subjected to specified pressure differential. The method for determining airtightness shall be with a helium mass spectrometer. The helium leak rate shall be converted to standard cubic centimeters of air. Failure to comply with the requirements of 3.5.2 shall be cause for rejection of the cartridge.

**4.7.6 Sealant application.** Five cartridges from each production lot shall be selected for this test. Failure of any cartridge to comply with the drawing requirements shall be cause for rejection of the lot of cartridges.

**4.7.7 Vibration test.** Twelve of the 21 assembled cartridges of the first article sample, x-rayed as directed in 4.7.4, properly identified, shall be subjected to vibration. The method and procedures for performing the vibration test shall be in accordance with MIL-STD-810, Method 514.3, Test Procedure I, Test Condition I-3.2.5 (see 6.2). Then the 12 vibrated cartridges shall be x-rayed again. Evidence of any disintegration of the primer, propellant, or igniter, or derangement of any component shall be cause for rejection of the sample.

**4.7.8 Functional.** The following tests shall be performed by the Government.

**4.7.8.1 Primer sensitivity.** A quantity of cartridges, in accordance with table I, void of igniter and propellant, from the first article sample and each subsequent lot shall be tested for sensitivity. In the event loaded cartridges are selected for test, remove and discard all powder charges from the test cartridge by sectioning the cartridge case around the periphery. Drop test at 15 inches (adjusted) using a steel ball 1 and 1/2-inch diameter, weighing 7.94 ± 0.02 ounces, in a primer sensitivity machine with a cartridge holder approved by the acquiring agency. The height of 15 inches shall be adjusted taking into consideration the actual weight of the ball so that the energy level specified in 3.6.1 is achieved. Failure of the sample to comply with 3.6.1 shall be cause for rejection of the sample or the lot.

**4.7.8.2 Ballistics.**

**4.7.8.2.1 First article.** Twenty-one cartridges of the first article sample shall be grouped and temperature conditioned as described in table II and 4.8. Following removal from the conditioning chamber, the cartridge shall be tested as required by 3.6.2.2. Failure of any cartridge to comply with 3.6.2.2 shall be cause for sample rejection.

**4.7.8.2.2 Production lot acceptance.** Twenty-one assembled cartridges from each production lot shall be loaded into acceptable M15 thrusters, divided into three equal groups, temperature conditioned, and fired in accordance with 3.6.2.2. Failure of any cartridge to comply with 3.6.2.2 shall be cause for rejection of the lot. In addition to the sample of cartridges for the above test, 10 additional cartridges shall be furnished from each production lot for investigative purposes.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

**4.7.8.2.2.1 Sealant application.** Five cartridges from each production lot shall be selected for this test. The cartridge shall be disassembled in such a manner that determination can be made that the sealant has been applied for the full length of the joining surfaces at the junction of the cartridge head and case sidewall and that the propellant cavity is free of sealant. Failure of any cartridge to comply with the drawing requirements shall be cause for rejection of the lot of cartridges.

**4.7.8.3 Retest.** There shall be no retests.

**4.7.8.3.1 Test failure.** If a test failure is attributable to an assignable cause, excluding the test cartridge, the original test results shall be discarded and that test reconducted.

**4.8 Temperature conditioning.** The conditioning chamber shall be preconditioned to the specified temperature. Once the temperature inside the chamber has stabilized, the samples shall be placed inside and maintained at the specified temperature for 4 hours minimum, 24 hours maximum.

**4.8.1 Reconditioning.** The sample must be tested within ten minutes after removal from the conditioning chamber. If this time is exceeded, the cartridge shall be reconditioned in accordance with 4.8.

**4.9 Inspection of packaging.** The sampling and inspection of the preservation, packing, and container marking shall be in accordance with the requirements of section 5.

## 5. PACKAGING

**5.1 Packing and marking.** Packing and marking shall be Level A or B, as specified by the contracting activity (see 6.2). Level A shall be in accordance with Drawings 8797725 and 8797267. Level B shall be in accordance with Drawings 8797725 and 9224945.

## 6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

**6.1 Intended use.** The assembly is used in cartridge actuated devices for Aircrew Emergency Escape Systems.

**6.2 Acquisition requirements.** Acquisition documents must specify the following:

a. Title, number, and revision letter of this specification

b. Issue of DODISS to be cited in the solicitation and, if required, the specific issue of individual documents referenced and that MIL-STD-810D shall be used (see 2.1, 3.5.3, and 4.7.7)

c. Whether a first article sample is required (see 3.1, 4.4, and 6.3)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

d. Test facility for first article tests (see 4.4.1)

e. Production test activity and lot size (see 4.1 and 4.5.1.2)

f. Any special test conditions (see 4.3)

g. Directions for shipping radiographs of primers and of entire lot of cartridge assemblies (see 4.7.1 and 4.7.4)

h. Level of preservation and packing (see 5.1)

i. That the safety precaution requirements of the ``Contractor's Safety Manual for Ammunition, Explosives, and Related Dangerous Material,'' DOD 4145.26M are applicable. NOTE: When this specification is used as part of the description of work to be accomplished by a Government activity, the safety precaution requirements of ``Ammunition and Explosives Ashore,'' OP 5 are applicable.

**6.3 First article.** When a first article inspection is required, the contracting officer should provide specific guidance to offerors whether the items should be a first article sample or a sample selected from the first production items (see 3.1), and the number of items to be tested as specified in 4.4. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examination, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

**6.4 Hazard notice.** The cartridge described herein and certain of its components are flammable or explosive and present hazards in manufacture, handling, storage, and shipment. The contractor should recognize these properties and take appropriate measures to guard and protect against fire, explosion, adverse environment, corrosive atmosphere, rough handling, and electrically induced incidents.

**6.5 Subject term (keyword) listing.**

Ejection systems, aircrew
Emergency escape systems, aircrew
Escape systems, aircrew
Life-saving systems, aircrew

**6.6 Changes from previous issue.** Marginal notations are not used to identify changes with respect to the previous issue because of the extensiveness of the changes.

Custodian: Preparing activity



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.

Navy - OS
Air Force - 99

Navy - OS
(Project 1377-0D90)

Review activity:
Air Force - 70



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:25Z
Check the source to verify that this is the current version before use.