MIL-C-46246F(AR)
18 MARCH 1983
SUPERSEDING
MIL-C-46246E(PA)
31 December 1973

MILITARY SPECIFICATION

CHARGES, DEMOLITION, TNT, BLOCK, 1/4 POUND, 1/2 POUND, AND 1 POUND

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers quality assurance provisions and preparation for delivery for Charges, Demolition, TNT, Block, 1/4 Pound, 1/2 Pound, and 1 Pound.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.1), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS (See 6.4)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

8797113 - Charge, Demolition, 1/4 Pound Block (TNT), Assembly and Marking.
8797739 - Packing and Marking for Charge, Demolition Block, 1/4 Lb. (TNT) w/Priming Adapters, M1A4.
8799162 - Box, Packing, Ammunition, for Charge, Demolition Block, 1 Pound or 1/2 Pound (TNT) w/Priming Adapters, M1A4.
8885245 - Charge, Demolition, Block (TNT), 1/2 Pound, Assembly.
8885249 - Charge, Demolition, Block (TNT), 1 Pound, Assembly.
9287850 - Charge, Demolition, 1/4 Pound Block (TNT) (Alternate Design).

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings, specifications and standards.

3.2 Parts. All parts shall comply with applicable drawings, specifications and standards.

3.3 Demolition charge. The Demolition Charge shall comply with all requirements specified on Drawings (Dwg.) 8797113, 8885245, 8885249 or 9287850, as applicable, all associated drawings, and with all requirements specified in applicable specifications and standards.

3.4 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T05:20Z
Check the source to verify that this is the current version before use.

3.5 Workmanship. All parts shall be fabricated and finished in a thorough, workmanlike manner. All parts and assemblies shall be free of burrs, chips, sharp edges, cracks, grazes, unblended radii, porosity, warpage, burn marks, checks, sinks, chipped edges, blisters, bubbles, excess flash, dirt, grease, rust and other foreign material. Charges shall be free of breaks, cracks and other defects. Painted surfaces shall be free of chips and scratches, and colors shall be uniform. The cleaning method shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated below and Table I.

Part Description	Drawings	Quantity
Body	8797116	5
End, Adapter	8797117	5
End	8797118	5
Disc	8797119	5
Body Assembly	8797114	5
Body	8885251-1	5
Body	8885251-2	5
End Plate	8885255-1	5
End Plate	8885255-2	5
Adapter, End	8885256-1	5
Adapter, End	8885256-2	5
Disc	8885253	5 (Note 1)
Body Assembly	8885250-1	5
Body Assembly	8885250-2	5
Body (Alternate)	9287848	5 (Note 1)
Cap (Alternate)	9287849	5 (Note 1)

Source: https://assist.dla.mil -- Downloaded: 202610-22T05:20Z
Check the source to verify that this is the current version before use.

Part Description	Drawing	Quantity
Charge, Demolition, 1/4 Pound Block	8797113	40
Charge, Demolition, 1/2 Pound Block	8885245	40
Charge, Demolition, 1 Pound Block	8885249	40
Charge, Demolition, 1/4 Pound Block	9287850	40

Note 1. Five (5) from each cavity shall be submitted. Parts from each cavity shall be identified as to permit tracing each part to the cavity in which it was molded.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 202610-22T05:20Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46246F(AR)

PARAGRAPH	TITLE		SHEET 1 OF 4		DRAWING NUMBER
	Charges, Demolition, TNT, Block				See Below
					NEXT HIGHER ASSEMBLY
					--
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Body (Dwg. 8797116)				
	Inspect for all drawing requirements	5		3.2	Gage/Visual
	End, Adapter (Dwg. 8797117)				
	Inspect for all drawing requirements	5		3.2	Gage/Visual
	End (Dwg. 8797118)				
	Inspect for all drawing requirements	5		3.2	Gage/Visual
	Disc (Dwg. 8797119)				
	Inspect for all drawing requirements	5		3.2	Gage/Visual
	Bursting strength test	5		3.2	(a)
	Body Assembly (Dwg. 8797114)				
	Inspect for all drawing requirements	5		3.2	Gage/Visual
	Pull test of crimped ends	5		3.2	4.5.2

NOTES: (a) Following acceptance of first article samples, this inspection shall be satisfied by certification as specified in 4.4.

DRDAR-QA Form 160 Jul 77

Source: https://assistdla.mil -- Downloaded: 2026-05-22 10:52 GMT
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46246F(AR)

PARAGRAPH	TITLE		SHEET 2 OF 4		DRAWING NUMBER
	Charges, Demolition, TNT, Block				See below
					NEXT HIGHER ASSEMBLY
					--
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Body (Dwg. 8885251-1 or 8885251-2)				
	Inspect for all drawing requirements	5		3.2	Gage/Visual
	End Plate (Dwg. 8885255-1 or 8885255-2)				
	Inspect for all drawing requirements	5		3.2	Gage/Visual
	Adapter, End (Dwg. 8885256-1 or 8885256-2)				
	Inspect for all drawing requirements	5		3.2	Gage/Visual
	Disc (Dwg. 8885253)				
	Inspect for all drawing requirements	5		3.2	Gage/Visual
	Bursting strength test	5		3.2	(a)
	Body Assembly (Dwg. 8885250-1 or 8885250-2)				
	Inspect for all drawings requirements	5		3.2	Gage/Visual
	Pull test of crimped ends	5		3.2	4.5.2

NOTES:
(a) Following acceptance of first article samples, this inspection shall be satisfied by certification as specified in 4.4.4.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-02-22 05:20Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46246F(AR)

PARAGRAPH	TITLE		SHEET 3 OF 4		DRAWING NUMBER
	Charges, Demolition, TNT, Block				See below
					NEXT HIGHER ASSEMBLY
					--
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Body (Alternate) (Dwg. 9287848)				
	Examination for defects	5		3.2	4.4.2.3
	Cap (Alternate) (Dwg. 9287849)				
	Examination for defects	5		3.2	4.4.2.4
	Charge, Demolition, 1/4 Pound Block (TNT), Assembly and Marking (Dwg. 8797113)				
	Examination for defects	40		3.3	4.4.2.1 and 4.4.2.2
	Pull test of crimped ends	40(a)		3.3	4.5.2
	Charge, Demolition, Block (TNT), 1/2 LB. Assembly (Dwg. 8885245)				
	Examination for defects	40		3.3	4.4.2. 1 and 4.4.2.2
	Pull test of crimped ends	40(a)		3.3	4.5.2

NOTES: (a) This test shall be performed on the samples subjected to the examination for defects. If two (2) or more assemblies fail to comply with the specified requirement, the first article sample shall be rejected.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T05:20Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46246F(AR)

PARAGRAPH	TITLE		SHEET 4 OF 4		DRAWING NUMBER
	Charges, Demolition, TNT, Block				See below
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Charge, Demolition, Block (TNT), 1LB, Assembly (Dwg. 8885249)				
	Examination for defects	40		3.3	4.4.2.1 and 4.4.2.2
	Pull test of crimped ends	40(a)		3.3	4.5.2
	Charge, Demolition, 1/4 Pound Block (TNT) (Alternate Design) (Dwg. 9287850)				
	Examination for defects	40		3.3	4.4.2.1 and 4.4.2.2
	Pull test of heat sealed cap	40(a)		3.3	4.5.3

NOTES: (a) This test shall be performed on the samples subjected to the examination for defects. If two (2) or more assemblies fail to comply with the specified requirement the first article sample shall be rejected.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T05:20Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each lot shall contain TNT charges from not more than two (2) lots from one manufacturer.

4.4.1.1 Cavity identification (Plastic parts). The contractor shall maintain an approved cavity identification system. Components shall be grouped and identified until all inspections have been completed (applicable when alternate design is specified in contract).

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the classification of Defects and Tests Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T05:20Z
Check the source to verify that this is the currentversion before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46246F(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Assembly (Prior to Assembling End Adapter or Cap, as applicable)	1 OF 1	8797113/8885245/8885249/ 9287850, as applicable
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Depth to bottom of fuze well, minimum (min.)		0.40%	3.2	Gage
102	Diameter of fuze well, min. (Dwg. 8797113, 8885249 or 9287850)		0.40%	3.2	Gage
103	Diameter of bottom portion of fuze well, min (Dwg. 8885245)		0.40%	3.2	Gage
104	Diameter of fuze well portion below counterbore, min.		0.40%	3.2	Gage
105	Depth of fuze well counterbore, min.,		0.40%	3.2	Gage
106	Diameter of fuze well counterbore		0.40%	3.2	Gage
107	Charge cracked or other evidence of damage		0.40%	3.5	Visual
108	Foreign matter in fuze well		0.40%	3.2	Visual
109	Specific Gravity of charge	(a)		3.2	4.5.1
110	Binder - Lubricant content of charge	-	-	3.2	Certification (4.4.4)
Minor					
201	Poor workmanship (excl. 107 above)		1.0%	3.5	Visual

NOTES: (a) Three (3) demolition charges (Dwg. 8797115, 8885248, or 8885252, as applicable, shall be selected from each lot for this test. If the average specific gravity of the sample fails to comply with the specified drawing requirement, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T05:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46246F(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.2	Charge, Demolition, Assembly	1	3	8797113/8885245/8885249/9287850, as applicable
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pull test of crimped ends (Dwg. 8797113, 8885245 or 8885249)	(a)		3.3	4.5.2
102	Pull test of heat sealed cap (Dwg. 9287850)	(b)		3.3	4.5.3
103	Assembly damaged (Body, end, or cup, cut, punctured, cracked, dented, wrinkled, or torn)		0.40%	3.3	Visual

(a) Eighty (80) demolition charge assemblies shall be selected from each lot for this test. If four (4) or more assemblies fail to comply with the specified drawing requirement, the lot shall be rejected. If two (2) or three (3) fail the test, a second sample of eighty (80) assemblies shall be tested. If a total of five (5) or more assemblies from both samples fail the test, the lot shall be rejected. An assembly shall be classed defective if the end shows any evidence of separation upon application of the minimum pull force.

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assistdocs.com - Downloaded: 2026-02-27 05:20Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46246F(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
Cont'd	Charge, Demolition, Assembly	2 OF 3	8797113/8885245/8885249/ 9287850, as applicable
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	(b) Eighty (80) demolition charge assemblies shall be selected from each lot for this test. If two (2) or more assemblies fail to comply with the specified drawing requirement, the lot shall be rejected. An assembly shall be classed defective if the cap shows any evidence of separation upon application of the minimum pull force.				
104	Adapter end or cap improperly assembled or missing		0.40%	3.3	Visual
105	Charge missing		0.40%	3.3	Visual
Minor					
201	Profile of end adapter helix		0.65%	3.3	Gage
202	Total length, maximum (max)		0.65%	3.3	Gage
203	Diameter across end crimps, max. (Dwg. 8797113 or 9287850)		0.65%	3.3	Gage
204	Width across end or cap crimps, max. (Dwg 8885245 or 8885249)		0.65%	3.3	Gage
205	Crimping of ends or cap improper (metal or paper, as applicable, gathered at edge of crimp)		0.65%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22 05:20Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46246F(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
Cont'd	Charge, Demolition, Assembly	3	3	8797113/8885245/8885249/ 9287850, as applicable
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
206	Disc or tape improperly assembled or missing		0.65%	3.3	Visual
207	Protective coating inadequate, improperly applied or missing		0.65%	3.3	Visual
208	Color code stripe incorrect or missing		0.65%	3.3	Visual
209	Marking incorrect, illegible, incomplete or missing		0.65%	3.3	Visual
210	Label peeling or missing (where applicable)		0.65%	3.3	Visual
Minor					
201	Poor workmanship		1.0%	3.5	Visual

NOTES:

Source: https://assistdocs.mil — Downloaded: 2026-02-27 05:20:07Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46246F(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Body (Alternate) (when applicable)	1 OF 1	9287848
			NEXT HIGHER ASSEMBLY 9287850

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Depth to bottom, max.		0.40%(a)	3.2	Gage
102	Inside diameter at base, min.		0.40%(a)	3.2	Gage
103	Inside diameter at open end, min.		0.40%(a)	3.2	Gage
104	Plastic workmanship poor		0.40%	3.5	Visual
Minor					
201	Length		0.65%(a)	3.2	Gage
202	Outside diameter at base end		0.65%(a)	3.2	Gage
203	Outside diameter at open end		0.65%(a)	3.2	Gage
204	Internal or external radius at base missing		0.65%(a)	3.2	Visual
205	Color incorrect		0.65%(a)	3.2	Visual
206	Poor workmanship (excl. 104 above)		1.0%	3.5	Visual

NOTES: (a) See 4.4.5 for alternate method of sampling.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T05:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46246F(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Cap (Alternate) (when applicable				9287849
					NEXT HIGHER ASSEMBLY 9287850
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter across rim, max.		0.40%(a)	3.2	Gage
102	Outside diameter across rim		0.40%(a)	3.2	Gage
103	Thickness of rim, min.		0.40%(a)	3.2	Gage
104	Outside diameter (felt side) (1.395)		0.40%(a)	3.2	Gage
105	Angle of rim		0.40%(a)	3.2	Gage
106	Pitch diameter of thread		0.40%(a)	3.2	Gage
107	Minor diameter of thread		0.40%(a)	3.2	Gage
108	Plastic workmanship poor		0.40%	3.5	Visual
Minor					
201	Smaller diameter between slot sides		0.65%(a)	3.2	Gage
202	Larger diameter between slot sides		0.65%(a)	3.2	Gage
203	Depth of slot (.150)		0.65%(a)	3.2	Gage
204	Total thickness of part		0.65%(a)	3.2	Gage
205	Largest outside diameter (slot side)		0.65%(a)	3.2	Gage
206	Color incorrect		0.65%(a)	3.2	Visual
207	Poor workmanship (excl. 108 above)		1.0%	3.5	Visual

NOTES: (a) See 4.4.5 for alternate method of sampling.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46246F(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Wood Packing Box (Unsealed)	1 OF 1	8797739 or 8799162
			NEXT HIGHER ASSEMBLY --

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Block assembly missing		0.40%	3.3	Visual
102	Block assembly incorrectly positioned (Detonator hole in downward position)		0.40%	3.3	Visual
103	Priming adapter bag missing		0.40%	3.3	Visual
104	Instruction sheet missing		0.40%	3.3	Visual
105	Pack not tight		0.40%	3.3	Visual
106	Marking instructions on bag incorrect, illegible or missing		0.40%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-02-22 10:52 CST
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46246F(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Wood Packing Box (Sealed)				8797739 or 8799162
					NEXT HIGHER ASSEMBLY
					--
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Strapping or hardware missing, broken or loose		0.40%	3.3	Visual/Manual
102	Box damaged to extent that contents are exposed or liable to become exposed		0.40%	3.3	Visual
103	Protruding nail		0.40%	3.3	Visual
Minor					
201	Contents loose (when box is tilted)		0.65%	3.3	Manual
202	Hardware or strapping improperly assembled or engaged		0.65%	3.3	Visual
203	Car seal missing, unsealed or improperly positioned		0.65%	3.3	Visual
204	Marking misleading or unidentifiable		0.65%	3.3	Visual

NOTES:

DRSAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First article and Quality Conformance Inspection tables.

4.4.4 Submission of product. At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all the quality assurance provisions specified within this specification.
b. Number of units of product inspected.
c. Results obtained for all inspections performed.
d. Drawing, specification number and date, together with an identification and date of changes.
e. Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.
f. Number of items in the lot.
g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.4.5 Dimensional control of molded parts. In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, and after a curing time for the parts has been approved (See Note), a sample of three (3) parts (as molded) from each cavity may be dimensionally inspected to qualify a new or reworked cavity for use in production or as a control of each cavity during production.

The inspection of the parts shall be performed only when the curing time for the parts has been reached. The inspection for control of each cavity during production shall be performed on the above quantities from each cavity after production of each 5000 parts or at the end of each shift, providing the number of parts produced during that shift is less than 5000 parts. Of the three (3) samples, one (1) sample shall be the last part produced. Parts that fail to comply with dimensional requirements after dimensional stability has been attained shall be classed defective.

If any defective parts are found during qualification of the cavity, the cavity producing the defective part will not be used in production. If any defective parts are found when inspection is

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

performed for control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for corrective action.

All cavities formerly removed from production because of some fault may, after reworking, be returned to production providing they pass the qualification test as above. The contractor may request a change of inspection frequency providing he presents objective evidence to substantiate the request to the Contracting Officer.

NOTE: Curing time shall be established by dimensionally checking ten (10) parts from each cavity at periodic intervals (e.g., every 30 min, 60 min, etc.), until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until dimensional stability is attained. The inspection data used in determining the curing time shall be sent to U.S. Army Armament Research and Development Command (ARRADCOM), Dover, NJ 07801, ATTN: DRDAR-QAT-M. If there is a change in material, cycle time, or if a cavity is reworked, or a new cavity is used, a new curing time shall be established and approved.

4.4.6 Inspection equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1, and the test method paragraph (See 4.5). The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.2 herein.

WARNING. This specification covers sampling and testing of explosive materials which are potentially hazardous to personnel. Accordingly, it is emphasized that all applicable safety rules, regulations and procedures must be followed in handling and processing these materials.

4.5 Methods of inspection.

4.5.1 Specific gravity of charge. The specific gravity of the explosive charge shall be determined as follows: All weight determinations shall be made on a suitable laboratory balance accurate to 0.1 gram. The pellet or pellets (as applicable) shall be removed from the container and weighed in air. The pellet or individual pellets shall be coated lightly with paraffin. The pellet or pellets shall be reweighed in air. The pellet shall be suspended (in case there is more than one pellet per charge, each individual pellet shall be suspended and the weights shall be added) from the balance by a fine thread, and weighed while submerged in water ascertaining that the hole for the blasting cap is completely filled with water. The temperature of the water shall be noted, and maintained within 1 degree celsius during the determination. The specific gravity shall be calculated as follows to determine

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

compliance with the specific gravity requirement specified on the drawing.

$$D = \frac{0.9\ dm}{m-0.1n-0.9w}$$

Where:
D = specific gravity of the TNT charge.
m = weight of the TNT pellet, or pellets, in air.
n = weight of coated TNT pellet, or pellets, in air.
w = weight of coated TNT pellet, or pellets, in water.
d = specific gravity of water at the temperature used relative to water at 4 degrees Celsius.

4.5.2 Pull test of crimped ends. The assembly shall be tested using applicable test equipment and the specified force applied to both ends in a direction so as to tend to separate the ends from the body.

4.5.3 Pull test of heat sealed cap. The assembly shall be tested using applicable test equipment which holds the body, and applies the specified force in a direction so as to pull the cap from the body.

5. PACKAGING

5.1 Preservation - packaging. (Not applicable)

5.2 Packing.

5.2.1 Level A. The demolition assemblies shall be packed in accordance with Dwg. 8797739 or 8799162, as applicable.

5.2.2 Level B. Packing shall be as specified in Level A.

5.2.3 Level C. Packing shall be as specified in Level A.

5.3 Marking. Marking shall be in accordance with Dwg. 8797739 or 8799162, as applicable.

5.4 Shipping. When components from more than one lot are shipped at one time, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Ordering data. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

6.2 Submission of inspection equipment designs for approval. (See MIL-A-48078). Equipment designs shall be submitted as required to: Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAT-I, Dover, New Jersey, 07801. Request letter of submittal should state contractor, contract number, specification number, item nomenclature, and classification of defects and tests paragraph number.

6.3 Data cards. (See MIL-A-48078). Distribution of data cards shall include the following: Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAT-M, Dover, New Jersey 07801.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARRADCOM.

6.5 International standardization agreement. Certain portions of this specification are the subject of international standardization agreement (STANAG No. 2818). When amendment, revision, or cancellation of this specification is proposed which will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A251)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARMAMENT R & D COMMAND
ATTN: DRDAR-QAT-M
DOVER, NEW JERSEY 07801

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-46246F (AR)	Charges, Demolition, TNT, Block, ¼ Pound, ½ Pound, and 1 Pound

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2025-10-22T05:20Z
Check the source to verify that this is the current version before use.