INCH-POUND

MIL-DTL-46246G
17 April 2024
SUPERSEDING
MIL-C-46246F
18 March 1983

DETAIL SPECIFICATION

CHARGES, DEMOLITION, TNT, BLOCK ¼ POUND, ½ POUND, AND 1 POUND, LOAD, ASSEMBLE, AND PACK

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements and applicable tests needed for the manufacture and acceptance of Charges, Demolition, TNT, Block, ¼ Pound (LB), ½ Pound, and 1 Pound.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3, 4 and 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4 and 5 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in solicitation or contract.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-1168 - Ammunition Lot Numbering and Ammunition Data Card

Comments, suggestions, or questions on this document should be addressed to: U.S. Army DEVCOM Armaments Center: FCDD-ACE-QSA, Picatinny Arsenal, New Jersey 07806-5000 or emailed to usarmy.pica.devcom-ac.list.ardec-stdzn-branch@army.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 1375

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

MIL-STD-1916 - DoD Preferred Methods for Acceptance of Product

(Copies of these documents are available online at https://quicksearch.dla.mil/.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

U.S. ARMY DEVCOM ARMAMENTS CENTER DRAWINGS

8797113	-	Charge, Demolition, ¼ Pound Block (TNT), Assembly and Marking
8797114	-	Body Assembly
8797115	-	Charge
8797116	-	Body
8797117	-	End, Adapter
8797118	-	End
8797119	-	Disc
8797739	-	Packing and Marking for Charge, Demolition Block, ¼ Pound, (TNT) w/Priming Adapters M1A5
8799162	-	Box, Packing, Ammunition, for Charge, Demolition Block, 1 Pound or ½ Pound (TNT) w/Priming Adapters M1A5
8885245	-	Charge Demolition: Block (TNT) ½ LB Assembly
8885248	-	Charge ½ Pound Block
8885249	-	Charge Demolition: Block (TNT) 1 LB Assembly
8885250	-	Body Assembly
8885251	-	Body
8885252	-	Charge 1 Pound Block
8885253	-	Disc
8885255	-	End Plate
8885256	-	Adapter, End
9287848	-	Body (Alternate)
9287849	-	Cap (Alternate)
9287850	-	Charge, Demolition, ¼ Pound Block (TNT) (Alternate Design)
13026911	-	Body (Alternative Design)
13026912	-	Cap (Alternative Design)
13027346	-	Charge Demolition Block (TNT) 1 LB Assembly (Plastic)
13027347	-	Charge Demolition Block (TNT) 1 LB Marking (Plastic)
13083918	-	Charge Demolition Block (TNT) ½ LB Marking (Plastic)
13101005	-	Charge Demolition Block (TNT) ½ LB Assembly (Plastic)

(Copies of these drawings may be requested via e-mail at usarmy.pica.devcom-ac.list.drawing-request-help-desk@army.mil)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

U.S. ARMY DEFENSE AMMUNITION CENTER (DAC) DRAWINGS

19-48-4116/120	-	Charge, Demolition, Block, Packed Various Quantities Per Wooden Box, Unitized 24 Boxes Per 35" X 45 ½" Pallet; Approx Box Size 22 ½"L X 11 ¼"W X 9 5/8"H

(Copies of these documents may be requested online at https://www.dau.edu/cop/ammo/page/AMC-Drawings.)

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Required inspections.

3.1.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.2.

3.1.2 Conformance inspection. A sample shall be subjected to conformance inspection in accordance with 4.3.

3.2 TNT demolition charge block. The TNT demolition charge block and all materials and parts used therein shall comply with all requirements specified on the applicable drawings (Dwgs.) in accordance with Table I.

TABLE I. Demolition charge block requirements.

Configuration	Charge block, materials and parts	Specific gravity	Pull force resistance		
			Crimped ends	Heat sealed cap	Snap end cap
¼ Pound Block	8797113 or 9287850	8797115	8797113 or 8797114	9287850	
½ Pound Block	8885245 or 13101005	8885248	8885245 or 8885250		13101005
1 Pound Block	8885249 or 13027346	8885252	8885249 or 8885250		13027346

3.3 Specific gravity. The specific gravity of the charge shall be in accordance with all requirements specified on the applicable drawings in accordance with Table I.

3.4 Pull force resistance.

3.4.1 Pull force of crimped ends. The pull force resistance of crimped ends shall be in accordance with all requirements specified on the applicable drawings in accordance with Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

3.4.2 Pull force of heat sealed cap. The pull force resistance of heat sealed cap shall be in accordance with all requirements specified on the applicable drawings in accordance with Table I.

3.4.3 Pull force of snap end cap. The pull force resistance of snap end cap shall be in accordance with all requirements specified on the applicable drawings in accordance with Table I.

3.5 Ammunition lot number. Ammunition lot numbers shall be assigned in accordance with MIL-STD-1168.

3.6 Workmanship. All parts and assemblies shall be free of burrs, chips, sharp edges, cracks, grazes, unblended radii, porosity, warpage, burn marks, checks, sinks, chipped edges, blisters, bubbles, excess flash, dirt, grease, rust, and other foreign material. Charges shall be free of breaks, cracks, and other defects. Painted surfaces shall be free of chips and scratches, and colors shall be uniform. The cleaning method shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agents. All required markings shall be neat, separated and sharply defined.

4. VERIFICATION

TABLE II. Requirements/verification cross reference matrix.

Methods of Verification 1 – Analysis 2 – Demonstration 3 – Examination 4 – Test						Classes of Verification A – First Article B – Conformance		
Section 3 and 5 Requirements	Description	Verification Method				Verification Class		Section 4 Verification
		1	2	3	4	A	B	
3.1.1	First article	X		X	X	X		4.2
3.1.2	Conformance inspection	X		X	X		X	4.3
3.2	TNT demolition charge block	X			X	X	X	4.3.2
3.3	Specific gravity				X	X	X	4.5.2
3.4.1	Pull force of crimped ends				X	X	X	4.5.3
3.4.2	Pull force of heat sealed cap				X	X	X	4.5.4
3.4.3	Pull force of snap end cap				X	X	X	4.5.5
3.5	Ammunition lot number	X		X		X	X	4.5.6
3.6	Workmanship			X		X	X	4.5.7
5.1	Packaging			X		X	X	4.3.2.7- 4.3.2.8
5.2	Unitization			X			X	4.3.2.9

4.1 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2)

b. Conformance inspection (see 4.3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

4.2 First article inspection.

4.2.1 First article quantity. A sample shall be subjected to first article inspection in accordance with Table III as applicable.

4.2.2 Rejection. If any sample fails to comply with any of the applicable requirements the first article quantity shall be rejected.

Table III. First article acceptance tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

Charges, Demolition, TNT, Block, ¼ Pound Parts and Assembly			
Examination or Test	No. of Sample Units	Requirement Paragraph	Inspection Method
Charge (Dwg. 8797115)			
Inspect for all drawing requirements and workmanship	5 (see note 1)	3.2, 3.6	Gage/Visual
Test for specific gravity	5	3.3	4.5.2
Body (Dwg. 8797116)			
Inspect for all drawing requirements and workmanship	5 (see note 1)	3.2, 3.6	Gage/Visual
End, Adapter (Dwg. 8797117)			
Inspect for all drawing requirements and workmanship	5 (see note 1)	3.2, 3.6	Gage/Visual
End (Dwg. 8797118)			
Inspect for all drawing requirements and workmanship	5 (see note 1)	3.2, 3.6	Gage/Visual
Disc (Dwg. 8797119)			
Inspect for all drawing requirements and workmanship	5	3.2, 3.6	Gage/Visual
Body Assembly (Dwg. 8797114)			
Inspect for all drawing requirements and workmanship	5	3.2, 3.6	Gage/Visual
Pull force of crimped ends	5	3.4.1	4.5.3
Charge, Demolition, Block, ¼ Pound Block (TNT), Assembly and Marking (Dwg. 8797113)			
Examination for defects	40	3.2, 3.6	4.3.2.2, 4.5.7
Pull force of crimped ends	40	3.4.1	4.5.3
Packing and Marking for Charge, Demolition Block, ¼ Pound (TNT) w/Priming Adapters M1A5 (8797739)			
Inspect for all drawings requirements and workmanship	1 box	3.2, 3.6	4.3.2.8

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

Table III. First article acceptance tests. (Continued)

Charges, Demolition, TNT, Block, ¼ Pound (Alternate Design) Parts and Assembly			
Examination or Test	No. of Sample Units	Requirement Paragraph	Inspection Method
Charge (Dwg. 8797115)			
Inspect for all drawing requirements and workmanship	5 (see note 1)	3.2, 3.6	Gage/Visual
Test for specific gravity	5	3.3	4.5.2
Body (Alternate) (Dwg. 9287848)			
Inspect for all drawing requirements and workmanship	5 (see note 1, 2)	3.2, 3.6	Gage/Visual
Cap (Alternate) (Dwg. 9287849)			
Inspect for all drawing requirements and workmanship	5 (see note 1, 2)	3.2, 3.6	Gage/Visual
Charge, Demolition, ¼ Pound Block (TNT) (Alternate Design) (Dwg. 9287850)			
Examination for defects	40	3.2, 3.6	4.3.2.1, 4.3.2.2, 4.5.7
Pull force of heat sealed cap	40	3.4.2	4.5.5
Packing and Marking for Charge, Demolition Block, ¼ Pound (TNT) w/Priming Adapters M1A5 (8797739)			
Inspect for all drawings requirements and workmanship	1 box	3.2, 3.6	4.3.2.8

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

Table III. First article acceptance tests. (Continued)

Charges, Demolition, TNT, Block, ½ Pound Parts and Assembly			
Examination or Test	No. of Sample Units	Requirement Paragraph	Inspection Method
Charge ½ Pound Block (Dwg. 8885248)			
Inspect for all drawing requirements and workmanship	5 (see note 1)	3.2, 3.6	Gage/Visual
Test for specific gravity	5	3.3	4.5.2
Body (Dwg. 8885251)			
Inspect for all drawing requirements and workmanship	5 (see note 1)	3.2, 3.6	Gage/Visual
End Plate (Dwg. 8885255)			
Inspect for all drawing requirements and workmanship	5 (see note 1)	3.2, 3.6	Gage/Visual
Adapter, End (Dwg. 8885256)			
Inspect for all drawing requirements and workmanship	5 (see note 1)	3.2, 3.6	Gage/Visual
Disc (Dwg. 8885253)			
Inspect for all drawing requirements and workmanship	5	3.2, 3.6	Gage/Visual
Body Assembly (Dwg. 8885250)			
Inspect for all drawing requirements and workmanship	5	3.2, 3.6	Gage/Visual
Pull force of crimped ends	5	3.4.1	4.5.3
Charge Demolition: Block (TNT) ½ LB Assembly (Dwg. 8885245)			
Examination for defects	40	3.2, 3.6	4.3.2.2, 4.5.7
Pull force of crimped ends	40	3.4.1	4.5.3
Box, Packing, Ammunition, For Charge, Demolition Block, ½ Pound (TNT) w/ Priming Adapters M1A5 (8799162)			
Inspect for all drawings requirements and workmanship	1 box	3.2, 3.6	4.3.2.8

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

Table III. First article acceptance tests. (Continued)

Charges, Demolition, TNT, Block, ½ Pound (Plastic) Parts and Assembly			
Examination or Test	No. of Sample Units	Requirement Paragraph	Inspection Method
Charge ½ Pound Block (Dwg. 8885248)			
Inspect for all drawing requirements and workmanship	5 (see note 1)	3.2, 3.6	Gage/Visual
Test for specific gravity	5	3.3	4.5.2
Body (Alternative Design) (Dwg. 13026911)			
Inspect for all drawing requirements and workmanship	5 (see note 1, 2)	3.2, 3.6	Gage/Visual
Cap (Alternative Design) (Dwg. 13026912)			
Inspect for all drawing requirements and workmanship	5 (see note 1, 2)	3.2, 3.6	Gage/Visual
Charge Demolition Block (TNT) ½ LB Assembly (Plastic) (Dwg. 13101005)			
Examination for defects	40	3.2, 3.6	4.3.2.2, 4.5.7
Pull force of snap end cap	40	3.4.3	4.5.5
Charge Demolition Block (TNT) ½ LB Marking (Plastic) (Dwg. 13083918)			
Examination for defects	40	3.2, 3.6	Gage/Visual, 4.5.7
Box, Packing, Ammunition, For Charge, Demolition Block, ½ Pound (TNT) w/ Priming Adapters M1A5 (8799162)			
Inspect for all drawings requirements and workmanship	1 box	3.2, 3.6	4.3.2.8

Table III. First article acceptance tests. (Continued)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

Charges, Demolition, TNT, Block, 1 Pound Parts and Assembly			
Examination or Test	No. of Sample Units	Requirement Paragraph	Inspection Method
Charge 1 Pound Block (Dwg. 8885252)			
Inspect for all drawing requirements and workmanship	5 (see note 1)	3.2, 3.6	Gage/Visual
Test for specific gravity	5	3.3	4.5.2
Body (Dwg. 8885251)			
Inspect for all drawing requirements and workmanship	5 (see note 1)	3.2, 3.6	Gage/Visual
Adapter, End (Dwg. 8885256)			
Inspect for all drawing requirements and workmanship	5 (see note 1)	3.2, 3.6	Gage/Visual
Charge Demolition: Block (TNT) 1 LB Assembly (Dwg. 8885249)			
Examination for defects	40	3.2, 3.6	4.3.2.2, 4.5.7
Pull force of crimped ends	40	3.4.1	4.5.3
Box, Packing, Ammunition, For Charge, Demolition Block, 1 Pound (TNT) w/ Priming Adapters M1A5 (8799162)			
Inspect for all drawings requirements and workmanship	1 box	3.2, 3.6	4.3.2.8

Table III. First article acceptance tests. (Continued)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

Charges, Demolition, TNT, Block, 1 Pound (Plastic) Parts and Assembly			
Examination or Test	No. of Sample Units	Requirement Paragraph	Inspection Method
Charge 1 Pound Block (Dwg. 8885252)			
Inspect for all drawing requirements and workmanship	5 (see note 1)	3.2, 3.6	Gage/Visual
Test for specific gravity	5	3.3	4.5.2
Body (Alternative Design) (Dwg. 13026911)			
Inspect for all drawing requirements and workmanship	5 (see note 1, 2)	3.2, 3.6	Gage/Visual
Cap (Alternative Design) (Dwg. 13026912)			
Inspect for all drawing requirements and workmanship	5 (see note 1, 2)	3.2, 3.6	Gage/Visual
Charge Demolition Block (TNT) 1 LB Assembly (Plastic) (Dwg. 13027346)			
Examination for defects	40	3.2, 3.6	4.3.2.2, 4.5.7
Pull force of snap end cap	40	3.4.3	4.5.5
Charge Demolition Block (TNT) 1 LB Marking (Plastic) (Dwg. 13027347)			
Examination for defects	40	3.2, 3.6	Gage/Visual, 4.5.7
Box, Packing, Ammunition, For Charge, Demolition Block, 1 Pound (TNT) w/ Priming Adapters M1A5 (8799162)			
Inspect for all drawings requirements and workmanship	1 box	3.2, 3.6	4.3.2.8
Notes: 1. A minimum of 5 (five) samples shall be inspected from each mold cavity configuration from each press. 2. Dimensional and visual inspections of injected molded parts shall be performed on cured parts (see 4.4).			

4.3 Conformance inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

4.3.1 Lot formation. Lot formation shall be in accordance with the lot formation requirements of MIL-STD-1916. Each lot shall contain TNT charges from not more than two (2) lots from one manufacturer. Each lot of TNT charges shall be comprised from not more than one lot of TNT material from one manufacturer. TNT demolition blocks delivered to the Government shall have a lot number assigned in accordance with MIL-STD-1168. In addition, inspection lots of TNT charges shall contain:

a. Parts or part assemblies from not greater than one interfix from one manufacturer.

b. TNT from not greater than one lot of TNT material from one manufacturer.

4.3.1.1 Cavity identification (plastic parts). Identification of cavities shall be maintained and components shall be grouped and identified until all inspections have been completed, as applicable for alternate plastic design.

4.3.2 Inspection requirements by classification of characteristics.

a. For the conformance inspection paragraph 4.3.2.1 thru 4.3.2.8, the definitions of critical, major, and minor defects are provided in paragraph “Definitions” of MIL-STD-1916 (Formation and identification of lots and batches).

b. The acceptance criteria for sampling inspection shall be in accordance with the levels provided in conformance examination/test paragraph and MIL-STD-1916.

c. Dimensional and visual inspections of injected molded parts shall be performed on cured parts (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

4.3.2.1	Assembly (Prior to Assembling End Adapter or Cap, as applicable).		Drawing Number 8797115, 8885248, 8885252, 9287850, as applicable	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major				
101	Depth to bottom of fuze well, minimum (min.)	VL-IV	3.2	Gage
102	Diameter of fuze well, min. (Dwg. 8797115, 8885252, or 9287850)	VL-IV	3.2	Gage
103	Diameter of bottom portion of fuze well, min. (Dwg. 8885248)	VL-IV	3.2	Gage
104	Diameter of fuze well portion below counterbore, min.	VL-IV	3.2	Gage
105	Depth of fuze well counterbore, min.	VL-IV	3.2	Gage
106	Diameter of fuze well counterbore	VL-IV	3.2	Gage
107	Charge cracked or other evidence of damage	VL-IV	3.2	Visual
108	Foreign matter in fuze well	VL-IV	3.2	Visual
109	Binder – lubricant content of charge	Once per lot	3.2	4.5.1
110	Specific gravity of charge	3 (see note 1)	3.3	4.5.2
Minor				
201	Evidence of poor workmanship	VL-II	3.6	4.5.7

Notes:
1. Three (3) demolition charges from each mold cavity configuration from each press (Dwg. 8797115, 8885248, or 8885252, as applicable), shall be selected from each lot for this test. If the specific gravity of any sample fails to comply with the specified drawing requirement, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

4.3.2.2	Charge, Demolition, Assembly.		Drawing Number 8797113, 8885245, 8885249, 9287850, 13027346, 13027347, 13083918, 13101005 as applicable	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major				
101	Pull force of crimped ends (Dwg. 8797113, 8885245, or 8885249)	80 (see note 1)	3.4.1	4.5.3
102	Pull force of heat sealed cap (Dwg. 9287850)	80 (see note 1)	3.4.2	4.5.4
103	Pull force of snap end cap (Dwg. 13101005 or 13027346)	80 (see note 1)	3.4.3	4.5.5
104	Assembly damaged (body, end, or cup, cut, punctured, cracked, dented, wrinkled, or torn)	VL-IV	3.2	Visual
105	Adapter end or cap improperly assembled or missing	VL-IV	3.2	Visual
106	Charge missing	VL-IV	3.2	Visual
Minor				
201	Profile of end adapter helix	VL-II	3.2	Gage
202	Total length, maximum (max.)	VL-II	3.2	Gage
203	Diameter across end crimps, max. (Dwg. 8797113 or 9287850)	VL-II	3.2	Gage
204	Width across end or cap crimps, max. (Dwg. 8885245 or 8885249)	VL-II	3.2	Gage
205	Crimping of ends or cap improper (metal or paper, as applicable, gathered at edge of crimp)	VL-II	3.2	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

4.3.2.2	Charge, Demolition, Assembly. (Continued)		Drawing Number 8797113, 8885245, 8885249, 9287850, 13027346, 13027347, 13083918, 13101005 as applicable	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
206	Disc or tape improperly assembled or missing	VL-II	3.2	Visual
207	Protective coating inadequate, improperly applied or missing	VL-II	3.2	Visual
208	Color code stripe incorrect or missing	VL-II	3.2	Visual
209	Marking incorrect, illegible, incomplete, or missing	VL-II	3.2	Visual
210	Label peeling or missing (where applicable)	VL-II	3.2	Visual
211	Ammunition lot number	VL-II	3.5	4.5.6
212	Evidence of poor workmanship	VL-II	3.6	4.5.7

Notes:
1. Eighty (80) demolition charge assemblies shall be selected from each lot for this test. An assembly shall be classed defective and fail the test if the end shows any evidence of separation upon application of the minimum pull force. If any assembly fails the test, the lot shall be rejected, otherwise non-defective units may be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

4.3.2.3	Body (Alternate) (¼ LB TNT Block Alternate Design).		Drawing Number 9287848 as applicable	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major				
101	Depth to bottom, max.	VL-IV	3.2	Gage
102	Inside diameter at base, min.	VL-IV	3.2	Gage
103	Inside diameter at open end, min.	VL-IV	3.2	Gage
Minor				
201	Length	VL-II	3.2	Gage
202	Outside diameter at base end	VL-II	3.2	Gage
203	Outside diameter at open end	VL-II	3.2	Gage
204	Internal or external radius at base missing	VL-II	3.2	Visual
205	Color incorrect	VL-II	3.2	Visual
206	Poor workmanship	VL-II	3.6	4.5.7

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

4.3.2.4	Cap (Alternate) (¼ LB TNT Block Alternate Design).		Drawing Number 9287849 as applicable	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major				
101	Inside diameter across rim, max.	VL-IV	3.2	Gage
102	Outside diameter across rim	VL-IV	3.2	Gage
103	Thickness of rim, min.	VL-IV	3.2	Gage
104	Outside diameter (felt side) (1.395)	VL-IV	3.2	Gage
105	Angle of rim	VL-IV	3.2	Gage
106	Pitch diameter of thread	VL-IV	3.2	Gage
107	Minor diameter of thread	VL-IV	3.2	Gage
Minor				
201	Smaller diameter between slot sides	VL-II	3.2	Gage
202	Larger diameter between slot sides	VL-II	3.2	Gage
203	Depth of slot (0.150)	VL-II	3.2	Gage
204	Total thickness of part	VL-II	3.2	Gage
205	Largest outside diameter (slot side)	VL-II	3.2	Gage
206	Color incorrect	VL-II	3.2	Visual
207	Poor workmanship	VL-II	3.6	4.5.7

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

4.3.2.5	Body (Alternate Design) (1/2 LB and 1 LB TNT Block Plastic).		Drawing Number 13026911	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major				
101	Overall length	VL-IV	3.2	Gage
102	Slot location	VL-IV	3.2	Gage
103	Slot width	VL-IV	3.2	Gage
104	Location between slots	VL-IV	3.2	Gage
105	Length of slots	VL-IV	3.2	Gage
Minor				
201	Distance to slots from cap end	VL-II	3.2	Gage
202	Wall thickness	VL-II	3.2	Gage
203	Inside width	VL-II	3.2	Gage
204	Color incorrect	VL-II	3.2	Visual
205	Chamfer over slots missing	VL-II	3.2	Visual
206	Poor workmanship	VL-II	3.6	4.5.7

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

4.3.2.6	Cap (Alternate Design) (1/2 LB and 1 LB TNT Block Plastic).		Drawing Number 13026912	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major				
101	Pitch of thread	VL-IV	3.2	Gage
102	Outside diameter across rim	VL-IV	3.2	Gage
103	Inner overall width	VL-IV	3.2	Gage
104	Location of tabs	VL-IV	3.2	Gage
105	Length of tabs	VL-IV	3.2	Gage
106	Location between tabs	VL-IV	3.2	Gage
107	Width of tabs	VL-IV	3.2	Gage
108	Tab gap thickness	VL-IV	3.2	Gage
Minor				
201	Overall thickness	VL-II	3.2	Gage
202	Overall cap tab width	VL-II	3.2	Gage
203	Height of tab	VL-II	3.2	Gage
204	Color incorrect	VL-II	3.2	Visual
205	Rib thickness (section B-B)	VL-II	3.2	Visual
206	Poor workmanship	VL-II	3.6	4.5.7

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

4.3.2.7	Wood packing box (Unsealed).		Drawing Number 8797739 or 8799162	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major				
101	Block assembly missing	VL-II	5.1	Visual/ Scale
102	Block assembly incorrectly positioned (detonator hole in downward position)	VL-II	5.1	Visual
103	Incorrect number of priming adapters	VL-II	5.1	Visual
104	Priming adapter bag missing	VL-II	5.1	Visual
105	Instruction sheet missing	VL-II	5.1	Visual
106	Pack not tight	VL-II	5.1	Visual
107	Marking instruction in bag incorrect, illegible, or missing	VL-II	5.1	Visual
Minor				
201	Poor workmanship	VL-I	3.6	4.5.7

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

4.3.2.8	Wood Packing Box (Sealed).		Drawing Number 8797739 or 8799162	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major				
101	Strapping or hardware missing, broken or loose	VL-II	5.1	Visual/ Manual
102	Box damaged to extent that contents are exposed or liable to become exposed	VL-II	5.1	Visual
103	Protruding nail	VL-II	5.1	Visual
Minor				
201	Contents loose (when box is tilted)	VL-I	5.1	Manual
202	Hardware or strapping improperly assembled or engaged	VL-I	5.1	Visual
203	Metallic seal missing, unsealed, or improperly positioned	VL-I	5.1	Visual
204	Marking misleading or unidentifiable	VL-I	5.1	Visual
205	Workmanship	VL-I	3.6	4.5.7

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

4.3.2.9	Unitization.		Drawing Number 19-48-4116/120	
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method
Critical	None defined			
Major				
101	Wood preservative and heat treatment markings for the pallet missing, incorrect, illegible, or not in proper location	VL-II	5.2	Visual
102	Pallet load markings -including 2D bar codes- missing, incorrect, illegible, or not in proper location	VL-II	5.2	Visual
103	Filler assembly not built, treated, or marked correctly (if applicable)	VL-II	5.2	Visual
104	Boxes incorrectly oriented or positioned on pallet	VL-II	5.2	Visual
105	Strapping not applied correctly or incorrect type	VL-II	5.2	Visual
106	Unit load not tightly strapped or any strap loose	VL-II	5.2	Visual/ Manual
Minor				
201	Contents loose	VL-I	5.2	Manual
202	Workmanship	VL-I	3.6	4.5.7

4.4 Molded parts.

4.4.1 Curing time. The dimensional and visual inspections of molded parts shall be performed after the molded part has been maintained at 73 ± 5 degrees Fahrenheit for not less than 24 hours after removal from the mold (see 6.5).

4.5 Methods of inspection.

4.5.1 Binder. Verify by examination of objective evidence that the binder and binder content are in accordance with the requirements of Drawings 8797113, 885245, 8885249, 9287850, 13101005, 13027346 as applicable.

4.5.2 Specific gravity. This is a destructive test; samples cannot be returned to the lot. The specific gravity of the TNT explosive charge shall be determined as follows.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

a. All weight determinations shall be made on a suitable laboratory balance accurate to 0.1 gram.

b. The pellet or pellets (as applicable) shall be removed from the container and weighed in air.

c. The pellet or pellets shall be coated lightly with paraffin and shall be reweighed in air.

d. The pellets shall be suspended (in case there is more than one pellet per charge, each individual pellet shall be suspended and the weights shall be added) from the balance by a fine thread, and weighed while submerged in water, ascertaining that the hole for the blasting cap is completely filled with water.

e. The temperature of the water shall be recorded and maintained within 1 degree Celsius during the determination.

f. The specific gravity shall be calculated as follows to determine compliance with the specific gravity requirement specified on the drawing.

$$\text{Specific gravity} = \frac{0.9d*m}{m - 0.1n - 0.9w}$$

Where:

m = weight of the TNT pellet(s) in air
n = weight of coated TNT pellet(s) in air
w = weight of coated TNT pellet(s) in water
d = specific gravity of water at the temperature used relative to water at 4 degrees Celsius (see Table IV)

Table IV. Water specific gravity versus temperature at atmospheric pressure.

Temperature [°C]	Specific gravity at 4 °C
4	1.00000
10	0.99973
15	0.99913
20	0.99823
25	0.99707
30	0.99567
35	0.9941
40	0.9922

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

4.5.3 Pull force of crimped ends. The assembly shall be tested using applicable test equipment and the specified force applied to both ends in an axial direction so as to tend to separate the end from the body.

4.5.4 Pull force of heat sealed cap. The assembly shall be tested using applicable test equipment which hold the body and applies the specified force in an axial direction so as to pull the cap from the body.

4.5.5 Pull force of snap end cap. The assembly shall be tested using applicable test equipment and the specified force applied in an axial direction so as to tend to separate the end from the body.

4.5.6 Ammunition lot number. Visually verify that an ammunition lot number has been assigned to each lot as described in MIL-STD-1168.

4.5.7 Workmanship. Visually verify for compliance with workmanship requirements.

5. PACKAGING

5.1 Packaging. The materials, components, and assemblies shall comply with all the requirements specified on Dwg. 8797739 or 8799162 as applicable.

5.2 Unitization. The unitization materials, components, and assemblies shall comply with all the requirements specified on Dwg. 19-48-4116/120 or 19-48-4116-120B as applicable.

6. NOTES

(This section contains information of general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. The ¼ pound TNT demolition charge block is primarily used for training purposes. The ½ pound and 1 pound TNT demolition charge blocks are used for all types of demolition work.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this detail specification.

b. Requirements for Acceptance Inspection Equipment (AIE) designs (see 6.3).

c. First article requirements.

d. Certificate of conformance for each lot of product.

6.3 Submissions for approval.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

6.3.1 Inspection equipment designs. Equipment designs should be submitted to the technical agency (see 6.4) as required per the Contract Data Requirements Lists (DD Form 1423).

6.3.2 Equivalent test methods. The test methods given in this specification are the official methods to be used. The contractor may request using other methods providing that the proposed method is equivalent (accuracy and precision) to the method given in the specification. Prior approval of the contracting officer is required for use of equivalent test methods. A description of the proposed method should be submitted through the contracting officer to the technical agency (see 6.4). This description should include but not be limited to the procedures used, the accuracy and precision of the method, test data to demonstrate the accuracy and precision and drawings of any special equipment required.

6.3.3 Process equipment designs. Copies of the process equipment designs should be submitted to the technical agency (see 6.4).

6.4 Technical agency. DEVCOM AC is the technical agency that is responsible for the preparation and revision of the specification. All correspondence to the Technical Agency should be submitted through the contracting officer to: DEVCOM AC, ATTN: FCDD-ACE-QEE, Picatinny Arsenal, NJ 07806-5000.

6.5 Establishment of alternate curing time. In place of the normal curing time in 4.4.1 and with the approval of the Technical Agency (6.4.1), a curing time can be established by dimensionally checking ten (10) parts from each cavity at periodic interval (e.g., every 30 minutes, 60 minutes, etc.), until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until dimensional stability is attained. If there is a change in material, cycle time, or if a cavity is reworked, or a new cavity is used, a new curing time should be established and approved.

6.6 Changes incorporated. Changes to this specification can be found in the engineering change proposal (ECP) number R23Q2030.

6.7 Subject term (keyword) listing.

Pressed explosive

6.8 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

CONCLUDING MATERIAL

Custodians:
Army-AR
Navy - OS
Air Force – 11

Preparing Activity:
Army- AR
Project (1375-2024-009)

Review Activities:
Army –TE

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

Navy – SH
Air Force – 70
Civil agency:
GSA-FAS

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.