MIL–R–46259A(MU)
10 OCTOBER 1962
SUPERSEDING
MIL–M–46259(ORD)
16 AUGUST 1960

MILITARY SPECIFICATION

ROCKET MOTOR, M3A2

PARTS FOR

1. SCOPE

1.1 This specification covers the metal parts for one type of rocket motor designated as Rocket Motor, M3A2 (see 6.4).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL–A–2550	—Ammunition and Special Weapons, General Specification For.
MIL–I–6868	—Inspection Process, Magnetic Particles.
MIL–M–11472	—Magnetic Particle Inspection; Process for Ferromagnetic Material.
MIL–I–45208	—Inspection Requirements, General Specifications For.
MIL–I–45607	—Inspection Equipment, Supply and Maintenance of.

STANDARDS

FEDERAL

FED–STD–151	—Metals, Test Methods

MILITARY

FED–STD–105	—Sampling Procedures and Tables for Inspection by Attributes.
MIL–STD–109	—Inspection Terms and Definitions.
MIL–STD–129	—Marking for Shipment and Storage.

DRAWINGS

ORDNANCE CORPS

8799794	—Motor, Rocket, M3A2, Metal Parts Assembly.
8835922	—Box, Packing, Ammunition, for Rocket Motor, M3, M3A1, and M3A2 Assembly Details and Packing.

PUBLICATIONS

ORDNANCE CORPS

ORD–M608–11	—Procedures and Tables for Continuous Sampling by Attributes.
IEL–8802332	—Index of Inspection Equipment Lists.

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurment functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 **Material.** Materials shall be in accord-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:22Z
Check the source to verify that this is the current version before use.

ance with applicable drawings and specifications.

3.2 Parts. The parts shall comply with all requirements specified in applicable drawings and specifications.

3.3 Rear trap assembly. The rear trap assembly shall withstand a minimum (min.) load of 2500 pounds when tested as specified in 4.4.1.

3.4 Electrical requirements.

3.4.1 *Insulation resistance.* The total insulation resistance of the igniter plug assembly shall not be less than 200 megohms when tested as specified in 4.4.2.

3.4.2 *Electrical resistance.* The total electrical resistance of the igniter plug assembly shall be not greater than 0.2 ohms when tested as specified in 4.4.3.

3.5 Surface requirements. There shall be no evidence of cracks in the nozzle or body when tested as specified in 4.4.6.

3.6 Workmanship. The item of shipment, its components and materials shall be free from dirt, chips, grease, corrosion and other foreign material. There shall be no cracks, scratches, burrs, dents, gouges, holes, porous areas, distortions, or other undesirable characteristics which would, in any way, detract from the useability of the product for its intended purpose. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents. The painting and coating on all components shall be restored when such paintings and coatings have been marred or obliterated.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions. The supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL–STD–190 in order to define terms used herein. The provisions of Specification MIL–A–2550 shall apply.

4.1.1 *Contractor quality assurance system.* The contractor shall provide and maintain an effective quality assurance system in compliance with the requirements of Specification MIL–I–45208.

4.1.2 *Submission of product.* At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

(a) A statement that the lot complies with all quality assurance provisions of the approved current written description of the system.

(b) Number of units of product inspected.

(c) Results obtained for all inspection performed.

(d) Drawing, specification number and date, together with an identification and date of changes.

(e) Certificates of analysis on all material procured directly by the contractor when such material is controlled by Government specifications referenced in any of the contractual documents.

(f) Number of items in the lot.

(g) Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:22Z
Check the source to verify that this is the current version before use.

with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.3 *Government verification.* Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be in accordance with Specification MIL–I–45208 and will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 Initial production inspection.

4.2.1 *Submission.* Prior to normal production the contractor shall submit an initial production sample consisting of twenty-five consecutively produced inert assemblies and a complete set of parts (i.e. five each of every individual component and every subassembly, excluding the body and nozzle) which have been produced by the production process which the contractor will use in fulfilling the contract, to a Government-approved facility designated by the contracting officer. All parts and material shall be obtained from the same source of supply as will be used in regular production. The initial production sample shall be accompanied by certificates of analyses for all materials. A sample shall also be submitted whenever a change occurs in manufacturing process, material used, drawing, specification, or source of supply such as to significantly affect product uniformity as determined by the Government.

4.2.2 *Inspections to be performed.* Each assembly and component shall be inspected by the Government for all the inspections specified in 4.3 and 4.4 of this specification and for all additional requirements of the applicable drawings.

4.2.3 *Rejection.* If any assembly or component fails to comply with the applicable requirements, the initial production sample shall be rejected. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit new supplemental quantities until such time as an acceptable sample is submitted, or until otherwise directed by the contracting officer.

4.3 Inspection provisions.

4.3.1 *Lot formation.* A lot shall consist of parts assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification, and same specification revision. Drawing, specification, and process changes not affecting safety, performance, or fit, as determined by the Government, shall not necessitate changing the lot number.

4.3.2 *Examination.* Sampling plans and procedures for the following classifications of defects shall be in accordance with Standard MIL–STD–105 except that inspection for critical defects, when listed, shall be 100 percent. Continuous sampling plans in accordance with Handbook ORD–M608–11 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to the individual characteristics listed using an AQL of 0.25 percent for each major defect and an AQL of 0.40 percent for each minor defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 *Front trap assembly (prior to painting) (see dwg. 8799797 covering a detail of dwg. 8799794).*

Categories	*Defects*	*Method of Inspection*	*Code No. (see 6.3)*
Critical: None defined.			
Major:	AQL 0.25 percent		
101.	Rod missing or loose	Visual-Manual	01001

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:22Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No. (see 6.3)
Minor:	AQL 4.0 percent		
201.	Total length to end of rod, maximum (max.)	Gage	01002
202.	Width of leg, min.	Gage	01003
203.	Thickness of trap, min.	Gage	01004
204.	Outside diameter of ring, maximum (max.)	Gage	01005
205.	Diameter of hub, min.	Gage	01006
206.	Diameter across legs, max.	Gage	01007
207.	Diameter of rod	Gage	01008
208.	Seated end of rod flush	Gage	01009
209.	Bevel missing from outer side of legs	Visual	01010
210.	Radii missing	Visual	01011
211.	Evidence of poor workmanship (see 3.6)	Visual	01012

4.3.2.2 *Front trap assembly (see dwg. 8799797 covering a detail of dwg. 8799794).*

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major: None defined.			
Minor:	AQL 1.5 percent		
201.	Bare spot other than slight scratches	Visual	02001
202.	Lacquer coating incomplete	Visual	02002
203.	Evidence of poor workmanship (see 3.6)	Visual	02003

4.3.2.3 *Rear trap assembly, prior to painting (see dwg. 8799799 covering a detail of dwg. 8799794).*

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.25 percent		
101.	Rod missing or loose	Visual	03001
Minor:	AQL 4.0 percent		
201.	Distance from propellant seating surface to end of rod, max.	Gage	03002
202.	Outside diameter of trap, max.	Gage	03003
203.	Thickness of leg at nozzle seating surface	Gage	03004
204.	Width of leg, min.	Gage	03005
205.	Diameter of center hole	Gage	03006
206.	Diameter of hub	Gage	03007
207.	Location of rods	Gage	03008
208.	Diameter of rod	Gage	03009
209.	Seated end of rod flush	Gage	03010
210.	Radii missing	Visual	03011
211.	Evidence of poor workmanship (see 3.6)	Visual	03012

4.3.2.4 *Rear trap assembly (see dwg. 8799799 covering a detail of dwg. 8799794).*

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major: None defined.			
Minor:	AQL 1.5 percent		
201.	Bare spot other than slight scratches	Visual	04001
202.	Pool or blob of paint on seating surfaces	Visual	04002
203.	Lacquer coating incomplete	Visual	04003
204.	Evidence of poor workmanship (see 3.6)	Visual	04004

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:22Z
Check the source to verify that this is the current version before use.

4.3.2.5 *Igniter plug assembly (see dwg. 8799802 covering a detail of dwg. 8799794).*

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.25 percent		
101.	Bare wire	Visual	05001
102.	Terminal nut loose or missing	Visual-Manual	05002
Minor:	AQL 2.5 percent		
201.	Diameter of nozzle closure at closed end, max.	Gage	05003
202.	Diameter of nozzle closure at open end, min.	Gage	05004
203.	Thickness of nozzle closure at terminal inserts	Gage	05005
204.	Height of tapered portion of nozzle closure, min.	Gage	05006
205.	Shorting wire missing or loose	Visual-Manual	05007
206.	Evidence of poor workmanship (see 3.6)	Visual	05008

4.3.2.6 *Nozzle (after hydrostatic test, prior to painting) (see dwg. 8799796 covering a detail dwg. 8799794).*

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 1.0 percent		
101.	Pitch diameter of thread	Gage	06001
102.	Concentricity of throat with pitch diameter of thread	Gage	06002
103.	Outside diameter at throat	Gage	06003
104.	Inside diameter at throat	Gage	06004
105.	Diameter of shoulder at bottom of trap seat	Gage	06005
106.	Concentricity of shoulder at bottom of trap seat with pitch diameter of thread.	Gage	06006
107.	Wall thickness of curved portion between trap seat and throat, min.	Gage	06007
108.	Finish at throat improper	Visual	06008
Minor:	AQL 4.0 percent		
201.	Total length, max.	Gage	06009
202.	Minor diameter of thread, max.	Gage	06010
203.	Diameter of trap seat, min.	Gage	06011
204.	Depth to trap seat shoulder, min.	Gage	06012
205.	Depth to start of thread, max.	Gage	06013
206.	Depth to end of thread, min.	Gage	06014
207.	Diameter of thread counterbore, min.	Gage	06015
208.	Outside diameter, min.	Gage	06016
209.	Wall thickness at exhaust end, min.	Gage	06017
210.	Inside diameter at exhaust end	Gage	06018
211.	Length of flat in throat, max.	Gage	06019
212.	Radii missing	Visual	06020
213.	Evidence of poor workmanship (see 3.6)	Visual	06021

4.3.2.7 *Nozzle (see dwg. 8799796 covering a detail of dwg. 8799794).*

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Hydrostatic test stamp missing	Visual	07001
Major:	AQL 0.25 percent		
101.	Roughness on nozzle interior	Visual	07002
102.	Rust on nozzle interior	Visual	07003
Minor:	AQL 2.5 percent		
201.	Bare spot on interior	Visual	07004
202.	Lacquer missing on interior	Visual	07005
203.	Bare spot on exterior other than slight scratches	Visual	07006
204.	Corrosion preventative missing or incomplete on threads	Visual	07007
205.	Evidence of poor workmanship (see 3.6)	Visual	07008

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:22Z
Check the source to verify that this is the current version before use.

4.3.2.8 *Body (after hydrostatic test, prior to painting) (see dwg. 8799795 covering a detail of dwg. 8799794).*

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.65 percent		
101.	Concentricity of inside diameter with pitch diameter of thread	Gage	08001
102.	Pitch diameter of thread	Gage	08002
103.	Length of perfect full thread, min.	Gage	08003
104.	Diameter of unthreaded portion beyond thread, max.	Gage	08004
Minor:	AQL 4.0 percent		
201.	Inside diameter, min.	Gage	08005
202.	Major diameter of thread	Gage	08006
203.	Diameter of thread pilot	Gage	08007
204.	Location of trap slots	Gage	08008
205.	Depth of trap slot	Gage	08009
206.	Width of trap slot	Gage	08010
207.	Distance from trap slot to larger datum diameter	Gage	08011
208.	Spherical radius of head	Gage	08012
209.	Wall thickness of body, min.	Gage	08013
210.	Wall thickness of head	Gage	08014
211.	Evidence of poor workmanship (see 3.6)	Visual	08015

4.3.2.9 *Body (see dwg. 8799795 covering a detail of dwg. 8799794).*

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Hydrostatic test stamp missing	Visual	09001
Major: None defined.			
Minor:	AQL 2.5 percent		
201.	Bare spot on interior	Visual	09002
202.	Lacquer missing on interior	Visual	09003
203.	Bare spot on exterior other than slight scratches	Visual	09004
204.	Corrosion preventative missing or incomplete on threads	Visual	09005
205.	Evidence of poor workmanship (see 3.6)	Visual	09006

4.3.3 *Testing.*

4.3.3.1 *Load test of rear trap assembly (see 3.3) Critical defect.* This test shall be conducted 100 percent. Any assembly which fails to meet the applicable requirement shall be classed defective and shall be removed from the lot. The test shall be performed in accordance with 4.4.1 using equipment specified in 4.3.4. Code No. 04005

4.3.3.2 *Hydrostatic test of body (see dwg. 8799795) and hydrostatic test of nozzle (see dwg. 8799796) Critical defect.* This test shall be performed 100 percent. Any nozzle or body which fails to meet the applicable requirement shall be classed defective and shall be removed from the lot. The test shall be performed in accordance with 4.4.5 using equipment specified in 4.3.4. Code No. 10001

4.3.3.3 *Magnetic particle inspection of nozzle and body (see 3.5)—Major defect.* This test shall be performed 100 percent. Any nozzle or body which fails to meet the applicable requirements shall be classed defective and shall be removed from the lot. The test shall be performed in accordance with 4.4.6 using equipment specified in 4.3.4. Code No. 10002

4.3.3.4 *Insulation resistance (see 3.4.1)—Major defect.* This test shall be performed 100 percent. Any assembly which fails to meet the applicable requirement shall be classed defective and shall be removed from the lot. The test shall be performed as specified in 4.4.2 using equipment in 4.3.4. Code No. 05009

4.3.3.5 *Electrical resistance (see 3.4.2)—Major defect.* This test shall be performed

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:22Z
Check the source to verify that this is the current version before use.

100 percent. Any assembly which fails to comply with the requirement specified shall be classed defective and shall be removed from the lot. The test shall be performed as specified in 4.4.3 using equipment specified in 4.3.4. Code No. 05010

4.3.3.6 *Pull test of each connection of plug assembly (see dwg. 8799807)—Major defect.* The sampling plan for this test shall be in accordance with Standard MIL–STD–105 using code letter J and an AQL of 1.00 percent. Any assembly which fails to comply with the requirement specified on the applicable drawing shall be classed defective. The test shall be performed as specified in 4.4.4 using equipment specified in 4.3.4. Code No. 05011

4.3.3.7 *Yield strength and elongation (see dwg. 8799795)—Major defect.* A sample of ten (10) bodies shall be selected, at random, from each lot for this test. Test shall be conducted as specified in 4.4.7. Acceptance or rejection shall be made in accordance with Standard MIL–STD–105, Code letter E at an AQL of 1.0 percent. Code No. 08017

4.3.3.8 *Hardness test (see dwg. 8799796) —Major defect.* This test shall be conducted 100 percent as specified in 4.4.8. Any nozzle that fails to comply with the requirements on applicable drawing shall be classed defective and shall be removed from the lot. Code No. 06022

Caution: **Care shall be taken that defective nozzles are not returned to the original lot or mixed with any other lot.**

4.3.4 *Inspection equipment.* Index of Inspection Equipment Lists Number IEL 8802332 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment with the instructions in paragraph 6.2.

4.3.4.1 Supply and maintenance of the equipment listed on the IEL shall be in accordance with Specification MIL–I–45607.

4.4 Test methods and procedures.

4.4.1 *Load test of rear trap assembly.* A min. axial load of 2500 pounds shall be applied to the center propellant grain support. Observation shall be made for evidence of permanent distortion in excess of drawing dimensions.

4.4.2 *Insulation resistance.* Without the shorting wire in place, the insulation resistance shall be measured across the terminal inserts of the igniter plug assembly. Observation shall be made for conformance to 3.4.1.

4.4.3 *Electrical resistance.* With the shorting wire in place, the resistance shall be measured across the terminal inserts. Observation shall be made for conformance to 3.4.2.

4.4.4 *Pull test of each connection of plug assembly.* Each connection must withstand a minimum pull test of 10 pounds specified on the applicable drawing.

4.4.5 *Hydrostatic test.*

4.4.5.1 *Body.* Each unpainted body shall be assembled in a test fixture, and shall be subjected to a hydrostatic pressure of not less than 4500 pounds per square inch gage (p.s.i.g.) specified on the applicable drawing for a minimum of five seconds. Water or oil having a viscosity which does not exceed 200 Saybolt Universal Seconds at 100 degrees Fahrenheit (degrees F.) shall be used in this test. (If water is used, extreme care should be taken to insure that the body is thoroughly dried after test to prevent rust). Observation shall be made for leakage or deformation (including threads) in excess of the drawing requirements. Code No. 08017

4.4.5.2 *Nozzle.* Each unpainted nozzle shall be assembled in a test fixture and shall be subjected to a hydrostatic pressure of not less than 4500 p.s.i.g. specified on the applicable drawing for a minimum of five seconds. Water or oil having a viscosity which does not exceed 200 Saybolt Universal Seconds at 100 degrees F. shall be used in this test. (If water is used, extreme care should be taken to prevent rust). Observation shall be made for leakage or deformation (including threads) in excess of the drawing requirements. Code No. 06023

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:22Z
Check the source to verify that this is the current version before use.

4.4.6 *Magnetic particle inspection of nozzle and body.* The nozzle and body, after successful completion of hydrostatic test, shall be magnetic particle inspected by continuous wet method as specified in MIL–M–11472. The equipment shall magnetize the shell circularly by passage of 2,000 plus or minus 200 amperes A.C. Inspection process shall be in accordance with MIL–I–6868 and methods shall be fluorescent, continuous, and circular. Observations shall be made for compliance with requirements as specified in 3.5.

4.4.7 *Yield strength and elongation.* This test shall be in accordance with Federal Test Method Standard 151 Method 211.1. The specimens shall consist of two type F2 test pieces. The specimen shall be prepared longitudinally from the motor body, i.e., the lengthwise axis of the specimen being parallel to the direction of the greatest extension of the body. These specimens shall be taken 90 degrees apart. One specimen shall be taken from the head of the body toward the rear and the other shall be taken from the rear of the body (excluding threaded section) toward the head. Observation shall be made for compliance with requirements on applicable drawing. Test equipment shall be in accordance with 4.3.4.

4.4.8 *Hardness test.* This test shall be conducted in accordance with Federal Test Method Standard 151, Method 243.1. An arbor shall be used in this test. Four hardness readings shall be taken on the external surface of the nozzle body 90 degrees apart. Two of these readings shall be taken over the midsection of the threads and 90 degrees apart. The remaining two readings shall be taken over the section where the threads end in the nozzle body. Observation shall be made for compliance with requirements on applicable drawing. Test equipment shall be in accordance with 4.3.4.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 *Level C.* The parts shall be preserved and packed in accordance with dwg. 8835922.

5.2 Packing.

5.2.1 *Level C.* The parts shall be packed in accordance with dwg. 8835922.

5.3 Marking. Marking shall be in accordance with MIL–STD–129.

5.4 Data cards. Data card information shall be as specified in Specification MIL–A–2550.

6. NOTES

6.1 Ordering data. Procurement documents should specify the title, number, and date of this specification.

6.1.1 Subject to rights in data acquired under the contract, engineering drawings and lists provided and revised under this specification may be used by the Department of Defense activities for design, procurements, manufacture, testing evaluation, production, production and receiving inspection, overhead, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey, and whenever engineering drawings are needed.

6.2 The contractor shall design inspection equipment as required by the referenced Inspection Equipment List in accordance with the instructions of paragraphs 6.2.1, 6.2.2, 6.2.3, 6.2.4 and 6.2.5.

6.2.1 Inspection Equipment Lists (IEL) indicate the availability of inspection equipment 00 Form 1242–3 the numbers of drawings of existing equipment design, or codes indicating "commercial item" or "contractor design". Design action required of the contractor with respect to the different types of drawings that may be listed is described in paragraphs 6.2.2 and 6.2.3. Action required of the contractor with respect to "commercial item" inspection equipment, is described in paragraph 6.2.4. The contractor will be required to prepare drawings for all equipment coded as "contractor design" in the number column. The code will further indicate whether detailed or specification

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:22Z
Check the source to verify that this is the current version before use.

control drawings are required. These contractor designs must be approved by the Government prior to the fabrication or procuring of the equipment. Designs shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, Dover, New Jersey, ATTN: SMUPA–ND.

6.2.2 *Detailed drawings.* Detailed drawings are drawings which completely depict all the information necessary for the fabrication equipment. Contractors need provide no design when a detailed drawing is listed for an item of inspection equipment and the contractor elects to use the Government design. The contractor may, however, with the approval of the Government, design alternate inspection equipment to facilitate his operations. Such contractor prepared designs must be approved by the Government prior to the fabrication or procuring of the equipment. Designs shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, Dover, New Jersey, ATTN: SMUPA–ND.

6.2.3 *Specification control drawings.* Specification control drawings depict the device in outline, descriptive, diagrammatic, or pictorial form only and specify the required performance or other characteristics. Contractors must prepare drawings of their designs in support of specification control drawings. The IEL code will indicate whether the drawings must be detailed. These contractor prepared designs must be approved by the Government prior to the fabrication or procurement of the equipment. Commercial equipment meeting the requirements of specification control drawings may be approved if described in sufficient detail to permit identification and evaluation by the Government. Designs shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, Dover, New Jersey, ATTN: SMUPA–ND.

6.2.4 *Commercial items.* Commercial item inspection equipment is equipment that has a universal application for a specific function. It is comprised of items commonly used by industry and government. Contractors are not required to furnish drawings of commercial item inspection equipment, but a list of such equipment must be approved by the Government. Lists shall be submitted for approval to the inspection element of the agency administering the contract.

6.2.5 *Use of standard measuring equipment.* If the contractor desires to use standard measuring equipment in lieu of government or contractor designed gages, diagrammatic sketches or other descriptions of the use of such equipment shall be submitted to the Commanding Officer, Picatinny Arsenal, Dover, New Jesrey, ATTN: SMUPA–ND for approval.

6.3 Inspection code numbers. The five-digit code numbers assigned to the inspection herein are to facilitate future data collection and analysis by the Government.

6.4 Former designation. Rocket Motor M3A2 was formerly designated as Jato, M3A1E1.

Notice. When Government drawings, specifications, or other date are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodian:
Army—MU

Preparing activity:
Army—MU

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:22Z
Check the source to verify that this is the current version before use.