MIL-T-46245F(MU)
29 September 1976
SUPERSEDING
MIL-T-46245E
25 January 1973

MILITARY SPECIFICATION

TRACER, PROJECTILE: M12, ASSEMBLY, PARTS FOR, AND LOADING, ASSEMBLING AND PACKAGING

This specification is approved for use by all Department and Agencies of the Department of Defense

1. SCOPE

1.1 This specification covers the parts for, and the loading, assembling and packaging for one type of tracer designated as Tracer, Projectile, M12, Assembly for use in Artillery Ammunition.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-A-2550	- Ammunition, General Specification for

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-414	- Sampling Procedures and Tables for Inspection by Variables for Percent Defective
MIL-STD-1167	- Ammunition Data Card
MIL-STD-1168	- Lot Numbering of Ammunition
MIL-STD-1169	- Packaging: Packing & Marking for Shipment of Inert Ammunition Components
MIL-STD-1234	- Pyrotechnics: Sampling, Inspection and Testing
MIL-STD-1235	- Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Frankford Arsenal, ATTN: SARFA-MDM, Phila., PA 19137, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1462) appearing at the end of this document or by letter.

FSC 1315

Source: https://assist.dla.mil -- Downloaded: 202610-22T05:20Z
Check the source to verify that this is the current version before use.

2.1 (cont'd)

DRAWINGS

Armament Command

C8853698	- Tracer, Projectile, M12, Assembly
C8837866	- Carton, Packing, Ammunition, For Tracer, Projectile, M12
C8837867	- Box, Packing, Ammunition, For Tracer, Projectile, M12, Assembly
LI-8853698	- Index of Inspection Equipment Lists for Tracer, Projectile, M12, Assembly

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Code of Federal Regulations

49CFR 71-90 -- Interstate Commerce Commission Rules and Regulations for the Transportation of Explosives and Other Dangerous Articles

(The Interstate Commerce Commission regulations are now a part of this Code of Federal Regulations (1967 Edition and revision) available from the Superintendent of Documents, Government Printing Office, Washington, D.C., 20315. Orders for the above publication, cite 49CFR 71-90 (latest revision).)

ANSI-B46.1 - Surface Texture

(Application for copies should be addressed to the American National Standards Institute (ANSI), 1430 Broadway, New York, NY 10018.)

ASTM Methods - American Society for Testing and Materials

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

3. REQUIREMENTS

3.1 General

3.1.1 Tracer and Igniter Compositions. The materials used in the tracer and igniter compositions shall comply with the requirements specified on the drawings and referenced specifications.

3.1.2 Metal Parts. The materials, parts and assemblies shall comply with the requirements specified on the applicable drawings and referenced specifications.

3.1.3 Tube. The materials used in the tube shall comply with the requirements specified on the applicable drawing and referenced specification.

Source: https://assist.dla.mil -- Downloaded: 202610-22T05:20Z
Check the source to verify that this is the current version before use.

3.2 Heat Treatment-Disc. The disc will be annealed to dead soft as specified on the applicable drawing and referenced specification.

3.3 Mechanical Properties.

3.3.1 Plug. The mechanical properties specified on the applicable drawing and referenced specifications shall apply throughout the plug.

3.4. Metal defects.

3.4.1 Body. The body, including the cavity, shall be free from cracks, splits, bursts, cold shuts, pipe, porosity, inclusions, folds, seams and other metal defects.

3.4.2 Body cavity. The body cavity shall be free of scale, fins, burrs, draw marks, laminations, imbedded foreign matter, pits and sharp edges.

3.4.3 Visual standards. Visual standards for metal defects will be established for each contract after the first month's production. However, the establishment of visual standards will not waive the requirement for compliance with 3.4.1 and 3.4.2 (see 6.2).

3.5 Workmanship. The requirements for workmanship are as shown on the applicable drawings, in the applicable specifications and the following:

3.5.1 Surface finish. The requirements for surface finish are as detailed on the applicable drawing.

3.5.2 Threads. Threads shall be full and undamaged for the entire minimum length as required by the applicable drawings and shall be in accordance with the provisions of MIL-A-2550.

3.5.3 Burr. No part shall have a burr which might interfere with the assembly or function of the round or which might be injurious to personnel handling the item.

3.5.4 Foreign matter. No part or assembly shall contain dirt, grease, chips, rust, corrosion, or other foreign matter. Particular attention shall be given to the cavity of the body assembly, to insure that no grit, scale, or other foreign matter remains therein after final cleaning.

3.6 Protective coating. Protective coating shall be in accordance with the applicable drawing and the specifications referenced thereon.

3.7 Moisture Content.

3.7.1 Tracer composition. The moisture content of the tracer compositon at the loading station at the time of loading of the tracer composition shall not exceed 0.10% when tested as specified in 4.3.3.1 and 4.4.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

3.7.2 Igniter composition. The moisture content of the tracer composition at the loading station at the time of loading the igniter composition shall not exceed 0.14% when tested as specified in 4.3.3.1 and 4.4.1.

3.8 Tracers. The tracers shall comply with all the requirements of Drawing C8853698 and with all the requirements specified in the applicable specifications. The tracers shall be free of dirt, chips, grease, rust and other foreign matter. The cleaning method shall not be injurious to the metal nor shall the tracer be contaminated by the cleaning agents used.

3.9 Proving Ground Test. The tracers shall ignite and there shall be visible evidence of burning of the tracer composition for 6.0 seconds minimum at ambient temperature, 125 degrees Farenheit (125°F) and minus 40 degrees Farenheit (-40°F) when tested as specified in 4.4.3.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality Assurance terms and definitions. Reference shall be made to MIL-STD-109 to define quality assurance terms used.

4.1.2 Inspection. Inspection shall be in accordance with MIL-A-2550, except as specified herein.

4.1.3 Inspection criteria.

a. Successful passage of all inspections required by the drawings and specifications shall be considered as a condition precedent to performing the Proving Ground functional test (see 4.4.3.1).

b. Acceptance or rejection of a lot by the Government shall be contingent on successful passage of the Proving Ground functional tests.

4.2 First article sample.

4.2.1 Initial production sample. At the beginning of regular production a sample shall be submitted in accordance with contract requirements and shall consist of assemblies and parts as follows:

55 Tracer Assemblies, complete, including protective coating
5 Metal Parts Assemblies, complete, including protective coating minus tracer and igniter compositions
5 Plug and disc assemblies
5 Sets of component parts, uncoated and unassembled

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

4.2.1 (cont'd)

Fifty-five of the above complete tracer assemblies shall be forwarded to a designated proving ground for burn time testing and other characteristics listed in 3.9. The samples shall be manufactured using the same materials, equipment, processes and procedures, including packaging and packing as will be used in regular production and shall be obtained from the same source of supply. A first article sample or portion thereof as directed by the procuring agency shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacture process, material used, drawing, specifications, or source of supply, such as to significantly affect product uniformity as determined by the responsible technical agency.

4.2.1.1 Examination and test. After inspection and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility specified in the contract.

4.2.1.2 Initial production sample failure. Failure of the sample to comply with the requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection.

4.3.1 Lot.

4.3.1.1 Submission of product. The product shall be submitted in accordance with MIL-STD-105.

4.3.1.2 Tracer Assembly Lot. A tracer assembly lot shall consist of tracer assemblies produced by one manufacturer, under one contract, in one unchanged process in accordance with the same drawing, same drawing revision, same specification and same specification revision.

4.3.2 Examination. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plans contained in MIL-STD-105. Continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity. An AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect shall be used. All nonconforming material shall be rejected. Four power (4x) magnification may be used in performing visual examination. The roughness comparison specimens prescribed by ANSI-B46.1 shall be used as a basis for surface roughness determination.

4.3.2.1 Plug, Drawing C8860516 covering a detail of Drawing C8860514.

Defect	Method of Inspection
CRITICAL	
None defined	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

4.3.2.1 (Cont'd)

	Defect	Method of Inspection
MAJOR		
101.	Pitch diameter of thread, min.	Gage
102.	Major diameter of thread, min.	Gage
103.	Diameter of hole	Gage
104.	True position of hole with pitch diameter of thread	Gage
105.	Height of crimping lip	Gage
MINOR		
201.	Length of thread	Gage
202.	Distance across wrench flats	Gage
203.	Diameter of disc recess	Gage
204.	Radii or chamfers missing or incorrect	Visual (see 6.1)
205.	Burrs	Visual
206.	Threads, damaged or not full	Visual
207.	Foreign matter	Visual

4.3.3.2 Disc, Drawing A8860515 covering detail of Drawing C8860514.

CRITICAL

None defined

MAJOR		
101.	Diameter	Gage
102.	Thickness, max.	Gage
103.	Foreign matter	Visual

MINOR

None defined

4.3.2.3 Plug and disc assembly, Drawing C8860514 covering a detail of Drawing C8853698.

CRITICAL

None defined

MAJOR		
101.	No multiple parts	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

4.3.2.3 (Cont'd)

	Defect	Method of Inspection
MINOR		
201.	Disc loose, punctured or torn	Visual/Manual
202.	Crimp not full for 360 degrees	Visual
203.	Absence of adhesive	Visual

4.3.2.4 Body, Drawing C8853699 covering a detail of Drawing C11738310.

CRITICAL		
	None defined	
MAJOR		
101.	Pitch diameter of internal thread, max.	Gage
102.	Minor diameter of internal thread, max.	Gage
103.	Pitch diameter of external thread, min.	Gage
104.	Major diameter of external thread, min.	Gage
105.	Runout of outside diameter with pitch diameter of external thread including front face of shoulder	Gage
106.	Diameter of charge cavity, max.	Gage
107.	Depth of charge cavity, max.	Gage
108.	True position of minor diameter of internal thread with charge cavity	Gage
109.	Metal defective before protective coating	Visual
110.	Protective finish incomplete or inadequate	Visual
MINOR		
201.	Pitch diameter of external thread, max.	Gage
202.	Major diameter of external thread, max.	Gage
203.	Outside diameter, max.	Gage
204.	Width of internal thread undercut, max.	Gage
205.	Diameter of external thread undercut, max.	Gage
206.	Width of external thread undercut, max.	Gage
207.	Distance across wrench flats	Gage
208.	Length of wrench flats, min.	Gage
209.	Distance from plug cavity to charge cavity	Gage
210.	Length from forward end to shoulder, min.	Gage
211.	Length from shoulder to rear face, min.	Gage
212.	Wall thickness variation	Gage
213.	Radii or chamfers, missing or incorrect	Visual (see 6.1)
214.	Burr	Visual
215.	Threads, damaged or not full	Visual
216.	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

4.3.2.5 Tube, Drawing A886017 covering a detail of Drawing C11738310.

	Defect	Method of Inspection
CRITICAL		
	None defined	
MAJOR		
	None defined	
MINOR		
201.	Inside diameter	Gage
202.	Length, max.	Gage
203.	Wax missing	Visual

4.3.2.6 Loading Assembly (prior to inserting charge) Dwg. C11738310 covering a detail of Drawing C8853698.

CRITICAL		
	None defined	
MAJOR		
101.	Tube missing	Visual
MINOR		
	None defined	

4.3.2.7 Loading Assembly, Drawing C11738310 covering a detail of Drawing C8853698.

CRITICAL		
	None defined	
MAJOR		
101.	Charge missing or less than min. required depth from shoulder	Visual
102.	No multiple parts if not required	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

4.3.2.7 (cont'd)

	Defect	Method of Inspection
MINOR		
201.	Igniter charge chipped or broken on any one step in excess of 1/3 the total area of the step, or total aggregate of chipped or broken area of all steps in excess of 1/3 of the total area of the largest step.	Visual

4.3.2.8 Tracer Assembly, Drawing C8853698.

CRITICAL		
	None defined	
MAJOR		
101.	Multiple or missing parts	Visual
102.	Plug and disc assembly fails to withstand min. disassembly torque.	Test
MINOR		
201.	Total length, max.	Gage
202.	Outside diameter, max. after retouch finish	Gage
203.	Sealing compound missing	Visual
204.	Protective finish of tracer body damaged during loading not retouched	Visual

4.3.2.9 Packing carton (prior to sealing) Drawing C8837866.

CRITICAL		
	None defined	
MAJOR		
101.	Number of tracers incorrect	Visual
MINOR		
	None defined	

Source: https://assist.dla.mil -- Downloaded: 202610-22T05:20Z
Check the source to verify that this is the currentversion before use.

4.3.2.10 Packing carton, (sealed) Drawing C8837866.

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR	
101. Carton damaged exposing contents	Visual
102. Marking missing, incorrect, or unidentifiable	Visual
MINOR	
201. Carotn insecurely sealed	Visual
202. Contents loose	Manual

4.3.2.11 Sealed wooden packing box, Drawing C8837867.

CRITICAL	
None defined	
MAJOR	
101. Box damaged exposing contents	Visual
102. Board broken, board loose or protruding nail	Visual
103. Strapping missing, loose or broken	Visual/Manual
104. ICC nomenclature missing, incorrect or unidentifiable	Visual
MINOR	
201. Strapping improperly engaged	Visual/Manual
202. Marking missing, incorrect or unidentifiable	Visual

4.3.3 Testing.

4.3.3.1 Moisture and total volatile content of tracer composition and igniter composition. The contractor shall provide adequate controls to assure the compliance of each lot with the applicable requirement. The contractor shall test a minimum of one randomly selected sample from each batch or from each 8 hours production, whichever is the lesser amount. Composite samples shall not be used for determining compliance. Failure to comply with the applicable requirement shall be cause for rejection of the parent quantity represented by the sample. Testing shall be performed as specified in 4.4.1.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T05:20Z
Check the source to verify that this is the currentversion before use.

4.3.3.2 Proving ground.

4.3.3.2.1 Functioning (see 3.9). This test shall be performed as specified in 4.4.3.1.

4.3.3.2.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, the sampling plan and procedure for this test shall be in accordance with MIL-STD-414, Section B-3, Code letter I and AQL of 1.50 percent. If any tracer fails to ignite or fails to produce visible evidence of burning, the lot shall be rejected.

4.3.3.2.1.2 After three consecutive lots have met the criteria of 4.3.3.2.1.1, the sampling plan and procedure for this test shall be in accordance with MIL-STD-414, Section B, Table B-3, Code letter F, and AQL of 1.50 percent. If any tracer fails to ignite or produce visible evidence of burning, the lot shall be rejected.

4.3.3.2.1.3 Refiring. If for any reason the proof director considers that the test conditions have detrimentally affected the test results, he shall declare the results invalid and perform a new test on additional tracers as required.

4.3.4 Inspection equipment. LI-8853698 identifies the inspection equipment required to perform the examinations and tests prescribed herein.

4.4 Test methods and procedures.

4.4.1 Determination of moisture and total volatile content of tracer composition and igniter composition. The moisture and total volatile content of the tracer composition and igniter composition shall be determined in accordance with MIL-STD-1234 Method 102.2. (See 6.4)

4.4.2 Protective coating. The procedure for testing the cleaning of components and the application of protective coatings shall be in accordance with the criteria for testing, as specified in the applicable specification. The salt spray test shall be performed utilizing the procedures and equipment prescribed by ASTM Method B117.

4.4.3 Proving ground.

4.4.3.1 Ballistic tracer functioning (acceptance test). The sample tracer shall be assembled to inert or HE loaded 105MM, HEP-T, M393A2 cartridges or other cartridges for which it is standard. The assembled rounds shall be fired at the temperatures listed in Table I from the appropriate weapon and the tracer burn times recorded. A timing device capable of measuring time to the nearest 0.01 seconds shall be used to measure burning time. Suitable aids, such as binoculars, should be used if necessary to insure visible contact with the tracer (see 6.6 and 6.7).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

This specification is approved for use by all

TABLE I

Temperature	Quantity
Ambient	25
+125°F 1/	15 2/
- 40°F 1/	15 2/

1/ The rounds shall be temperature conditioned for a minimun period of 18 hours.

2/ After first article sample and three (3) consecutive production lots have been tested successfully, the temperature conditioning phase may be discontinued with the approval of the procuring agency. However, implementation of the temperature conditioning phase shall be instituted whenever directed by the procuring contracting officer (P.C.O.).

4.4.4 Government use of contractor's inspection equipment. The contractor shall make available to the Government all inspection equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 The tracer assemblies shall be preserved and packaged in accordance with drawing C8837866 and the requirements of Level C in MIL-STD-1169.

5.2 Packing.

5.2.1 The cartons shall be packed in accordance with drawing C8837867 and the requirements of Level C in MIL-STD-1169.

5.3 Marking.

5.3.1 The cartons and boxes shall be marked in accordance with drawings C8837866, C8837867 and MIL-STD-1168.

5.4 Data Card. - Data card information shall be as specified in MIL-STD-1167.

6. NOTES

6.1 Visual examination qualification. When compliance with the applicable requirement is in doubt as a result of visual examination, this characteristic may be measured or gaged to determine acceptability.

6.2 Visual standards. Visual standards to be established at contractor's plant in accordance with 3.4.3.

6.3 Ordering data. Procurement documents should specify the title, number, and date of this specification.

Source: https://assist.dla.mil -- Downloaded: 202610-22T05:20Z
Check the source to verify that this is the current version before use.

6.4 Moisture. The igniter and tracer compositions, and the pellets formed thereof, are hygroscopic and will deteriorate rapidly when exposed to moisture. Small amounts of moisture present in or absorbed by the compositions or pellets, prior to or after loading into tracers will eventually result in unsatisfactory functioning. It is highly desirable that the ingredients, compositions, pellets, and loaded tracer be carefully safeguarded from exposure to moisture and humid atmospheres. For assurance of a satisfactory loaded tracer, it is recommended that the blending and pelletizing buildings be air conditioned in a manner which will hold the humidity of the atmosphere as low as practicable.

6.5 Alternative testing procedures. Alternative testing procedures may be used by the contractor when such testing and procedures provide as a minimum the quality assurance provisions specified herein. Prior to applying alternative procedures, the contractor shall describe them in a written proposal and shall demonstrate for approval of the responsible technical agency that their effectivness is equal to or better than the quality assurance provisions specified herein.

6.6 When a product is being inspected in accordance with MIL-STD-1235 and a defective characteristic is found, the product produced prior to the discovered defect will be screened back 2000 tracer assemblies and all defects culled out.

6.7 Shipping. It is not intended to ship these compositions or pellets. It is intended that the compositions and pellets thereof be prepared at the plant where the loading of the tracers will be accomplished. If shipment is necessary, Department of Transportation (DOT) Class and Marking cited on the affected item drawing is applicable. Material must be adequately and properly packaged in accordance with applicable DOT Packaging Requirements (Para 173.61, CODE OF FEDERAL REGULATIONS(CFR) Title 49.).

6.8 Hazard notice. The tracer described herein and certain of its components are flammable and/or explosive and consequently present hazards in manufacture, adverse environment, corrosive atmosphere, rough handling and electrically induced incidents.

6.9 Combining of proving ground tests. When the contractor for the tracer is also contractor for the complete round or one of the loaded components thereof, the proving ground tests may be combined in order to save expense, upon agreement between the procuring activity and the contractor.

Source: https://assist.dla.mil -- Downloaded: 202610-22T05:20Z
Check the source to verify that this is the currentversion before use.

6.10 Submission of firing and test data. In addition to the normal distribution of records for each lot of tracers, when the item is procured by the Department of Defense, copies should be sent to:

Commander
Frankford Arsenal
ATTN: SARFA-QAA-Q(1) (1 copy)
SARFA-MDP-Y (1 copy)
Philadelphia, PA 19137

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1315 -A286

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE MIL-T-46245F(MU) Tracer, Projectile: M12, Assembly, Parts for, and Loading, Assembling and Packaging

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:20Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
Frankford Arsenal
ATTN: SARFA-MDM
Philadelphia, PA 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 202640-22T05:20Z
Check the source to verify that this is the current version before use.