MIL-A-45648(Ord)
15 June 1961
SUPERSEDING
FA(FC)-PD-541
19 August 1959

MILITARY SPECIFICATION

AMPLIFIER ASSEMBLY, DUAL RELAY: 8644114

1. SCOPE

1.1 This specification covers one type of dual relay amplifier used in the Gun Direction Computers: M15 and M15C which are part of Field Artillery Fire Control Systems: M35 and M35C. The dual relay amplifier hereinafter referred to as "amplifier" is used as a phase-sensitive device to operate relays.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-F-13926	Fire Control Materiel: General Specification Governing the Manufacture and Inspection Of
MIL-F-14619	Fire Control Parts, Equipment and Tools; Packaging Of
MIL-I-45208	Inspection Requirements General Specification For

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-130	Identification Marking of U. S. Military Property
MIL-STD-202	Test Methods for Electronic and Electrical Component Parts

FSC 1220

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.

DRAWINGS

Ordnance Corps

D8643954	Electrical Schematic, Dual Relay Amplifier
F8644114	Dual Relay Amplifier

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Production model. - At the beginning of production, one amplifier, representative of production, shall be made available to the Government to determine that the amplifier meets all requirements of this specification.

3.2 Materials. - Materials shall be in accordance with drawings, material specifications and general specifications forming a part of this specification.

3.3 Construction. - The amplifier shall be manufactured in accordance with Drawing F8644114, "Dual Relay Amplifier", and drawings pertaining thereto. The requirements of this specification are detailed only to the extent considered necessary to obtain the desired mechanical and electrical characteristics, performance and permanence to insure inherent quality and performance capabilities prior to final acceptance by the Government.

3.3.1 Ground potential. - The design and construction of the amplifier shall insure that all external parts, exclusive of electrical connections, are at ground potential at all times.

3.4 General specification. - The contractor shall be responsible for adherence to, and compliance with, the following requirements of Specification MIL-F-13926:

(a) Order of precedence
(b) Protective finished surfaces
(c) Special accuracy
(d) Finish, painting and protective
(e) Electrical
(f) Workmanship

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.

3.5 Environmental.

3.5.1 Vibration. - The amplifier shall be subjected to a simple harmonic motion having an amplitude of .015 inch (0.03 inch maximum excursion). The frequency shall be varied uniformly between the limits of 10 and 55 cycles per second and return to 10 cycles and shall be traversed in approximately 1 minute. This motion shall be applied for a period of 10 minutes in each of the 3 mutually perpendicular directions (total of 30 minutes). Subsequent to vibration the amplifier shall not be damaged or adversely affected and shall meet all requirements of this specification.

3.5.2 Operating temperatures. - The amplifier shall meet the requirements of 3.6 when thermally stabilized at ambient temperatures of minus 40 degrees and plus 150 degrees Fahrenheit.

3.5.3 Storage temperatures. - The amplifier shall show no evidence of physical failure and shall meet the requirements of 3.6 at room temperature (plus 60 to 90 degrees Fahrenheit) after having been thermally stabilized at ambient temperatures of plus 160 degrees and minus 65 degrees Fahrenheit.

3.6 Performance.

3.6.1 Input voltages. - Each amplifier shall be capable of operating from 28 volts, dc regulated voltage and a reference voltage of 25 volts, 400 cps.

3.6.1.1 Integral relay circuit. - Each amplifier shall be considered integral with an externally mounted relay. The 25 volts, 400 cps, reference voltage shall be applied in series with the externally mounted Relay, 8643036.

3.6.2 Zero signal input. - With a zero signal input, each amplifier shall be so biased that the current in the relay winding shall be just below the drop-out value of 0.8 milliampere, dc, and the relay shall be non-operative.

3.6.3 In-phase signal input. - When the input signal is in-phase with the reference voltage, the current in the relay winding shall decrease and the relay shall be non-operative.

3.6.4 Out-of-phase signal input. - When the signal input is out-of-phase with the reference voltage the current in the relay winding shall increase and the relay shall operate at 2.2 milliamperes, dc.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.

3.6.5 Sensitivity of relay. - The minimum out-of-phase signal that will cause the relay to operate shall be no less than 20 millivolts nor greater than 100 millivolts. The relay shall remain operative to an increased value of 2.5 volts.

3.6.5.1 Drop-out-voltage. - The relay shall release when the out-of-phase signal drops to not more than 20 millivolts and shall remain non-operative for all in-phase signals.

3.6.6 Circuitry. - Circuitry shall be in accordance with electrical schematic, Drawing D8643954.

3.7 Alinement and calibration. - Alinement and calibration of all amplifiers shall be performed using the same power source to insure uniformity of product. The reference voltages supplied shall be from a power source maintained as standard.

3.8 Identification marking. - Unless otherwise specified, identification marking shall be in accordance with Standard MIL-STD-130.

4. QUALITY ASSURANCE PROVISIONS

4.1 General provisions. - The quality assurance provisions of referenced documents to the extent specified herein, together with provisions of this section are applicable to inspection performed by the contractor and for Government verification.

4.1.1 The contractor shall provide an inspection system in accordance with Specification MIL-I-45208.

4.2 Production model. - Unless otherwise specified in the contract, one amplifier shall be selected by the Government inspector as soon as practicable after the start of production, and be inspected by the contractor under the surveillance of the Government. This inspection shall be conducted at the contractor's facility, or Government approved laboratory, using test equipment authorized for use on the contract. The model shall be inspected for all requirements of this specification by utilizing examination and testing methods prescribed herein.

4.2.1 Production model failure. - Should the production model fail to pass the prescribed tests, the contractor shall cease those operations which are causing the rejection and shall make the necessary corrections.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.

When corrections in the process have been made, a new production model shall be examined and tested by the contractor under the surveillance of the Government. Acceptance of production lots will not commence until an acceptable production model is submitted and corrective actions have been taken to eliminate deficiencies.

4.3 Lot formation. - Inspection lot sizes and lot formation shall be in accordance with Standard MIL-STD-105.

4.3.1 Defective units and lots shall be processed as specified in Standard MIL-STD-105.

4.4 Inspection of components. - All positional and functional characteristics shown on the drawings contained in the contract shall be inspected by the contractor for conformance with drawing requirements prior to acceptance. These characteristics are defined as drawing requirements affecting concentricity, squareness, parallelism, micro-finishes 64 RMS or better, threads, identification marking, and all dimensions on which the tolerances indicate a precision requirement that have a bearing on the functional accuracy and performance of the amplifier. Also included in the above category are all performance requirements specified in notes directly on the drawings, or in separate performance specifications referenced therein.

4.4.1 Sampling inspection. - Sampling inspection of components may be used in lieu of 100 percent inspection, and shall be in accordance with Table I.

TABLE I - SAMPLING PLAN

Lot Size Inclusive	Sample Size	Accept Lot	Reject Lot
0 - 25	Use 100% Inspection		
26 - 35	20	0	1
36 - 50	25	0	1
51 - 150	30	0	1
151 - 300	30	1	2
301 - over	60	2	3

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.

4.4.2 Disposition of non-conforming product. - Acceptance and rejection numbers are expressed in terms of defective units. One or more defects on any unit shall constitute a defective unit. Disposition of non-conforming components shall be in accordance with Standard MIL-STD-105.

4.5 Material. - Control of material shall be in accordance with Test Data Requirements of Specification MIL-I-45208.

4.6 Inspection equipment. - Supply, calibration, maintenance and use of inspection equipment shall be in accordance with Specification MIL-I-45208.

4.6.1 Accuracy requirements. - Inspection equipment which incorporates features for measuring values or sizes established by product requirements shall be capable of measuring those values within an accuracy of ten percent of the specified tolerance, except as otherwise specified. In cases where the ten percent accuracy imposes impractical or very difficult design and fabrication problems, or results in a test equipment cost factor which is exorbitant in relation to the cost and application of the product to be inspected, the Government shall be expeditiously advised in order that necessary appropriate action can be taken.

4.6.2 Accuracy requirements for special testing devices.

4.6.2.1 Device to test vibration requirements. - The device shall consist of a vibrating machine which will produce motion as specified. It shall be equipped with a medium capable of holding the unit securely to the vibrating machine in the specified positions.

4.7 Tests.

4.7.1 Classification of defects. - The classification of defects in Tables II and III shall constitute the minimum inspection requirements to be performed prior to acceptance or rejection by lots. The Government reserves the right to inspect for any or all applicable requirements and to reject individual non-conforming items.

4.7.1.1 Disposition of rejected lots. - Rejected lots shall be screened for all defective characteristics. After corrections have been made and the Government inspector informed of the corrective action taken, the lots shall be resubmitted for acceptance as outlined in Standard MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.

TABLE II - CLASSIFICATION OF DEFECTS

Use Inspection Level L7, and Sampling Plan Table IV-A of Standard MIL-STD-105

CRITICAL: None defined

MAJOR: AQL 4.0%	Req't Par.	Q.A. Par.	Test Method
101. Post vibration	3.5.1	4.7.2	Device, special testing (DST)
102. Operating temperatures	3.5.2	4.7.3	DST

MINOR: None defined

TABLE III - CLASSIFICATION OF DEFECTS

Use Inspection Level II, and Sampling Plan Table IV-A of Standard MIL-STD-105

CRITICAL: None defined

MAJOR: AQL 1.5%	Req't Par.	Q.A. Par.	Test Method
101. Input voltage	3.6.1	4.7.5	Standard Measuring Equipment (SME)
102. Zero signal input	3.6.2	4.7.6	(SME)
103. In-phase signal input	3.6.3	4.7.7	SME
104. Out-of-phase signal input	3.6.4	4.7.8	SME
105. Sensitivity of relay	3.6.5	4.7.9	SME
106. Drop-out-voltage	3.6.5.1	4.7.10	SME
107. Circuitry	3.6.6	4.7.11	SME
108. Identification marking	3.8	4.7.12	Visual

MINOR: None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.

4.7.2 Vibration. - This test shall be conducted in accordance with Method 201A of Standard MIL-STD-202, except that the time period for applied motion in each direction shall be specified herein. Tests and performance measurements prior to or during vibration are not required for final acceptance. Subsequent to vibration, the amplifier shall be subjected to a visual-tactile examination for damage. The amplifier shall then be subjected to all the tests in this specification.

4.7.3 Operating temperatures. - This test shall be conducted in accordance with Procedure I of Specification MIL-F-13926, except that the temperature shall not be reduced beyond condition "C" or raised beyond condition "G". When the amplifier is stabilized at each indicated temperature, it shall be subjected to the tests specified in 4.7.5 to 4.7.11 inclusive and shall meet the requirements specified.

4.7.4 Storage temperature. - This test shall be conducted in accordance with Procedure II, condition "B" and "H" of Specification MIL-F-13926. Upon completion of the storage temperature cycling, the amplifier shall be subjected to tests specified in 4.7.5 to 4.7.11 inclusive and shall meet the requirements specified. This test shall be performed on the production model only.

4.7.5 Input voltages. - Using SME, the dc regulated and ac reference voltages shall be checked for conformance to the input voltage requirements. This test shall be performed concurrently with each of the other performance tests to ascertain that the amplifier is capable of functioning properly with the specified voltages induced.

NOTE: Each amplifier shall be considered integtal with an externally mounted relay. The reference voltage (25 volts, 400 cps) shall be applied in series with the externally mounted Relay, 8643036.

4.7.6 Zero signal input. - When the input signal is zero the current in the relay winding shall be measured for compliance with the requirements of 3.6.2.

4.7.7 In-phase signal input. - When the signal input is in-phase with the reference voltage, the measured current in the relay winding shall comply with the requirements of 3.6.3.

4.7.8 Out-of-phase signal input. - When the signal input is out-of-phase with the reference voltage, the measured current in the relay winding shall comply with the requirements of 3.6.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.

4.7.9 Sensitivity of relay. - The sensitivity of the relay shall be measured and shall comply with the requirements of 3.6.5.

4.7.10 Drop-out voltage. - The measured drop-out voltage that will cause the release of the relay shall conform to the requirements of 3.6.5.1. The relay shall remain non-operative when in-phase signals are introduced.

4.7.11 Circuitry. - An electrical point-to-point measuring check shall be made using standard measuring equipment to ascertain that the values of the circuits conform to the electrical schematic.

4.7.12 Identification marking. - Marking shall be visually inspected for conformance to Standard MIL-STD-130.

5. PREPARATION FOR DELIVERY

5.1 Packaging and packing. - The amplifier shall be cleaned, preserved, packed, and marked in accordance with Specification MIL-F-14619 P8516. The level of protection shall be as specified in the procurement document.

6. NOTES

6.1 Intended use. - The dual relay amplifier is one unit consisting of two identical, independent transistorized amplifier circuits intended to function as a phase-sensitive device operating a relay with an impedance of 8000 ohms plus or minus 10 percent. Both amplifiers are mounted on a single chassis.

6.2 Ordering data. - Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Selection of applicable level of preservation, packaging and packing.
(c) Applicable stock number.
(d) Provisions for production model including date of delivery (see 3.1).

6.3 Design information. - Information regarding specific design not covered or referenced by this specification may be obtained from the procuring activity upon the specific request of the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.

6.4 Definitions.

6.4.1 Standard measuring equipment (SME). - Standard measuring equipment (SME) is defined as the common hand type measuring devices which are usually stocked by commercial supply houses for ready supply (shelf items), and which are normally used by an inspector to perform dimensional inspection of items under procurement. This category also includes commercial testing equipment such as meters, optical comparators, etc.

6.4.2 Special testing device (DST). - Special testing devices are defined as special inspection fixtures, instruments, and modified standard measuring equipment.

6.4.3 Skillful manipulation or sensing.

6.4.4 Production model. - A model in its final mechanical and electrical form of final production design made by production methods, tools, jigs and fixtures.

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any invention that may in any way be related thereto.

Custodian:

Army - Ordnance

Preparing activity:

Army - Ordnance

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.