MILITARY SPECIFICATION

MOUNT, PERISCOPE: M119

This amendment forms a part of Military Specification MIL-M-45671E(MU), dated 30 September 1970.

Paragraph 2.1, list of Drawings, add:

"A8644448	Push-Pull Gage
F10554660	Holding Fixture
F10554662	Set-Up Final Test Fixture for Mount Periscope: M119
F10554664	Test Standard for Mount Periscope: M119"

Paragraph 4.6.2: Delete and substitute:

"4.6.2 Orientation.- Special test equipment conforming to the requirements of Drawing F10554660 (Holding Fixture) shall be utilized to accept the mount, completely assembled, and secure it in the position required by 3.4. Set-up of the test equipment and installation of the mount under test shall be performed in accordance with the applicable set-up instructions contained on Drawing F10554662 (Set-Up Final Test Fixture for Mount Periscope: M119)."

Paragraph 4.6.3: Second sentence: Delete "testing device (Figure 1)" and substitute "holding fixture".

Paragraph 4.6.4: Delete and substitute:

"4.6.4 Holding features.- A test standard conforming to the requirements of Drawing F10554664 shall be utilized in lieu of the referenced gages (see 3.2.1 & 3.5.2). With the mount positioned on the holding fixture, the Test Standard 10554664 shall be inserted into the mount utilizing the procedure described in 4.6.3. Subsequent to insertion of the test standard, both wing nuts shall be screwed down until tight against the mount surface. This will secure the test standard in the mount. A dial indicator graduated in .0001 inch increments shall be positioned so that it contacts the front or the rear button provided on the left side of the test standard, and then adjusted to read zero with respect to the indicating hand. Apply a slow steady pressure of 10 pounds, by means of a push-pull gage conforming to Drawing A8644448, to the opposite side of the dial indicator contact point; and then upon releasing the pressure, the indicating hand of the dial indicator shall not exceed the tolerance specified in 3.5.2. Reverse the equipment and repeat the above procedure. Upon satisfactory completion of this portion

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:42Z
Check the source to verify that this is the current version before use.

of the test, repeat the entire above procedure at the front and rear buttons on the right side of the test standard."

Delete "Figure 1" in its entirety.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A386

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:42Z
Check the source to verify that this is the current version before use.