MILITARY SPECIFICATION

MOUNT, PERISCOPE: M119

This amendment forms a part of Military Specification MIL-M-45671E(MU), dated 30 September 1970 and is approved for use by all Departments and Agencies of the Department of Defense.

Paragraph 2.1, List of Drawings, add:

"A8644448	Push-Pull Gage
F10554660	Holding Fixture
F110554662	Set-Up Final Test Fixture for Mount Periscope: M119
F10554664	Test Standard for Mount Periocope: M119"

* Paragraph 3.4, 1st sentence, lines 2 and 3: Delete all after "- - - - - horizontal plane".

* Paragraph 3.5.4 through 3.5.4.3: Delete in its entirety.

* Paragraph 4.3.2.2, Table - I: Delete Characteristics 104, 105, and 106 in their entirety.

* Paragraph 4.4.2, Table III: Delete Characteristics 306, 307, and 308 in their entirety.

Paragraph 4.6.2: Delete and substute:

"4.6.2 Orientation.- Special test equipment confoming to the requirements of Drawing F10554660 (Holding Fixture) shall be utilized to accept the mounts completely assembled, and secure it in the position required by 3.4. Set-up of the test equipment and installation of the mount under test shall be performed in accordance with the applicable set-up instructions contained on Drawing F10554662 (Set-up Final Test Fixture for Mount Periscope: M119)."

* Paragraph 4.6.3, 2nd sentence: Delete and substitute: "The mount shall be positioned in the holding fixture".

Paragraph 4.6.4: Delete and substitute:

"4,6.4 Holding features.- A test standard conforming to the requirements of Drawing F10554664 shall be utilized in lieu of the referenced gages (see 3.2.1. & 3.5.2). With the mount positioned on the holding fixture, the Test Standard 10554664 shall be inserted into the mount utilizing

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:42Z
Check the source to verify that this is the current version before use.

the procedure described in 4.6.3. Subsequent to insertion of the test standard, both wing nuts shall be screwed down until tight against the mount surface. This will secure the test standard in the mnount. A dial indicator graduated in .0001 inch increments shall be positioned so that it contacts the front or the rear button provided on the left side of the test standard, and then adjusted to read zero with respect to the indicating hand. Apply a slow steady pressure of tem pounds, by means of a push-pull gage conforming to Drawing A8644448, to the opposite side of the dial Indicator contact point; and then upon releasing the pressure, the indicating hand of the dial indicator shall not exceed the tolerance specified in 3.5.2. Reverse the equipment and repeat the above procedure. Upon satisfactory completion of this portion of the test, Repeat the entire above procedure at the front and rear buttons on the right side of the test standard."

Paragraph 4.6.6 through 4.6.6.3: Delete in its entirety.

Paragraph 6.1, line 2: Delete "M34" and "M36" and substitute "M36" and "M36E1" respectively.

Figure 1: Delete in its entirety.

* The outside margins have been marked to indicate where additions to the previous amendments have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirements of this document baeed on the entire content as written Irrespective of the marginal notation and relationshlp to the last previous amendment,

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1240-A585

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:42Z
Check the source to verify that this is the current version before use.