MIL-P-45650(Ord)
AMENDMENT 1
11 April 1960

MILITARY SPECIFICATION

PERISCOPES XM32 AND XM35; PACKAGING OF

This amendment forms a part of Military Specification MIL-P-45650(Ord), dated 10 December 1959.

Page 4, paragraph 3.3.1.4.1: Delete and substitute the following:

"3.3.1.4.1 Immobilizing and wrapping the wedge coupling.- A flat steel spring shall be placed between the stop and the end surfaces of the wedge coupling in such a manner that there is no movement of the coupling. The size of the spring shall be such that it does not extend beyond the surfaces of the coupling in such a manner that it would damage the water-vaporproof bag specified in 3.3.1.4.3. The preservative coated surfaces of the wedge shall be wrapped with greaseproofed barrier material conforming to type II, grade A, class 2 of Specification MIL-B-121. The barrier material shall be secured in place with pressure-sensitive tape conforming to Specification UU-T-106. A tag, specified in 3.5.1, shall be attached to the wrapped coupling."

Page 4, paragraph 3.3.1.4.5: Delete the last sentence and substitute:

"The fiberboard box shall be closed with two strips of 2 inch wide pressure-sensitive tape conforming to Specification PPP-T-76. The tape shall be applied over the top and bottom seams and extend at least 3 inches onto each end panel."

Page 5, paragraph 3.3.2.2(c): Delete the last sentence and substitute "The box shall be closed as specified in 3.3.1.4.5, except that 2 inch wide gummed tape conforming to the gummed tape specified in 3.3.1.4.2 shall be used."

Page 6, paragraph 3.5.1: Add the following after the first sentence:

"The tag to be attached to the wrapped coupling, specified in 3.3.1.4.1, shall contain the following: DO NOT REMOVE FLAT STEEL SPRING IMMOBILIZING COUPLING UNTIL THE PERISCOPE IS PLACED IN TANK."

Custodian:

Army - Ordnance Corps

Preparing Activity:

Army - Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:38Z
Check the source to verify that this is the current version before use.