MILITARY SPECIFICATION

PERISCOPE TANK: M34

1. SCOPE

1.1 This specification covers a tank commander's binocular type periscope incorporating a unity power optical system and a 7X optical system (see, 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-O-13830	Optical Components for Fire Control Instruments; General Specification Governing the Manufacture, Assembly, and Inspection of
MIL-F-13926	Fire-Control Materiel, General Specification Governing the Manufacture and Inspection of
MIL-P-14232	Parts, Equipment and Tools for Army Materiel, Packaging and Packing of
MIL-H-14844	Head Assembly; 8619900
MIL-B-14849	Body Assembly: 8619880
MIL-I-45607	Inspection Equipment, Supply and Maintenance of

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	Quality Assurance Terms and Definitions

FSC 1240

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:44Z
Check the source to verify that this is the current version before use.

DRAWINGS

U.S. Army, Frankford Arsenal

F8565556	Pressure Tester Two - Station
F8565964	Test Fixture for Periscope M34 and M36
F8575658	Vibration Adapter for Periscope M34 and M36
F8619700	Periscope, Tank M34: 8619700
F10540499	Universal Test Stand and Set-up Instructions
F10547434	10" Collimator

PACKAGING DATA SHEET

8619700	Packaging of Periscope, Tank M34

(Copies of specifications, standards, drawings and packaging data sheets required by suppliers in connection with specific procurement functions should be obtained from the procuring activity-or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials.- The materials shall be in accordance with the drawings, material specifications and general specifications forming a part of this specification.

3.2 Fabrication.- The periscope shall be manufactured in accordance with Drawing F8619700 and drawings pertaining thereto. The following modules shall have met their respective specifications

Head Assembly:	8619900	MIL-H-14844
Body Assembly:	8619880	MIL-B-14849

3.2.1 Interchangeability.- The periscope shall meet all requirements of this specification without need for realignment of components or selective assembly of above modules. Adjustments, other than those specified herein, are prohibited.

3.3 General specifications.- The contractor shall be responsible for adherence to, and compliance with the following requirements of MIL-O-13830 and MIL-F-13926:

3.3.1 MIL-O-13830.

Cleanliness
Illuminated reticle

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:44Z
Check the source to verify that this is the current version before use.

3.3.2 MIL-F-13926.

Order of precedence
a. Dimensions and tolerances
c. Inorganic protective surface finishes
d. Part identification and marking
e. Workmanship

3.4 Vibration.- The periscope shall be vibrated at a constant frequency of 30 cycles per second with an amplitude of 1/16 inch (1/8 in. total excursion) for a period of 5 minutes plus or minus 15 seconds. Subsequent to vibration, there shall be no evidence of physical failure and the periscope shall meet the requirements of 3.5 to 3.6 inclusive.

3.5 Cleanliness.- With the periscope disassembled, the two modular units shall meet the following requirements.

a. Defects.- There shall be no evidence of moisture, grease, fingerprints, condensates, fractures, and adhesive separations on any glass component when viewing through either end of each module (including the unity power system).

b. Dirt.

(1) Body assembly.- When viewed through either eyepiece, there shall be no more than three (3) dirt particles appearing on the reticle (or reticle blank) within a 50 mil diameter central field of view. There shall be no more than three (3) dirt particles appearing outside the above field of view. The angular separation between dirt particles shall be at least 15 mils. Dirt particles smaller than 1/4 reticle line width shall be ignored regardless of distribution. There shall be no more than three (3) particles of dirt or foreign material (classed as dirt) on any glass component of the unity power system and the window and objective lenses of the 7X system. The size of any dirt particle shall not exceed 0.05 inch.

(2) Head assembly.- There shall be no more than three (3) particles of dirt or foreign material (classed as dirt) on any glass component. The size of any dirt particle shall not exceed 0.05 inch.

3.6 Performance.

3.6.1 Orientation.- Datum Plane "B" (ref. Dwg. F8619900) shall lie in a vertical plane. The elevation input arm shall be positioned as indicated on Drawing F8619900. The Datum Plane "A" (F8619900) shall lie in a horizontal plane.

3.6.2 Parallax.- Parallax between the reticle and the image of a target at 1200 meters as viewed through the right eyepiece shall not exceed 0.2 mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:44Z
Check the source to verify that this is the current version before use.

3.6.3 Collimation.- These requirements shall be met prior to meeting the requirements of 3.4.

a. An incident line of sight which is perpendicular within 0.2 mil to Datum Plane "B".

b. The input coupling arm positioned in accordance with Drawing F8619900.

3.6.3.1 Pre-vibration setting.- Rotate boresight knobs to establish coincidence of boresight cross with the incoming line of sight (see 3.6.3a) prior to meeting requirements of 3.4.

3.6.3.1.1 Elevation knob travel.- The boresight knob shall provide a minimum travel of 5.0 mils in elevation and 8.0 mils in depression from the collimated setting of 3.6.3.

3.6.3.1.2 Deflection knob travel.- The boresight knob shall provide a minimum travel of 6.5 mils in each direction from the collimated setting of 3.6.3.

3.6.3.1.3 Line of sight variations.- Variation in the line of sight in elevation, as the deflection knob is rotated by at least 6.5 mils in each direction from the position established in 3.6.3, shall not exceed 0.1 mil (total variation not to exceed 0.2 mil).

3.6.3.2 Post vibration.- The original setting of each reticle boresight relative to the incoming line of sight established in 3.6.3 shall not deviate more than 0.6 mil as observed through the eyepiece subsequent to meeting requirements of 3.4.

3.6.4 collimation repeatability.

3.6.4.1 Assembling periscope into mount.- The periscope shall be capable of repeating an original line of sight within 0.20 mil when removed and reinstalled (a minimum of 3 times) into the test fixture specified in 4.5.2.3.2.

3.6.4.2 Assembling body to head assembly.- An original line of sight shall not deviate more than 0.2 mil when the body assembly is removed and reinstalled (a minimum of 3 times) into the head assembly.

3.6.5 Image tilt.- The image of a target line which is originally parallel to the intersection of Datum Planes "A" and "B" shall emerge from the right eyepiece parallel to this same intersection within 2.0 degrees of arc.

3.6.6 Parallelism of reticle and image.- A line originally parallel to the intersection of datum planes "A" and "B" shall be parallel to the horizontal reticle line within 2.0 degrees of arc.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:44Z
Check the source to verify that this is the current version before use.

3.6.7 Resolution.- The resolution through either eyepiece shall be 10 seconds of arc or less in all four meridians. Eyepiece focus shift between any two meridians shall not exceed 0.25 diopters.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may , Utilize his own facilities or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 General provisions.- The component and subassembly inspection requirements of MIL-F-13926 form a part of the quality assurance provisions in this specification. Definitions of inspection terms shall be as listed in MIL-STD-109.

4.2 First article (initial production) approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of 3 periscopes, plus 3 each of all items covered by SQAP. The sample shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.2.1 Government testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.2.2 Contractor testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection.

4.3 Inspection provisions.

4.3.1 Submission of product.- Unless otherwise specified by the contracting officer, inspection lot size, lot formation and presentation of lots shall be in accordance with "Submission of Product" provisions of MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:44Z
Check the source to verify that this is the current version before use.

4.3.2 Examination and tests.

4.3.2.1 Components and subassemblies.- All components and subassemblies shall be inspected in accordance with the inspection provisions contained in Supplementary Quality Assurance Provisions (SQAP) listed in the technical data package (TDP). In the absence of (SQAP), the applicable Quality Assurance Provisions of MIL-F-13926 shall apply. Examination and tests related to Section 3 herein shall be performed on a single defect (individual characteristic) basis in accordance with MIL-STD-105 and the sampling plans specified in Tables I, II and III herein. Examination and tests for packaging, packing, and marking shall be in accordance with MIL-P-14232 and Section 5 herein. The tabulated classification of defects in Tables I, II and III shall constitute the minimum inspection to be performed by the supplier after first article approval and prior to Government acceptance or rejection by item or lot.

4.3.2.2 100 Percent inspection.- The following requirements and related tests shall be subjected to 100% inspection:

CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
1. Collimation, pre-vibration setting	3.6.3.1	4.6.1
2. Vibration	3.4	4.6.2
3. Cleanliness	3.5	4.6.3
4. Collimation, post vibration	3.6.3.2	4.6.4.5
5. Collimation repeatability, assembling periscope into mount	3.6.4.1	4.6.4.6.1
6. Collimation repeatability, assembling body to head assembly	3.6.4.2	4.6.4.6.2

TABLE I - CLASSIFICATION OF DEFECTS

CLASS

CRITICAL: NONE

MAJOR: AQL 0.65% Defective

	REQUIREMENT	TEST PROCEDURE
101. Parallax	3.6.2	4.6.4.1
102. Elevation knob travel	3.6.3.1.1	4.6.4.2
103. Deflection knob travel	3.6.3.1.2	4.6.4.3
104. Line of sight variation	3.6.3.1.3	4.6.4.4
105 l Image tilt	3.6.5	4.6.4.7
106. Parallelism of reticle and image	3.6.6	4.6.4.8
107. Resolution	3.6.7	4.6.4.9

MINOR: NONE

NOTE: The tests in Table I shall be conducted at a temperature between +60° and +90°F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:44Z
Check the source to verify that this is the current version before use.

4.3.3 Acceptance and rejection .- Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with "Acceptance and Rejection" as specified in MIL-STD-105.

4.4 Special sampling.

4.4.1 General.- One periscope shall be selected at random as a special sampling from each 100 produced. The sample shall meet the requirements and tests in Table II.

TABLE II

CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
301. Fabrication	3.2	Applicable drawing visual
302. General specification	3.3	MIL-F-13926 - visual

4.4.1.1 Three periscopes that have met the requirements and tests in 4.3.2.2 and in Table I shall be selected at random as a special sample from each months production. Each sample shall. then meet the requirement and test in Table III.

TABLE III

NO.	CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
303.	Interchangeability	3.2.1	4.6.4.10

4.4.2 Failure of sample.- Should any one item of a special sampling fail to meet the specified test requirements, acceptance of the represented inspection lot shall be suspended by the Government until necessary corrections have been made by the contractor and resubmitted samples have been approved (see 4.3.3).

4.5 Inspection equipment.- Except as otherwise provided for by the contract, the contractor shall supply and maintain inspection equipment in accordance with the applicable requirements of MIL-I-45607.

4.5.1 Government furnished inspection equipment.- Where the contract provides for Government furnished test equipment, supply and maintenance of test equipment shall be in accordance with the applicable requirements specified in MIL-I-45607.

4.5.2 Contractor furnished inspection equipment.

4.5.2.1 Government design.- Unless otherwise specified in the contract, all inspection equipment specified by drawing number in specifications or SQAP forming a part cf the contract shall be supplied by the contractor in accordance with technical data listed in the technical data package (TDP).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:44Z
Check the source to verify that this is the current version before use.

4.5.2.2 Contractor design.- The contractor shall design and supply inspection equipment compatible with the "Test Methods and Procedures" specified in 4.6 of this specification and with the component inspection procedures specified in "Examination" and "Test Facilities" requirements of MIL-F-13926. Since tolerance of test equipment is normally considered to be within 10% of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions and tolerances used in the design of test equipment shall be so selected and controlled as to insure that the test equipment will "reliably indicate acceptability of a product which does not exceed 90% of the prescribed tolerance limit, and permit positive rejection when non-conforming. Construction shall be such as to facilitate routine calibration of test equipment.

4.5.2.3 Inspection equipment design requirements.

4.5.2.3.1 Sealing.- The pressure testing equipment to test sealing of the periscope shall conform to the internal pressure test requirements of Sheet 1 of Drawing F8565556, Pressure Tester-Two Station.

4.5.2.3.2 Performance.- Special test equipment to determine performance of the periscope shall conform to the requirements of Drawing F8565964 (Test Fixture for Periscopes, M34 and M36) and Drawing F10540499 (Universal Test Stand and Set Up Instructions). The "Test Stand Components" depicted on Drawing F10540499 form a part of the test equipment. For use with testing herein, remove infrared filter from eyepiece of Collimator Projector FI0547434.

4.6 Test methods and procedures.

NOTE : Caution shall be exercised during the following tests to prevent Arm Assembly. 8635116 and Arm 8619845 from striking hard against their respective stop pins.

4.6.1 Collimation, pre-vibration setting.- Prior to the vibration test, the periscope shall be positioned as in 4.6.4. While viewing through the eyepiece, obtain coincidence of the periscope reticle boresight cross and the projected target image crosslines, by means of the boresight knobs. With established coincidence of the reticle and target image lines, slip the samples of the boresight knobs to Index 4. Record this setting for use in the test in 4.6.4.5. The periscope shall then be subjected to the test in 4.6.2. Caution must be exercised during this transfer of the periscope. All unnecessary shocks which would disturb the boresight knob settings for subsequent tests shall be avoided and under no circumstances is the elevation input shaft to be snapped against its stops.

4.6.2 Vibration.- Standard vibrating equipment capable of providing the amplitude and frequency specified in 3.4 shall be utilized for the vibration test. Unless otherwise specified, the test equipment shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:44Z
Check the source to verify that this is the current version before use.

in accordance with the "Test Facilities" requirements of MIL-F-13926. The periscope shall be clamped on the vibrating equipment by means of an adapter that conforms to Drawing F8575658, Vibration Adapter for Periscopes M34 and M36. The vibration motion shall be in the vertical plane for the time duration specified in 3.4. During this test, the input elevation shaft shall be immobilized to any position that shall prevent Arm Assembly 8635116 and Arm 8619845 from contacting their respective travel stop pins. Immediately following vibration, and prior to the examination for physical defects resulting from poor workmanship and materials, the periscope shall be subjected to the test in 4.6.4.5. Caution shall again be exercised during transfer of the periscope as specified in 4.6.1. Subsequent to the test in 4.6.4.5, the periscope shall be thoroughly examined for physical defects resulting from poor workmanship and materials to determine compliance with 3.4. A visual examination shall be made for missing or damaged parts, glass chips, foreign matter and bonding (separations, chipping or rupture). A tactile examination shall be made for functioning of moving parts for undue irregularities of movement, friction or looseness. An audible examination shall also be made of the periscope for loose internal optical and mechanical components. Any one of the possible defects defined above shall be cause to consider a periscope defective. Periscopes which have passed the above examinations shall be subjected to the remaining tests specified in 4.6.3 through 4.6.4.9 to determine full compliance with 3.4.

4.6.3 Cleanliness.- Remove the body assembly from the head assembly. The optical surfaces of each assembly shall be inspected for cleanliness in accordance with MIL-O-13830. Each assembly shall conform to the applicable cleanliness requirements of 3.5. Upon successful completion of this test, the body assembly shall be reinstalled into the head assembly.

4.6.4 Performance.- The following tests shall be performed with the periscope positioned on the special test equipment specified in 4.5.2.3.2. Set-up of the test equipment and installation of the periscope under test shall be performed in accordance with the set-up and operating instructions which are included on the applicable test equipment drawings. Unless otherwise specified during these tests, the eyepiece assemblies shall be set at the proper interpupillary distance to suit the individual's requirement; the diopter adjustment knob of each eyepiece shall be set for best focus of the target image; the sector lever of the Fixture F8565964 shall be engaged in the zero degree elevation position on the index plate. The Collimator Projector F10547434 shall be adjusted for 1200 meters during these tests.

4.6.4.1 Parallax.- View through the eyepiece assemblies and position the intersecting point of the periscope reticle boresight cross coincident with the intersecting point of the vertical and horizontal target line image, by means of the boresight knobs. While viewing through the right eyepiece, parallax will be recognized by any apparent displacement of the intersecting point of the periscope reticle boresight cross with respect to the intersecting point of the vertical and horizontal target line image when the observer's head is moved from side to side or up and down. Displacement between the periscope reticle and target image shall not exceed the tolerance specified in 3.6.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:44Z
Check the source to verify that this is the current version before use.

4.6.4.2 Elevation knob travel.- Establish coincidence of the periscope reticle boresight cross and the projected target image crosslines by means of the boresight knobs. Rotate the elevation knob to its clockwise stop using the knob scale to measure travel (mils). Reestablish coincidence of the periscope reticle boresight cross and the projected target image crosslines by means of the boresight knob. Rotate the elevation knob to its counterclockwise stop using the knob scale to measure travel (mils). These rotations of the elevation knob shall provide the minimum travel (mils) specified in 3.6.3.1.1, as measured on the boresight knob scale.

NOTE: During rotation of the boresight knob, it will be necessary to slip the knob scale as required in order to measure travel (mils). The knob shall be in the lock position while slipping the scale.

4.6.4.3 Deflection knob travel.- Perform this test utilizing the procedure in 4.6.4.2. Deflection knob travel shall meet the requirements specified in 3.6.3.1.2, as measured on the boresight knob scale.

4.6.4.4 Line of sight variation.- Establish coincidence of periscope reticle boresight cross and the projected target image crosslines by means of the boresight knobs. While observing the intersecting point of the periscope reticle boresight cross, rotate the deflection knob through its full excursion. During rotation of the deflection knob, any variation in elevation in the line of sight through the periscope reticle boresight cross, shall not exceed the values specified in 3.6.3.1.3.

4.6.4.5 Collimation, post vibration.- Observe through the eyepiece assemblies and adjust by means of the boresight knobs to obtain coincidence of the periscope reticle boresight cross with the target image. Boresight knob adjustments shall not exceed the tolerance specified in 3.6.3.2, as measured on the boresight knob scales. Record collimation setting for use in the test in 4.6.4.6.1.

4.6.4.6 Collimation repeatability.

4.6.4.6.1 Assembling periscope into mount.- Perform this test in sequence to the test in 4.6.4.5. Remove the periscope from the testing equipment. Repeated removal and installation (a minimum of three times) shall be performed. The periscope shall be inspected after each installation for repeatability of the collimation setting, recorded in 4.6.4.5. The periscope shall meet the requirements specified in 3.6.4.1, as measured on the boresight knobs. Subsequent to the last installation of the periscope, record collimation setting for use in the test in 4.6.4.6.2.

4.6.4.6.2 Assembling body to head assembly.- Perform this test in sequence to the test in 4.6.4.6.1. Remove the body assembly from the head assembly. Repeated removal and installation (a minimum of three items) shall be performed. The periscope shall be inspected after each installation for repeatability of the collimation setting recorded in 4.6.4.6.1. The periscope shall meet the requirements of 3.6.4.2, as measured on the boresight knobs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:44Z
Check the source to verify that this is the current version before use.

4.6.4.7 Image tilt.- The right and left optical systems of the periscope shall be inspected utilizing an auxiliary telescope containing a crossline reticle pattern. The vertical reticle line of the auxiliary telescope shall be aligned plumb when in the test position on a qualified level surface. With aid of the auxiliary telescope, view through the right eyepiece of the periscope and establish one extremity of the telescope vertical reticle line coincident to the vertical target image line. The image of the vertical target line shall be parallel to the telescope vertical reticle line within the tolerance specified in 3.6.5, as measured on the target. Repeat the above procedure with the auxiliary telescope positioned at the left eyepiece of the periscope. The images formed by the two optical systems of the periscope shall meet the requirements specified in 3.6.5.

4.6.4.8 Parallelism of reticle and image.- Perform this test while observing through the periscope right eyepiece with the unaided eye. Position one extremity of the periscope reticle, 400 meter range line, coincident to the horizontal target image line. The periscope reticle, 400 meter range line, shall be parallel to the horizontal target line within the tolerance specified in 3.6.6, as measured on the target.

4.6.4.9 Resolution.- The right and left optical systems of the periscope shall be inspected for resolution utilizing a calibrated dioptometer with a magnification of at least 3 power (3X). Set the dioptometer objective scale to zero and adjust the dioptometer eyepiece for best focus of the dioptometer reticle. Set the diopter adjustment knob of the periscope right eyepiece to indicate zero diopter. Position the dioptometer at the periscope right eyepiece. While viewing through the dioptometer, adjust the objective scale of the dioptometer for best focus of the resolution target image. Any change in diopter readings by adjustment of the dioptometer objective scale to obtain the detectable line structure and proper line count in all four meridians shall be recorded, as measured on the dioptometer objective scale. Repeat the above procedure with the dioptometer positioned at the periscope left eyepiece. The difference between the recorded readings for any two meridians shall not exceed the value specified in 3.6.7 for each optical system.

4.6.4.10 Interchangeability.- Each sample periscope (see 4.4.1.1) shall be disassembled (removal of body from head) to permit interchange of the component modules. The modules shall be identified and interchanged as shown in Table IV.

TABLE IV

Original Module Positions

	Periscope 1	Periscope 2	Periscope 3
Head Assembly (HA)	HA- 1	HA-2	HA-3
Body Assembly (BA)	BA- 1	BA-2	BA-3

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:44Z
Check the source to verify that this is the current version before use.

Interchanged Module Positions

	Periscope 1	Periscope 2	Periscope 3
Head Assembly (HA)	HA- 1	HA-2	HA-3
Body Assembly (BA)	BA-2	BA-3	BA-1

Upon reassembly of the three interchanged periscopes, each periscope shall be subjected to the tests specified in 4.3.2.2 Characteristics 1 through 6 inclusive and shall then meet the requirements and tests in Table I.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking.- Packaging, packing and marking shall be in accordance with Packaging Data Sheet 8619700.

6. NOTES

6.1 Intended use.- The Periscope, M34 is a tank commander's periscope primarily intended for use in the fire control system of the 105mm Gun, Tank M60 Series, and is used for machine gun sighting and observing.

6.2 Ordering data.- Procurement documents should specify the following:

Title, number and date of this specification
a. b. Selection of applicable levels of preservation, packaging and packing
c. Applicable stock number

6.3 Elevation shaft.- At no time shall the elevation shaft be allowed to strike hard against the travel stop screw.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A238

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:44Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

YES NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:44Z
Check the source to verify that this is the current version before use.