MILITARY SPECIFICATION

PERISCOPE, TANK: M34

This amendment forms a part of Military Specification MIL-P-45682D(MU), dated 6 April 1970.

Paragraph 2.1: Under "DRAWINGS" add:

"F11732167 Gage, Interchangeability, maximum
F11732168 Gage, Interchangeability, minimum"

Paragraph 3.2.1: Delete and substitute:

"3.2.1 Interchangeability.-

a. Modules.- The periscope shall meet all requirements of this specification without need for realignment of components or selection of modules listed in 3.2. Adjustments, other than those specified herein; are prohibited.

b. Periscope with mount.- The periscope shall be capable of insertion into the gages specified in 4.6.4.10.2. After insertion, the periscope shall be capable of being firmly secured and subsequently removed."

Paragraph 4.3.2.2: Add the following characteristic:

"7. Interchangeability, periscope with mount 3.2.lb 4.6.4.10.2"

Paragraph 4.4.1.1, Table III, Characteristic No. 303: Delete and substitute:

"303 Interchangeability, modules 3.2.la 4.6.4.10.1"

Paragraph 4.6.4.10: Delete and substitute:

"4.6.4.10 Interchangeability.

4.6.4.10.1 Modules.- Each sample periscope (see 4.4.1.1) shall be disassembled (removal of body from head) to permit interchange of the the component modules. The modules shall be identified and interchanged as shown in Table IV.

TABLE IV

Original Module Positions

	Periscope 1	Periscope 2	Periscope 3
Head Assembly (HA)	HA-1	HA-2	HA-3
Body Assembly (BA	BA-1	BA-2	BA-3

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T03:43Z
Check the source to verify that this is the current version before use.

Interchanged Module Positions

	Periscope 1	Periscope 2	Periscope 3
Head Assembly (HA)	HA-1	HA-2	HA-3
Body Assembly (BA)	BA-2	BA-3	BA-1

Upon reassembly of the three interchanged periscopes, each periscope shall be subjected to the tests specified in 4.3.2.2, Characteristics 1 through 7 inclusive and shall then meet the requirements and tests in Table I."

Following paragraph 4.6.4.10.1, add new paragraph:

"4.6.4.10.2 Periscope with mount.- This test shall be performed utilizing the maximum and minimum interchangeability gages conforming to Drawings F11732167 and F11732168 respectively to determine compliance with 3.2.1.b.'[1]

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A250

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:43Z
Check the source to verify that this is the current version before use.