MILITARY SPECIFICATION

RETICLE PROJECTOR, XM14

This amendment forms a part of Military Specification MIL-R-45672, 22 June 1960.

Page 3, paragraph 3.5.1 - Delete: "The reticle projector shall be energized to provide reticle illumination."

Page 3, paragraph 3.5.2 - Delete entire paragraph and substitute:
"3.5.2 Electrical circuitry - The complete circuitry shall be energized in accordance with schematic drawing D-10515973. A reference voltage of 115 volts, 400 cycles per second (cps), shall be applied to pins A and B of connector J1. A voltage of 24 volts, 400 cps, shall be applied to pins C and F of connector J1 so that when the voltage at pin F is in phase with the voltage at pin A, the reticle shall move to the right. The voltage between pins H and N of connector J1 shall be measured to insure that the voltage at pin H is in phase with the voltage at pin A.

The follow-up potentiometer shall be energized by connecting 48 volts plus or minus 0.5, center tapped, 400 cps, between pins K and J with the center tap connected to pin L of connector J1 so that the voltage at pin J is in phase with the voltage at pin A.

Twenty four volts direct current (dc) shall be applied between pins P and N of connector J1 so that the voltage at pin P is positive with respect to pin N. Connectors J2 and J3 shall be connected together."

Page 4, table I - Delete the tolerance values in the "Tol. (mils)" column and substitute ± .05 for all readings.

Page 4, paragraph 3.6.1 - Delete entire paragraph.

Page 13, paragraph 4.3.4.2.4 - Delete entire paragraph and substitute:
"4.3.4.2.4 Performance test equipment - The special test equipment to test for performance requirements shall be capable of mounting the reticle projector as specified. The bottom surface of the key shall be horizontal within 10 seconds.

4.3.4.2.4.1 Energizing shall be in accordance with drawing D-10515973. The device shall contain adequate facility for supplying, through connector J1, the voltages specified and determining phase relationship. The potentiometer shall have a load of 250 K ohms plus or minus 0.1 percent between the wiper arm and the center tap.

FSC 1240

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:43:
Check the source to verify that this is the current version before use.

4.3.4.2.4.2 Auxiliary telescope - The device shall contain an auxiliary telescope adjusted for zero (0) parallax at infinity, and will permit autocollimation of the telescope with the projected image of the reticle projector. The auxiliary telescope reticle shall be clearly defined and the lines shall not exceed 0.0010 in width. Angular tolerance shall not exceed five seconds (0°0'5"). The auxiliary telescope reticle pattern shall permit testing for the following requirements: reticle accuracy, reticle plumb, parallax, and reticle movement values listed in table I."

Page 13, paragraph 4.4.1.2 - Delete entire paragraph and substitute:
"4.4.1.2 Electrical circuitry - With the reticle projector mounted on the special test equipment the circuitry shall be energized with the specified voltages and the phase relationships checked. The electrical circuitry of the reticle projector shall be as specified in 3.5.2."

Page 17, paragraph 5.2.3, line 2 - Delete "6" and add "6.2."

Custodian:
Army - Ordnance Corps

Preparing activity:
Army - Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:42Z
Check the source to verify that this is the current version before use.