MILITARY SPECIFICATION

ATTENUATORS, FIXED
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-A-3933E, dated 24 April 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 5

3.4.4.1, delete and substitute:

"3.4.4.1 Connector metal parts. Unless otherwise specified, the male center contact pins shall be captivated and made of corrosion-resisting steel or beryllium copper. Corrosion-resisting steel pins shall be type 302 or type 304 in accordance with QQ-S-763, or type 303 in accordance with ASTM A582. Beryllium copper pins shall conform to QQ-C-530 and shall be silver plated in accordance with QQ-S-365 or gold plated in accordance with MIL-G-45204, type II, class 1. The female center contact pins shall be captivated and made of beryllium copper conforming to QQ-C-530 and silver plated in accordance with QQ-S-365 or gold plated in accordance with MIL-G-45204, type II, class 1."

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - MI
Air Force - 11, 17, 99
DLA - ES

User activities:
Navy - AS, MC, SH
Army - AR

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5985-0998)

FSC 5985

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:28Z
Check the source to verify that this is the current version before use.