INCH-POUND

MIL-DTL-3933F
SUPPLEMENT 1
7 November 2002

DETAIL SPECIFICATION

ATTENUATORS, FIXED,
GENERAL SPECIFICATION FOR

This supplement forms a part of Detail Specification MIL-DTL-3933F, dated 7 November 2002

SPECIFICATION SHEETS

MIL-DTL-3933/10	-	ATTENUATORS, FIXED COAXIAL LINE (SERIES N), FREQUENCY RANGE: DC TO 18 GHz, MEDIUM POWER.
MIL-DTL-3933/14	-	ATTENUATORS, FIXED, COAXIAL LINE (SMA CONNECTORS), FREQUENCY RANGE: DC TO 12.4 GHz, LOW POWER.
MIL-A-3933/16	-	ATTENUATORS, FIXED, COAXIAL LINE (SMA CONNECTORS), FREQUENCY RANGE: DC TO 18 GHz, CLASS IV, LOW POWER.
MIL-DTL-3933/17	-	ATTENUATORS, FIXED, COAXIAL LINE (TNC CONNECTORS), FREQUENCY RANGE: DC TO 18 GHz, LOW POWER.
MIL-DTL-3933/18	-	ATTENUATORS, FIXED COAXIAL LINE (SERIES N), FREQUENCY RANGE: DC TO 12.4 GHz, AND DC TO 18 GHz, LOW POWER.
MIL-DTL-3933/19	-	ATTENUATORS, FIXED COAXIAL LINE (BNC CONNECTORS), FREQUENCY RANGE: DC TO 4.5 GHz, LOW POWER.
MIL-DTL-3933/25	-	ATTENUATORS, FIXED, MINIATURE, COAXIAL LINE (SMA CONNECTORS), FREQUENCY RANGE: DC TO 18 GHz, LOW POWER.

Preparing activity:
DLA - CC

Project (5985-1229-99)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:28Z
Check the source to verify that this is the current version before use.