MILITARY SPECIFICATION

INSULATING AND JACKETING COMPOUNDS,
ELECTRICAL (FOR CABLES, CORDS, AND WIRES),
GENERAL SPECIFICATION FOR

This supplement forms a part of Military Specification MIL-I-3930E, dated , and is approved for use by all Departments and Agencies of the Department of Defense.

SPECIFICATION SHEETS

MIL-I-3930/1 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Insulating Compound, Type IP-Medium-low temperature, polyvinylchloride (PVC) and polyvinylchloride acetate (PVCA).

MIL-I-3930/2 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Insulating Compound, Type IS-Medium-low temperature, styrene-butadiene rubber (SBR).

MIL-I-3930/3 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Insulating Compound, Type IS-L-low temperature, heat-resistant, styrene-butadiene rubber (SBR).

MIL-I-3930/4 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Insulating Compound, Type IR-Low temperature, natural rubber.

MIL-I-3930/5 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Insulating Compound, Type IL-Low temperature, natural rubber deposited from a rubber latex compound.

MIL-I-3930/6 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Insulating Compound, Type IJ-S-Medium-low temperature, insulating and jacketing, styrene-butadiene rubber (SBR).

MIL-I-3930/7 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Insulating Compound, Type IL-H-Low temperature, heat-resistant, natural rubber deposited from a rubber-latex compound.

MIL-I-3930/8 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Insulating Compound, Type IL-RN-Low temperature, layer of natural rubber latex and a color-coded outer layer of chloroprene rubber (CR) latex bonded together.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:22Z
Check the source to verify that this is the current version before use.

FSC 5970

MIL-I-3930/9 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Insulating Compound, Type IH-Low temperature, heat and ozone resistant, ethylene-propylene rubber (EPM) or ethylene-propylene-diene rubber (EPDM).

MIL-I-3930/10 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Insulating Compound, Type IJ-H-Low temperature, heat and weather resistant, insulating and jacketing, ethylene-propylene rubber (EPM) or ethylene-propylene-diene rubber (EPDM).

MIL-I-3930/11 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Insulating Compound, Type IE-Polyethylene in accordance with L-P-390, Type II, Class L, Grade 3 or 4, Category 5.

MIL-I-3930/12 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Insulating and Jacketing Compound, Type TPE-S-Low temperature, heat and ozone resistant, styrenic thermoplastic elastomer.

MIL-I-3930/13 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Insulating and Jacketing Compound, Type TPE-O-Low temperature, weather resistant, olefinic thermaplastic elastomer.

MIL-I-3930/14 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Jacketing Compound, Type JP-Medium-low temperature, polyvinylchloride (PVC) and polyvinylchloride-acetate (PVCA).

MIL-I-3930/15 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Jacketing Compound, Type JS-Medium-low temperature, styrene-butadiene rubber (SBR).

MIL-I-3930/16 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Jacketing Compound, Type JS-L-Low temperature, heat-resistant, styrene-butadiene rubber.

MIL-I-3930/17 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Jacketing Compound, Type JR-Low temperature, natural rubber.

MIL-I-3930/18 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Jacketing Compound, Type JN-Moderate-low temperature, chloroprene rubber (CR).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:22Z
Check the source to verify that this is the current version before use.

MIL-I-3930/19 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Jacketing Compound, Type JN-L-Low temperature, chloroprene rubber (CR).

MIL-I-3930/20 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Jacketing Compound, Type JH-Low temperature, heat and weather resistant, ethylene-propylene (EPM), or ethylene-propylene-diene rubber (EPDM).

MIL-I-3930/21 - Insulating and Jacketing Compounds, Electrical (For Cables, Cords, and Wires) Jacketing Compound, Type JU-Low temperature, heat and weather resistant, polyurethane thermoplastic elastomer.

Preparing activity:
Army-CR

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:22Z
Check the source to verify that this is the current version before use.